

Modeling Module 1


August 12, 2020

Outline

- ▶ What's a Model?
- ▶ State-Transition Systems (Kripke Structures)
- ▶ Behaviors, Properties, and the Model Checking Problem
- ▶ Modeling and Abstraction
- ▶ Modeling Examples


An Continuous Domain Example

An Example



Our model:

$$\frac{\delta^2 \theta}{\delta t^2} = -\frac{g}{L} \sin \theta$$





Plot of θ over time


A Hardware Abstraction Example

We always omit some detail.

Example:



x	$\neg x$
0	1
1	0



Abstraction

Modeling: States

- ▶ Our systems have a state,
the model has a set of states

Modeling: States

- ▶ Our systems have a state,
the model has a set of states
- ▶ This is typically given as a valuation of state variables
 - ▶ θ
 - ▶ Velocity
 - ▶ Data stored in program variables
 - ▶ Data stored in hardware registers/flip-flops
 - ▶

Modeling: States

- ▶ Our systems have a state,
the model has a set of states
- ▶ This is typically given as a valuation of state variables
 - ▶ θ
 - ▶ Velocity
 - ▶ Data stored in program variables
 - ▶ Data stored in hardware registers/flip-flops
 - ▶
- ▶ We focus on discrete state variables

Modeling State Transitions

- ▶ When the state changes with time, we have a state transition

Modeling State Transitions

- ▶ When the state changes with time, we have a state transition
- ▶ Time can be modeled as
 - ▶ continuous
 - ▶ discrete

Modeling State Transitions

- ▶ When the state changes with time, we have a state transition
- ▶ Time can be modeled as
 - ▶ continuous
 - ▶ discrete
- ▶ We will focus on discrete-time transitions

Definition Transition System

Definition (Transition System)

A *Transition System* is a 3-tuple $M = (S, S_0, T)$ consisting of


- ▶ a set of states S ,
- ▶ a set of initial states $S_0 \subseteq S$
- ▶ a transition relation $T \subseteq (S \times S)$

Modeling Sequential Code: An Example

```
0: x=0;  
1: y=0;  
2: while (1) {  
3:   x = (x+1) mod 2;  
4:   y = x+1; }  
■
```

Modeling Sequential Code: An Example

```
0: x=0;  
1: y=0;  
2: while (1) {  
3:   x = (x+1) mod 2;  
4:   y = x+1; }  
■
```




Modeling Sequential Code: An Example

```


0: x=0;
1: y=0;
2: while (1) {
3:   x = (x+1) mod 2;
4:   y = x+1; }

```



TS : $M = (S, S_0, R)$

- ▶ $S = (D_1 \times D_2)$, where $D_1 = \{0, 1, 2\}$, $D_2 = \{0, 1, 2, 3\}$
- ▶ $S_0 = \{(0, 0)\}$
- ▶ $R = \{((0, 0), (1, 2)), ((0, 1), (1, 2)), ((1, 2), (2, 3)), ((2, 3), (0, 1))\}$



Towards Symbolic Representation for TS:

Notation for States

- ▶ S - set of states
- ▶ $s \in S$ - one particular state
- ▶ s, x - the value of some variable x in state s .
These are called state variables

Towards Symbolic Representation for TS:

The Transition Relation

The **transition relation** T relates a pre-state to a post-state:

$$\begin{array}{ccc} & T \subseteq S \times S & \\ \nearrow & & \nwarrow \\ \text{pre-state} & & \text{post-state} \end{array}$$

The transition relation captures how the state can be transformed by a **single transition**.

Towards Symbolic Representation for TS:

Characteristic Functions

Notation: We typically write the transition relation using a **characteristic function**.

This is useful for any kind of set:

$$S = \{0, 2, 4, 6, 8, \dots\}$$

$$x \in S \iff x \bmod 2 = 0$$

$$S = \{1, 2, \dots, 9, 10\}$$

$$x \in S \iff 1 \leq x \wedge x \leq 10$$

$$S = \{1, 2, 4, 8, 16, 32, \dots\}$$

$$x \in S \iff \exists y. x = 2^y$$

Towards Symbolic Representation for TS:

The Transition Relation Again

Example:

$$T \subseteq \mathbb{N}_0 \times \mathbb{N}_0$$

$$T(x, x') \iff x' = x + 1$$

This corresponds to the set

$$\{(0, 1), (1, 2), (2, 3), \dots\}$$


By convention, **primed variables** (x') denote the value of a state variable in the next state.

Symbolic TS for the Code Example

```
0: x=0;  
1: y=0;  
2: while (1) {  
3:   x = (x+1) mod 2;  
4:   y = x+1; }  
■
```



Symbolic TS for the Code Example

```
0: x=0;  
1: y=0;  
2: while (1) {  
3:   x = (x+1) mod 2;  
4:   y = x+1; }  
■
```



Symbolic TS for the Code Example

```
0: x=0;  
1: y=0;  
2: while (1) {  
3:   x = (x+1) mod 2;  
4:   y = x+1; }  
■
```



TS : $M = (S, S_0, R)$

- ▶ $S = (D_1 XD_2)$, where $D_1 = \{0, 1, 2\}$, $D_2 = \{0, 1, 2, 3\}$
- ▶ $S_0(s) : (s.x = 0 \wedge s.y = 0)$
- ▶ $R(s, s') : (s'.x = s.x + 1 \bmod 3) \wedge (s'.y = s'.x + 1)$

Role of Nondeterminism in Modeling

- ▶ *Nondeterminism* is used to abstract, i.e., not deliberately committing, to certain details in modeling systems

Role of Nondeterminism in Modeling

- ▶ *Nondeterminism* is used to abstract, i.e., not deliberately committing, to certain details in modeling systems
 - ▶ Initial nondeterminism: Initial state need not be unique

Role of Nondeterminism in Modeling

- ▶ *Nondeterminism* is used to abstract, i.e., not deliberately committing, to certain details in modeling systems
 - ▶ Initial nondeterminism: Initial state need not be unique
 - ▶ Inputs (environment) nondeterminism: Inputs can change arbitrarily

Role of Nondeterminism in Modeling

- ▶ *Nondeterminism* is used to abstract, i.e., not deliberately committing, to certain details in modeling systems
 - ▶ Initial nondeterminism: Initial state need not be unique
 - ▶ Inputs (environment) nondeterminism: Inputs can change arbitrarily
 - ▶ Scheduler nondeterminism (concurrent systems): Multiple successor states possible for a transition

Initial State Nondeterminism


```
0: while (1) {  
1:   x = (x+1) mod 2;  
2:   y = x+1; }
```

Initial State Nondeterminism

```
0: while (1) {  
1:   x = (x+1) mod 2;  
2:   y = x+1; }
```

Initial State Nondeterminism


```
0: while (1) {  
1:   x = (x+1) mod 2;  
2:   y = x+1; }
```



$TS : M = (S, S_0, R)$


- ▶ $S = (Nat \times Nat)$
- ▶ $S_0(s) : (s.y = 0)$
- ▶ $R(s, s') : (s'.x = s.x + 1 \bmod 3) \wedge (s'.y = s'.x + 1)$

Modeling Clocked Hardware





- ▶ One global clock: *clk*
- ▶ One input: *rst*
- ▶ Next-state logic: dashed box

Modeling Inputs in TS



Modeling Inputs in TS



Modeling Inputs in TS

