


作业思考题

一、为什么Demo里面没有创建Topic，却可以使用？

- 当配置了nameserver时，可以正常使用
- 当没有配置nameserver时，无法使用，会报错如下

Java

```
1 producer.setNamesrvAddr("47.102.136.138:9876");
```



```
Debugger Console
D:\Java\jdk-1.8\bin\java.exe ...
Connected to the target VM, address: '127.0.0.1:61851', transport: 'socket'
java.lang.IllegalStateException Create breakpoint : org.apache.rocketmq.remoting.exception.RemotingConnectException: connect to null failed
    at org.apache.rocketmq.client.impl.factory.MQClientInstance.updateTopicRouteInfoFromNameServer(MQClientInstance.java:680)
    at org.apache.rocketmq.client.impl.factory.MQClientInstance.updateTopicRouteInfoFromNameServer(MQClientInstance.java:510)
    at org.apache.rocketmq.client.impl.producer.DefaultMQProducerImpl.tryToFindTopicPublishInfo(DefaultMQProducerImpl.java:681)
    at org.apache.rocketmq.client.impl.producer.DefaultMQProducerImpl.sendDefaultImpl(DefaultMQProducerImpl.java:554)
    at org.apache.rocketmq.client.impl.producer.DefaultMQProducerImpl.send(DefaultMQProducerImpl.java:1365)
    at org.apache.rocketmq.client.impl.producer.DefaultMQProducerImpl.send(DefaultMQProducerImpl.java:1309)
    at org.apache.rocketmq.client.impl.producer.DefaultMQProducer.send(DefaultMQProducer.java:335)
    at org.apache.rocketmq.example.quickstart.Producer.main(Producer.java:67)
Caused by: org.apache.rocketmq.remoting.exception.RemotingConnectException Create breakpoint : connect to null failed
    at org.apache.rocketmq.remoting.netty.NettyRemotingClient.invokeSync(NettyRemotingClient.java:407)
    at org.apache.rocketmq.client.impl.MQClientAPIImpl.getTopicRouteInfoFromNameServer(MQClientAPIImpl.java:1378)
    at org.apache.rocketmq.client.impl.MQClientAPIImpl.getTopicRouteInfoFromNameServer(MQClientAPIImpl.java:1368)
    at org.apache.rocketmq.client.impl.factory.MQClientInstance.updateTopicRouteInfoFromNameServer(MQClientInstance.java:623)
```

顺着报错的信息从代码中进行分析：

1. DefaultMQProducerImpl.sendDefaultImpl(DefaultMQProducerImpl.java:554)



```
private SendResult sendDefaultImpl(
    Message msg,
    final CommunicationMode communicationMode,
    final SendCallback sendCallback,
    final long timeout
) throws MQClientException, RemotingException, MQBrokerException, InterruptedException {
    this.makeSureStateOK();
    Validators.checkMessage(msg, this.defaultMQProducer);
    final long invokeID = random.nextLong();
    long beginTimestampFirst = System.currentTimeMillis();
    long beginTimestampPrev = beginTimestampFirst;
    long endTimestamp = beginTimestampFirst;

    TopicPublishInfo topicPublishInfo = this.tryToFindTopicPublishInfo(msg.getTopic());
    if (topicPublishInfo != null && topicPublishInfo.ok()) {...}

    validateNameServerSetting();

    throw new MQClientException("No route info of this topic: " + msg.getTopic() + FAQUrl.suggestTodo(FAQUrl.NO_TOPIC_ROUTE_INFO),
        null).setResponseCode(ClientErrorCode.NOT_FOUND_TOPIC_EXCEPTION);
}
```

可以看到，必须找到 TopicPublishInfo 才能正确发送，否则就会失败

2. 进入

DefaultMQProducerImpl.tryToFindTopicPublishInfo(DefaultMQProducerImpl.java:681)

```
private TopicPublishInfo tryToFindTopicPublishInfo(final String topic) {
    TopicPublishInfo topicPublishInfo = this.topicPublishInfoTable.get(topic);
    if (null == topicPublishInfo || !topicPublishInfo.ok()) {
        this.topicPublishInfoTable.putIfAbsent(topic, new TopicPublishInfo());
        this.mQClientFactory.updateTopicRouteInfoFromNameServer(topic);
        topicPublishInfo = this.topicPublishInfoTable.get(topic);
    }

    if (topicPublishInfo.isHaveTopicRouterInfo() || topicPublishInfo.ok()) {
        return topicPublishInfo;
    } else {
        this.mQClientFactory.updateTopicRouteInfoFromNameServer(topic, isDefault: true, this.defaultMQProducer);
        topicPublishInfo = this.topicPublishInfoTable.get(topic);
        return topicPublishInfo;
    }
}
```

可以发现会先从本地的 `topicPublishInfoTable` 中获取该topic的信息，在初始阶段，本地 `topicPublishInfoTable` 中没有TopicTest的信息。我们看 `topicPublishInfoTable` 中存了什么，最后可以看到在broker创建的时候如果设置了 `isAutoCreateTopicEnable`，会自动缓存TBW102这个topic。

```
public class TopicValidator {

    public static final String AUTO_CREATE_TOPIC_KEY_TOPIC = "TBW102"; // Will be created at broker when isAutoC
    public static final String RMQ_SYS_SCHEDULE_TOPIC = "SCHEDULE_TOPIC_XXXX";
    public static final String RMQ_SYS_BENCHMARK_TOPIC = "BenchmarkTest";
    public static final String RMQ_SYS_TRANS_HALF_TOPIC = "RMQ_SYS_TRANS_HALF_TOPIC";
    public static final String RMQ_SYS_TRACE_TOPIC = "RMQ_SYS_TRACE_TOPIC";
    public static final String RMQ_SYS_TRANS_OP_HALF_TOPIC = "RMQ_SYS_TRANS_OP_HALF_TOPIC";
```

所以在执行函数 `tryToFindTopicPublishInfo` 时，会调用 `updateTopicRouteInfoFromNameServer` 函数从nameserver中获取topic，可以看到调用了两次，第一次 `isDefault` 是false，从nameserver未获得TopicTest，因为还没有将其同步到nameserver，第二次置 `isDefault` 为true，从nameserver获取的是TBW102的信息。

3. 进入MQClientInstance.updateTopicRouteInfoFromNameServer(MQClientInstance.java:680)

```

public boolean updateTopicRouteInfoFromNameServer(final String topic, boolean isDefault,
DefaultMQProducer defaultMQProducer) {
    try {
        if (this.lockNamesrv.tryLock(LOCK_TIMEOUT_MILLIS, TimeUnit.MILLISECONDS)) {
            try {
                TopicRouteData topicRouteData;
                if (isDefault && defaultMQProducer != null) {
                    topicRouteData = this.mQClientAPIImpl.getDefaultTopicRouteInfoFromNameServer(defaultMQProducer.getCreateTopicKey(),
                        clientConfig.getMqClientApiTimeout());
                    if (topicRouteData != null) {
                        for (QueueData data : topicRouteData.getQueueDatas()) {
                            int queueNums = Math.min(defaultMQProducer.getDefaultTopicQueueNums(), data.getReadQueueNums());
                            data.setReadQueueNums(queueNums);
                            data.setWriteQueueNums(queueNums);
                        }
                    }
                } else {
                    topicRouteData = this.mQClientAPIImpl.getTopicRouteInfoFromNameServer(topic, clientConfig.getMqClientApiTimeout());
                }
            }
        }
    }
}

```

可以发现在broker启动时，会将TBW102Topic的路由信息注册到nameserver，在使用TopicTest这个Topic去获取的其实是TBW102的路由信息，并根据该路由信息构建一个TopicPublishInfo来使用。所以TopicTest的信息会发到TBW102所在的broker中。

二、元数据的生命周期

下面分析路由元数据的生命周期

路由元数据存储于nameserver中的RouteInfoManager，由nameserver进行路由注册和删除工作

```

public class RouteInfoManager {
    private static final InternalLogger log = InternalLoggerFactory.getLogger(LoggerName.NAMESRV_LOGGER_NAME);
    private final static long BROKER_CHANNEL_EXPIRED_TIME = 1000 * 60 * 2;
    private final ReadWriteLock lock = new ReentrantReadWriteLock();
    private final HashMap<String/* topic */, Map<String/* brokerName */, QueueData>> topicQueueTable;
    private final HashMap<String/* brokerName */, BrokerData> brokerAddrTable;
    private final HashMap<String/* clusterName */, Set<String/* brokerName */>> clusterAddrTable;
    private final HashMap<String/* brokerAddr */, BrokerLiveInfo> brokerLiveTable;
    private final HashMap<String/* brokerAddr */, List<String/* Filter Server */> filterServerTable;
}

```

服务端

创建/更新元数据

每次启动一个broker，broker会触发路由注册，broker启动时会和所有nameserver创建心跳连接，向NameServer发送Broker的相关信息。在下面【Broker 注册到 Nameserver】可以看到具体流程。

Broker 注册到 Nameserver

在BrokerController的start方法中，可以看到broker在启动时，会向nameserver注册，之后会通过定时任务，每隔30s以心跳的方式上报。

```

if (!messageStoreConfig.isEnabledDLegerCommitLog()) {
    startProcessorByHa(messageStoreConfig.getBrokerRole());
    handleSlaveSynchronize(messageStoreConfig.getBrokerRole());
    this.registerBrokerAll( checkOrderConfig: true, oneway: false, forceRegister: true);
}

this.scheduledExecutorService.scheduleAtFixedRate(new Runnable() {

    @Override
    public void run() {
        try {
            BrokerController.this.registerBrokerAll( checkOrderConfig: true, oneway: false, brokerConfig.isForceRegister());
        } catch (Throwable e) {
            Log.error("registerBrokerAll Exception", e);
        }
    }
}, initialDelay: 1000 * 10, Math.max(10000, Math.min(brokerConfig.getRegisterNameServerPeriod(), 60000)), TimeUnit.MILLISECONDS);

```

30s

```

public synchronized void registerBrokerAll(final boolean checkOrderConfig, boolean oneway, boolean forceRegister) {
    TopicConfigSerializeWrapper topicConfigWrapper = this.getTopicConfigManager().buildTopicConfigSerializeWrapper();

    if (!PermName.isWritable(this.getBrokerConfig().getBrokerPermission())
        || !PermName.isReadable(this.getBrokerConfig().getBrokerPermission())) {
        ConcurrentHashMap<String, TopicConfig> topicConfigTable = new ConcurrentHashMap<>();
        for (TopicConfig topicConfig : topicConfigWrapper.getTopicConfigTable().values()) {
            TopicConfig tmp =
                new TopicConfig(topicConfig.getTopicName(), topicConfig.getReadQueueNums(), topicConfig.getWriteQueueNums(),
                    this.brokerConfig.getBrokerPermission());
            topicConfigTable.put(topicConfig.getTopicName(), tmp);
        }
        topicConfigWrapper.setTopicConfigTable(topicConfigTable);
    }

    if (forceRegister || needRegister(this.brokerConfig.getBrokerClusterName(),
        this.getBrokerAddr(),
        this.brokerConfig.getBrokerName(),
        this.brokerConfig.getBrokerId(),
        this.brokerConfig.getRegisterBrokerTimeoutMills())) {
        doRegisterBrokerAll(checkOrderConfig, oneway, topicConfigWrapper);
    }
}

```

调用远程服务判断是否需要发送注册请求

执行注册

```

private void doRegisterBrokerAll(boolean checkOrderConfig, boolean oneway,
    TopicConfigSerializeWrapper topicConfigWrapper) {
    List<RegisterBrokerResult> registerBrokerResultList = this.brokerOuterAPI.registerBrokerAll(
        this.brokerConfig.getBrokerClusterName(),
        this.getBrokerAddr(),
        this.brokerConfig.getBrokerName(),
        this.brokerConfig.getBrokerId(),
        this.getHAServerAddr(),
        topicConfigWrapper,
        this.filterServerManager.buildNewFilterServerList(),
        oneway,
        this.brokerConfig.getRegisterBrokerTimeoutMills(),
        this.brokerConfig.isCompressedRegister());

    if (registerBrokerResultList.size() > 0) {
        RegisterBrokerResult registerBrokerResult = registerBrokerResultList.get(0);
        if (registerBrokerResult != null) {
            if (this.updateMasterHAServerAddrPeriodically && registerBrokerResult.getHaServerAddr() != null) {
                this.messageStore.updateHaMasterAddress(registerBrokerResult.getHaServerAddr());
            }

            this.slaveSynchronize.setMasterAddr(registerBrokerResult.getMasterAddr());

            if (checkOrderConfig) {
                this.getTopicConfigManager().updateOrderTopicConfig(registerBrokerResult.getKvTable());
            }
        }
    }
}

```

调用远程服务，向nameserver注册当前broker信息

获取master节点的地址

更新master地址

Client 访问 Nameserver

客户端定时向nameserver发起请求GET_ROUTEINFO_BY_TOPIC，获取对应的路由信息

```

public TopicRouteData getTopicRouteInfoFromNameServer(final String topic, final long timeoutMillis,
    boolean allowTopicNotExist) throws MQClientException, InterruptedException, RemotingTimeoutException, RemotingSendRequestException, RemotingConn
    GetRouteInfoRequestHeader requestHeader = new GetRouteInfoRequestHeader();
    requestHeader.setTopic(topic);

    RemotingCommand request = RemotingCommand.createRequestCommand(RequestCode.GET_ROUTEINFO_BY_TOPIC, requestHeader);

    RemotingCommand response = this.remotingClient.invokeSync(addr: null, request, timeoutMillis);
    assert response != null;
    switch (response.getCode()) {
        case ResponseCode.TOPIC_NOT_EXIST: {
            if (allowTopicNotExist) {
                Log.warn("get Topic [{}] RouteInfoFromNameServer is not exist value", topic);
            }

            break;
        }
        case ResponseCode.SUCCESS: {
            byte[] body = response.getBody();
            if (body != null) {
                return TopicRouteData.decode(body, TopicRouteData.class);
            }
        }
    }
}

```

心跳感知与动态删除

- nameserver启动后，每10s会扫描一次brokerLiveTable，若某个broker的lastUpdateTimestamp在120s没有更新，nameserver会移除该broker的路由信息。

在RouteInfoManager中有方法scanNotActiveBroker()

```

public int scanNotActiveBroker() {
    int removeCount = 0;
    Iterator<Entry<String, BrokerLiveInfo>> it = this.brokerLiveTable.entrySet().iterator();
    while (it.hasNext()) {
        Entry<String, BrokerLiveInfo> next = it.next();
        long last = next.getValue().getLastUpdateTimestamp();
        if ((last + BROKER_CHANNEL_EXPIRED_TIME) < System.currentTimeMillis()) {
            RemotingUtil.closeChannel(next.getValue().getChannel());
            it.remove();
            // 删除broker相关信息
            Log.warn("The broker channel expired, {} {}ms", next.getKey(), BROKER_CHANNEL_EXPIRED_TIME);
            this.onChannelDestroy(next.getKey(), next.getValue().getChannel());

            removeCount++;
        }
    }

    return removeCount;
}

```

在NamesrvController中的initialize()方法中可以看到该心跳感知

```

public boolean initialize() {
    this.kvConfigManager.load();

    this.remotingServer = new NettyRemotingServer(this.nettyServerConfig, this.brokerHousekeepingService);

    this.remotingExecutor =
        Executors.newFixedThreadPool(nettyServerConfig.getServerWorkerThreads(), new ThreadFactoryImpl( threadNamePrefix: "RemotingExecutorThread_"));

    this.registerProcessor();

    this.scheduledExecutorService.scheduleAtFixedRate(new Runnable() {
        @Override
        public void run() { NamesrvController.this.routeInfoManager.scanNotActiveBroker(); }
    }, initialDelay: 5, period: 10, TimeUnit.SECONDS);

    this.scheduledExecutorService.scheduleAtFixedRate(new Runnable() {
        @Override
        public void run() { NamesrvController.this.kvConfigManager.printAllPeriodically(); }
    }, initialDelay: 1, period: 10, TimeUnit.MINUTES);
}

```

每隔10s

- broker自己关闭时，会发送UNREGISTER_BROKER 命令通知nameserver删除该路由信息

在BrokerController的shutdown方法中会调用unregisterBrokerAll()方法来注销 Broker

unregisterBrokerAll()在BrokerOuterAPI中：

```

public void unregisterBrokerAll(
    final String clusterName,
    final String brokerAddr,
    final String brokerName,
    final long brokerId
) {
    List<String> nameServerAddressList = this.remotingClient.getNameServerAddressList();
    if (nameServerAddressList != null) {
        for (String namesrvAddr : nameServerAddressList) {
            try {
                this.unregisterBroker(namesrvAddr, clusterName, brokerAddr, brokerName, brokerId);
                Log.info("unregisterBroker OK, NamesrvAddr: {}", namesrvAddr);
            } catch (Exception e) {
                Log.warn("unregisterBroker Exception, {}", namesrvAddr, e);
            }
        }
    }
}

```

```

public void unregisterBroker(
    final String namesrvAddr,
    final String clusterName,
    final String brokerAddr,
    final String brokerName,
    final long brokerId
) throws RemotingConnectException, RemotingSendRequestException, RemotingTimeoutException, InterruptedException, MQBrokerException {
    UnRegisterBrokerRequestHeader requestHeader = new UnRegisterBrokerRequestHeader();
    requestHeader.setBrokerAddr(brokerAddr);
    requestHeader.setBrokerId(brokerId);
    requestHeader.setBrokerName(brokerName);
    requestHeader.setClusterName(clusterName);
    RemotingCommand request = RemotingCommand.createRequestCommand(RequestCode.UNREGISTER_BROKER, requestHeader);

    RemotingCommand response = this.remotingClient.invokeSync(namesrvAddr, request, timeoutMillis: 3000);
    assert response != null;
    switch (response.getCode()) {
        case ResponseCode.SUCCESS: {
            return;
        }
        default:
            break;
    }
}

```

客户端

获取元数据

客户端定时向nameserver发起请求GET_ROUTEINFO_BY_TOPIC，获取对应的信息。

```

public TopicRouteData getTopicRouteInfoFromNameServer(final String topic, final long timeoutMillis,
boolean allowTopicNotExist) throws MQClientException, InterruptedException, RemotingTimeoutException, RemotingSendRequestException, RemotingConn
GetRouteInfoRequestHeader requestHeader = new GetRouteInfoRequestHeader();
requestHeader.setTopic(topic);

RemotingCommand request = RemotingCommand.createRequestCommand(RequestCode.GET_ROUTEINFO_BY_TOPIC, requestHeader);

RemotingCommand response = this.remotingClient.invokeSync(addr, null, request, timeoutMillis);
assert response != null;
switch (response.getCode()) {
    case ResponseCode.TOPIC_NOT_EXIST: {
        if (allowTopicNotExist) {
            Log.warn("get Topic [{}] RouteInfoFromNameServer is not exist value", topic);
        }

        break;
    }
    case ResponseCode.SUCCESS: {
        byte[] body = response.getBody();
        if (body != null) {
            return TopicRouteData.decode(body, TopicRouteData.class);
        }
    }
}
}

```

感知元数据的变化

在topic对应的路由信息变化后，nameserver不会通知客户端。需要客户端定时获取topic的最新路由，具体实现如下流程：

```

producer.start();--->this.defaultMQProducerImpl.start();--->mQClientFactory.start();--->
this.startScheduledTask();--->updateTopicRouteInfoFromNameServer();--->
mQClientAPIImpl.getTopicRouteInfoFromNameServer();

```

```

this.scheduledExecutorService.scheduleAtFixedRate(() -> {
    try {
        MQClientInstance.this.updateTopicRouteInfoFromNameServer();
    } catch (Exception e) {
        log.error("ScheduledTask updateTopicRouteInfoFromNameServer exception", e);
    }
}, initialDelay: 10, this.clientConfig.getPollNameServerInterval(), TimeUnit.MILLISECONDS);

```

清除不必要的元数据

客户端在启动之后，会定时向broker发送心跳，定时检查broker是否掉线，及时清理已经过期的元数据。

```

this.scheduledExecutorService.scheduleAtFixedRate(() -> {
    try {
        MQClientInstance.this.cleanOfflineBroker();
        MQClientInstance.this.sendHeartbeatToAllBrokerWithLock();
    } catch (Exception e) {
        log.error("ScheduledTask sendHeartbeatToAllBroker exception", e);
    }
}, initialDelay: 1000, this.clientConfig.getHeartbeatBrokerInterval(), TimeUnit.MILLISECONDS);

```



```

while (itBrokerTable.hasNext()) {
    Entry<String, HashMap<Long, String>> entry = itBrokerTable.next();
    String brokerName = entry.getKey();
    HashMap<Long, String> oneTable = entry.getValue();

    HashMap<Long, String> cloneAddrTable = new HashMap<>();
    cloneAddrTable.putAll(oneTable);

    Iterator<Entry<Long, String>> it = cloneAddrTable.entrySet().iterator();
    while (it.hasNext()) {
        Entry<Long, String> ee = it.next();
        String addr = ee.getValue();
        if (!this.isBrokerAddrExistInTopicRouteTable(addr)) {
            it.remove();
            log.info("the broker {} {} is offline, remove it", brokerName, addr);
        }
    }

    if (cloneAddrTable.isEmpty()) {
        itBrokerTable.remove();
        log.info("the broker[] name's host is offline, remove it", brokerName);
    } else {
        updatedTable.put(brokerName, cloneAddrTable);
    }
}
}

```

移除掉线的broker

向broker发送心跳

```

try {
    int version = this.mQClientAPIImpl.sendHeartbeat(addr, heartbeatData, clientConfig.getMqClientApiTimeout());
    if (!this.brokerVersionTable.containsKey(brokerName)) {
        this.brokerVersionTable.put(brokerName, new HashMap<String, Integer>(initialCapacity: 4));
    }
    this.brokerVersionTable.get(brokerName).put(addr, version);
    if (times % 20 == 0) {
        log.info("var1: send heart beat to broker[] {} {} success", brokerName, id, addr);
        log.info(heartbeatData.toString());
    }
} catch (Exception e) {
    if (this.isBrokerInNameServer(addr)) {
        log.info("var1: send heart beat to broker[] {} {} failed", brokerName, id, addr, e);
    } else {
        log.info("var1: send heart beat to broker[] {} {} exception, because the broker not up, forget it", brokerName, id, addr, e);
    }
}
}

```

```
public int sendHeartbeat(
    final String addr,
    final HeartbeatData heartbeatData,
    final long timeoutMillis
) throws RemotingException, MQBrokerException, InterruptedException {
    RemotingCommand request = RemotingCommand.createRequestCommand(RequestCode.HEART_BEAT, customHeader: null);
    request.setLanguage(clientConfig.getLanguage());
    request.setBody(heartbeatData.encode());
    RemotingCommand response = this.remotingClient.invokeSync(addr, request, timeoutMillis);
    assert response != null;
    switch (response.getCode()) {
        case ResponseCode.SUCCESS: {
            return response.getVersion();
        }
        default:
            break;
    }

    throw new MQBrokerException(response.getCode(), response.getRemark(), addr);
}
```