

Detection of 3D circles / Ellipses in a photo

Supervisor: Prof. YAN Hong

WU Zihan

August 14, 2022

Catalogue

Target

Background

Definition

Related Work

Methods

Arc segments

Parameters Prediction

cocluster

Validation

Department of
Electrical Engineering



香港城市大學
City University of Hong Kong

Project Target

To detect ellipses in the images/videos.



Figure: Input



Figure: Output

Ellipse I

To describe an ellipse we need 5 parameters:

$$Ax^2 + Bxy + Cy^2 + Dx + Ey + F = 0, \text{ where } B^2 - 4AC < 0.$$

Or in another way, we need the coordinates of the ellipse's center (x_0, y_0) , semi-major/semi-minor axes (a, b) , and a rotation angle (φ) .




Figure: Parameters for the ellipse

Two practical ways

Hough Transform

- ▶ Slow
- ▶ Sacrifice accuracy for efficiency

Edge Following

- ▶ Derived from Arc-support LS
- ▶ use greyscale image (gradient)
- ▶ Greedy for efficiency

Methods

- ▶ To detect the arc segments;
- ▶ (To form arcs;)
- ▶ To predict the 5 parameters for ellipses;
- ▶ Co-clustering;
- ▶ Validation.

LSD: A Fast Line Segment Detector with a False Detection Control

IEEE TRANSACTIONS ON PATTERN ANALYSIS AND MACHINE INTELLIGENCE

- ▶ Finding line-support region (region growing algorithm)
- ▶ Rectangular Approximation of Regions
- ▶ Validation




Figure: Region generation




Figure: Rectangular Approximation

Arc segments' result






Figure: Source Images

Department of
Electrical Engineering

Figure: Arc Detection Results

Caluculating the Parameters



$$x^2 + bxy + cy^2 + dx + ey + f = 0;$$

$$\begin{pmatrix} x & y & 1 \end{pmatrix} \begin{pmatrix} 1 & \frac{b}{2} & \frac{d}{2} \\ \frac{b}{2} & c & \frac{e}{2} \\ \frac{d}{2} & \frac{e}{2} & f \end{pmatrix} \begin{pmatrix} x \\ y \\ 1 \end{pmatrix} = O_{3 \times 3};$$


$$\begin{pmatrix} x_1 & y_1 & 1 \\ \vdots & \vdots & \vdots \\ x_n & y_n & 1 \end{pmatrix} \begin{pmatrix} 1 & \frac{b}{2} & \frac{d}{2} \\ \frac{b}{2} & c & \frac{e}{2} \\ \frac{d}{2} & \frac{e}{2} & f \end{pmatrix} \begin{pmatrix} x_1 & \dots & x_n \\ y_1 & \dots & y_n \\ 1 & \dots & 1 \end{pmatrix} = O_{3 \times 3}.$$

Figure: Arc Segment

Example

Department of
Electrical Engineering

Caluculating the Parameters



We can also alter it into:

$$\mathbf{D}\alpha = \mathbf{0},$$

where

$$\mathbf{D} = \begin{pmatrix} 1 & x_1y_1 & y_1^2 & x_1 & y_1 & 1 \\ x_2^2 & x_2y_2 & y_2^2 & x_2 & y_2 & 1 \\ \vdots & \vdots & \vdots & \vdots & \vdots & \vdots \\ x_n^2 & x_ny_n & y_n^2 & x_n & y_n & 1 \end{pmatrix};$$

$$\alpha^T = (1 \ b \ c \ d \ e \ f)$$

Figure: Arc Segment

Example

Cluster/Co-cocluster I

After all the α_i (i means the i th arc) are predicted, We correlate each two of them and then do co-clustering.

Advantages of coclustering:

1. Fast for high-dimensional cluster jobs;
2. Define co-distance in parameter space to represent the relativity.

Cluster/Co-cocluster II




Figure: cocluster method

Cluster/Co-cocluster III




Figure: cocluster result

Direct Least Square Fitting of Ellipses I

PATTERN ANALYSIS AND MACHINE INTELLIGENCE

Lagrange multipliers

$$\mathbf{D} = \begin{bmatrix} x_1^2 & x_1y_1 & y_1^2 & x_1 & y_1 & 1 \\ x_2^2 & x_2y_2 & y_2^2 & x_2 & y_2 & 1 \\ \vdots & \vdots & \vdots & \vdots & \vdots & \vdots \\ x_n^2 & x_ny_n & y_n^2 & x_n & y_n & 1 \end{bmatrix}_{n \times 6}$$

$$\mathbf{C} = \begin{bmatrix} 0 & 0 & -1 & \cdots & 0 \\ 0 & 2 & 0 & & \\ -1 & 0 & 0 & & \vdots \\ \vdots & & & \ddots & \\ 0 & \cdots & & & 0 \end{bmatrix}_{6 \times 6}$$

Direct Least Square Fitting of Ellipses II

PATTERN ANALYSIS AND MACHINE INTELLIGENCE


To minimize $\|Da\|^2$

It turns into an optimization problem.

$$2D^T Da - 2\lambda Ca = 0$$

$$a^T Ca = 1$$

Pilot Result



Summary

1. Co-clustering is effective in grouping data with good accuracy taking ellipses for example.
2. Co-clustering can serve as an unsupervised learning model in grouping problems.

Q&A

Thank you!