

# 开发和部署以太坊DApp——投票系统

## 1、项目简介

本篇文章将介绍如何基于以太坊平台开发简单的投票系统DApp，将学习到以下内容：

- 搭建开发环境（使用到Truffle框架）
- 编写和部署智能合约到区块链
- Web3和智能合约的交互
- MetaMask的使用

该项目比较简单，初始化一组候选人，任何人可以投票给候选人，并显示每个候选人得到的总票数。麻雀虽小，五脏俱全。通过编写此项目，可以学习到编译、部署和交互的全过程。

**注意：**以下操作均在MacOS上面操作

## 2、搭建开发环境

进行该项目前，需要安装Node.js和Truffle框架。

- 安装Node.js

官网：<https://nodejs.org/en/>

安装很简单，只需要下载安装包直接安装即可，可以先通过终端检查安装情况再安装，没有对应结果显示再安装：

```
wenzildeiMac:~ wenzil$ npm -v
3.10.10
wenzildeiMac:~ wenzil$ node -v
v6.9.5
```

- 安装Truffle：

Truffle是目前比较流行的Solidity智能合约开发框架，功能十分强大，可以帮助开发者快速地开发一个DApp。

```
npm install -g truffle
```

- 安装Ganache CLI：

Ganache CLI是以太坊节点仿真器软件ganache的命令行版本，可以方便开发者快速进行以太坊DApp的开发与测试，Ganache CLI已经取代了TestRPC。

```
npm install -g ganache-cli
```

### 3、通过Truffle创建项目

建一个项目的目录，然后进入到该目录，如下：

```
carisokdeiMac:study carisok$ pwd
/Users/carisok/Desktop/study
carisokdeiMac:study carisok$ mkdir VotingSystem
carisokdeiMac:study carisok$ cd VotingSystem/
```

然后通过Truffle创建项目，如下：

```
carisokdeiMac:VotingSystem carisok$ truffle unbox react-box
Downloading...
Unpacking...
Setting up...
Unbox successful. Sweet!

Commands:

  Compile:          truffle compile
  Migrate:          truffle migrate
  Test contracts:   truffle test
  Test dapp:        npm test
  Run dev server:   npm run start
  Build for production: npm run build
```


创建项目过程可能会有点慢，因为会安装项目中"package.json"里面的第三方依赖包，打开"node\_modules"目录查看占用了182.1MB。

**node\_modules**

182.1 MB, 959 项

上次修改时间 2018年5月30日

### 4、查看项目结构



简单说明：

- \* contracts/：存放智能合约Solidity代码的文件夹
- \* migrations/：存放部署智能合约脚本的文件夹
- \* src/：存放前端Web代码的文件夹，这里集成了React
- \* tests/：存放用于智能合约测试用例的文件夹
- \* package.json：定义了项目所需要的各个模块，项目的配置信息（比如名称、版本、许可证等数据）
- \* truffle.js：Truffle默认的配置文件

## 5、编写智能合约

在contracts目录下，创建一个名为Voting.sol的合约文件，代码如下：

```
pragma solidity ^0.4.18;
```

```

contract Voting {
    /*
    mapping: 称为映射或者字典，一种键值对的映射关系存储结构
    mapping的key: 存储类型为bytes32，存储的是候选人名字
    mapping的value: 存储类型为uint8的无符号整型，
    bytes32类型: 能存储32个字节，即32*8=256位的二进制内容
    uint8类型: 能存储8个字节，即8*8=64位的二进制内容
    */
    mapping (bytes32 => uint8) public votesReceived;

    /*
    Solidity目前不允许字符串数组，这里使用bytes32类型的数组来存储候选人名字
    */
    bytes32[] public candidateList;

    /*
    构造函数，传入bytes32类型的数组，初始化所有候选人名字
    */
    constructor(bytes32[] candidateNames) public {
        candidateList = candidateNames;
    }

    /*
    查询指定候选人的总票数
    */
    function totalVotesFor(bytes32 candidate) constant public returns (uint8)
    {
        /*
        require像其他语言中的断言(assert)，用于条件检查。
        条件满足时继续执行，条件不满足则抛出异常。
        */
        require(validCandidate(candidate));
        return votesReceived[candidate];
    }

    /*
    对指定候选人进行投票
    */
    function voteForCandidate(bytes32 candidate) public {
        // 投票前判断是否为候选人名字
        require(validCandidate(candidate));
        votesReceived[candidate] += 1;
    }

    /*
    检查投票名字的有效性，即判断投票名字是否在候选人名字里面
    */
    function validCandidate(bytes32 candidate) constant public returns (bool)

```

```

{
  // 循环遍历候选人列表
  for(uint i = 0; i < candidateList.length; i++) {
    // 判断投票名字是否为候选人
    if (candidateList[i] == candidate) {
      return true;
    }
  }
  return false;
}
}

```

然后，修改Migrations.sol文件的内容

```

function Migrations() public {
  owner = msg.sender;
}

```

修改为

```

constructor() public {
  owner = msg.sender;
}

```

## 6、编写智能合约部署脚本

在"migrations"目录中新建一个文件，名字为"3\_deploy\_voting.js"，内容如下：

```

var Voting = artifacts.require("./Voting.sol");

module.exports = function(deployer) {
  deployer.deploy(Voting, ['Jack Chen', 'Andy Lau', 'Stephen Chow', 'Wenzil'], {
    gas: 6700000
  });
};

```

## 7、修改truffle.js

修改全局网络配置信息，可以设置默认gas（为了部署合约的时候忘记设置gas）

```

module.exports = {
  networks: {
    development: {
      host: 'localhost',

```

```
    port: 8545,  
    network_id: '*',  
    gas: 470000  
  }  
}  
};
```

## 8、编译和部署智能合约

### 8.1 启动Ganache CLI

输入"ganache-cli"命令启动:

```
carisokdeiMac:~ carisok$ ganache-cli  
Ganache CLI v6.1.0 (ganache-core: 2.1.0)
```

#### Available Accounts

=====

```
(0) 0x137b0be0e36b991277193a243a5c02203df54055  
(1) 0xaf96555135bf00727c9efc36d42823fd5a7a9364  
(2) 0xb28720c0f3263b72bb7c742418b9b7a4e4fa707c  
(3) 0xb9aa64aef84476493ed9db31549141846c66e59e  
(4) 0xfe1825f4039531e88990e1a6e4a102f0ed930fa2  
(5) 0x10c26ac6076fb665541dd60e50da2f759c4e5801  
(6) 0x93a546b3acc2d34f0a37825ed27fc1ed6618157f  
(7) 0xc0c633249d3c241b17f9ed9282c9754397b676c8  
(8) 0x565262091159e0baf4eb5b78477187f3e9f4bd6e  
(9) 0x6f8653f1174f09edc7a38b66a7567f02408938c4
```

#### Private Keys

=====

```
(0) b5ee4dd415b7616b0fd1d4af585579d70970b5b71e4033b02bd7bdb9b5e8ccad  
(1) 0f91e7d5f7a4b366a0d95dbae9c4917d22ae95809b1acb4117feadd1a60da5de  
(2) 4a61d911ccc12f02ae426c5771fcffffcd2c718dc1fc183e0ce30ed61f0bee8cc  
(3) 928c4151d6c8e12f6e6aa72fe01c9baa362032eb7b5af9bd0928bf30cdc39375  
(4) 98a9d8938a2375f598b0f0f19b1bfe64509f186333dbf75fef9e44f4d5189d6  
(5) b2e43d00fb5f0b1d7360bdba4f7e408b0a0d45618121d566b56c41fe28c5d4eb  
(6) e4f9df75683ccce2a05865d017f756e3091cfd66c858e856b9a82273c5accbb1  
(7) 627add4d489b0a8d44a6c87d684ac1119d715bbf44e87fe35fb00a2a309f3df6  
(8) 6b37dd934ea80056290f7edad3c294b592b8d1548259685e50c93ca90cb94f03  
(9) f4ccb4df8bf5fa6caba9a0daf3112eea09a1bde8d2056b9e129dac939bd93403
```

#### HD Wallet

=====

```
Mnemonic:      arch innocent borrow fog forward pepper legal bulk deposit or  
chard decline actor  
Base HD Path:  m/44'/60'/0'/0/{account_index}
```

```
Listening on localhost:8545
```

看到启动后自动建立了10个帐号（Accounts），每个帐号中都有100个测试用的以太币（Ether），还有每个帐号对应的私钥（Private Key）。可以用私钥来导入账号进行测试（如在MetaMask设置对应的IP和端口号，然后导入私钥）

## 8.2 编译智能合约

然后打开新的终端，确认在当前项目的根目录，输入"truffle compile"命令进行编译：

```
carisokdeiMac:VotingSystem carisok$ pwd
/Users/carisok/Desktop/study/VotingSystem
carisokdeiMac:VotingSystem carisok$ ls
box-img-lg.png      node_modules        test
box-img-sm.png      package.json        truffle-config.js
config              public              truffle.js
contracts           scripts
migrations          src
carisokdeiMac:VotingSystem carisok$ truffle compile
Compiling ./contracts/Migrations.sol...
Compiling ./contracts/SimpleStorage.sol...
Compiling ./contracts/Voting.sol...
Writing artifacts to ./build/contracts
```

## 8.3 部署智能合约

最后，执行"truffle migrate"命令部署智能合约：

```
carisokdeiMac:VotingSystem carisok$ truffle migrate
Using network 'development'.

Running migration: 1_initial_migration.js
  Deploying Migrations...
  ... 0xcea6c6aabbf29a213f4e9bd35d4b2f47fe247777e120532e3269467442a99b41
  Migrations: 0x712e510be1dea2093c9d8e5b49bf34096410f4de
Saving successful migration to network...
  ... 0x1e6cbd04ba0883ceace67973bf2aa2f773e6fd06575691db5c2888a2343f088d
Saving artifacts...
Running migration: 2_deploy_contracts.js
  Deploying SimpleStorage...
  ... 0x55908414c1c4c8c6f0799fa9dce3841aa1015e3cf30ee5436618092c67739303
  SimpleStorage: 0x3d29036cf74ca5045c9c445638db3c2afd46d502
Saving successful migration to network...
```

```

... 0x19ad61a3711f497ec95818ee7a4218ab095a3d044ee90bd905f89bc14eb1ac1d
Saving artifacts...
Running migration: 3_deploy_voting.js
Deploying Voting...
... 0x80327895bb6e741d620bb5a2034c8cf9d2c6738c044aba1b03eaac4d9947ab75
Voting: 0x66c4af2ff3ca1856b57eaa89df38f7435d9ca4cb
Saving successful migration to network...
... 0xe7754eedfb46de0a0c740d19c4f669edf3c6912a1822bac65c651fcdfd28ac82
Saving artifacts...

```

## 9、与投票合约交互

如果智能合约部署成功的话，可以通过truffle控制台进行交互，比如投票和投票统计操作，如下：

```

truffle(development)> var contract;
truffle(development)> Voting.deployed().then(instance => contract = instance
)
TruffleContract {
  constructor:
    { [Function: TruffleContract]
      _static_methods:
        { setProvider: [Function: setProvider],
          new: [Function: new],
          at: [Function: at],
          deployed: [Function: deployed],
          defaults: [Function: defaults],
          hasNetwork: [Function: hasNetwork],
          isDeployed: [Function: isDeployed],
          detectNetwork: [Function: detectNetwork],
          setNetwork: [Function: setNetwork],
          resetAddress: [Function: resetAddress],
          link: [Function: link],
          clone: [Function: clone],
          addProp: [Function: addProp],
          toJSON: [Function: toJSON] },
        _properties:
          { contract_name: [Object],
            #####此处省略N行打印输出#####

truffle(development)> contract.voteForCandidate('Wenzil').then( (result) =>
{ console.log(result) })
{ tx: '0x92f72a7f4ad535a0e4bdf20cc90ee875747345f08ce065b3b538a5cfab7cfe1e',
  receipt:
    { transactionHash: '0x92f72a7f4ad535a0e4bdf20cc90ee875747345f08ce065b3b53
8a5cfab7cfe1e',

```





+  
-

browser/Voting.sol x

ContractDefinition Voting ↗ 0 reference(s) ^ v

```
11 mapping (bytes32 => uint8) public votesReceived;  
12  
13 /*  
14 Solidity目前不允许字符串数组，这里使用bytes32类型的数组来存储候选人名字  
15 */  
16 bytes32[] public candidateList;  
17  
18 /*  
19 构造函数，传入bytes32类型的数组，初始化所有候选人名字  
20 */  
21 constructor(bytes32[] candidateNames) public {  
22     candidateList = candidateNames;  
23 }  
24  
25 /*  
26 查询指定候选人的总票数  
27 */  
28 function totalVotesFor(bytes32 candidate) constant public returns (uint8) {  
29     /*  
30      require像其他语言中的断言(assert)，用于条件检查。  
31      条件满足时继续执行，条件不满足则抛出异常。  
32      */  
33     require(validCandidate(candidate));  
34     return votesReceived[candidate];  
35 }  
36  
37 /*  
38 对指定候选人进行投票  
39 */  
40 function voteForCandidate(bytes32 candidate) public {  
41     // 投票前判断是否为候选人名字  
42     require(validCandidate(candidate));  
43     votesReceived[candidate] += 1;  
44 }  
45  
46 /*  
47 检查投票名字的有效性，即判断投票名字是否在候选人名字里面  
48 */  
49 function validCandidate(bytes32 candidate) constant public returns (bool) {  
50     // 循环遍历候选人列表  
51     for(uint i = 0; i < candidateList.length; i++) {  
52         // 判断投票名字是否为候选人  
53         if (candidateList[i] == candidate) {  
54             return true;  
55         }  
56     }  
57     return false;  
58 }  
59 }
```

Compile Run Settings Analysis Debugger Support

Environment Injected Web3 Kovan (42)

Account 0x43a...08991 (19.937439162 e ↕ 📄 🔒)

Gas limit 3000000

Value 0 wei

Voting  
["Jack Chen", "Andy Lau", "Stephen Cl Create  
Load contract from Address At Address

0 pending transactions 📄 💾 ▶️

Voting at 0x782...fc114 (blockchain) 📄

votesReceived "Jack Chen" 0: uint8:  
0

validCandidate "Wenzil" 0: bool:  
true

totalVotesFor "Wenzil" 0: uint8:  
2

candidateList 0: bytes32:  
0x4a61636b204368656e000000  
0000000000000000000000000000  
0000000000000000000000000000

voteForCandid ate "Wenzil"

[2] only remix transactions, script Search transactions Listen on network

```

    margin: 0 0 -1px 0;
}

.dataItem {
    flex: 1;
    align-items: center;
    justify-content: center;
    display: flex;
    padding: 5px;
}

.inputName {
    width: 180px;
    height: 30px;
    margin: 10px 10px 10px 0;
}

.voteButton {
    height: 38px;
    margin-left: 10px;
}

```

修改App.js文件，文件内容：

```

import React, {
  Component
}
from 'react'
import VotingContract from '../build/contracts/Voting.json'
import getWeb3 from './utils/getWeb3'

import './css/oswald.css'
import './css/open-sans.css'
import './css/pure-min.css'
import './App.css'
import './main.css'

// 合约的实例
var votingContractInstance;
// 投票合约地址
const contractAddr = "0x7829abb7d424f118f1243ec13207a02f5bffc114"

class App extends Component {
  constructor(props) {
    super(props)

    this.state = {

```

```

    storageValue: 0,
    web3: null,
    candidateList: [{
      "candidateId": 1,
      "candidateName": "Jack Chen",
      "voteNumber": 0
    }, {
      "candidateId": 2,
      "candidateName": "Andy Lau",
      "voteNumber": 0
    }, {
      "candidateId": 3,
      "candidateName": "Stephen Chow",
      "voteNumber": 0
    }, {
      "candidateId": 4,
      "candidateName": "Wenzil",
      "voteNumber": 0
    }
  ]
}

```

```

componentWillMount() {
  // Get network provider and web3 instance.
  // See utils/getWeb3 for more info.

```

```

  getWeb3
    .then(results => {
      this.setState({
        web3: results.web3
      })

      // Instantiate contract once web3 provided.
      this.instantiateContract()
    })
    .catch(() => {
      console.log('Error finding web3.')
    })
}

```

```

instantiateContract() {
  /*
   * SMART CONTRACT EXAMPLE
   *
   * Normally these functions would be called in the context of a
   * state management library, but for convenience I've placed them here.
   */

```

```

const contract = require('truffle-contract')
const votingContract = contract(VotingContract)
votingContract.setProvider(this.state.web3.currentProvider)

// Declaring this for later so we can chain functions on SimpleStorage.

// Get accounts.
this.state.web3.eth.getAccounts((error, accounts) => {
  votingContract.at(contractAddr).then((instance) => {
    votingContractInstance = instance
    // 读取合约成功后，遍历所有候选人的票数，并更新到前端
    var candidateListTemp = this.state.candidateList;
    for (let i = 0; i < this.state.candidateList.length; i++) {
      let object = candidateListTemp[i];
      votingContractInstance.totalVotesFor(object.candidateName).then(re
sult => {
        object.voteNumber = result.c[0]
        this.setState({
          candidateList: candidateListTemp
        })
      });
    }
  })
})
}

render() {
  return (
    <div className="App" style={{margin:20}}>
      <div className="pageTitle">以太坊DApp投票系统</div>
      <div className="dataContent">
        <div className="dataItem">候选人</div>
        <div className="dataItem">票数</div>
      </div>
      {/* 读取当前页面的候选人列表，并显示 */}
      {
        this.state.candidateList.map((item) => {
          return (
            <div className="dataContent" key={item.candidateId}>
              <div className="dataItem">{item.candidateName}</div>
              <div className="dataItem">{item.voteNumber}</div>
            </div>
          )
        })
      }
      <input className="inputName" placeholder="请输入候选人名字" ref="inputN
ame" />
      {/* 获取输入框的内容 */}

```

```

<button className="voteButton"
  onClick={() => {
    let candidateName = this.refs.inputName.value;
    let account = this.state.web3.eth.accounts[0];
    {/* 为输入的候选人投票，写入到区块链中 */}
    votingContractInstance.voteForCandidate(candidateName,{from: acc
ount}).then((result) => {
      var currentCandidateIndex = 0;
      {/* 获取输入候选人的数组下标 */}

      for(let i = 0; i < this.state.candidateList.length; i++) {
        let currentCandidate = this.state.candidateList[i];
        if (currentCandidate.candidateName === candidateName) {
          currentCandidateIndex = i;
          break;
        }
      }
      {/* 根据合约读取区块中的候选人列表数据，并刷新到前端页面 */}
      votingContractInstance.totalVotesFor(candidateName).then(resul
t => {
        var candidateListTemp = this.state.candidateList;
        {/* 根据输入候选人的数组下标来更新列表数据 */}
        for (let i = 0; i < candidateListTemp.length; i++) {
          if (candidateName === candidateListTemp[currentCandidateIn
dex].candidateName) {
            candidateListTemp[currentCandidateIndex].voteNumber = re
sult.c[0]
          }
        }
        this.setState({
          candidateList: candidateListTemp
        })
      })
    })
  }}>投票</button>
</div>
);
}
}

export default App

```

输入"npm run start"命令启动服务器，会自动打开网页。

## 以太坊DApp投票系统


候选人	票数
Jack Chen	0
Andy Lau	0
Stephen Chow	0
Wenzil	6

请输入候选人名字

投票

刚开始"Wenzil"的投票是1，因为在[Remix Solidity IDE](#)部署合约的时候投了1票，然后手动投票了好几次，所以为6，没有重新实验了。

演示下为"Jack Chen"投票，会弹出MetaMask确认交易



等几秒之后，页面自动更新票数。




如果输入非候选人名字的话，MetaMask会显示错误信息。



MetaMask Notification

CONFIRM TRANSACTION




Account 1


43a8E9...8991

19.935 ETH

11370.88 USD



>



7829aB...C114

Amount

0 ETH

0.00 USD

Gas Limit

UNITS

Gas Price

GWEI

Max Transaction Fee

0.098800 ETH

56.35 USD

Max Total

0.098800 ETH

56.35 USD

Data included: 36 bytes

Transaction Error. Exception thrown in contract code.

RESET

SUBMIT

REJECT

继续提交，打开Etherscan查看区块链信息，显示如图:

← → ↺ 安全 | https://kovan.etherscan.io/tx/0xc1a9883680529f9a4f8efaab9d9bdc349ad211beefbe7b1ddf69d8aef3f4e18e

Overview

Transaction Information ⏪ ⏩ Tools & Utilities ▾

TxHash:

0xc1a9883680529f9a4f8efaab9d9bdc349ad211beefbe7b1ddf69d8aef3f4e18e

Block Height:

7513375 (6 block confirmations)

TimeStamp:

44 secs ago (May-30-2018 11:43:24 AM +UTC)

From:

0x43a8e9e3e25b8a0f48dfeec5e716ca0e3b08991

To:

Contract 0x7829abb7d424f118f1243ec13207a02f5bffc114 ⚠  
Warning! Error encountered during contract execution [Reverted] ☹

Value:

0 Ether (\$0.00)

Gas Limit:

7600000

Gas Used By Txn:

25237

Gas Price:

0.000000013 Ether (13 Gwei)

Actual Tx Cost/Fee:

0.000328081 Ether (\$0.000000)

Nonce & {Position}:

46 | {1}

Input Data:

Function: voteForCandidate(bytes32 candidate) \*\*\*

MethodID: 0xcc9ab267

[0]: 7300

Convert To UTF8

搞定，收工。