



SGS GERMANY GMBH
Rodingsmarkt 16
D-20459 Hamburg
GERMANY

ANALYTICAL REPORT SR-6307100.01.A02

P. 1/3

grade NAPHTHA
reference no. PO: 101508395 SAP: 7022369
**REPLACE
Analytical report with reference SR.6268398.A01
Change of sulphur result

sample 002 Sample received from client
Sample packed in glass, quantity approx. 4x1L
Sample marked as Shore Tank W / GOER, Rostock
sampling date: 04.06.2024 / Open sampling / Running samples
date received 04.06.2024

	<u>002</u>
<u>Density at 15°C, kg/L</u> (ASTM D 4052)	0.6665
<u>Distillation at 101.3 kPa (760 mm Hg)</u> (ASTM D 86)	
- initial boiling point, °C	33.6
- 5% recovered, °C	42.9
- 10% recovered, °C	44.4
- 50% recovered, °C	54.2
- 70% recovered, °C	64.4
- 90% recovered, °C	87.7
- 95% recovered, °C	111.3
- final boiling point, °C	127.1
- recovery, % vol	97.3
- residue, % vol	1.1
- loss, % vol	1.6
<u>Saybolt colour</u> (ASTM D 156)	+30
<u>Hydrogensulphide as H₂S, mg/kg</u> (UOP 163)	<1.0
<u>Mercaptan as S, mg/kg</u> (UOP 163)	1.1
<u>Sulphur, mg/kg</u> (ASTM D 2622)	<3
<u>Total organic chlorides, mg/kg Cl</u>	<1.0

ANALYTICAL REPORT SR-6307100.01.A02

P. 2/3

(UOP 779)	
<u>Lead as Pb</u> , µg/kg (UOP 952)	<10
<u>DVPE</u> , psi (ASTM D 5191)	11.73
<u>Gaschromatographic analysis</u> (ASTM D 5443 modified, PIONA analyser)	
- Total paraffins, % vol	85.9
# - i-Paraffins, % vol	39.9
# - n-Paraffins, % vol	46.0
- Aromatics, % vol	2.3
- Naphtenes, % vol	11.8
# - Olefins, % vol	<0.1
- Benzene, % vol	1.28
- Compounds with BP over 200°C, % vol	<0.1
<u>Research Octane Number</u> (ASTM D 2699)	68
<u>Motor Octane Number</u> (ASTM D 2700)	65
<u>Gaschromatographic analysis</u> (SGS SPI 403/A)	
- Methyl tertiary butyl ether, mg/kg	<1.0
- Total oxygenates, mg/kg	<10
<u>Mercury</u> , µg/kg (UOP 938, appendix B)	<1.0

Please note that the precision of method UOP 938 is not fully established, specifically no reproducibility has yet been published. Please also note that the lower limit of quantitation is 1 ng/mL (m/v-ppb).

<u>Doctor test</u> (IP 30)	negative
<u>Copper corrosion, 3 hours at 50°C</u> (ASTM D 130)	Class 1
<u>CS₂ in hydrocarbons</u> , mg/kg (SGS SPI 812)	<1

This result is reported as requested. The determination is made outside of the scope as defined by the method, and as such, the precision is not defined

Samples will be retained for 3 months unless instructed otherwise.

End of analytical results



ANALYTICAL REPORT SR-6307100.01.A02

P. 3/3

Spijkenisse, the 13th June 2024
SGS Nederland B.V. - Oil, Gas and Chemicals

K. Melissant
Supervisor Customer Service - Analytical Services

The results shown in this test report specifically refer to the sample(s) tested as received unless otherwise stated. All tests have been performed using the latest revision of the methods indicated, unless specifically marked otherwise on the report. Precision parameters apply in the determination of the above results. Users of analytical results, when establishing conformance with commercial or regulatory requirements should note the full provisions of ASTM D3244, IP 367 and ISO 4259 in that context, the default confidence level of petroleum testing having been set at the 95% confidence level. Your attention is specifically drawn to Sections 7.3.6., 7.3.7 and 7.3.8 of ASTM D3244. SGS' sole responsibility is to its client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Warning: The sample(s) to which the findings recorded herein (the 'Findings') relate was (were) drawn and / or provided by the Client or by a third party acting at the Client's direction. The Findings constitute no warranty of the sample's representativeness of any goods and strictly relate to the sample(s). The Company accepts no liability with regard to the origin or source from which the sample(s) is/are said to be extracted.