

Report of Analysis

Client: BP Oil International Ltd
Customer Reference: BP Oil International Ltd
Job Location: Intertek CB Middlesbrough

Lab Reference Number: 2025-TEES-002498
Phoenix Job Number: uk180-0026158
Date Sampled: 25-Jul-2025
Date Submitted: 25-Jul-2025
Date Tested: 25-Jul-2025

Description	Method	Test	Result	Units	Spec Limit
Condensate Tank 154					
2025-TEES-002498-002					
	^a ASTM D4052	Density @ 15°C (in vac)	0.6655	g/cm ³	Max 0.735
	^a ASTM D5191	DVPE	12.23	psi	Max 12.50
	ASTM D156	Saybolt Color Units	+30		
	IP 224	Lead Content	<10	ppb	Max 50
	ISO 20846	Sulfur Content	<3.0	mg/kg	
	^a ASTM D86	Initial Boiling Point	33.3	°C	Min 30.0
		10% Evaporated	42.4	°C	
		20% Evaporated	43.9	°C	
		30% Evaporated	45.9	°C	
		40% Evaporated	48.1	°C	
		50% Evaporated	51.1	°C	
		60% Evaporated	55.5	°C	
		70% Evaporated	62.5	°C	
		80% Evaporated	74.1	°C	
		90% Evaporated	92.7	°C	
		95% Evaporated	114.0	°C	
		Final Boiling Point	114.0	°C	Max 180.0
	^a ASTM D5443	n-Paraffins	39.60	Vol %	
		Iso-Paraffins	42.57	Vol %	
		Paraffins	82.17	Vol %	Min 65.00
		Naphthenes	39.60	Vol %	
		Aromatics	4.72	Vol %	
		Benzene	2.84	Vol %	
		Olefins Content	<0.1	Vol %	
	ASTM D4810	Hydrogen Sulphide	<1.0	ppm	
	ASTM D4810	Mercaptan sulphur	<3	ppm	
	ASTM D7359 MOD	Total Chloride Content	<1.0	mg/kg	Max 10.0
	IP 466 MOD	ETBE Content	<5	mg/kg	
		MTBE Content	<5	mg/kg	Max 50
		Methanol Content	<5	mg/kg	
		Ethanol Content	<5	mg/kg	
		Total Propanol Content	<5	mg/kg	
		Total Butanol Content	<5	mg/kg	
		Total Oxygenates Content	<30	mg/kg	Max 100
	UOP 938	Mercury	<0.300	ppb Wt	Max 5



0102



The analysis results denoted by (a) are part of the laboratory UKAS accreditation to ISO/IEC 17025.

By submitting this test request, unless otherwise agreed in writing, you (the client) accept and acknowledge that we (Intertek) will apply Simple Acceptance when establishing conformity of test results with any given specification, except where the given specification provides clear decision rules, which would take precedence. Since the Simple Acceptance decision rule can have an associated probability of false acceptance as high as 50%, you are advised to review the guidance in ILAC G08 (and specifically ISO4259/IP367 for standard petroleum methods) to understand the significance of the uncertainty of measurement in relation to any conformity statement we produce. Note that uncertainty estimates (budgets) are available on request. In the case of standard test methods, the published test precision would apply.

This report has been reviewed for accuracy, completeness, and comparison against specifications when available. The reported results are only representative of the samples submitted for testing and are subject to confirmation upon completion of the final report, which may contain warnings, exceptions and terms and conditions which are pertinent to the data supplied herein. It is the position of Intertek that the final report is the prevailing document, and that the use of interim documents by the client is at their own risk. This report shall not be reproduced except in full without written approval of the laboratory.

Measurement Uncertainty available upon request.

Signed: _____
Anthony Littlefair, Laboratory Manager

Date: _____



0102

