



Certificate of Quality

Vessel:	HISTRIA GEMMA
Location:	Bourgas, Oil Terminal Rossenetz
Grade:	Naphtha
Date:	11-Jul-2025

Client:	LUKOIL NEFTOHIM BURGAS AD, LITASCO SA
Client ref:	437/28.06.2025, VGN25_02686
Lab ref:	3197, 3198, 3199, 3140 / 11.07.2025
SGS ref:	BU2530-0040

The results shown in this test report specifically refer to the sample(s) tested as received unless otherwise stated. All tests have been performed using the latest revision of the methods indicated, unless specifically marked otherwise on the report. Precision parameters apply in the determination of the results below. Users of the data shown on this report should refer to the latest published revisions of ASTM D3244; IP 367 and ISO 4259 and when utilising the test data to determine conformance with any specification or process requirement. This Test Report is issued under the Company's General Conditions of Service (copy available upon request or on the company website at www.sgs.com). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues defined therein. This report shall not be reproduced except in full, without the written approval of the laboratory.

Sample Source:	Shore tanks composite sample		Source ID:	5, 6, 9, 12, 15, 24	
Sample Type:	running		Sampled By:	SGS	
Sampled:	11-Jul-2025		Registered:	11-Jul-2025	
Analysed:	11-Jul-2025		Completed:	11-Jul-2025	
PROPERTY	METHOD	RESULT	UNITS	MIN	MAX
Density at 15°C ^A	ASTM D 4052-22	689.5	g/cm³	--	732.0
Distillation characteristics ^A	ASTM D 86-23				
IBP		33.3	°C	30.0	--
5% v/v evaporated at		48.5	°C	--	--
10% v/v evaporated at		52.5	°C	--	75
50% v/v evaporated at		77.0	°C	--	125
90% v/v evaporated at		122.8	°C	--	170
FBP		149.6	°C	--	180
Difference in temperatures (T ₉₀ -T ₅)	calculated	74.3	°C	60	--
RVP* ^A	ASTM D 5191-22	65.0	kPa	--	85
Saybolt colour ^A	ASTM D 156-15	28	rating	20	--
Sulphur ^A	ASTM D 5453-19 a	326	mg/kg	--	500
Watersoluble acids ^A	ASTM D 1093-23	NIL		--	nill
Lead content ^A	VLMI 06/2015	<20.0	ppb mass	--	50
Aromatics	ASTM D 5134-21	4.57	% (m/m)	--	12.00
Paraffins	ASTM D 5134-21	76.37	% (m/m)	65.00	--
Naphthenes	ASTM D 5134-21	18.70	% (m/m)	12.00	40.00
Olefins	ASTM D 5134-21	0.36	% (m/m)	--	1.00
Total Chlorine	UOP 558	1.0	mg/kg	--	10
Organic Chlorine	UOP 779-2008	0.5	mg/kg	--	3
Copper strip corrosion ^A	ASTM D 130-19	1a	rating	--	2
Mercaptans	ASTM D 3227-23	0.0173	% (m/m)	--	0.02
MTBE	ASTM D 7423 (mod)-17	14.4	mg/kg	--	54
Appearance	visual	clear without substances in suspension			
H2S	UOP 163:2005	<1.0	ppm	--	10
Ethanol	EN 13132	<0.17	% v/v	--	<0.17
Existent gum content (solvent washed)	EN ISO 6246	0.5	mg/100 ml	--	5.0
** End of Analytical Results **					

Remarks

* RVP result based on proportional calculation of the individual tanks results. A - parameters tested under ISO 17025 accreditation.

This document is only valid in its entirety and your attention is drawn to the Terms and Conditions on Page 1 of this report

For SGS:	Daniel Dobrev
Date:	11.07.2025

