Q0 Before you start; before you submit

I read Handout 6 on NP-hardness proofs before starting, and the reductions below follow it: describe the reduction, show that it runs in polynomial time, and prove the two directions of correctness separately, naming the solution I start from in each direction. I did not collaborate with anyone on this homework.

Q1 Self assessment

[TO FILL IN: copy or screenshot of my midterm answer for the chosen part, then a few sentences on what was deficient and how to fix it.]

Q2.1 Defining languages (a)

$$\textsc{Long-Path} = \left\{ (G, s, t, k) : \begin{array}{l} G = (V, E) \text{ is a graph, } s, t \in V, \ k \text{ is a nonnegative integer,} \\ \text{and } G \text{ has a path from } s \text{ to } t \text{ with no repeated vertex} \\ \text{and at least } k \text{ edges} \end{array} \right\}.$$

The optimization problem asks for the longest cycle-free path; the language adds a threshold k and asks the yes/no question "is there a cycle-free path from s to t of length at least k?" A path with no cycle is one that does not repeat a vertex. Since we are maximizing, the threshold is a lower bound ("at least k"): the length of the longest such path is the largest k for which $(G, s, t, k) \in \textsc{Long-Path}$. If G is weighted, "at least k edges" is replaced by "total weight at least k."

Q2.2 Defining languages (b)

$$\textsc{Candy} = \left\{ (C, s, k) : \begin{array}{l} C = \{c_1, \ldots, c_n\} \text{ is a set of positive integers, } s \text{ and } k \text{ are nonnegative} \\ \text{integers, and there is a subset } I \subseteq C \text{ with } |I| \leq k \text{ and } \sum_{c \in I} c \geq s \end{array} \right\}.$$

In words: (C, s, k) is in the language if some choice of at most k candy pieces has at least s grams of sugar in total. Since we are minimizing the number of pieces, the threshold is an upper bound ("at most k"): the minimum number of pieces needed is the smallest k for which $(C, s, k) \in \textsc{Candy}$.

Q3.1 ϒ's Scary P-NP Warmup (a)

V does not run in polynomial time, so it is not an *efficient* verifier.

A polynomial-time verifier for L_{ACC} must run in time polynomial in the size of the instance $(\langle M\rangle, x)$, and the certificates it needs must have size polynomial in the size of the instance as well. V fails this for two reasons.

The running time is exponential in the size of c. The certificate c is an integer written in binary, so it takes only about $\log_2 c$ bits to write down, but V simulates M for c steps. A certificate of length ℓ bits can be as large as $2^\ell - 1$, so V may take about 2^ℓ steps: exponential, not polynomial, in the length of its input. Even if we only allow certificates of length polynomial in $|(\langle M\rangle, x)|$, the simulation can still take time exponential in the size of the instance.

The certificate that is needed is not bounded by any polynomial. For $(\langle M\rangle, x) \in L_{\text{ACC}}$, the only certificates that make V accept are the integers $c \geq T$, where T is the number of steps M takes to accept x. T has nothing to do with the size of $(\langle M\rangle, x)$: a small machine can run for an enormous number of steps on a short input before accepting. So there is no polynomial p such that every "yes" instance has an accepting certificate of length at most $p(|(\langle M\rangle, x)|)$, and no polynomial bound on the time V needs to confirm it.

Note that V does satisfy the correctness condition: M accepts x if and only if there is some c such that M accepts x within c steps. The only problem is efficiency. (No fix is possible: every language in NP is decidable, by Q5(b), and L_{ACC} is undecidable, so L_{ACC} has no polynomial-time verifier at all.)

Q3.2 ϒ's Scary P-NP Warmup (b)

The certificate is the clique itself, given as a list of vertices.

Input: A graph $G = (V, E)$ and a certificate c
Output: accept if c is a clique of G with at least $|V|/2$ vertices, reject otherwise

```
1: function V_HC(⟨G⟩, c)
2:     if c is not a list of distinct vertices of V then return reject
3:     end if
4:     Let S be the set of vertices listed in c
5:     if |S| < |V|/2 then return reject
6:     end if
7:     for each pair of distinct vertices u, v ∈ S do
8:         if (u, v) ∉ E then return reject
9:         end if
10:    end for
11:    return accept
12: end function
```

Efficiency. Let $n = |V|$. A certificate that passes the first check lists at most n vertices, so its size is polynomial in the size of $\langle G \rangle$ (a longer c can be rejected as soon as it is seen to have more than n entries). Checking that the entries are distinct vertices of V takes $O(n^2)$ comparisons, comparing $|S|$ with $n/2$ takes $O(n)$ time, and the loop looks at $\binom{|S|}{2} = O(n^2)$ pairs, each needing one lookup in E, which takes at most $O(|E|)$ time. So V_{HC} runs in $O(n^2 |E|)$ time, which is polynomial in the size of $\langle G \rangle$.

Correctness. I show $\langle G \rangle \in$ HALF-CLIQUE $\iff \exists c$ such that $V_{\text{HC}}(\langle G \rangle, c)$ accepts.

($\Longrightarrow$) Suppose $\langle G \rangle \in$ HALF-CLIQUE. Then G has a clique $K \subseteq V$ with $|K| \geq |V|/2$. Let c be the list of the vertices of K, each written once. Then c is a list of distinct vertices of V, $|S| = |K| \geq |V|/2$, and every two distinct vertices of K are adjacent because K is a clique, so no check fails and $V_{\text{HC}}(\langle G \rangle, c)$ accepts.

($\Longleftarrow$) Suppose $V_{\text{HC}}(\langle G \rangle, c)$ accepts for some c. Then every check passed: c lists a set $S \subseteq V$, $|S| \geq |V|/2$, and every pair of distinct vertices of S is joined by an edge of E. So S is a clique of G of size at least $|V|/2$, and $\langle G \rangle \in$ HALF-CLIQUE.

Equivalently, if $\langle G \rangle \notin$ HALF-CLIQUE, then no c can pass all checks, so V_{HC} rejects for every certificate. Hence V_{HC} is an efficient verifier for HALF-CLIQUE, and HALF-CLIQUE $\in$ NP.

Q3.3 ϒ's Scary P-NP Warmup (c)

A set of $|V|-1$ vertices is V with exactly one vertex removed. So there are only $|V|$ candidates for the clique, and we can try them all.

Input: A graph $G = (V, E)$
Output: accept if G has a clique of size $|V| - 1$, reject otherwise

```
1: function D_BC(⟨G⟩)
2:     for each vertex w ∈ V do
3:         ok ← true
4:         for each pair of distinct vertices u, v ∈ V \ {w} do
5:             if (u, v) ∉ E then ok ← false
6:             end if
7:         end for
8:         if ok then return accept
9:         end if
10:    end for
11:    return reject
12: end function
```

Correctness. The subsets of V of size exactly $|V|-1$ are exactly the sets $V \setminus \{w\}$ for $w \in V$. In the iteration for w, the variable ok is true at the end of the inner loop if and only if every pair of distinct vertices of $V \setminus \{w\}$ is joined by an edge, i.e., if and only if $V \setminus \{w\}$ is a clique.

- If $\langle G \rangle \in$ BIG-CLIQUE, then G has a clique K with $|K| = |V| - 1$, so $K = V \setminus \{w\}$ for some $w \in V$. The outer loop either accepts before reaching w, or reaches w, finds ok true, and accepts. Either way D_{BC} accepts.
- If $\langle G \rangle \notin$ BIG-CLIQUE, then no set $V \setminus \{w\}$ is a clique, so in every iteration some pair is not adjacent, ok becomes false, and the iteration does not accept. After the outer loop ends, D_{BC} rejects.

(If the definition is read as "at least $|V|-1$," nothing changes: a clique of size $|V|$ contains a clique of size $|V|-1$, since every subset of a clique is a clique.)

Runtime. Let $n = |V|$. The outer loop runs at most n times. Each iteration looks at $\binom{n-1}{2} = O(n^2)$ pairs, and for each pair does one lookup in E, which takes $O(1)$ time with an adjacency matrix and at most $O(|E|) = O(n^2)$ time with an edge list. So the total time is $O(n \cdot n^2 \cdot n^2) = O(n^5)$ in the worst case ($O(n^3)$ with an adjacency matrix). The size of $\langle G \rangle$ is at least n, so this is polynomial in the input size, and all loops are finite, so D_{BC} always halts. Therefore D_{BC} is a polynomial-time decider for BIG-CLIQUE, and BIG-CLIQUE $\in$ P.

The difference from HALF-CLIQUE is the number of candidates: there are $\binom{n}{n/2}$ sets of size $n/2$, which is exponential in n, but only n sets of size $n-1$.

Q4.1 Placing haunted houses (a)

The certificate is the set S of neighborhoods that get a haunted house.

Input: A graph $G = (V, E)$, an integer k with $0 \le k \le |V|$, and a certificate c
Output: accept if c is a set of at most k vertices to which every vertex has access, reject otherwise

1: **function** $V_{\text{HH}}((G, k), c)$
2: **if** c is not a list of distinct vertices of V **then return** reject
3: **end if**
4: Let S be the set of vertices listed in c
5: **if** $|S| > k$ **then return** reject
6: **end if**
7: **for** each vertex $v \in V$ **do**
8: **if** $v \notin S$ and there is no $u \in S$ with $(u, v) \in E$ **then return** reject
9: **end if**
10: **end for**
11: **return** accept
12: **end function**

Efficiency. Let $n = |V|$. A certificate that passes the first check lists at most n vertices, so its size is polynomial in the size of (G, k). Checking that c is a list of distinct vertices of V takes $O(n^2)$ comparisons, and comparing $|S|$ with k takes $O(n)$ time. The loop runs n times; each iteration checks membership of v in S in $O(n)$ time and, for each of the at most n vertices $u \in S$, looks up (u, v) in E in at most $O(|E|)$ time. The total is $O(n^2\,|E|)$, polynomial in the size of (G, k).

Correctness. I show $(G, k) \in$ Haunted-House $\iff \exists c$ such that $V_{\text{HH}}((G, k), c)$ accepts.

($\Longrightarrow$) Suppose $(G, k) \in$ Haunted-House. Then there is a set $S \subseteq V$ with $|S| \le k$ such that every $v \in V$ is in S or adjacent to some $u \in S$. Let c be the list of the vertices of S, each written once. Then the first two checks pass, and for every $v \in V$ the condition in the loop is false, so V_{HH} reaches the last line and accepts.

($\Longleftarrow$) Suppose $V_{\text{HH}}((G, k), c)$ accepts for some c. Then every check passed: c lists a set $S \subseteq V$, $|S| \le k$, and for every $v \in V$ either $v \in S$ or there is some $u \in S$ with $(u, v) \in E$. So every vertex has access to S, and $(G, k) \in$ Haunted-House.

Hence V_{HH} is an efficient verifier for Haunted-House, and Haunted-House $\in \mathsf{NP}$.

Q4.2 Placing haunted houses (b)

Take G to be a triangle, $V = \{a, b, c\}$ and $E = \{(a, b), (b, c), (a, c)\}$, with $k = 1$. This is a legal instance: $k = 1 \leq 3 = |V|$ and no vertex is isolated.

$(G, 1) \notin$ **Vertex-Cover.** A single vertex cannot cover all three edges: a does not cover (b, c), b does not cover (a, c), and c does not cover (a, b). The empty set covers nothing. So G has no vertex cover of size at most 1.

$f(G, 1) = (G, 1) \in$ **Haunted-House.** Take $S = \{a\}$. Then $a \in S$, and b and c are both adjacent to a, so every vertex has access to S, and $|S| = 1 \leq k$.

So $(G, 1) \notin$ Vertex-Cover but $f(G, 1) \in$ Haunted-House, which violates the requirement $x \in$ Vertex-Cover $\iff f(x) \in$ Haunted-House. The reason is that covering edges is a stronger requirement than covering vertices: in a triangle one vertex is next to everything, but it still misses the edge opposite to it.

Q4.3 Placing haunted houses (c)

Let $n = |V|$ and $m = |E|$. The input (G, k) has size at least $n + m$ (the graph has to list its vertices and edges), plus $O(\log n)$ bits for $k \leq n$.

- Initializing G' with $V' = V$ and $E' = E$ copies the graph, which takes $O(n + m)$ time.
- The **for** loop runs once per edge of G, i.e., exactly m times. (It iterates over the original edge set E, not over E', so the new edges do not create more iterations.) Each iteration creates one new vertex and adds two new edges, which is a constant number of insertions, $O(1)$ time each with any reasonable representation (and certainly at most polynomial in $n+m$). So the loop takes $O(m)$ time.
- Returning (G', k) writes out the new graph and copies k. G' has $|V'| = n + m$ vertices and $|E'| = m + 2m = 3m$ edges, so the output has size $O(n + m)$ and writing it takes $O(n + m)$ time.

In total f runs in $O(n + m)$ time, which is linear, and in particular polynomial, in the size of the input (G, k).

Q4.4 Placing haunted houses (d)

Assume $(G, k) \in$ Vertex-Cover, and let $S \subseteq V$ be a vertex cover of G with $|S| \leq k$. I claim that $S' = S$ works for G'. Since $S \subseteq V \subseteq V'$, S' is a set of vertices of G', and $|S'| = |S| \leq k$. (Also $k \leq |V| \leq |V'|$, so (G', k) is a legal instance.) It remains to show that every vertex of V' has access to S'. The vertices of V' are of two kinds.

Original vertices $v \in V$. By assumption G has no isolated vertices, so v is an endpoint of some edge $(u, v) \in E$. Since S is a vertex cover, it contains an endpoint of this edge: $v \in S$ or $u \in S$. If $v \in S = S'$, then v has access to S'. If $u \in S = S'$, then v is adjacent to u in G', because $(u, v) \in E \subseteq E'$, so again v has access to S'.

New vertices w_{uv}, for $(u, v) \in E$. Since S is a vertex cover of G and $(u, v) \in E$, we have $u \in S$ or $v \in S$. The reduction added both edges (w_{uv}, u) and (w_{uv}, v) to E', so w_{uv} is adjacent in G' to a vertex of $S = S'$, and w_{uv} has access to S'.

So every vertex of V' has access to S' and $|S'| \leq k$, i.e., $f(G, k) = (G', k) \in$ Haunted-House.

Q4.5 Placing haunted houses (e)

Assume $(G', k) \in$ HAUNTED-HOUSE, and let $S' \subseteq V'$ be a set with $|S'| \leq k$ such that every vertex of V' has access to S'. S' may contain new vertices w_{uv}, which are not vertices of G, so S' itself may not be a vertex cover of G. I replace each new vertex in S' by one endpoint of its edge.

For each edge $(u, v) \in E$, fix one of its endpoints and call it $e(w_{uv})$ (say, $e(w_{uv}) = u$). Define

$$S = (S' \cap V) \ \cup \ \left\{ e(w_{uv}) : w_{uv} \in S' \right\}.$$

$S \subseteq V$ and $|S| \leq k$. Every element of S is an original vertex. Each element of S' contributes at most one element to S: an original vertex contributes itself, and a new vertex w_{uv} contributes $e(w_{uv})$. (Several elements of S' may contribute the same vertex, which only makes S smaller.) So $|S| \leq |S'| \leq k$.

S is a vertex cover of G. Let $(u, v) \in E$ be any edge of G. The reduction created the vertex $w_{uv} \in V'$, and by assumption w_{uv} has access to S'. There are two cases.

- $w_{uv} \in S'$. Then $e(w_{uv}) \in S$, and $e(w_{uv})$ is an endpoint of (u, v), so S covers (u, v).
- $w_{uv} \notin S'$. Then w_{uv} is adjacent in G' to some vertex of S'. The only edges of G' at w_{uv} are (w_{uv}, u) and (w_{uv}, v): the reduction adds exactly these two when it creates w_{uv}, and never adds an edge between two new vertices. So the only neighbors of w_{uv} are u and v, and hence $u \in S'$ or $v \in S'$. Both are original vertices, so $u \in S' \cap V \subseteq S$ or $v \in S' \cap V \subseteq S$, and S covers (u, v).

In both cases S contains an endpoint of (u, v). Since the edge was arbitrary, S is a vertex cover of G.

So G has a vertex cover of size at most k, i.e., $(G, k) \in$ VERTEX-COVER.

Together with parts (c) and (d), this shows that f is a polynomial-time mapping reduction, so VERTEX-COVER $\leq_p$ HAUNTED-HOUSE and HAUNTED-HOUSE is NP-hard. With part (a), HAUNTED-HOUSE is NP-complete.

Q5.1 Understanding P, NP, and polynomial-time mapping reductions (a)

The verifier ignores the certificate and decides x by itself using M.

1: **function** $V(x, c)$
2: Run M on x ▷ c is ignored
3: **if** M accepts x **then return** accept
4: **else return** reject
5: **end if**
6: **end function**

V **is efficient.** M is an efficient decider, so there is a polynomial p such that M halts on x within $p(|x|)$ steps. V runs M on x once and then does constant extra work, and it never reads c. So V runs in time $O(p(|x|))$, polynomial in $|x|$, whatever c is.

V **is correct.** I show $x \in L \iff \exists c$ such that $V(x, c)$ accepts.

($\Longrightarrow$) Suppose $x \in L$. Since M decides L, M accepts x. Then $V(x, c)$ accepts for every c; in particular it accepts for $c = \varepsilon$, a certificate of size 0, which is certainly polynomial in $|x|$. So there exists a c such that $V(x, c)$ accepts.

($\Longleftarrow$) I prove the contrapositive. Suppose $x \notin L$. Since M decides L, M rejects x. Then $V(x, c)$ rejects for every c, because V's answer does not depend on c. So there is no c such that $V(x, c)$ accepts.

Hence V is an efficient verifier for L, and $L \in \mathsf{NP}$. Since $L \in \mathsf{P}$ was arbitrary, $\mathsf{P} \subseteq \mathsf{NP}$.

Q5.2 Understanding P, NP, and polynomial-time mapping reductions (b)

Since $L \in \mathsf{NP}$, there is an efficient verifier V for L: there is a polynomial p such that $V(x, c)$ halts within $p(|x|)$ steps for every x and c, and $x \in L$ if and only if $V(x, c)$ accepts for some c. The decider tries every certificate that could matter.

Input: A string x
Output: accept if $x \in L$, reject otherwise

```
1: function D(x)
2:     for each string c of length at most p(|x|) do
3:         if V(x, c) accepts then return accept
4:         end if
5:     end for
6:     return reject
7: end function
```

D **always halts.** The alphabet is finite, so there are finitely many strings of length at most $p(|x|)$, and each call $V(x, c)$ halts because V is a verifier.

D **is correct.**

- If $x \in L$, then $V(x, c)$ accepts for some certificate c. We may take $|c| \leq p(|x|)$: V makes at most $p(|x|)$ steps, so it reads at most the first $p(|x|)$ symbols of c, and it behaves the same way on the prefix of c of that length. The loop reaches this certificate (unless it has accepted earlier), so D accepts.
- If $x \notin L$, then $V(x, c)$ rejects for every c, so the loop never accepts and D rejects.

So D decides L. Since $L \in \mathsf{NP}$ was arbitrary, every language in NP is decidable. (D takes exponential time, since there are exponentially many certificates, but a decider only has to halt.)

Q5.3 Understanding P, NP, and polynomial-time mapping reductions (c)

Assume $A \leq_p B$. By the first definition there is a polynomial-time computable function f such that $x \in A \iff f(x) \in B$ for every string x.

To show $A \leq_T B$, I must give a Turing machine that decides A using an oracle for B. Let O be an oracle that decides B: O halts on every input, and $O(y)$ accepts if and only if $y \in B$.

Input: A string x
Output: accept if $x \in A$, reject otherwise

1: **function** $M_A(x)$
2: Compute $y \leftarrow f(x)$
3: **return** $O(y)$
4: **end function**

M_A **always halts.** f is computable in polynomial time, so computing $f(x)$ halts (after at most polynomially many steps). Then M_A makes one call to O, which halts because O decides B, and returns its answer.

Correctness. By the property of f, the fact that O decides B, and the code of M_A,

$$\begin{aligned} x \in A &\implies f(x) \in B \\ &\implies O(f(x)) \text{ accepts} \\ &\implies M_A(x) \text{ accepts,} \end{aligned}$$

$$\begin{aligned} x \notin A &\implies f(x) \notin B \\ &\implies O(f(x)) \text{ rejects} \\ &\implies M_A(x) \text{ rejects.} \end{aligned}$$

So M_A decides A given an oracle for B, that is, $A \leq_T B$.

A polynomial-time mapping reduction is thus a very restricted Turing reduction: it calls the oracle exactly once, returns the oracle's answer unchanged, and does only polynomial work before the call.

Q5.4 Understanding P, NP, and polynomial-time mapping reductions (d)

Assume $A \leq_p B$ and $B \leq_p C$. Then there are functions f and g and polynomials p and q such that

- f is computable in time at most $p(|x|)$ on input x, and $x \in A \iff f(x) \in B$ for all x;
- g is computable in time at most $q(|y|)$ on input y, and $y \in B \iff g(y) \in C$ for all y.

We may assume p and q have nonnegative coefficients (otherwise replace each coefficient by its absolute value, which only makes the bounds larger), so both are nondecreasing.

Define $h(x) = g(f(x))$: first compute $y = f(x)$, then compute and output $g(y)$.

Correctness. For every x, using the property of f and then the property of g with $y = f(x)$,

$$x \in A \iff f(x) \in B \iff g(f(x)) \in C \iff h(x) \in C.$$

Running time. Let $n = |x|$. Computing $y = f(x)$ takes at most $p(n)$ steps. The time to compute $g(y)$ is at most $q(|y|)$, which is polynomial in $|y|$, not in n, so we need to bound $|y|$ in terms of n. A Turing machine writes at most one tape cell per step, so after at most $p(n)$ steps the tape of the machine computing f holds at most $n + p(n)$ symbols (the n input cells plus at most $p(n)$ newly written ones). Hence

$$|y| = |f(x)| \leq n + p(n).$$

Since q is nondecreasing, computing $g(y)$ takes at most $q(|y|) \leq q(n + p(n))$ steps. The total time to compute $h(x)$ is at most

$$p(n) + q(n + p(n)).$$

Substituting a polynomial into a polynomial gives a polynomial (if p has degree a and q has degree b, then $q(n+p(n))$ has degree at most $\max(a, 1) \cdot b$), and the sum of two polynomials is a polynomial. So h is computable in time polynomial in $n = |x|$, the size of the input to A.

Therefore h is a polynomial-time computable function with $x \in A \iff h(x) \in C$, i.e., $A \leq_p C$.

Q6 Trick-or-Treating is (NP-)Hard

I show Ham-Cycle $\leq_p$ TSP. Since Ham-Cycle is NP-hard (lecture), this proves that TSP is NP-hard.

Step 1: the reduction. Given an unweighted graph $G = (V, E)$ with $n = |V|$ vertices, keep the same vertices, make the graph complete, give weight 1 to the pairs that are edges of G and weight 2 to the pairs that are not, and set the budget to n.

Input: An unweighted graph $G = (V, E)$
Output: A weighted complete graph G' and a budget k

```
function f(G)
    n ← |V|
    Initialize G' = (V, E') with E' = ∅
    for each pair of distinct vertices u, v ∈ V do
        Add the edge (u, v) to E'
        if (u, v) ∈ E then w(u, v) ← 1
        else w(u, v) ← 2
        end if
    end for
    return (G', k = n)
end function
```

G' is a complete weighted graph on V, so (G', n) is an instance of TSP. The reduction never looks for a Hamiltonian cycle; it only looks at which pairs are edges.

Step 2: polynomial time. The size of G is at least n. The loop runs $\binom{n}{2} = O(n^2)$ times, and each iteration adds one edge and does one lookup in E, which takes at most $O(|E|) = O(n^2)$ time. Writing $k = n$ takes $O(\log n)$ time. So f runs in $O(n^4)$ time, polynomial in the size of G.

In both directions below I use the following fact: a cycle that visits every one of the n vertices exactly once consists of exactly n edges (one leaving each vertex).

Step 3a: $G \in$ Ham-Cycle $\implies (G', n) \in$ TSP. Assume $G \in$ Ham-Cycle, and let H be a cycle in G that visits every vertex exactly once. H uses n edges, all of them in E. G' has the same vertex set and contains every pair as an edge, so H is also a cycle in G' that visits every vertex exactly once. Each edge of H is in E, so it has weight 1 in G', and the total weight of H in G' is $n \cdot 1 = n \leq k$. So $(G', n) \in$ TSP.

Step 3b: $(G', n) \in$ TSP $\implies G \in$ Ham-Cycle. Assume $(G', n) \in$ TSP, and let T be a cycle in G' of total weight at most n that visits every vertex exactly once. T uses exactly n edges, and every edge of G' has weight 1 or 2. If T used an edge of weight 2, its total weight would be at least $(n-1) \cdot 1 + 2 = n + 1 > n$, a contradiction. So every edge of T has weight 1. By construction, an edge of G' has weight 1 only if it is an edge of G. So all n edges of T are in E, which means T is a cycle in G that visits every vertex exactly once. So $G \in$ Ham-Cycle.

By Steps 3a and 3b, $G \in$ Ham-Cycle $\iff f(G) = (G', n) \in$ TSP, and by Step 2, f is computable in polynomial time. So Ham-Cycle $\leq_p$ TSP, and since Ham-Cycle is NP-hard, TSP is NP-hard.

Q7.1 Subset Sum (a)

Step 3: It constructs a target sum s that has $m+n$ decimal digits, where the first m digits are all **3** and the last n digits are all **1**.

That is,

$$s = \underbrace{33\cdots3}_{m}\,\underbrace{11\cdots1}_{n}.$$

Q7.2 Subset Sum (b)

Here $m = 2$ and $n = 3$, so by part (a)

$$s = 33111.$$

The formula $\phi = (x_1 \vee \overline{x_2} \vee x_3) \wedge (\overline{x_1} \vee x_2 \vee \overline{x_3})$ is satisfied by $x_1 = x_2 = x_3 = \text{true}$: the first clause is true because of x_1 (and x_3), and the second because of x_2. Following this assignment, take t_1, t_2, t_3, and then fill up the clause digits with a_1, a_2, b_2:

$$I = \{t_1, t_2, t_3, a_1, a_2, b_2\} = \{10100,\ 1010,\ 10001,\ 10000,\ 1000,\ 1000\}.$$

Number	$j=1$	$j=2$	$i=1$	$i=2$	$i=3$
t_1	1	0	1	0	0
t_2	0	1	0	1	0
t_3	1	0	0	0	1
a_1	1	0	0	0	0
a_2	0	1	0	0	0
b_2	0	1	0	0	0
sum	3	3	1	1	1

Check:

$$10100 + 1010 + 10001 + 10000 + 1000 + 1000 = 33111 = s.$$

I is a submultiset of A: it uses one copy of 10000 (of the two copies a_1, b_1 in A) and both copies of 1000 (a_2 and b_2). So $(A, s) \in$ Subset-Sum.

Q7.3 Subset Sum (c)

$\phi' = (x_1 \vee x_1 \vee x_1) \wedge (\overline{x_1} \vee \overline{x_1} \vee \overline{x_1})$ has $n = 1$ variable and $m = 2$ clauses, so all numbers have $m + n = 3$ digits. The literal x_1 appears in c_1 only, and $\overline{x_1}$ appears in c_2 only.

Number	$j = 1$	$j = 2$	$i = 1$
a_1	1	0	0
b_1	1	0	0
a_2	0	1	0
b_2	0	1	0
t_1	1	0	1
f_1	0	1	1
s	3	3	1

The Subset-Sum instance is

$$(A = \{100,\ 100,\ 10,\ 10,\ 101,\ 11\},\ s = 331).$$

This instance is not in Subset-Sum. The sum of all six numbers in A is $100 + 100 + 10 + 10 + 101 + 11 = 332$. A submultiset I of A with sum 331 would have to leave out numbers that sum to exactly $332 - 331 = 1$. Every number in A is at least 10, so this is impossible. Hence no submultiset of A sums to s.

The same thing in terms of the formula: the last digit of s is 1, so I must contain exactly one of t_1, f_1. If it contains t_1 but not f_1, the only numbers left with a 1 in the second digit are a_2 and b_2, so the second digit of the sum is at most $2 < 3$. If it contains f_1 but not t_1, the first digit is at most $2 < 3$ in the same way. This matches the fact that ϕ' is not satisfiable: setting x_1 true leaves clause c_2 unsatisfied, and setting it false leaves c_1 unsatisfied.

Q7.4 Subset Sum (d)

I number the digits $1, \ldots, m+n$ from the left as in the table, and call the first m the *clause digits* and the last n the *variable digits*. The following fact is used in this part and the next.

No-carry fact. *For any submultiset $I \subseteq A$ and any position d, the dth digit of $\sum_{a \in I} a$ equals the number of elements of I whose dth digit is* 1.

Proof: every digit of every number in A is 0 or 1, so it is enough to show that at most 9 numbers of A have a 1 in any given position; then adding up a column never produces a carry. In a variable digit $m+i$, only t_i and f_i have a 1. In a clause digit j, the numbers with a 1 are a_j, b_j, and those t_i or f_i whose literal (x_i or $\overline{x_i}$, respectively) appears in c_j. Different such numbers correspond to different literals of c_j, and c_j has three literals, so there are at most $2+3=5$ numbers with a 1 in digit j. In both cases the count is at most $5 \leq 9$. □

Now assume $\phi \in$ 3SAT, and let α be a satisfying assignment of ϕ. I use α to build a submultiset $I \subseteq A$ with sum s.

Variable numbers. For each $i = 1, \ldots, n$: if $\alpha(x_i) =$ true, put t_i into I; if $\alpha(x_i) =$ false, put f_i into I. Call the number chosen for x_i the *selected* number u_i. So u_i has a 1 in clause digit j exactly when the literal of x_i that is true under α appears in c_j.

Clause numbers. For each $j = 1, \ldots, m$, let r_j be the number of selected numbers $u_1, \ldots, u_n$ whose jth digit is 1.

- $r_j \geq 1$: α satisfies c_j, so c_j contains a literal that is true under α. If this literal is x_i, then $\alpha(x_i) =$ true, so $u_i = t_i$, and the jth digit of t_i is 1 because x_i appears in c_j. If it is $\overline{x_i}$, then $\alpha(x_i) =$ false, so $u_i = f_i$, and the jth digit of f_i is 1 because $\overline{x_i}$ appears in c_j.
- $r_j \leq 3$: selected numbers with a 1 in digit j correspond to different variables whose literals appear in c_j, and c_j has only three literals.

So $3 - r_j \in \{0, 1, 2\}$. If $3 - r_j = 1$, put a_j into I; if $3 - r_j = 2$, put both a_j and b_j into I; if $3 - r_j = 0$, put neither.

The sum of I is s. By the no-carry fact it is enough to count the 1s of I in each position.

- Variable digit $m+i$: the only numbers of A with a 1 here are t_i and f_i, and I contains exactly one of them. So this digit of the sum is 1.
- Clause digit j: the numbers of I with a 1 here are the r_j selected numbers counted above, plus the $3 - r_j$ numbers among a_j, b_j that were added. (The numbers $a_{j'}, b_{j'}$ for $j' \neq j$ have a 0 here.) So this digit of the sum is $r_j + (3 - r_j) = 3$.

So the sum of I has 3 in each of the first m digits and 1 in each of the last n digits, which is exactly s.

Therefore $I \subseteq A$ and $\sum_{a \in I} a = s$, i.e., $f(\phi) = (A, s) \in$ Subset-Sum.

Q7.5 Subset Sum (e)

Assume $(A, s) \in$ Subset-Sum, and let $I \subseteq A$ be a submultiset with $\sum_{a \in I} a = s$. I use I to build a satisfying assignment of ϕ. Here (A, s) is not an arbitrary instance but the one constructed from ϕ, so I can use its structure; in particular the no-carry fact from part (d) applies. By that fact, for each position d, the number of elements of I with a 1 in digit d equals the dth digit of s: it is 3 for each clause digit and 1 for each variable digit.

I contains exactly one of t_i, f_i for each i. The only numbers of A with a 1 in the variable digit $m + i$ are t_i and f_i. Exactly one element of I has a 1 in this digit, so exactly one of t_i, f_i is in I.

The assignment. Define α by

$$\alpha(x_i) = \begin{cases} \text{true} & \text{if } t_i \in I, \\ \text{false} & \text{if } f_i \in I. \end{cases}$$

By the previous paragraph exactly one of the two cases holds for each i, so α is a well-defined assignment to $x_1, \ldots, x_n$.

α satisfies every clause. Fix a clause c_j. Exactly three elements of I have a 1 in the clause digit j. Among the clause numbers, only a_j and b_j have a 1 in digit j, so they account for at most two of the three. Hence at least one of the three is a variable number: there is some i such that $t_i \in I$ or $f_i \in I$, and that number has a 1 in digit j.

- If $t_i \in I$ and the jth digit of t_i is 1: by construction the literal x_i appears in c_j, and $\alpha(x_i) = \text{true}$ because $t_i \in I$. So c_j contains a true literal.
- If $f_i \in I$ and the jth digit of f_i is 1: by construction the literal $\overline{x_i}$ appears in c_j, and $\alpha(x_i) = \text{false}$ because $f_i \in I$ (and so $t_i \notin I$). So $\overline{x_i}$ is true under α, and c_j contains a true literal.

In both cases α satisfies c_j. Since c_j was arbitrary, α satisfies every clause of ϕ.

Therefore ϕ is satisfiable, i.e., $\phi \in$ 3SAT.

Together with part (d) and the fact that the reduction runs in polynomial time, this shows 3SAT $\leq_p$ Subset-Sum, so Subset-Sum is NP-hard.

Q8 (Optional extra credit)

Since $L_1, L_2 \in \mathsf{NP} \cap \mathsf{coNP}$, there are four efficient verifiers:

- V_1 for L_1 and $\overline{V_1}$ for $\overline{L_1}$;
- V_2 for L_2 and $\overline{V_2}$ for $\overline{L_2}$.

So both "$x \in L_i$" and "$x \notin L_i$" have short certificates that can be checked in polynomial time. Write $L = L_1 \oplus L_2$. For every x,

$$x \in L \iff (x \in L_1 \text{ and } x \in \overline{L_2}) \text{ or } (x \in \overline{L_1} \text{ and } x \in L_2),$$
$$x \in \overline{L} \iff (x \in L_1 \text{ and } x \in L_2) \text{ or } (x \in \overline{L_1} \text{ and } x \in \overline{L_2}).$$

Each of the four cases is a statement that two of the verifiers can check, so a certificate says which case holds and gives one certificate for each of the two verifiers.

function $V(x, c)$ ▷ verifier for $L_1 \oplus L_2$
  if c is not of the form (b, c_1, c_2) with $b \in \{1, 2\}$ **then return** reject
  end if
  if $b = 1$ and $V_1(x, c_1)$ accepts and $\overline{V_2}(x, c_2)$ accepts **then return** accept
  end if
  if $b = 2$ and $\overline{V_1}(x, c_1)$ accepts and $V_2(x, c_2)$ accepts **then return** accept
  end if
  return reject
end function

function $\overline{V}(x, c)$ ▷ verifier for $\overline{L_1 \oplus L_2}$
  if c is not of the form (b, c_1, c_2) with $b \in \{1, 2\}$ **then return** reject
  end if
  if $b = 1$ and $V_1(x, c_1)$ accepts and $V_2(x, c_2)$ accepts **then return** accept
  end if
  if $b = 2$ and $\overline{V_1}(x, c_1)$ accepts and $\overline{V_2}(x, c_2)$ accepts **then return** accept
  end if
  return reject
end function

Efficiency. Each of V and $\overline{V}$ parses c and makes at most four calls to verifiers that run in time polynomial in $|x|$, so it runs in polynomial time. The certificates c_1, c_2 needed below have size polynomial in $|x|$, so $c = (b, c_1, c_2)$ does too.

V is correct, so $L \in \mathsf{NP}$.

($\Longrightarrow$) Suppose $x \in L$. If $x \in L_1$ and $x \notin L_2$, there are c_1, c_2 such that $V_1(x, c_1)$ and $\overline{V_2}(x, c_2)$ accept, so $V(x, (1, c_1, c_2))$ accepts. If $x \notin L_1$ and $x \in L_2$, there are c_1, c_2 such that $\overline{V_1}(x, c_1)$ and $V_2(x, c_2)$ accept, so $V(x, (2, c_1, c_2))$ accepts.

($\Longleftarrow$) Suppose $V(x, c)$ accepts for some $c = (b, c_1, c_2)$. If it accepted with $b = 1$, then $V_1(x, c_1)$ and $\overline{V_2}(x, c_2)$ accept, so $x \in L_1$ and $x \in \overline{L_2}$, because a verifier accepts some certificate only for strings in its language. If it accepted with $b = 2$, then in the same way $x \in \overline{L_1}$ and $x \in L_2$. In both cases x is in exactly one of L_1, L_2, so $x \in L$.

$\overline{V}$ is correct, so $\overline{L} \in \mathsf{NP}$, i.e., $L \in \mathsf{coNP}$.

($\Longrightarrow$) Suppose $x \in \overline{L}$, so x is in both of L_1, L_2 or in neither. If $x \in L_1$ and $x \in L_2$, there are c_1, c_2 such that $V_1(x, c_1)$ and $V_2(x, c_2)$ accept, so $\overline{V}(x, (1, c_1, c_2))$ accepts. If $x \notin L_1$ and $x \notin L_2$, there are c_1, c_2 such that $\overline{V_1}(x, c_1)$ and $\overline{V_2}(x, c_2)$ accept, so $\overline{V}(x, (2, c_1, c_2))$ accepts.

($\Longleftarrow$) Suppose $\overline{V}(x, c)$ accepts for some $c = (b, c_1, c_2)$. If $b = 1$, then $V_1(x, c_1)$ and $V_2(x, c_2)$ accept, so $x \in L_1 \cap L_2$. If $b = 2$, then $\overline{V_1}(x, c_1)$ and $\overline{V_2}(x, c_2)$ accept, so $x \notin L_1$ and $x \notin L_2$. In both cases x is not in exactly one of L_1, L_2, so $x \in \overline{L}$.

Hence $L_1 \oplus L_2 \in \mathsf{NP}$ and $L_1 \oplus L_2 \in \mathsf{coNP}$, that is, $L_1 \oplus L_2 \in \mathsf{NP} \cap \mathsf{coNP}$.