ancestors
- ◆ ANCESTOR_UUID CHAR(32)
- ◆ DESCENDANT_UUID CHAR(32)

Indexes ▶

uuids_attributes
- 📍 UUID CHAR(32)
- ◇ BASE_ID VARCHAR(10)
- ◇ SUBMISSION_ID VARCHAR(170)
- ◇ DESCENDANT_COUNT INT

Indexes ▶

uuids
- 🔑 UUID CHAR(32)
- ◇ ENTITY_TYPE VARCHAR(20)
- ◇ TIME_GENERATED TIMESTAMP
- ◇ USER_ID VARCHAR(50)
- ◇ USER_EMAIL VARCHAR(50)

Indexes ▶

files
- 📍 UUID CHAR(32)
- ◇ BASE_DIR VARCHAR(50)
- ◇ PATH MEDIUMTEXT
- ◇ CHECKSUM VARCHAR(50)
- ◇ SIZE BIGINT
- ◇ LAST_MODIFIED TIMESTAMP

Indexes ▶

data_centers
- 📍 UUID CHAR(32)
- ◇ DC_UUID VARCHAR(40)

1 more...

Indexes ▶

organs
- ◆ DONOR_UUID CHAR(32)
- ◇ ORGAN_CODE VARCHAR(8)
- ◇ ORGAN_COUNT INT

Indexes ▼

IDX_ORGAN_CODE

Note this model is NOT set to use global default settings. All settings should be explicit in this model

The model options for Foreign Key/Relationship defaults ON UPDATE and ON DELETE are set to NO ACTION.

Utility routines ▼
ancestor_PTR
all_descendants
2 routines

Version: 2.2
Add LAST_MODIFIED column to files table
Revised by: Karl Burke
2023-01-12