

Project Description: An Inliner for the Jive compiler

Nico Reissmann

December 12, 2014

Compilers have become an essential part of every modern computer system since their rise along with the emergence of machine-independent languages at the end of the 1950s. From the start, they not only had to translate between a high-level language and a specific architecture, but had to incorporate optimizations in order to improve code quality and be a par with human-produced assembly code. One such optimization performed by virtually every modern compiler is *inlining*. In principle, inlining is very simple: just replace a call to a function by an instance of its body. However, in practice careless inlining can easily result in extensive *work* and *code duplication*. An inliner must therefore decide carefully when and where to inline a function in order to achieve good performance without unnecessary code bloat.

The overall goal of this project is to implement and evaluate an inliner for the Jive compiler back-end. The project is split in a practical and an optional theoretical part. The practical part includes the following:

- Implementation of an inliner for the Jive compiler back-end. The inliner must be able to handle recursive functions and allow for the configuration of different heuristics to permit rapid exploration of the parameter space.
- An evaluation of the implemented inliner. A particular emphasis is given to different heuristics and their consequences for the resulting code in terms of work and code duplication.

The Jive compiler back-end uses a novel intermediate representation (IR) called the Regionalized Value State Dependence Graph (RVSDG). If time permits, the theoretical part of the project is going to clarify the consequences of using the RVSDG along with an inliner. It tries to answer the following research questions:

- What impact does the RVSDG have on the design of an inliner and the process of inlining?
- Does the RVSDG simplify/complicate the implementation of an inliner and the process of inlining compared to other commonly used IRs?

The outcome of this project is threefold:

1. A working implementation of an inliner in the Jive compiler back-end fulfilling the aforementioned criteria.
2. An evaluation of the implemented inliner.
3. A project report following the structure of a research paper.