

Lab07

Xiaoxuan Teng (PID: A69028742)

2024-02-04

```
url <- "https://tinyurl.com/UK-foods"
x <- read.csv(url)
dim(x)
```

```
[1] 17  5
```

Q1. How many rows and columns are in your new data frame named x? What R functions could you use to answer this questions?

17 rows and 5 columns. Use dim() function (or nrow() & ncol()) to answer this.

```
## Preview the first 6 rows
#head(x)

rownames(x) <- x[,1]
x <- x[,-1]
head(x)
```

	England	Wales	Scotland	N.Ireland
Cheese	105	103	103	66
Carcass_meat	245	227	242	267
Other_meat	685	803	750	586
Fish	147	160	122	93
Fats_and_oils	193	235	184	209
Sugars	156	175	147	139

```
# another method to set the correct row names
x <- read.csv(url, row.names=1)
head(x)
```


	England	Wales	Scotland	N.Ireland
Cheese	105	103	103	66
Carcass_meat	245	227	242	267
Other_meat	685	803	750	586
Fish	147	160	122	93
Fats_and_oils	193	235	184	209
Sugars	156	175	147	139

Q2. Which approach to solving the ‘row-names problem’ mentioned above do you prefer and why? Is one approach more robust than another under certain circumstances?

I prefer the second method. This is because when I run the `x <- x[, -1]` code multiple times, it will keep removing the first column of the dataset and setting it as the row name.

If I want to manipulate the dataset before setting the row names, then the first method would allow me to do so. If the dataset is very large, then the second method would be preferred as it can be more time-efficient and save more memory.


```
barplot(as.matrix(x), beside=T, col=rainbow(nrow(x)))
```



Q3: Changing what optional argument in the above `barplot()` function results in the following plot?

Change `beside=FALSE` or leave it out. The default setting of `barplot()` is `beside=FALSE`.


```
barplot(as.matrix(x), beside=F, col=rainbow(nrow(x)))
```



Q5: Generating all pairwise plots may help somewhat. Can you make sense of the following code and resulting figure? What does it mean if a given point lies on the diagonal for a given plot?

pairs() function generate a matrix of scatterplots. Where **x** is the dataset to be visualized; **col** set the color of the points which represents different groups within the data; **pch** sets the plotting character as filled circle. Each plot represents the relationship between two variables in the dataset. In each scatterplot, the points represent individual observations in the dataset with their respective values for the two variables being compared. When a point lies on the diagonal, it would mean that for that particular observation, the values of the two variables are equal.

```
pairs(x, col=rainbow(10), pch=16)
```



Q6. What is the main differences between N. Ireland and the other countries of the UK in terms of this data-set?

Compared to the other countries, N. Ireland's data points do not align tightly along a straight line. This suggest that the variables for N. Ireland and those for the other countries have less strong linear relationships.

```
pca <- prcomp(t(x))
summary(pca)
```


Importance of components:

	PC1	PC2	PC3	PC4
Standard deviation	324.1502	212.7478	73.87622	2.921e-14
Proportion of Variance	0.6744	0.2905	0.03503	0.000e+00
Cumulative Proportion	0.6744	0.9650	1.00000	1.000e+00

Q7. Complete the code below to generate a plot of PC1 vs PC2. The second line adds text labels over the data points.


```
# Plot PC1 vs PC2
plot(pca$x[,1], pca$x[,2], xlab="PC1", ylab="PC2", xlim=c(-270,500))
```

```
text(pca$x[,1], pca$x[,2], colnames(x))
```



Q8. Customize your plot so that the colors of the country names match the colors in our UK and Ireland map and table at start of this document.

```
plot(pca$x[,1], pca$x[,2], xlab="PC1", ylab="PC2", xlim=c(-270,500))
text(pca$x[,1], pca$x[,2], colnames(x), col = c("orange", "red", "blue", "darkgreen"))
```



```
summary(pca)
```

Importance of components:

	PC1	PC2	PC3	PC4
Standard deviation	324.1502	212.7478	73.87622	2.921e-14
Proportion of Variance	0.6744	0.2905	0.03503	0.000e+00
Cumulative Proportion	0.6744	0.9650	1.00000	1.000e+00

```
pca$sdev
```

```
[1] 3.241502e+02 2.127478e+02 7.387622e+01 2.921348e-14
```


```
v <- round( pca$sdev^2/sum(pca$sdev^2) * 100 )
v
```

```
[1] 67 29 4 0
```


```
z <- summary(pca)
z$importance
```

	PC1	PC2	PC3	PC4
Standard deviation	324.15019	212.74780	73.87622	2.921348e-14
Proportion of Variance	0.67444	0.29052	0.03503	0.000000e+00
Cumulative Proportion	0.67444	0.96497	1.00000	1.000000e+00

```
barplot(v, xlab="Principal Component", ylab="Percent Variation")
```




```
## Lets focus on PC1 as it accounts for > 90% of variance
par(mar=c(10, 3, 0.35, 0))
barplot( pca$rotation[,1], las=2 )
```

Q9: Generate a similar ‘loadings plot’ for PC2. What two food groups feature prominently and what does PC2 mainly tell us about?

Fresh potatoes and soft drinks are two prominent food groups. “Fresh potatoes” has a strong negative loading, and “soft drinks” has a strong positive loading on PC2. PC2 seems mainly capture a variance in the dataset between these two types of consumption.


```
par(mar=c(10, 3, 0.35, 0))
barplot( pca$rotation[,2], las=2 )
```




```
library(ggplot2)

df <- as.data.frame(pca$x)
df_lab <- tibble::rownames_to_column(df, "Country")

# Our first basic plot
ggplot(df_lab) +
  aes(PC1, PC2, col=Country) +
  geom_point()
```




```
ggplot(df_lab) +  
  aes(PC1, PC2, col=Country, label=Country) +  
  geom_hline(yintercept = 0, col="gray") +  
  geom_vline(xintercept = 0, col="gray") +  
  geom_point(show.legend = FALSE) +  
  geom_label(hjust=1, nudge_x = -10, show.legend = FALSE) +  
  expand_limits(x = c(-300,500)) +  
  xlab("PC1 (67.4%)") +  
  ylab("PC2 (28%)") +  
  theme_bw()
```




```
ld <- as.data.frame(pca$rotation)
ld_lab <- tibble::rownames_to_column(ld, "Food")


ggplot(ld_lab) +
  aes(PC1, Food) +
  geom_col()
```



```
ggplot(ld_lab) +
  aes(PC1, reorder(Food, PC1), bg=PC1) +
  geom_col() +
  xlab("PC1 Loadings/Contributions") +
  ylab("Food Group") +
  scale_fill_gradient2(low="purple", mid="gray", high="darkgreen", guide=NULL) +
  theme_bw()
```



```
## The inbuilt biplot() can be useful for small datasets
biplot(pca)
```



2. PCA of RNA-seq data

```
url2 <- "https://tinyurl.com/expression-CSV"
rna.data <- read.csv(url2, row.names=1)
# head(rna.data)
dim(rna.data)
```


```
[1] 100 10
```

Q10: How many genes and samples are in this data set?

There are 100 genes and 10 samples in the data set.

```
## Again we have to take the transpose of our data
pca <- prcomp(t(rna.data), scale=TRUE)

## Simple un polished plot of pc1 and pc2
plot(pca$x[,1], pca$x[,2], xlab="PC1", ylab="PC2")
```




```
summary(pca)
```

Importance of components:

	PC1	PC2	PC3	PC4	PC5	PC6	PC7
Standard deviation	9.6237	1.5198	1.05787	1.05203	0.88062	0.82545	0.80111
Proportion of Variance	0.9262	0.0231	0.01119	0.01107	0.00775	0.00681	0.00642
Cumulative Proportion	0.9262	0.9493	0.96045	0.97152	0.97928	0.98609	0.99251

	PC8	PC9	PC10
Standard deviation	0.62065	0.60342	3.345e-15
Proportion of Variance	0.00385	0.00364	0.000e+00
Cumulative Proportion	0.99636	1.00000	1.000e+00

```
plot(pca, main="Quick scree plot")
```




```
## Variance captured per PC
pca.var <- pca$sdev^2

## Percent variance is often more informative to look at
pca.var.per <- round(pca.var/sum(pca.var)*100, 1)
pca.var.per
```



```
[1] 92.6  2.3  1.1  1.1  0.8  0.7  0.6  0.4  0.4  0.0
```


```
barplot(pca.var.per, main="Scree Plot",
        names.arg = paste0("PC", 1:10),
        xlab="Principal Component", ylab="Percent Variation")
```



```
## A vector of colors for wt and ko samples
colvec <- colnames(rna.data)
colvec[grep("wt", colvec)] <- "red"
colvec[grep("ko", colvec)] <- "blue"

plot(pca$x[,1], pca$x[,2], col=colvec, pch=16,
     xlab=paste0("PC1 (", pca.var.per[1], "%)"),
     ylab=paste0("PC2 (", pca.var.per[2], "%)"))


text(pca$x[,1], pca$x[,2], labels = colnames(rna.data), pos=c(rep(4,5), rep(2,5)))
```



```
library(ggplot2)


df <- as.data.frame(pca$x)

# Our first basic plot
ggplot(df) +
  aes(PC1, PC2) +
  geom_point()
```



```
# Add a 'wt' and 'ko' "condition" column
df$samples <- colnames(rna.data)
df$condition <- substr(colnames(rna.data),1,2)


p <- ggplot(df) +
  aes(PC1, PC2, label=samples, col=condition) +
  geom_label(show.legend = FALSE)
p
```



```
p + labs(title="PCA of RNASeq Data",
  subtitle = "PC1 clearly separates wild-type from knock-out samples",
  x=paste0("PC1 (", pca.var.per[1], "%)"),
  y=paste0("PC2 (", pca.var.per[2], "%)"),
  caption="Class example data") +
theme_bw()
```

PCA of RNASeq Data

PC1 clearly separates wild-type from knock-out samples



Class example data