

All Stainless Steel Bimetal Thermometer Model FI

Nominal size: 3", 4", 5", 6"
 Accuracy: Class 1.0 according to N13190
 1.5% or 1.0% according to JB/T 8803-1998
 Range: -70...30 °C to 0...600 °C
 Dual scale on request

FEATURES

- Rugged stainless steel construction
- Applies to harsh and aggressive environments
- Fast response
- External zero adjustment
- Dry or liquid filled

APPLICATIONS

- Chemical and petrochemical industry
- Machine and apparatus construction
- Food and beverage industry
- Water treatment industry
- Pulp and paper industry



SPECIFICATIONS

General

Dial size	3"(80mm), 4"(100mm), 5"(127mm), 6"(150mm)
Construction	Cylindrical case with crimp ring, hermetically sealed and external adjustment
Measuring principle	Bimetallic coil
Range [°C]	-70...600 °C (Note: Ranges in °F and dual scale, or other specific range on request)
Overtemperature	130% F.S
Accuracy	Class 1.0 according to N13190 1.5% or 1.0% according to JB/T 8803-1998
Stem diameter	¼"(6.4mm), 6mm, 8mm, 10mm
Stem length	60...1500 mm, Minimum length depends on range Length > 1500mm on request

Process connection

Connection	Lower mount, Back mount, Every angle position
Connection type	Fix thread, Swivel thread, Sliding thread, Tri-clamp connection
Connection size	1/2NPT, G1/2, M20×1.5, M27×2 Other connections on request

Material

Connector&Stem	SS 304, or SS 316L
Case	SS 304, or SS 316L
Window	Instrument glass, Safety glass
Dial	Aluminum, black marks, white background
Pointer	Aluminum, black

SPECIFICATIONS

Others

Ingress protection	IP66 (EN 60 529/IEC 529)
Case filling	Silicon oil (Maximum range up to 300 °C (ambient temperature maximum 65 °C)
Storage and transport	-50...70 °C
Ambient temperature	-40...70 °C
Max. pressure at stem	2.5 Mpa
Certificates	Calibration report, Material Other certificates on request
Accessories	Thermowells

Normal range

-50/50 °C	0/160 °C
-40/60 °C	0/200 °C
-30/70 °C	0/250 °C
-20/40 °C	0/300 °C
-20/80 °C	0/400 °C
-20/120 °C	0/500 °C
-20/160 °C	0/600 °C
0/60 °C	
0/100 °C	
0/120 °C	
0/150 °C	
Range in °F or dual scale on request	

All Stainless Steel Bimetal Thermometer

Model FI

Order code		40	=	FI	=	L	=	60	=	E	=	300	=	-40/60	=	C	=	SD08
Dial Size																		
30	3" (80 mm)	30																
40	4" (100 mm)	40																
50	5" (125 mm)	50																
60	6" (160 mm)	60																
Model																		
FI	bimetal type	FI																
Case filling																		
	No filling																	
L	filled case					L												
Process connection																		
60	Fixed 1/2 NPT Male	60																
57	Fixed 3/8 NPT Male	57																
62	Fixed 3/4 NPT Male	62																
105	Fixed 3/4 BSPT Male	105																
101	Fixed 1/2 BSPT Male	101																
65	Fixed M20X1.5 Male	65																
61	Fixed G1/2A Male	61																
63	Fixed G3/4A Male	63																
103	Fixed M27X2 Male	103																
201	Fixed ZG3/8 (3/8 BSPT) Male	201																
90	Sliding M20X1.5 Male	90																
71	Sliding G1/2A Male	71																
73	Sliding G3/4A Male	73																
97	Sliding M27X2 Male	97																
99	Sliding 1/2 BSPT Male	99																
72	Sliding 3/4 NPT Male	72																
111	Sliding 3/8 NPT Male	111																
202	Sliding ZG3/8 (3/8 BSPT) Male	202																
203	Sliding ZG3/4 (3/4 BSPT) Male	203																
70	Sliding 1/2 NPT Male	70																
87	swivel M20x1.5 Male	87																
80	swivel G1/2A Male	80																
88	swivel M20X1.5 Female	88																
81	swivel G1/2A Female	81																
122	swivel G3/4 Female	122																
204	swivel M27X2 Male	204																
205	swivel G3/4 Male	205																
206	swivel M27X2 Female	206																
Mounting direction																		
L	Lower									L								
R	back										R							
E	every angle										E							
Stem length																		
60-1500 mm										60-1500								
Range																		
-50/50	-30/70	-10/50				0/150				0/500								
-50/150	-20/40	0/50				0/160				0/600								
-50/200	-20/80	0/60				0/200												
-50/300	-20/100	0/80				0/250												
-40/60	-20/120	0/100				0/300												
-40/80	-20/160	0/120				0/400												
Unit																		
C	°C															C		
F	°F															F		
Option																		
SD06	6mm stem																SD06	
SD08	8mm stem																SD08	
SD09	9mm stem																SD09	
SD10	10mm stem																SD10	
AN15	JB/T8803 1.5%																AN15	
AN10	JB/T8803 1.0%																AN10	
NH	Tag plate																NH	
CS	Dual range																CS	
SG	Safety glass																SG	
YW	316L Case																YW	
3L	316L connector																3L	
CD6	Material Certificate																CD6	
C4	Calibration Report																C4	