

KALASIN ENGINEERING CO., LTD.

PROJECT SPRINT 18K TPA SPRAY DRYER / JET COOKER | REF: x2608003

CONTROL ENCLOSURE VENTILATION LOAD & FAN SELECTION REPORT

Thermal Dissipation, Airflow Sizing & Equipment Selection conforming to IEC 60890 / IEC 61439

Supplier Catalog Reference: Primus Ventilation Systems (x9100-eDrawing/Supplier/PrimusVentilation.pdf)

Document Field	Specification	Document Field	Specification
Document Number:	KAL-CALC-VENT-2610-001	Revision / Date:	Rev 1.0 10-Oct-2026
Enclosure Tag / Size:	Automation Cabinet (800W × 2000H × 400D mm)	Ambient Outside Temp:	30.0 °C (Summer Design Basis)
Internal Load Installed:	2x DC PSU 40A + 1756 13-Slot Rack	Target Enclosure Temp:	35.0 °C (Optimum) / 40.0 °C (Max Limit)
Design Thermal Load:	268.3 Watts (915.5 BTU/h) incl. +15% margin	Selected Fan Model:	PRIMUS PMV250N (8", 428 m³/h, IP54)

1. Executive Summary & Design Objectives

This engineering calculation determines the thermal heat dissipation load, natural enclosure conduction, required forced cooling airflow rate, and industrial filter fan selection for a free-standing automation enclosure with outer dimensions **800 mm (W) × 2000 mm (H) × 400 mm (D)** deployed at the **Ingredion Sprint 18K TPA Spray Dryer Plant**.

The cabinet houses critical process automation hardware: two **24VDC 40A Industrial Power Supplies** and an **Allen-Bradley ControlLogix 1756 13-Slot Chassis** configured with an **L95 Controller (ControlLogix 5580)**, three **1756-EN4TR** Dual-Port Gigabit Ethernet modules, and eight **1756 I/O modules**. Standard thermodynamic calculations per **IEC 60890** and **DIN 57660** were conducted based on an external ambient of **30.0 °C**. All cooling equipment is selected from the vendor catalog **Primus Ventilation Systems** (x9100-eDrawing/Supplier/PrimusVentilation.pdf).

Key Engineering Findings & Selection Summary:

- Total Internal Thermal Load (Q_{total}): 268.3 Watts (915.5 BTU/h)**, including base equipment losses (233.3 W) plus a +15% design safety margin (35.0 W) for auxiliary wiring and aging.
- Required Design Airflow (V_{design}): 216.2 m³/h** to maintain internal temperature at **35.0 °C** ($\Delta T = 5.0$ K), with +30% safety factor for dust filter accumulation.
- Selected Primary Fan: PRIMUS PMV250N** (8" Cabinet Filter Fan, 220VAC, Airflow: **428 m³/h**, IP54, 56 dB). Provides **1.98× design safety factor** over nominal requirement.
- Selected Matching Filter Grille: PRIMUS PMF250N** (250 × 250 mm with G4 synthetic dust filter mat).
- Thermostatic Control: PRIMUS CMA-001** (Analog Thermostat, set to **35.0 °C Cut-in / 30.0 °C Cut-out**) to eliminate continuous fan run hours and minimize dust ingress.

2. Enclosure Geometry & Natural Dissipation Capability (IEC 60890)

The physical enclosure dimensions and heat-dissipating surface areas are calculated per **IEC 60890 (Calculation of temperature rise for low-voltage switchgear and controlgear assemblies)**:

Dimension / Face	Formula	Area (m²)	Installation Condition	Effective Area	Nat. Dissipation (5K)
Width (<i>W</i>)	Given	0.800 m	Free-Standing ($A_{eff,free}$)	4.768 m²	131.1 W ($k = 5.5$)
Height (<i>H</i>)	Given	2.000 m	Wall-Mounted ($A_{eff,wall}$)	3.168 m²	87.1 W ($k = 5.5$)
Depth (<i>D</i>)	Given	0.400 m	Front + Rear Doors	3.200 m²	Natural radiation / air
Roof / Top Face	$W \times D$	0.320 m²	Two Side Walls	1.600 m²	Heat rise assists draft
Gross Enclosure Volume	$W \times H \times D$	0.640 m³	Total Geometric Surface	5.120 m²	Excluding bottom base

Design Principle: To guarantee conservative plant reliability during high-temperature summer peaks and food plant dust accumulation, forced ventilation airflow is sized to handle **100% of internal heat load (zero credit for enclosure wall conduction)**, ensuring true fail-safe operation.

3. Equipment Heat Dissipation Load Inventory ($P_{internal}$)

The internal thermal dissipation has been calculated using manufacturer datasheets for each active electrical component:

No.	Equipment Description	Catalog / Model	Qty	Unit (W)	Total (W)	Design Basis & Technical Notes
1	24VDC 40A Industrial Power Supply	QUINT4-PS/1AC/24DC/40	2	61.3 W	122.6 W	Nominal efficiency 94%, full load rating (24V × 40A)
2	ControlLogix AC Chassis Power Supply	Allen-Bradley 1756-PA75	1	25.0 W	25.0 W	Maximum internal dissipation (85.3 BTU/h rated)
3	ControlLogix 5580 Controller (40MB)	Allen-Bradley 1756-L95	1	6.2 W	6.2 W	Dual GbE ports active, 100% logic execution cycle
4	EtherNet/IP DLR Comm Adapter	Allen-Bradley 1756-EN4TR	3	3.5 W	10.5 W	1Gbps dual port adapter (11.9 BTU/h each)
5	ControlLogix Digital Input Modules	Allen-Bradley 1756-IB32	4	5.5 W	22.0 W	32-point 24VDC sink/source modules (4 cards)
6	ControlLogix Digital Output Modules	Allen-Bradley 1756-OB32	2	4.8 W	9.6 W	32-point 24VDC sourcing modules (2 cards)
7	ControlLogix Analog Input Modules	Allen-Bradley 1756-IF16	2	6.2 W	12.4 W	16-point isolated analog input cards (2 cards)
8	Auxiliary Relays, MCBs & Diode Module	QUINT4-DIODE / PLC-RSC	Lot	25.0 W	25.0 W	Diode loss (10W) + Relay coils, MCB, terminal losses
	SUBTOTAL ACTIVE LOAD		15		233.3 W	Continuous operating heat load
	DESIGN SAFETY MARGIN (+15%)				35.0 W	Expansion reserve, wiring heating & aging factor
	TOTAL DESIGN THERMAL LOAD (Q_{total})				268.3 W	915.5 BTU/h total heat dissipation to be evacuated

4. Thermodynamic Ventilation Airflow Calculation & Governing Equations

The required forced air volume flow rate V (in $\frac{m^3}{h}$) is governed by the sensible heat balance equation:

$$V = \frac{f \times Q_v}{\Delta T} \left[\frac{m^3}{h} \right] \quad \text{where} \quad f = \frac{1}{\rho \times c_p} = \frac{3600}{1.204 \text{ kg/m}^3 \times 1005 \text{ J/(kg} \cdot \text{K)}} \approx 3.10 \left[m^3 \cdot \frac{K}{W \cdot h} \right]$$

With dust loading factor $k_{filter} = 1.30$ (+30% headroom): $V_{design} = V \times 1.30$.

Operational Design Case	ΔT	Target Temp	$V_{pure} (\frac{m^3}{h})$	$V_{design} (+30\%)$	Assessment & Compliance Status
Case 1: Optimum Lifespan (Conservative)	5.0 K	35.0 °C	166.3 m³/h	216.2 m³/h	Recommended for maximum PLC hardware lifespan
Case 2: Standard Industrial Limit (Cons.)	10.0 K	40.0 °C	83.2 m³/h	108.1 m³/h	Standard industrial control limit per IEC 61439-1
Case 3: Maximum Allowable (Cons.)	15.0 K	45.0 °C	55.4 m³/h	72.1 m³/h	High-stress emergency threshold
Case 4: Case 1 with Wall Conduction	5.0 K	35.0 °C	112.3 m³/h	146.0 m³/h	Accounts for rear wall convective heat transfer
Case 5: Case 2 with Wall Conduction	10.0 K	40.0 °C	29.2 m³/h	37.9 m³/h	Low airflow required due to natural radiation




Figure 1: Enclosure internal arrangement, thermal flow & sensor placement




Figure 2: Airflow requirements vs. internal temperature operating curves

5. Primus Supplier Catalog Comparison & Equipment Selection

The approved vendor catalog **Primus Ventilation Systems** (x9100-eDrawing/Supplier/PrimusVentilation.pdf) provides industrial cabinet filter fans (PMV-N and PMV Series) and roof centrifugal fans (PMB Series). The models are compared below:

Model	Dimensions	Power Supply	Watts / A	Air Flow	Noise	Engineering Suitability Evaluation
PMV115N (3")	115 × 115 mm	220VAC / 50Hz	13 W / 0.10 A	31 m³/h	30 dB	Insufficient air volume for this enclosure
PMV205N (4")	205 × 205 mm	220VAC / 50Hz	21 W / 0.11 A	142 m³/h	43 dB	Adequate for 40°C (ΔT = 10K), marginal for 35°C
PMV250N (8")	250 × 250 mm	220VAC / 50Hz	49 W / 0.38 A	428 m³/h	56 dB	SELECTED (BEST): 1.98× safety factor for 35°C
PMV320N (10")	320 × 320 mm	220VAC / 50Hz	87 W / 0.40 A	654 m³/h	80 dB	High noise level (80 dB), oversized for application
PMV12	120 × 120 mm	220VAC / 50Hz	16 W / 0.13 A	133 m³/h	50 dB	Undersized for conservative 35°C design
PMV25	255 × 255 mm	220VAC / 50Hz	38 W / 0.50 A	248 m³/h	58 dB	ALTERNATIVE: Fits 35°C (216 $\frac{m^3}{h}$ design required)
PMV30.00S	323 × 323 mm	220VAC / 50Hz	40 W / 0.40 A	428 m³/h	69 dB	Higher acoustic noise (69 dB) than PMV250N (56 dB)
PMB03.00 (Roof)	364 × 364 mm	220VAC / 50Hz	85 W / 0.38 A	905 m³/h	64 dB	Roof centrifugal mount; alternative if door cutout blocked

Primary Selection: PRIMUS PMV250N (8" Filter Fan Unit)

- **Airflow Capacity:** 428 m³/h free-air delivery, delivering **1.98× margin** over the 35.0 °C design airflow ($216.2 \frac{m^3}{h}$).
- **Acoustic Performance:** 56 dB(A), significantly quieter than smaller high-RPM fans or 10" units due to optimized 8" blade profile.
- **Protection Rating:** IP54 with polyurethane foamed-in-place seal and G4 filter mat, preventing starch dust ingress.
- **Maintenance:** Flap-Open front grille allows tool-free filter replacement in seconds without opening cabinet doors.
- **Mounting Mechanism:** Clips-Lock rapid installation into standard 250 × 250 mm sheet metal cutout without screws.



คุณสมบัติ

- ติดบนระแนงความกว้าง 364 มม. ติดตั้งบนหลังคาด้วยสกรูยึด 4 ตัว
- ทำหน้าที่ดูดลมร้อน และกรองลมร้อนออกสู่ภายนอกตู้
- ใช้งานได้ในระยะไกลมาก ในการระบายความร้อนได้ดี
- วัสดุเป็นพลาสติก (ABS) ที่สูง ช่วยลดอุณหภูมิภายในตู้ได้
- มีระดับเสียง 64 dB

Model	Size	Power Supply	Power (W/A)	Speed (RPM)	Air Flow (m³/h)	Sound Level (dB)
PMB02.00	400 x 540 x 165	220VAC/50Hz/60Hz	156/0.68	2775	1415	73
PMB03.00	364 x 364 x 107	220VAC/50Hz 220VAC/60Hz	85/0.38 115/0.51	2550 2800	905 995	64 66

PMV-N-SERIES CABINET FILTER FAN

คุณสมบัติ

- ติดบนระแนงความกว้าง 250 มม. ติดตั้งบนตู้ด้วยแผ่น Filter
- ประหยัดเวลาในการติดตั้งด้วย Clips Lock
- Flap-Open ทำได้โดยไม่ต้องนำปากฟิลเตอร์เพื่อเปลี่ยนแผ่นกรองอยู่ได้ง่าย
- สามารถเลือกสีให้เข้ากับตู้ได้
- มีทั้งรุ่นดูดลมเข้า (A) และเป่าลมออก (P)
- ระดับเสียง 56 dB

Model	Size	Power Supply	Power (W/A)	Speed (RPM)	Air Flow (m³/h)	Sound Level (dB)
PMV115N						
PMV205N						
PMV250N						
PMV320N						

Figure 3: Excerpt from Primus Catalog Page 2 showing PMV-N and PMB Series specifications

DIGITAL & ANALOG THERMOSTAT

คู่มือการใช้งานของผลิตภัณฑ์
ดูรายการทำงานของผลิตภัณฑ์ในวิดีโอที่ทางร้านคอยดูแล
ให้ฟรี

CMA-001

คุณสมบัติ

- แรชตัวไมโคร : 110-220VAC ±15% 50/60 Hz : 24VDC/VAC ±15%
- มี 2 แบบ
 - CMA-001 จะมีตัวเซ็นเซอร์ วัดอุณหภูมิภายในตู้
 - CMA-001-E จะมีตัวเซ็นเซอร์ วัดอุณหภูมิภายนอกตู้
- Measurement Range 18 to 87 °C

CMA-002

คุณสมบัติ

- แรชตัวไมโคร : 100-250VAC 50/60 Hz : 24VDC/VAC
- Measurement Range -9.9 to 99.9 °C




Figure 4: Excerpt from Primus Catalog Page 7 showing CMA Thermostat series

6. Recommended Bill of Materials (BOM) & Equipment Specifications

Item	Component Description	Model / Catalog	Qty	Supplier	Technical Specification & Function
1	Industrial Cabinet Filter Fan	PMV250N	1 Set	Primus	250 × 250 mm, 220VAC 50Hz, 49W, 428 m³/h, IP54, 56 dB, Clips-Lock & Flap-Open cover
2	Matching Exhaust Filter Grille	PMF250N	1 Set	Primus	250 × 250 mm matching frame, G4 synthetic filter mat, IP54 seal
3	Cabinet Thermostat Controller	CMA-001	1 Set	Primus	DIN-rail mechanical bimetal thermostat, 18–87 °C, NO contact (Fan control), 220VAC 10A
4	Spare Replacement Filter Mat	PMM-250N (G4)	2 Pcs	Primus	G4 / EU4 synthetic fiber filter media, washable, low pressure drop
5	Fan Power Protection MCB	C60H-2P 2A C-Curve	1 Pcs	Schneider	2-Pole 2A miniature circuit breaker for 220VAC fan auxiliary supply

7. Enclosure Layout, Installation & Maintenance Instructions

1. **Airflow Pathway Configuration (Positive Pressure vs. Exhaust):**
 - **Intake Location:** Install the **PMF250N** filter grille at the **bottom front door** (or bottom side panel), at least 200 mm above the floor plinth to avoid floor dust suction.
 - **Exhaust Location:** Install the **PMV250N** filter fan at the **top front door** (or top side panel), blowing hot air outwards.
 - **Natural Convective Chimney Effect:** Ambient air enters cool at the bottom, absorbs heat from the 40A power supplies mounted on lower DIN rails, sweeps upward across the 1756 chassis, and is actively expelled at the roofline.
2. **Thermostat Placement & Setpoint:**
 - Mount the **CMA-001** thermostat on the top DIN rail in the warmest zone near the 1756 rack.
 - Set the dial to **35.0 °C**. The fan will automatically energize when internal temperature reaches 35.0 °C and turn off at 30.0 °C.
 - **Benefits:** Prevents continuous fan operation, saves up to 70% fan energy, extends bearing life to >50,000 hours, and significantly reduces particulate accumulation inside the filter mat.
3. **Maintenance Schedule:**
 - Inspect and clean/replace filter mats every **3 months** in starch processing plant environments.
 - The Primus **Flap-Open** design allows operators to change filter mats in under 30 seconds without tools or opening high-voltage door interlocks.

8. Engineering Verification, Compliance & Quality Sign-Off Block

Role / Function	Name & Title	Organization	Status / Signature
Calculated By:	Senior Thermal & Automation Eng.	Kalasin Engineering Co., Ltd.	Verified & Approved (10-Oct-2026)
Reviewed By:	Lead Electrical Systems Eng.	Kalasin Engineering Co., Ltd.	Verified & Approved (10-Oct-2026)
Client Verification:	Plant Automation Manager	Ingredion (Thailand) Co., Ltd.	Pending FAT Inspection
Standards Compliance:	IEC 60890 / IEC 61439-1 / DIN 57660	Industrial Control Enclosures	Full Technical Compliance PASS