- · Answers only -

CSE 461 - HW4 - Yousef James 3/11/19 # (cse 461 only do 6 questions, any more is extra points!) \* \* Or. Tong Yu #IA) P3 should deliver the message immediately

C3[2] = tm[2]-1 and C3[K]>= tm[K] where (K = 1,3,4) #18) We know that C2[]=tm[2]-1, but C2[4] Ltm [4] . Pz should buffer message until it receives the previous message from P.

#3 C is inconsistent cut because:

$$te > \begin{pmatrix} C_1 & [1] \\ C_2 & [2] \end{pmatrix} = \begin{pmatrix} 2 \\ 2 \\ 3 \end{pmatrix}$$
and since  $CE_1 = TCE_1$ 

$$E_1 = TCE_1$$

$$E_2 = TCE_1$$

Fig. Care = \$2 \tag{6} \text{ for } \text{ for

C31

032

\$10

\$0

· Condition I is needed to guarantee the mutual exclusion b/c all the queues that each process needs to be in synchronization. Since each of the processes own giver might not be updated the same as the other. 2 processes might think that they are the TOP of queue, when they are not. -> This condition (1) serves as a substitution of shared memory, since they do not have shared memory . If condition 2 is removed, the algorithim still works uncler a certain case. A" release message" serves as a reply. A release message from the process who entered the Critical Section can signal another process who's pext in give, to prepare another process to enter the Critical Section . (2,A),(1,B)

. It is not necessary. If it is executing the Critical section, then it already has usited the C.S.; then it doesn't need to be @ the top of the gueve when we exit the contral section, process Pi removes it's request from the head of its request - queve and sends a timestamp RELEASE to every other process. release (IA) (B->CS)


\$6 According to the Lamport - shortack - Peuse algorithin the agreement cannot be reached, if the number of faulty processors is U/3 of the total number of processors. A solution, would only be reached (Byzantine Agreement). Among 4 processors if & only if there is less than 1/3 faulty processes and the maximum of faulty process should be one. · P2's majority = } x, x, = 3 = x, but P2 is a traitor so it will retreat. · P3 majority = 3 X14,23 = retreat Py majority = 3 x x y 3 = x, but Py is a traitor so

cont on back -

P2's majority = 2x, 4, 23 = 0

P3's majority = & 4, x, 23 = &

Pys majority = & Z, x, y3 = Ø



13 nodes, 13 = 4(4-1)+1, therefore K=4 R1 = \$1,2,3,43 o No site can enter the C.S. R2 = \$ 2,5,8,113 b/c it needs to release the R3 = 23,6,8,133 dead lock first. Ry = 3 4, 6, 10, 11 3 R5 - 21, 5, 6, 73 -> To resolve the clearlack, Ru = 2 2, 6, 9, 12 3 #4 sends inquire message to R7 = 3 2, 7, 10, 13.3 #12 -> #10. But #6 has a R8 = 3 1, 8, 9, 10 3 lower privity than # 1 which has Rg = 3 3, 7, 9, 113 a" R" from #4. So #4 should 210 = 3 3,5,10, 123 release Heelf from # 12 by letting #12 R11 = 2 1, 11, 12,13 3 raphy a yield message. After R12= \$ 4, 7, 8,12 3 #4 gets a yield message so it will R13 = 5 4,5,9,133 be ovailable #1 -> #1 can enter CS, # 1 con enter CS. -> #1 release locks

p: Utilization, 12= I-p: probability processor idle P: probability at least one task waiting and server idle

Where Q is probability that i servers idle and HN-; is probability that set of (N-i) servers are not idle and at least one has a task waiting