test_alpha
test_version.py:259

__init__
import_fixture.py:7

calls×30 [#1]

__eq__
host.py:40

calls×3 [#3]

__ne__
host.py:45

calls×3 [#8]

__lt__
version.py:65

calls×4 [#15]

__gt__
version.py:75

calls×2 [#20]

raises

calls [#22]

__enter__
test_encrypt.py:31

calls [#26]

ValueError

raises (caught) __exit__

test_encrypt.py:35

calls [#32]

__le__
version.py:78

calls×3 [#41]

__ge__
version.py:81

calls×2 [#50]

_call_reprcompare

calls [#77]

_should_repr_global_name

calls×2 [#100]

_saferepr

calls×4 [#101]

format_explanation

calls [#148]

AssertionError
assert not 'a' > 'a'

raises (caught)

calls [#24]

expected_exceptions
(<class 'ValueError'>,)

writes

e

<class 'ValueError'>

writes

_parse_exc

calls [#25]

check_ispytest

calls [#29]

calls×3 [#9]

raises (caught)

calls [#23] calls×4 [#21]

__tracebackhide__
(3 writes)
True

writes

passed to

_check_match

passed to

for_later

calls [#27] calls [#28]

writes

matches
parsing.py:314

calls [#33]

exc_info
(<class 'ValueError'>, ValueError(), <traceback object at 0x71e5cc1cc880>)

writes

fill_unfilled

calls [#38]

_check_type
[closure inside _check_size_and_type]
openssl_privatekey.py:551

calls [#34] calls [#36]

_check_check

calls [#37]

_check_raw_type

calls [#35]

passed to

calls×2 [#43]

calls×3 [#42]

calls×2 [#51] loops(×4)

i
0

writes

res

(2 writes, 2 distinct)
True
None

writes

expl
'%(py4)s
{%(py4)s = %(py0)s(%(py2)s)
} > %(py10)s
{%(py10)s = %(py6)s(%(py8)s)
}'

writes

done
False

writes

callbinrepr

calls [#78]

argname
(6 writes, 4 distinct)
'config'
'right'
'op'
'left'

writes

firstresult
False

writes

_hookexec

calls [#83]

hook_result
[]

writes

custom
None

writes

__getattr__
callback_debug.py:22

calls [#79]

__call__
singleton.py:21

calls [#80]

hook
<HookCaller 'pytest_assertrepr_compare'>

writes

is_historic

calls [#81]

_verify_all_args_are_provided

calls [#82]

writes

passed to

_multicall

passed to

calls [#84]

writes writes

writes×4

results
[]

writes

exception
None

writes

teardowns
[]

writes

hook_impl
<HookImpl plugin_name='assertion', plugin=<module '_pytest.assertion' from '/home/shashwat/BTP/.venv/lib/python3.12/site…

writes

args

[<_pytest.config.Config object at 0x71e5ce27c6b0>, '>', 'a', 'a']

writes

pytest_assertrepr_compare

calls [#85]

result
(6 writes, 5 distinct)
[]
["assert not 'a'"]
["assert not 'a'", " + where 'a' = _Alpha('a')"]
["assert not 'a' > 'a'", " + where 'a' = _Alpha('a')"]
["assert not 'a' > 'a'", " + where 'a' = _Alpha('a')", " + and 'a' = _Alpha('a')"]

assertrepr_compare writes

calls [#86]

get_verbosity

calls [#87]

verbose
0

writes

maxsize
(5 writes, 2 distinct)
31
240

writes

saferepr

calls×2 [#91] left_repr

"'a'"

writes

right_repr
"'a'"

writes

summary
"'a' > 'a'"

writes

get_terminal_writer

calls [#97]

highlighter
<bound method TerminalWriter._highlight of <_pytest._io.terminalwriter.TerminalWriter object at 0x71e5cd4b9460>>

writes

explanation
None

writes

isset

calls [#99]

getoption

calls×5 [#88]

global_level
(5 writes)
0

writes×5

_verbosity_ini_name

calls×5 [#89]

ini_name
(5 writes)
'verbosity_assertions'

writes×5

getini

calls×5 [#90]

level
(5 writes)
'auto'

writes×5

val
(6 writes, 2 distinct)
0
'auto'

writes writes×5

canonical_name
(5 writes)
'verbosity_assertions'

writes×5

KeyError
'verbosity_assertions'

raises (caught)

repr_instance

passed to

passed to

passed to

_ellipsize

passed to

calls×6 [#92]

repr

calls×6 [#93]

s

(10 writes, 3 distinct)
"'a'"
'where '
'and '

writes×6

calls×2 [#120] calls×4 [#110]

passed to

get_plugin

calls [#98]

terminalreporter
<_pytest.terminal.TerminalReporter object at 0x71e5cdde2cc0>

writes

passed to

_split_explanation

passed to

writes×4

calls×4 [#107]

_get_maxsize_for_saferepr

calls×4 [#102]

calls×4 [#103]

verbosity
(4 writes)
0

writes×4

writes×2

calls×2 [#122]

__repr__
collections.py:31

calls×2 [#121]

writes

loops(×4)

calls [#149]

lines
(4 writes, 3 distinct)
["assert not 'a'"]
["assert not 'a'", "{'a' = _Alpha('a')"]
["assert not 'a'", "{'a' = _Alpha('a')", "} > 'a'", "{'a' = _Alpha('a')", '}']

writes×2

values
(2 writes, 2 distinct)
"{'a' = _Alpha('a')"
'}'

writes

_format_lines

calls [#150]

raw_lines
["assert not 'a'", "{'a' = _Alpha('a')", "} > 'a'", "{'a' = _Alpha('a')", '}']

writes×2 writes×4 writes passed to writes×2 writes

stack
(5 writes, 3 distinct)
[0]
[0, 1]
[0, 2]

writes×5

stackcnt
(7 writes, 5 distinct)
[0]
[1]
[1, 0]
[2]
[2, 0]

writes×7

line
(4 writes, 3 distinct)
"{'a' = _Alpha('a')""} > 'a'"
'}'

writes×4