test_find_hook
Finds the specified hook.
test_hooks.py:66

work_in
Context manager version of os.chdir.
utils.py:49

calls [#1]

sep
(11 writes)
'/'

writes×2

cwd
(3 writes)
'/home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-hooks'

writes

path
(11 writes, 5 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-hooks'
'/home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-hooks/hooks/pre_gen_project.py'
'/home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-hooks/hooks'
'hooks'
'hooks/pre_gen_project.py'

writes×3

b
(4 writes, 3 distinct)
'hooks/pre_gen_project.py'
'hooks'
'pre_gen_project.py'

writes expected_pre
'/home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-hooks/hooks/pre_gen_project.py'

writes

find_hook
Return a dict of all hook scripts provided.
hooks.py:39

calls [#2]

actual_hook_path
'/home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-hooks/hooks/pre_gen_project.py'

writes

_call_reprcompare

calls [#5]

_saferepr

calls×2 [#45]

format_explanation

calls [#65]

AssertionError

assert '/home/shashw...en_project.py' == '/'

raises (caught)

curdir
'/home/shashwat/BTP/BugsInPy/workspace/cookiecutter'

writes

valid_hook
Determine if a hook file is valid.
hooks.py:22

passed to

passed to passed to

passed to

passed to

getvalue
fallback.py:66

passed to

writes×2 writes×3 writes×8 writes×5

st

os.stat_result(st_mode=16893, st_ino=4196184, st_dev=66309, st_nlink=2, st_uid=1000, st_gid=1000, st_size=4096, st_atime…

writes

hook_file
(2 writes, 2 distinct)
'post_gen_project.sh'
'pre_gen_project.py'

writes×2

calls×2 [#3]

passed to writes×4

i
(4 writes)
0

writes×2

filename
(2 writes, 2 distinct)
'post_gen_project.sh'
'pre_gen_project.py'

writes×2

extsep
(2 writes)
'.'

writes×2

sepIndex
(2 writes)
- 1

writes×2

dotIndex
(2 writes, 2 distinct)
16
15

writes×2

filenameIndex
(2 writes)
0

writes×2

basename
(2 writes, 2 distinct)
'post_gen_project'
'pre_gen_project'

writes×2

matching_hook
(2 writes, 2 distinct)
False
True

writes×2

supported_hook
(2 writes)
True

writes×2

backup_file
(2 writes)
False

passed to writes×2

passed to

writes

loops(×4)

res

(3 writes, 3 distinct)
False
["'/home/shashw...en_project.py' == '/'", '', '- /', '+ /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-ho…
"'/home/shashw...en_project.py' == '/'
~

~- /
~ + /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-hooks/…

writes×2

expl
'%(py0)s == %(py3)s'

writes

done
True

writes

callbinrepr

calls [#6]

argname
(6 writes, 4 distinct)
'config'
'right'
'op'
'left'

writes

firstresult
False

writes

_hookexec

calls [#11] hook_result

[["'/home/shashw...en_project.py' == '/'", '', '- /', '+ /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-h…

writes

new_expl
["'/home/shashw...en_project.py' == '/'", '', '- /', '+ /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-ho…

writes

truncate_if_required

calls [#31]

line
(6 writes, 6 distinct)
"'/home/shashw...en_project.py' == '/'"

''

'- /'
'+ /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-hooks/hooks/pre_gen_project.py'
'~'

'~+ /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-hooks/hooks/pre_gen_project.py'

writes×4

calls [#43]

custom

"'/home/shashw...en_project.py' == '/'
~

~- /
~ + /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-hooks/…

writes

__getattr__
dep_util.py:6

calls [#7]

__call__
_common.py:13

calls [#8]

hook
<HookCaller 'pytest_assertrepr_compare'>

writes

is_historic

calls [#9]

_verify_all_args_are_provided

calls [#10]

writes

passed to

_multicall

passed to

calls [#12]

writes

writes×4

__tracebackhide__
True

writes

results
(2 writes, 2 distinct)
[]
[["'/home/shashw...en_project.py' == '/'", '', '- /', '+ /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-h…

writes×2

exception
None

writes

teardowns
[]

writes

hook_impl
<HookImpl plugin_name='assertion', plugin=<module '_pytest.assertion' from '/home/shashwat/BTP/.venv/lib/python3.12/site…

writes

args

[<_pytest.config.Config object at 0x7306daa971a0>, '==', '/home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-…

writes

pytest_assertrepr_compare

calls [#13]

result
(5 writes, 4 distinct)
[["'/home/shashw...en_project.py' == '/'", '', '- /', '+ /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-h…
["assert '/home/shashw...en_project.py' == '/'"]
["assert '/home/shashw...en_project.py' == '/'", ' ']
["assert '/home/shashw...en_project.py' == '/'", ' ', ' - /', ' + /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/…

writes

assertrepr_compare

calls [#14]

get_verbosity

calls [#15]

verbose
(2 writes)
0

writes

maxsize
(3 writes, 2 distinct)
30
240

writes

saferepr

calls×2 [#19]

left_repr
"'/home/shashw...en_project.py'"

writes

right_repr
"'/'"

writes

summary

"'/home/shashw...en_project.py' == '/'"

writes

get_terminal_writer

calls [#25] highlighter

<bound method TerminalWriter._highlight of <_pytest._io.terminalwriter.TerminalWriter object at 0x7306da176810>>

writes

explanation
(7 writes, 4 distinct)
None
[]
['- /', '+ /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-hooks/hooks/pre_gen_project.py']
['', '- /', '+ /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-hooks/hooks/pre_gen_project.py']

_compare_eq_any writes×3

calls [#27]

getoption calls×4 [#16]

global_level
(4 writes)
0

writes×4

_verbosity_ini_name

calls×4 [#17]

ini_name
(4 writes)
'verbosity_assertions'

writes×4

getini

calls×4 [#18]

level
(4 writes)
'auto'

writes×4

val
(8 writes, 4 distinct)
0
'auto'
None
'rewrite'

writes×5

writes×3

canonical_name
(8 writes, 3 distinct)
'verbosity_assertions'
'truncation_limit_lines'
'truncation_limit_chars'

writes×6 KeyError
'verbosity_assertions'

raises (caught)

_getini

calls×2 [#34]

passed to

_diff_text

passed to

passed to

__init__
_compat.py:6

passed to _ellipsize

passed to

calls×4 [#20]

repr

calls×4 [#21]

s

(4 writes, 3 distinct)
"'/home/shashw...en_project.py'""'/'""'/home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-hooks/hooks/pre_gen_project.py'"

writes×4

calls×2 [#54]

passed to

get_plugin

calls [#26]

terminalreporter
<_pytest.terminal.TerminalReporter object at 0x7306d9588230>

writes

passed to

passed to

passed to

passed to

_split_explanation

passed to

istext writes×2

calls [#30] calls×2 [#28]

writes writes×2

ndiff
<function ndiff at 0x7306da37f560>

writes

keepends
True

writes

_get_truncation_parameters

calls [#32]

max_lines
(3 writes, 2 distinct)
None
8

writes

max_chars
(3 writes, 2 distinct)
None
640

writes

should_truncate
(2 writes)
True

_truncate_explanation writes

calls [#42] calls [#37]

calls×2 [#33]

writes

writes×2 writes×2

running_on_ci

calls [#41]

writes

writes×2

_description
(2 writes, 2 distinct)
'Set threshold of LINES after which truncation will take effect'
'Set threshold of CHARS after which truncation will take effect'

writes×2

type
(2 writes)
'string'

writes×2

default
(2 writes)
None

writes×2

candidates
(2 writes)
[]

writes×2

alias
(2 writes)
'xfail_strict'

writes×2

target
(2 writes)
'strict_xfail'

writes×2

passed to passed to

passed to passed to

raises (caught)

env_vars
['CI', 'BUILD_NUMBER']

writes

var

(2 writes, 2 distinct)
'CI'
'BUILD_NUMBER'

writes×2

passed to

input_char_count
134

writes

tolerable_max_chars
710

writes

tolerable_max_lines
10

writes

calls [#44]

writes×2

calls×2 [#51]

_get_maxsize_for_saferepr

calls×2 [#46]

calls×2 [#47]

verbosity
(2 writes)
0

writes×2

writes×2

writes

loops(×6)

calls [#66]

lines
(4 writes, 3 distinct)
["assert '/home/shashw...en_project.py' == '/'"]
["assert '/home/shashw...en_project.py' == '/'", '~']
["assert '/home/shashw...en_project.py' == '/'", '~', '~- /', '~+ /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tes…

writes×2

values
(2 writes, 2 distinct)
'~'

'~+ /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tests/test-hooks/hooks/pre_gen_project.py'

writes

_format_lines
Just format the tokens, without any wrapping tags.
html.py:830

calls [#67]

stack
(3 writes, 3 distinct)
[0]
[1]
[3]

writes

raw_lines
["assert '/home/shashw...en_project.py' == '/'", '~', '~- /', '~+ /home/shashwat/BTP/BugsInPy/workspace/cookiecutter/tes…

writes writes writes×2 passed to

writes×2

writes writes×2

stackcnt
[0]

writes

indent
1

writes