setUp
testsite.py:9

get_crawler
Return an unconfigured Crawler object. If settings_dict…
test.py:89

calls [#1]

_create_spider
<function Crawler._create_spider at 0x78d363aa1800>

calls [#529]

from_crawler
extensions.py:10

calls [#538] crawler

<scrapy.crawler.Crawler object at 0x78d363b92a80>

writes

_get_spiderargs
test_spidermiddleware_offsite.py:23

calls [#528]

spider_opened
useragent.py:18

calls [#551]

TypeError
expected string or bytes-like object, got 'NoneType'

raises (caught)

loops(×565)

KeyError
'scrapy.crawler'

raises (caught)

lock
(2 writes, 2 distinct)
None

_ModuleLock('scrapy.crawler') at 132849306512672

writes×2

cb
<function _get_module_lock.<locals>.cb at 0x78d363bb8cc0>

writes

tid
(2 writes)
132849362768000

writes×2

o

(4 writes, 4 distinct)
None

<scrapy.extensions.corestats.CoreStats object at 0x78d3639a1e50>
<scrapy.extensions.logstats.LogStats object at 0x78d3638b07a0>
<scrapy.spidermiddlewares.offsite.OffsiteMiddleware object at 0x78d363a35970>

writes

path
(15 writes, 5 distinct)
None

['/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy']
['/home/shashwat/BTP/.venv/lib/python3.12/site-packages/zope/interface']
['/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/core']
['/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/utils']

writes×14

parent
(8 writes, 5 distinct)
'scrapy'
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__'
'zope.interface'
'scrapy.core'
'scrapy.utils'

writes×8

parent_spec
(14 writes, 5 distinct)
None

ModuleSpec(name='scrapy', loader=<_frozen_importlib_external.SourceFileLoader object at 0x78d366475040>, origin='/home/s…
ModuleSpec(name='zope.interface', loader=<_frozen_importlib_external.SourceFileLoader object at 0x78d3662e67e0>, origin=…
ModuleSpec(name='scrapy.core', loader=<_frozen_importlib_external.SourceFileLoader object at 0x78d363bc2c60>, origin='/h…
ModuleSpec(name='scrapy.utils', loader=<_frozen_importlib_external.SourceFileLoader object at 0x78d3659cfb90>, origin='/…

writes×14

parent_module
(7 writes, 4 distinct)
<module 'scrapy' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__init__.py'>
<module 'zope.interface' from '/home/shashwat/BTP/.venv/lib/python3.12/site-packages/zope/interface/__init__.py'>
<module 'scrapy.core' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/core/__init__.py'>
<module 'scrapy.utils' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/utils/__init__.py'>

writes×7

child
(7 writes, 7 distinct)
'crawler'
'verify'
'engine'
'extension'
'interfaces'
'signalmanager'
… +1 more values

writes×7

meta_path
[<_distutils_hack.DistutilsMetaFinder object at 0x78d366670410>, <class '_frozen_importlib.BuiltinImporter'>, <class '_f…

writes

is_reload
False

writes

finder
(6 writes, 5 distinct)
<_distutils_hack.DistutilsMetaFinder object at 0x78d366670410>
<class '_frozen_importlib.BuiltinImporter'>
<class '_frozen_importlib.FrozenImporter'>
<class '_frozen_importlib_external.PathFinder'>
FileFinder('/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy')

writes×6

find_spec
(4 writes, 4 distinct)
<bound method DistutilsMetaFinder.find_spec of <_distutils_hack.DistutilsMetaFinder object at 0x78d366670410>>
<bound method BuiltinImporter.find_spec of <class '_frozen_importlib.BuiltinImporter'>>
<bound method FrozenImporter.find_spec of <class '_frozen_importlib.FrozenImporter'>>
<bound method PathFinder.find_spec of <class '_frozen_importlib_external.PathFinder'>>

writes×4

spec
(12 writes, 8 distinct)
None

ModuleSpec(name='scrapy.crawler', loader=<_frozen_importlib_external.SourceFileLoader object at 0x78d363bc2690>, origin=…
ModuleSpec(name='zope.interface.verify', loader=<_frozen_importlib_external.SourceFileLoader object at 0x78d363bc2b10>, …
ModuleSpec(name='scrapy.core.engine', loader=<_frozen_importlib_external.SourceFileLoader object at 0x78d363bc2c90>, ori…
ModuleSpec(name='scrapy.extension', loader=<_frozen_importlib_external.SourceFileLoader object at 0x78d363bdf7d0>, origi…
ModuleSpec(name='scrapy.interfaces', loader=<_frozen_importlib_external.SourceFileLoader object at 0x78d363bffec0>, orig…
… +2 more values

writes×12

info
None

writes

namespace_path
[]

writes

entry
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy'

writes

is_namespace
False

writes

tail_module
'crawler'

writes

mtime
1780556330.7972753

writes

cache
set(len=43)

writes

cache_module
'crawler'

writes

suffix
(2 writes, 2 distinct)
'.cpython-312-x86_64-linux-gnu.so'
'.py'

writes×2

loader_class
(2 writes, 2 distinct)
<class '_frozen_importlib_external.ExtensionFileLoader'>
<class '_frozen_importlib_external.SourceFileLoader'>

writes×2

part
(6 writes, 4 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy'
'crawler.cpython-312-x86_64-linux-gnu.so'
'crawler.py'
'crawler.cpython-312.pyc'

writes×6

full_path
(2 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.cpython-312-x86_64-linux-gnu.so'
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py'

writes×2

stat_info
os.stat_result(st_mode=33204, st_ino=3555193, st_dev=66309, st_nlink=1, st_uid=1000, st_gid=1000, st_size=13374, st_atim…

writes

loader
(2 writes)
<_frozen_importlib_external.SourceFileLoader object at 0x78d363bc2690>

writes×2

head
(2 writes)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy'

writes×2

tail
(2 writes)
'crawler.py'

writes×2

base
(5 writes, 4 distinct)
'crawler'
<InterfaceClass zope.interface.Interface>
REPR FAILED

BoundMethodWeakref(OffsiteMiddleware.spider_opened)

writes×2

sep
(2 writes)
'.'

writes×2

rest

(2 writes)
'py'

writes×2

tag
(2 writes)
'cpython-312'

writes×2

almost_filename
(2 writes)
'crawler.cpython-312'

writes×2

optimization
(2 writes)

''

writes×2

filename
(3 writes)
'crawler.cpython-312.pyc'

writes×3

source_path
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py'

writes

source_mtime
(2 writes, 2 distinct)
None
1780556330

writes×2

source_bytes
(2 writes, 2 distinct)
None

bytes(len=13374)

writes×2

source_hash
None

writes

hash_based
False

writes

check_source
True

writes

p
'/'

writes

i
(2 writes, 2 distinct)
51
63

writes×2

bytecode_path
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.pyc'

writes

st

(2 writes, 2 distinct)
os.stat_result(st_mode=33204, st_ino=3555193, st_dev=66309, st_nlink=1, st_uid=1000, st_gid=1000, st_size=13374, st_atim…
{'mtime': 1780556330.7942753, 'size': 13374}

writes×2

file
(4 writes, 4 distinct)
<_io.BufferedReader name='/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.pyc'>
<_io.BufferedReader name='/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py'>
<_io.FileIO name=3 mode='wb' closefd=True>
<_io.FileIO [closed]>

writes×4

data
(7 writes, 6 distinct)
bytes(len=19104)
bytearray(b'xcb

')
bytearray(b'xcb

x00x00x00x00')
bytearray(b'xcb

x00x00x00x00*"!j')
bytearray(b'xcb

x00x00x00x00*"!j>4x00x00')
bytearray(b'xcb

x00x00x00x00*"!j>4x00x00xe3x00x00x00x00x00x00x00x00x00x00x00x00x05x00x00x00…

writes×7

exc_details
{'name': 'scrapy.crawler', 'path': '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.…

writes

magic
b'xcb

'

writes

flags
(2 writes)
0

writes×2

bytes_data
<memory at 0x78d363c8ab00>

writes

message

"bytecode is stale for 'scrapy.crawler'"

writes

ImportError
bytecode is stale for 'scrapy.crawler'

raises (caught)

code_object
<code object <module> at 0x1256a320, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py", line 1>

writes

mode
(2 writes)
33204

writes×2

path_parts
[]

writes

path_tmp
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.pyc.132849306734256'

writes

fd
3

writes

code
(5 writes, 5 distinct)
<code object <module> at 0x1256a320, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py", line 1>
<code object from_settings at 0x78d363a85a70, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py"…
<code object load at 0x78d363a89330, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py", line 62…
<code object list at 0x78d363a33000, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py", line 79…
<code object find_by_request at 0x78d363cfee20, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.p…

writes

logging
<module 'logging' from '/usr/lib/python3.12/logging/__init__.py'>

writes

pprint
<module 'pprint' from '/usr/lib/python3.12/pprint.py'>

writes

signal
<module 'signal' from '/usr/lib/python3.12/signal.py'>

writes

warnings
<module 'warnings' from '/usr/lib/python3.12/warnings.py'>

writes

x

(8 writes, 7 distinct)
'defer'
'signals'
'Spider'
'overridden_settings'
'Settings'
6023
… +1 more values

writes×6

defer
<module 'twisted.internet.defer' from '/home/shashwat/BTP/.venv/lib/python3.12/site-packages/twisted/internet/defer.py'>

writes

DoesNotImplement
<class 'zope.interface.exceptions.DoesNotImplement'>

writes

verifyClass
<function verifyClass at 0x78d363bb9800>

writes

signals
(6 writes, 5 distinct)
<module 'scrapy.signals' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/signals.py'>
{}
{<object object at 0x78d3670b0e00>: []}
{<object object at 0x78d3670b0e00>: [<weakref at 0x78d3639e3830; to 'function' at 0x78d3639bc0e0 (<lambda>)>]}
{<object object at 0x78d3670b0e00>: [<weakref at 0x78d3639e3830; to 'function' at 0x78d3639bc0e0 (<lambda>)>, BoundMetho…

writes

Spider
(2 writes)
<class 'scrapy.spiders.Spider'>

writes×2

ExecutionEngine
<class 'scrapy.core.engine.ExecutionEngine'>

writes

ScrapyDeprecationWarning
<class 'scrapy.exceptions.ScrapyDeprecationWarning'>

writes

ExtensionManager
<class 'scrapy.extension.ExtensionManager'>

writes

ISpiderLoader
<InterfaceClass scrapy.interfaces.ISpiderLoader>

writes

overridden_settings
<function overridden_settings at 0x78d363a53c40>

writes

Settings
<class 'scrapy.settings.Settings'>

writes

SignalManager
<class 'scrapy.signalmanager.SignalManager'>

writes

configure_logging
<function configure_logging at 0x78d363a53ce0>

writes

get_scrapy_root_handler
<function get_scrapy_root_handler at 0x78d363a70400>

writes

install_scrapy_root_handler
<function install_scrapy_root_handler at 0x78d363a70360>

writes

log_scrapy_info
<function log_scrapy_info at 0x78d363a70540>

writes

LogCounterHandler
<class 'scrapy.utils.log.LogCounterHandler'>

writes

create_instance
<function create_instance at 0x78d364cdab60>

writes

load_object
<function load_object at 0x78d364cd9e40>

writes

install_shutdown_handlers
<function install_shutdown_handlers at 0x78d363bba0c0>

writes

signal_names
dict(len=33)

writes

install_reactor
<function install_reactor at 0x78d364b04860>

writes

verify_installed_reactor
<function verify_installed_reactor at 0x78d363cab4c0>

writes

logger
<Logger scrapy.crawler (WARNING)>

writes

__module__
(3 writes)
'scrapy.crawler'

writes×3

__qualname__
(3 writes, 3 distinct)
'Crawler'
'CrawlerRunner'
'CrawlerProcess'

writes×3

__init__
(3 writes, 3 distinct)
<function Crawler.__init__ at 0x78d363aa1440>
<function CrawlerRunner.__init__ at 0x78d363aa1a80>
<function CrawlerProcess.__init__ at 0x78d363aa20c0>

writes×3

spiders
(2 writes, 2 distinct)
<property object at 0x78d363bd3a10>
<property object at 0x78d363ac89f0>

writes×2

inlineCallbacks

calls×3 [#3]

crawl
(2 writes, 2 distinct)
<function Crawler.crawl at 0x78d363aa1760>
<function CrawlerRunner.crawl at 0x78d363aa1bc0>

writes×2

writes

_create_engine
<function Crawler._create_engine at 0x78d363aa18a0>

writes

stop
(2 writes, 2 distinct)
<function Crawler.stop at 0x78d363aa19e0>
<function CrawlerRunner.stop at 0x78d363aa1e40>

writes×2

Crawler
<class 'scrapy.crawler.Crawler'>

writes

__doc__
(2 writes, 2 distinct)

"

This is a convenient helper class that keeps track of, manages and runs
crawlers inside an already setup :mo…

"

A class to run multiple scrapy crawlers in a process simultaneously.

This class extends :class:`~scrapy.cr…

writes×2

crawlers
<property object at 0x78d363ac8b80>

writes

_crawl
<function CrawlerRunner._crawl at 0x78d363aa1c60>

writes

create_crawler
<function CrawlerRunner.create_crawler at 0x78d363aa1d00>

writes

_create_crawler
<function CrawlerRunner._create_crawler at 0x78d363aa1da0>

writes join
<function CrawlerRunner.join at 0x78d363aa1f80>

writes

_handle_twisted_reactor
(2 writes, 2 distinct)
<function CrawlerRunner._handle_twisted_reactor at 0x78d363aa2020>
<function CrawlerProcess._handle_twisted_reactor at 0x78d363aa2480>

writes×2

CrawlerRunner
(2 writes)
<class 'scrapy.crawler.CrawlerRunner'>

writes×2

_signal_shutdown
<function CrawlerProcess._signal_shutdown at 0x78d363aa2160>

writes

_signal_kill
<function CrawlerProcess._signal_kill at 0x78d363aa2200>

writes

start
<function CrawlerProcess.start at 0x78d363aa22a0>

writes

_graceful_stop_reactor
<function CrawlerProcess._graceful_stop_reactor at 0x78d363aa2340>

writes

_stop_reactor
<function CrawlerProcess._stop_reactor at 0x78d363aa23e0>

writes

__classcell__
<cell at 0x78d36648d120: empty>

writes

CrawlerProcess
<class 'scrapy.crawler.CrawlerProcess'>

writes

_get_spider_loader
<function _get_spider_loader at 0x78d363aa13a0>

writes

args

(<code object <module> at 0x1256a320, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py", line 1>, {'…

writes

update
datatypes.py:53

calls×2 [#356]

set

Sets value if priority is higher or equal than current …
__init__.py:46

calls×36 [#23]

__iter__
sitemap.py:23

calls [#83]

__getitem__
datatypes.py:22

calls×31 [#84]

settings
<scrapy.settings.Settings object at 0x78d363bc0230>

writes

freeze
Disable further changes to the current settings.
__init__.py:351

calls [#527] runner <scrapy.crawler.CrawlerRunner object at 0x78d363b92a50>

writes

defvalue
(2 writes, 2 distinct)
False
'Scrapy/2.0.0 (+https://scrapy.org)'

writes

d
{}

writes

connect

Connect a receiver function to a signal.
signalmanager.py:10

calls [#460] lf_cls

<class 'scrapy.logformatter.LogFormatter'>

writes

calls×2 [#466]

build_component_list
Compose a component list from a { class: order } dictio…
conf.py:12

calls [#476]

_map_keys
<function build_component_list.<locals>._map_keys at 0x78d3639bcb80>

calls [#478]

k
(8 writes, 3 distinct)
'scrapy.extensions.corestats.CoreStats'
'scrapy.extensions.throttle.AutoThrottle'
'scrapy.extensions.telnet.TelnetConsole'

writes×5

v

(3 writes)
0

writes

without_none_values
Return a copy of ``iterable`` with all ``None`` entries…
python.py:298

calls [#479] compdict

{'scrapy.extensions.corestats.CoreStats': 0, 'scrapy.extensions.telnet.TelnetConsole': 0, 'scrapy.extensions.memusage.Me…

writes

mwlist
['scrapy.extensions.corestats.CoreStats', 'scrapy.extensions.telnet.TelnetConsole', 'scrapy.extensions.memusage.MemoryUs…

writes

middlewares
(5 writes, 5 distinct)
[]
[<scrapy.extensions.corestats.CoreStats object at 0x78d3639a1e50>]
[<scrapy.extensions.corestats.CoreStats object at 0x78d3639a1e50>, <scrapy.extensions.telnet.TelnetConsole object at 0x7…
[<scrapy.extensions.corestats.CoreStats object at 0x78d3639a1e50>, <scrapy.extensions.telnet.TelnetConsole object at 0x7…
[<scrapy.extensions.corestats.CoreStats object at 0x78d3639a1e50>, <scrapy.extensions.telnet.TelnetConsole object at 0x7…

writes×5

enabled
(5 writes, 5 distinct)
[]
['scrapy.extensions.corestats.CoreStats']
['scrapy.extensions.corestats.CoreStats', 'scrapy.extensions.telnet.TelnetConsole']
['scrapy.extensions.corestats.CoreStats', 'scrapy.extensions.telnet.TelnetConsole', 'scrapy.extensions.memusage.MemoryUs…
['scrapy.extensions.corestats.CoreStats', 'scrapy.extensions.telnet.TelnetConsole', 'scrapy.extensions.memusage.MemoryUs…

writes×5

clspath
(9 writes, 9 distinct)
'scrapy.extensions.corestats.CoreStats'
'scrapy.extensions.telnet.TelnetConsole'
'scrapy.extensions.memusage.MemoryUsage'
'scrapy.extensions.memdebug.MemoryDebugger'
'scrapy.extensions.closespider.CloseSpider'
'scrapy.extensions.feedexport.FeedExporter'
… +3 more values

writes×9

mwcls
(9 writes, 9 distinct)
<class 'scrapy.extensions.corestats.CoreStats'>
<class 'scrapy.extensions.telnet.TelnetConsole'>
<class 'scrapy.extensions.memusage.MemoryUsage'>
<class 'scrapy.extensions.memdebug.MemoryDebugger'>
<class 'scrapy.extensions.closespider.CloseSpider'>
<class 'scrapy.extensions.feedexport.FeedExporter'>
… +3 more values

writes×9

mw

(6 writes, 4 distinct)
<scrapy.extensions.corestats.CoreStats object at 0x78d3639a1e50>
<scrapy.extensions.telnet.TelnetConsole object at 0x78d363bc2570>
<scrapy.extensions.memusage.MemoryUsage object at 0x78d363bc2450>
<scrapy.extensions.logstats.LogStats object at 0x78d3638b07a0>

writes×5

scrapy.exceptions.NotConfigured

raises (caught)

e

(5 writes)
NotConfigured()

writes×5

_add_middleware
__init__.py:20

calls [#526]

passed to passed to

passed to

passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to

passed to

passed to passed to passed to

passed to

passed to

_removeOldBackRefs

passed to

passed to

_verify

calls [#366]

calls [#455]

iter_default_settings
Return the default settings as an iterator of (name, va…
__init__.py:453

calls [#454]

writes

calls×9 [#482]

raises (caught)

dot
(12 writes, 7 distinct)
19
22
27
24
26
29
… +1 more values

writes×12

mod
(12 writes, 12 distinct)
<module 'scrapy.spiderloader' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py'>
<module 'scrapy.statscollectors' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/statscollectors.py'>
<module 'scrapy.logformatter' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/logformatter.py'>
<module 'scrapy.extensions.corestats' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/extensions/corestats.py'…
<module 'scrapy.extensions.telnet' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/extensions/telnet.py'>
<module 'scrapy.extensions.memusage' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/extensions/memusage.py'>
… +6 more values

writes×12

obj
(13 writes, 13 distinct)
<class 'scrapy.spiderloader.SpiderLoader'>
<class 'scrapy.statscollectors.MemoryStatsCollector'>
<class 'scrapy.logformatter.LogFormatter'>
<class 'scrapy.extensions.corestats.CoreStats'>
<class 'scrapy.extensions.telnet.TelnetConsole'>
<class 'scrapy.extensions.memusage.MemoryUsage'>
… +7 more values

writes×12

writes×2 calls [#440] calls [#453]

calls×6 [#7]

calls×18 [#9]

setmodule
Store settings from a module with a given priority.
__init__.py:270

calls [#11]

calls [#438] get

headers.py:44

calls [#447]

copy

Return a copy of this Response
__init__.py:82

calls [#432]

getlist
headers.py:50

calls [#411]

getbool
Get a setting value as a boolean.
__init__.py:108

calls×2 [#417]

_load_all_spiders
spiderloader.py:43

calls [#423]

update_settings
__init__.py:87

calls [#433]

handler
<LogCounterHandler (DEBUG)>

writes

remove

(5 writes, 5 distinct)
<function connect.<locals>.remove at 0x78d3639bc5e0>
<function connect.<locals>.remove at 0x78d36371d620>
<function BoundMethodWeakref.__init__.<locals>.remove at 0x78d36371dda0>
<function BoundMethodWeakref.__init__.<locals>.remove at 0x78d36371dd00>
<function connect.<locals>.remove at 0x78d36371dda0>

writes×2 writes raises (caught)

calls [#525]

calculateKey

calls×2 [#546]

unwindGenerator
(3 writes, 3 distinct)
<function Crawler.crawl at 0x78d363aa1760>
<function Crawler.stop at 0x78d363aa19e0>
<function CrawlerRunner.join at 0x78d363aa1f80>

writes×3

calls [#530]

passed to

calls [#430]

calls [#431]

calls [#426]

calls [#365]

calls [#364]

calls [#359]

cls_path
'scrapy.spiderloader.SpiderLoader'

writes

loader_cls
<class 'scrapy.spiderloader.SpiderLoader'>

writes

frozencopy
Return an immutable copy of the current settings.
__init__.py:361

calls [#406]

from_settings
Return an instance of the class for the given settings
interfaces.py:6

calls [#409] passed to

passed to

passed to

passed to

__new__
trackref.py:28

passed to

_assert_mutability
__init__.py:335

calls×20 [#10]

calls×9 [#93]

calls [#12]

calls×2 [#13]

calls×30 [#17]

calls×47 [#14]

calls×17 [#107]

get_settings_priority
Small helper function that looks up a given string prio…
__init__.py:19

calls×47 [#15]

__contains__
datatypes.py:31

calls×47 [#16] calls×41 [#85]

passed to

passed to

passed to

passed to

passed to

passed to

_get_mwlist_from_settings
extension.py:15

passed to

job_dir
job.py:4

passed to

calls×11 [#360]

tester

<built-in method implementedBy of InterfaceClass object at 0x78d363be7e50>

writes

excs

[]

writes

namesAndDescriptions

calls [#367]

desc
(4 writes, 4 distinct)
<zope.interface.interface.Method object at 0x78d363bc1160 scrapy.interfaces.ISpiderLoader.from_settings(settings)>
<zope.interface.interface.Method object at 0x78d363b93200 scrapy.interfaces.ISpiderLoader.load(spider_name)>
<zope.interface.interface.Method object at 0x78d363bc0710 scrapy.interfaces.ISpiderLoader.list()>
<zope.interface.interface.Method object at 0x78d363a18050 scrapy.interfaces.ISpiderLoader.find_by_request(request)>

writes×4

_verify_element

calls×4 [#369]

writes

calls [#368]

r

(3 writes, 2 distinct)
{}
{'from_settings': <zope.interface.interface.Method object at 0x78d363bc1160 scrapy.interfaces.ISpiderLoader.from_setting…

writes×3

passed to

attr

(4 writes, 4 distinct)
<bound method SpiderLoader.from_settings of <class 'scrapy.spiderloader.SpiderLoader'>>
<function SpiderLoader.load at 0x78d363aa2e80>
<function SpiderLoader.list at 0x78d363aa2fc0>
<function SpiderLoader.find_by_request at 0x78d363aa2f20>

writes×4

fromMethod

calls [#370]

fromFunction

calls×3 [#380]

meth
(4 writes, 4 distinct)
<zope.interface.interface.Method object at 0x78d363912b70 scrapy.interfaces.ISpiderLoader.from_settings(settings)>
<zope.interface.interface.Method object at 0x78d36390fe00 scrapy.interfaces.ISpiderLoader.load(spider_name)>
<zope.interface.interface.Method object at 0x78d36390f5c0 scrapy.interfaces.ISpiderLoader.list()>
<zope.interface.interface.Method object at 0x78d36390fe00 scrapy.interfaces.ISpiderLoader.find_by_request(request)>

writes×4

getSignatureInfo

calls×8 [#374]

_incompat

calls×4 [#378]

mess

(4 writes)
None

writes×4

func
<function SpiderLoader.from_settings at 0x78d363aa2de0>

writes

calls [#371]

calls×4 [#372] writes×4 passed to

method
(11 writes, 11 distinct)
<zope.interface.interface.Method object at 0x78d363912b70 from_settings()>
<zope.interface.interface.Method object at 0x78d363912b70 from_settings(settings)>
<zope.interface.interface.Method object at 0x78d363912b70 scrapy.interfaces.ISpiderLoader.from_settings(settings)>
<zope.interface.interface.Method object at 0x78d36390fe00 load()>
<zope.interface.interface.Method object at 0x78d36390fe00 load(spider_name)>
<zope.interface.interface.Method object at 0x78d36390fe00 scrapy.interfaces.ISpiderLoader.load(spider_name)>
… +5 more values

writes×11

defaults
(4 writes)
()

writes×4

na

(4 writes, 2 distinct)
1
0

writes×4

names

(4 writes, 4 distinct)
('settings',)
('spider_name',)
()
('request', 'name', 'cls')

writes×4

opt
(4 writes)
{}

writes×4

defaults_count
(4 writes)
0

writes×4

nr

(4 writes, 2 distinct)
1
0

writes×4

_set_optional

calls×4 [#373]

argno
(4 writes, 2 distinct)
1
0

writes×4

passed to

_get_optional

calls×8 [#375]

calls [#407]

calls [#408]

calls [#410]

calls [#469]

calls [#412]

calls×2 [#418]

got
(3 writes, 2 distinct)
False
True

writes×3

_check_name_duplicates
spiderloader.py:26

calls [#424]

dupes
[]

writes

setdict
__init__.py:267

calls [#434]

calls [#435]

writes×5

calls×3 [#461]

kwargs
(10 writes)
{'sender': <scrapy.crawler.Crawler object at 0x78d363b92a80>}

writes×10

safeRef

calls×3 [#462]

receiver
(3 writes, 3 distinct)
<weakref at 0x78d3639e3830; to 'function' at 0x78d3639bc0e0 (<lambda>)>
<weakref at 0x78d363705ad0; to 'function' at 0x78d364cd9580 (close)>
BoundMethodWeakref(OffsiteMiddleware.spider_opened)

writes×3

senderkey
(3 writes)
132849306512000

writes×3

writes×3

weakSender
(3 writes, 3 distinct)
<weakref at 0x78d3639e1bc0; to 'Crawler' at 0x78d363b92a80>
<weakref at 0x78d36373efc0; to 'Crawler' at 0x78d363b92a80>
<weakref at 0x78d36373f7e0; to 'Crawler' at 0x78d363b92a80>

writes×3

receiverID
(3 writes, 3 distinct)
132849304746032
132849301740240
132849306515792

writes×3

receivers
(6 writes, 6 distinct)
[]
[<weakref at 0x78d3639e3830; to 'function' at 0x78d3639bc0e0 (<lambda>)>]
[BoundMethodWeakref(CoreStats.spider_closed), BoundMethodWeakref(LogStats.spider_closed)]
[BoundMethodWeakref(CoreStats.spider_closed), BoundMethodWeakref(LogStats.spider_closed), <weakref at 0x78d363705ad0…
[BoundMethodWeakref(CoreStats.spider_opened), BoundMethodWeakref(LogStats.spider_opened)]
[BoundMethodWeakref(CoreStats.spider_opened), BoundMethodWeakref(LogStats.spider_opened), BoundMethodWeakref(Offsit…

writes×6

current

(10 writes, 3 distinct)
None
[]
[132849306512000]

writes×9

calls×2 [#537]

passed to

passed to

passed to

passed to

passed to

passed to

calls [#547]

calls [#543]

reference

BoundMethodWeakref(OffsiteMiddleware.spider_opened)

writes

passed to

passed to

passed to

passed to

writes×3

calls×9 [#483]

calls [#468]

calls [#500]

calls×8 [#484]

raises (caught)

getfloat
Get a setting value as a float.
__init__.py:148

calls [#512] interval

60.0

writes

calls [#519]

jobdir
None

writes

calls [#531]

spider
<Spider 'foo' at 0x78d363b930b0>

writes

_set_crawler
__init__.py:53

calls [#533]

getwithbase
Get a composition of a dictionary-like setting and its …
__init__.py:200

calls [#470]

calls [#471]

calls [#473] calls [#472]

compbs
(2 writes, 2 distinct)
<scrapy.settings.BaseSettings object at 0x78d363bc21e0>
<scrapy.settings.BaseSettings object at 0x78d363929fd0>

writes

_check_components
<function build_component_list.<locals>._check_components at 0x78d3639bca40>

writes

writes _validate_values
<function build_component_list.<locals>._validate_values at 0x78d3639bcae0>

writes

passed to

writes

writes writes

prio
0

writes

writes writes×2

passed to

passed to passed to

writes

passed to

passed to

bad_hostname
None

writes

writes×2

calls [#545]

writes

calls [#544] writes

passed to

get_host_regex
Override this method to implement a different offsite p…
offsite.py:51

passed to

calls [#534]

ValueError
<weakref at 0x78d363705ad0; to 'function' at 0x78d364cd9580 (close)> is not in list

raises (caught)

__str__
test_logformatter.py:22

calls [#550]

calls [#552]

raises (caught)

allowed_domains
['scrapytest.org', None, None]

writes

url_pattern
re.compile('^https?://.*$')

writes

domain
(2 writes, 2 distinct)
'scrapytest.org'
None

writes×2 raises (caught)