setUp
test_spidermiddleware_referer.py:10

get_crawler
Return an unconfigured Crawler object. If settings_dict…
test.py:48

calls [#1]

_create_spider
<function Crawler._create_spider at 0x720bd29ff1a0>

calls [#548]

from_crawler
extensions.py:9

calls [#557]

loops(×344)

KeyError
'scrapy.crawler'

raises (caught)

lock
(2 writes, 2 distinct)
None

_ModuleLock('scrapy.crawler') at 125395121090592

writes×2

cb
<function _get_module_lock.<locals>.cb at 0x720bd3a82a20>

writes

tid
(3 writes)
125395174690944

writes×2

o

(3 writes, 3 distinct)
None

<scrapy.extensions.corestats.CoreStats object at 0x720bd2a7ce60>
<scrapy.extensions.logstats.LogStats object at 0x720bd289eb70>

writes

parent
(9 writes, 5 distinct)
'scrapy'
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__'
'zope.interface'
'scrapy.core'
'scrapy.utils'

writes×9

parent_module
(8 writes, 4 distinct)
<module 'scrapy' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__init__.py'>
<module 'zope.interface' from '/home/shashwat/BTP/.venv/lib/python3.12/site-packages/zope/interface/__init__.py'>
<module 'scrapy.core' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/core/__init__.py'>
<module 'scrapy.utils' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/utils/__init__.py'>

writes×8

child
(8 writes, 8 distinct)
'crawler'
'verify'
'engine'
'resolver'
'interfaces'
'extension'
… +2 more values

writes×8

meta_path
[<_distutils_hack.DistutilsMetaFinder object at 0x720bd6270440>, <class '_frozen_importlib.BuiltinImporter'>, <class '_f…

writes

is_reload
False

writes

finder
(10 writes, 6 distinct)
<_distutils_hack.DistutilsMetaFinder object at 0x720bd6270440>
<class '_frozen_importlib.BuiltinImporter'>
<class '_frozen_importlib.FrozenImporter'>
<class '_frozen_importlib_external.PathFinder'>
FileFinder('/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy')
FileFinder('/usr/lib/python3.12/encodings')

writes×6

find_spec
(7 writes, 4 distinct)
<bound method DistutilsMetaFinder.find_spec of <_distutils_hack.DistutilsMetaFinder object at 0x720bd6270440>>
<bound method BuiltinImporter.find_spec of <class '_frozen_importlib.BuiltinImporter'>>
<bound method FrozenImporter.find_spec of <class '_frozen_importlib.FrozenImporter'>>
<bound method PathFinder.find_spec of <class '_frozen_importlib_external.PathFinder'>>

writes×4

info
(2 writes)
None

writes

namespace_path
(2 writes)
[]

writes

entry
(2 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy'
'/usr/lib/python3.12/encodings'

writes

is_namespace
False

writes

tail_module
'crawler'

writes

mtime
1780556529.6224816

writes

cache
set(len=55)

writes

cache_module
'crawler'

writes

suffix
(2 writes, 2 distinct)
'.cpython-312-x86_64-linux-gnu.so'
'.py'

writes×2

loader_class
(2 writes, 2 distinct)
<class '_frozen_importlib_external.ExtensionFileLoader'>
<class '_frozen_importlib_external.SourceFileLoader'>

writes×2

part
(6 writes, 4 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy'
'crawler.cpython-312-x86_64-linux-gnu.so'
'crawler.py'
'crawler.cpython-312.pyc'

writes×6

full_path
(2 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.cpython-312-x86_64-linux-gnu.so'
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py'

writes×2

stat_info
os.stat_result(st_mode=33204, st_ino=3555188, st_dev=66309, st_nlink=1, st_uid=1000, st_gid=1000, st_size=12310, st_atim…

writes

loader
(3 writes, 2 distinct)
<_frozen_importlib_external.SourceFileLoader object at 0x720bd3a968a0>
<_frozen_importlib_external.SourceFileLoader object at 0x720bd2a7d580>

writes×2

head
(2 writes)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy'

writes×2

tail
(2 writes)
'crawler.py'

writes×2

base
(3 writes, 2 distinct)
'crawler'
<InterfaceClass zope.interface.Interface>

writes×2

sep
(2 writes)
'.'

writes×2

rest

(2 writes)
'py'

writes×2

tag
(2 writes)
'cpython-312'

writes×2

almost_filename
(2 writes)
'crawler.cpython-312'

writes×2

optimization
(2 writes)

''

writes×2

filename
(3 writes)
'crawler.cpython-312.pyc'

writes×3

source_path
(2 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py'
'/usr/lib/python3.12/encodings/idna.py'

writes

source_mtime
(4 writes, 3 distinct)
None
1780556471
1772540118

writes×2

source_bytes
(3 writes, 2 distinct)
None

bytes(len=12310)

writes×2

source_hash
(2 writes)
None

writes

hash_based
(2 writes)
False

writes

check_source
(2 writes)
True

writes

p
'/'

writes

i
(2 writes, 2 distinct)
51
63

writes×2

bytecode_path
(2 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.pyc'
'/usr/lib/python3.12/encodings/__pycache__/idna.cpython-312.pyc'

writes

st

(3 writes, 3 distinct)
os.stat_result(st_mode=33204, st_ino=3555188, st_dev=66309, st_nlink=1, st_uid=1000, st_gid=1000, st_size=12310, st_atim…
{'mtime': 1780556471.2527416, 'size': 12310}
{'mtime': 1772540118.0, 'size': 9710}

writes×2

file
(4 writes, 4 distinct)
<_io.BufferedReader name='/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.pyc'>
<_io.BufferedReader name='/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py'>
<_io.FileIO name=3 mode='wb' closefd=True>
<_io.FileIO [closed]>

writes×4

data
(8 writes, 7 distinct)
bytes(len=18820)
bytearray(b'xcb

')
bytearray(b'xcb

x00x00x00x00')
bytearray(b'xcb

x00x00x00x00xb7"!j')
bytearray(b'xcb

x00x00x00x00xb7"!jx160x00x00')
bytearray(b'xcb

x00x00x00x00xb7"!jx160x00x00xe3x00x00x00x00x00x00x00x00x00x00x00x00x05x00x…
… +1 more values

writes×7

exc_details
(2 writes, 2 distinct)
{'name': 'scrapy.crawler', 'path': '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.…
{'name': 'encodings.idna', 'path': '/usr/lib/python3.12/encodings/__pycache__/idna.cpython-312.pyc'}

writes

magic
b'xcb

'

writes

flags
(3 writes)
0

writes×2

bytes_data
(2 writes, 2 distinct)
<memory at 0x720bd3b862c0>
<memory at 0x720bd2b65900>

writes

message

"bytecode is stale for 'scrapy.crawler'"

writes

ImportError
bytecode is stale for 'scrapy.crawler'

raises (caught)

code_object
<code object <module> at 0x2ebdfc10, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py", line 1>

writes

mode
(2 writes)
33204

writes×2

path_parts
[]

writes

path_tmp
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.pyc.125395121265840'

writes

fd
3

writes

code
(6 writes, 6 distinct)
<code object <module> at 0x2ebdfc10, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py", line 1>
<code object from_settings at 0x720bd2b74c70, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py"…
<code object load at 0x720bd2ad35a0, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py", line 35…
<code object list at 0x720bd2b71680, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py", line 52…
<code object find_by_request at 0x720bd3bb7750, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.p…
<code object <module> at 0x2ecc0270, file "/usr/lib/python3.12/encodings/idna.py", line 1>

writes

six

<module 'six' from '/home/shashwat/BTP/.venv/lib/python3.12/site-packages/six.py'>

writes

signal
<module 'signal' from '/usr/lib/python3.12/signal.py'>

writes logging <module 'logging' from '/usr/lib/python3.12/logging/__init__.py'>

writes

warnings
<module 'warnings' from '/usr/lib/python3.12/warnings.py'>

writes

sys

<module 'sys' (built-in)>

writes

from_name
'twisted.internet.reactor'

writes

reactor

<twisted.internet.epollreactor.EPollReactor object at 0x720bd3a97500>

writes

defer
<module 'twisted.internet.defer' from '/home/shashwat/BTP/.venv/lib/python3.12/site-packages/twisted/internet/defer.py'>

writes

verifyClass
<function verifyClass at 0x720bd2b0f2e0>

writes

DoesNotImplement
<class 'zope.interface.exceptions.DoesNotImplement'>

writes

ExecutionEngine
<class 'scrapy.core.engine.ExecutionEngine'>

writes

CachingThreadedResolver
<class 'scrapy.resolver.CachingThreadedResolver'>

writes

ISpiderLoader
<InterfaceClass scrapy.interfaces.ISpiderLoader>

writes

ExtensionManager
<class 'scrapy.extension.ExtensionManager'>

writes

Settings
<class 'scrapy.settings.Settings'>

writes

SignalManager
<class 'scrapy.signalmanager.SignalManager'>

writes

ScrapyDeprecationWarning
<class 'scrapy.exceptions.ScrapyDeprecationWarning'>

writes

install_shutdown_handlers
<function install_shutdown_handlers at 0x720bd29feca0>

writes

signal_names
dict(len=34)

writes

load_object
<function load_object at 0x720bd3b3bc40>

writes

LogCounterHandler
<class 'scrapy.utils.log.LogCounterHandler'>

writes

configure_logging
<function configure_logging at 0x720bd2b79940>

writes

log_scrapy_info
<function log_scrapy_info at 0x720bd29a8ea0>

writes

logger
<Logger scrapy.crawler (WARNING)>

writes

__module__
(3 writes)
'scrapy.crawler'

writes×3

__qualname__
(3 writes, 3 distinct)
'Crawler'
'CrawlerRunner'
'CrawlerProcess'

writes×3

__init__
(3 writes, 3 distinct)
<function Crawler.__init__ at 0x720bd29fede0>
<function CrawlerRunner.__init__ at 0x720bd29ff420>
<function CrawlerProcess.__init__ at 0x720bd29ff9c0>

writes×3

spiders
(2 writes, 2 distinct)
<property object at 0x720bd3abe070>
<property object at 0x720bd2a2fd80>

writes×2

inlineCallbacks

calls×3 [#3]

crawl
(2 writes, 2 distinct)
<function Crawler.crawl at 0x720bd29ff100>
<function CrawlerRunner.crawl at 0x720bd29ff560>

writes×2

writes

_create_engine
<function Crawler._create_engine at 0x720bd29ff240>

writes

stop
(2 writes, 2 distinct)
<function Crawler.stop at 0x720bd29ff380>
<function CrawlerRunner.stop at 0x720bd29ff7e0>

writes×2

Crawler
<class 'scrapy.crawler.Crawler'>

writes

__doc__
(2 writes, 2 distinct)

"

This is a convenient helper class that keeps track of, manages and runs
crawlers inside an already setup Twi…

"

A class to run multiple scrapy crawlers in a process simultaneously.

This class extends :class:`~scrapy.cr…

writes×2 crawlers <property object at 0x720bd2a2ff10>

writes

_crawl
<function CrawlerRunner._crawl at 0x720bd29ff600>

writes

create_crawler
<function CrawlerRunner.create_crawler at 0x720bd29ff6a0>

writes

_create_crawler
<function CrawlerRunner._create_crawler at 0x720bd29ff740>

writes join <function CrawlerRunner.join at 0x720bd29ff920>

writes

CrawlerRunner
(2 writes)
<class 'scrapy.crawler.CrawlerRunner'>

writes×2

_signal_shutdown
<function CrawlerProcess._signal_shutdown at 0x720bd29ffa60>

writes

_signal_kill
<function CrawlerProcess._signal_kill at 0x720bd29ffb00>

writes

start
<function CrawlerProcess.start at 0x720bd29ffba0>

writes

_get_dns_resolver
<function CrawlerProcess._get_dns_resolver at 0x720bd29ffc40>

writes

_graceful_stop_reactor
<function CrawlerProcess._graceful_stop_reactor at 0x720bd29ffce0>

writes

_stop_reactor
<function CrawlerProcess._stop_reactor at 0x720bd29ffd80>

writes

__classcell__
<cell at 0x720bd2b40cd0: empty>

writes

CrawlerProcess
<class 'scrapy.crawler.CrawlerProcess'>

writes

_get_spider_loader
<function _get_spider_loader at 0x720bd29fe520>

writes

args
(2 writes, 2 distinct)
(<code object <module> at 0x2ebdfc10, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py", line 1>, {'…
(<code object <module> at 0x2ecc0270, file "/usr/lib/python3.12/encodings/idna.py", line 1>, {'__name__': 'encodings.idn…

writes

Spider
<class 'scrapy.spiders.Spider'>

writes

update
memusage.py:75

calls×2 [#374]

set

Sets value if priority is higher or equal than current …
__init__.py:51

calls×36 [#23]

iteritems

headers.py:73

calls×2 [#83]

__iter__
sitemap.py:20

calls [#84]

__getitem__
headers.py:39

calls×29 [#85] settings

<scrapy.settings.Settings object at 0x720bd3a94320>

writes

freeze
Disable further changes to the current settings.
__init__.py:346

calls [#547] runner <scrapy.crawler.CrawlerRunner object at 0x720bd2b3ab40>

writes

calls×9 [#488]

build_component_list
Compose a component list from a { class: order } dictio…
conf.py:15

calls [#483]

k
(12 writes, 7 distinct)
'scrapy.extensions.corestats.CoreStats'
'scrapy.extensions.throttle.AutoThrottle'
'scrapy.extensions.telnet.TelnetConsole'
'scrapy.extensions.memusage.MemoryUsage'
'scrapy.extensions.memdebug.MemoryDebugger'
'scrapy.extensions.spiderstate.SpiderState'
… +1 more values

writes×8

v

(4 writes, 2 distinct)
0
b'/axe7xe3o'

writes

without_none_values
Return a copy of `iterable` with all `None` entries rem…
python.py:339

calls [#485] compdict

{'scrapy.extensions.corestats.CoreStats': 0, 'scrapy.extensions.telnet.TelnetConsole': 0, 'scrapy.extensions.memusage.Me…

writes

mwlist
['scrapy.extensions.corestats.CoreStats', 'scrapy.extensions.telnet.TelnetConsole', 'scrapy.extensions.memusage.MemoryUs…

writes

middlewares
(4 writes, 4 distinct)
[]
[<scrapy.extensions.corestats.CoreStats object at 0x720bd2a7ce60>]
[<scrapy.extensions.corestats.CoreStats object at 0x720bd2a7ce60>, <scrapy.extensions.telnet.TelnetConsole object at 0x7…
[<scrapy.extensions.corestats.CoreStats object at 0x720bd2a7ce60>, <scrapy.extensions.telnet.TelnetConsole object at 0x7…

writes×4

enabled
(4 writes, 4 distinct)
[]
['scrapy.extensions.corestats.CoreStats']
['scrapy.extensions.corestats.CoreStats', 'scrapy.extensions.telnet.TelnetConsole']
['scrapy.extensions.corestats.CoreStats', 'scrapy.extensions.telnet.TelnetConsole', 'scrapy.extensions.logstats.LogStats…

writes×4

clspath
(9 writes, 9 distinct)
'scrapy.extensions.corestats.CoreStats'
'scrapy.extensions.telnet.TelnetConsole'
'scrapy.extensions.memusage.MemoryUsage'
'scrapy.extensions.memdebug.MemoryDebugger'
'scrapy.extensions.closespider.CloseSpider'
'scrapy.extensions.feedexport.FeedExporter'
… +3 more values

writes×9

mwcls
(9 writes, 9 distinct)
<class 'scrapy.extensions.corestats.CoreStats'>
<class 'scrapy.extensions.telnet.TelnetConsole'>
<class 'scrapy.extensions.memusage.MemoryUsage'>
<class 'scrapy.extensions.memdebug.MemoryDebugger'>
<class 'scrapy.extensions.closespider.CloseSpider'>
<class 'scrapy.extensions.feedexport.FeedExporter'>
… +3 more values

writes×9

mw

(5 writes, 3 distinct)
<scrapy.extensions.corestats.CoreStats object at 0x720bd2a7ce60>
<scrapy.extensions.telnet.TelnetConsole object at 0x720bd2ab2240>
<scrapy.extensions.logstats.LogStats object at 0x720bd289eb70>

writes×4

scrapy.exceptions.NotConfigured

raises (caught)

e

(6 writes)
NotConfigured()

writes×6

_add_middleware
__init__.py:18

calls [#546]

passed to

passed to passed to

passed to

passed to passed to

passed to passed to

passed to

passed to passed to passed to

passed to

passed to

passed to

escape_ajax
Return the crawleable url according to:
url.py:48

passed to

passed to passed to

passed to

connect

Connect a receiver function to a signal.
signalmanager.py:11

passed to

_removeOldBackRefs

passed to

_verify

calls [#390]

dot
(12 writes, 7 distinct)
19
22
27
24
26
29
… +1 more values

writes×12

mod
(12 writes, 12 distinct)
<module 'scrapy.spiderloader' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py'>
<module 'scrapy.statscollectors' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/statscollectors.py'>
<module 'scrapy.logformatter' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/logformatter.py'>
<module 'scrapy.extensions.corestats' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/extensions/corestats.py'…
<module 'scrapy.extensions.telnet' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/extensions/telnet.py'>
<module 'scrapy.extensions.memusage' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/extensions/memusage.py'>
… +6 more values

writes×12

calls×2 [#454]

calls×12 [#7]

calls×19 [#9]

setmodule
Store settings from a module with a given priority.
__init__.py:265

calls [#11]

calls×4 [#452]

get
headers.py:45

calls [#461]

copy

Return a copy of this Response
__init__.py:67

calls [#445]

getlist
headers.py:51

calls×2 [#435]

_load_all_spiders
spiderloader.py:26

calls [#441]

update_settings
__init__.py:79

calls [#446]

getbool
Get a setting value as a boolean.
__init__.py:113

calls×5 [#457]

handler
<LogCounterHandler (DEBUG)>

writes

calls×3 [#467]

lf_cls
<class 'scrapy.logformatter.LogFormatter'>

writes

calls×2 [#473]

writes raises (caught)

getfloat
Get a setting value as a float.
__init__.py:143

calls [#519]

getint
Get a setting value as an int.
__init__.py:131

calls×5 [#520]

calls [#545]

_set_url
text.py:30

calls×3 [#579]

_set_body
text.py:39

calls×3 [#586]

unwindGenerator
(3 writes, 3 distinct)
<function Crawler.crawl at 0x720bd29ff100>
<function Crawler.stop at 0x720bd29ff380>
<function CrawlerRunner.join at 0x720bd29ff920>

writes×3 calls [#549]

passed to

calls [#443]

calls [#444]

calls [#389]

calls [#388]

calls×3 [#377]

cls_path
'scrapy.spiderloader.SpiderLoader'

writes

loader_cls
<class 'scrapy.spiderloader.SpiderLoader'>

writes

frozencopy
Return an immutable copy of the current settings.
__init__.py:356

calls [#430]

from_settings
Return an instance of the class for the given settings
interfaces.py:5

calls [#433]

passed to

passed to

passed to

__new__
item.py:27

passed to

passed to

replace
text.py:49

passed to

pop

[closure inside _serializable_queue]
squeues.py:19

passed to _assert_mutability

__init__.py:330

calls×20 [#10]

calls×18 [#94] calls×9 [#95]

writes writes

seq

dict_items([('Location', b'/axe7xe3o')])

writes

iseq
<generator object CaselessDict.update.<locals>.<genexpr> at 0x720bd279b100>

writes

normkey
Normalize key to bytes
headers.py:14

calls [#594]

normvalue
Normalize values to bytes
headers.py:18

calls [#596]

calls [#12]

calls×2 [#13]

calls×30 [#17]

calls×47 [#14]

calls×17 [#109]

get_settings_priority
Small helper function that looks up a given string prio…
__init__.py:24

calls×47 [#15]

__contains__
__init__.py:98

calls×47 [#16]

calls [#605]

calls×44 [#86]

calls [#608]

calls [#609]

passed to

passed to

passed to

passed to

_get_mwlist_from_settings
extension.py:14

passed to

job_dir
job.py:3

passed to

calls×16 [#378]

tester

<built-in method implementedBy of InterfaceClass object at 0x720bd2b099d0>

writes

excs

[]

writes

namesAndDescriptions

calls [#391]

desc
(4 writes, 4 distinct)
<zope.interface.interface.Method object at 0x720bd2b1bf50 scrapy.interfaces.ISpiderLoader.from_settings(settings)>
<zope.interface.interface.Method object at 0x720bd2aea9c0 scrapy.interfaces.ISpiderLoader.load(spider_name)>
<zope.interface.interface.Method object at 0x720bd2b1be30 scrapy.interfaces.ISpiderLoader.list()>
<zope.interface.interface.Method object at 0x720bd2b1bf20 scrapy.interfaces.ISpiderLoader.find_by_request(request)>

writes×4

_verify_element

calls×4 [#393]

writes

calls [#392]

r

(3 writes, 2 distinct)
{}
{'from_settings': <zope.interface.interface.Method object at 0x720bd2b1bf50 scrapy.interfaces.ISpiderLoader.from_setting…

writes×3

passed to

attr

(4 writes, 4 distinct)
<bound method SpiderLoader.from_settings of <class 'scrapy.spiderloader.SpiderLoader'>>
<function SpiderLoader.load at 0x720bd28ac2c0>
<function SpiderLoader.list at 0x720bd28ac400>
<function SpiderLoader.find_by_request at 0x720bd28ac360>

writes×4

fromMethod

calls [#394]

fromFunction

calls×3 [#404]

meth
(4 writes, 4 distinct)
<zope.interface.interface.Method object at 0x720bd289d5e0 scrapy.interfaces.ISpiderLoader.from_settings(settings)>
<zope.interface.interface.Method object at 0x720bd289d7f0 scrapy.interfaces.ISpiderLoader.load(spider_name)>
<zope.interface.interface.Method object at 0x720bd289d6a0 scrapy.interfaces.ISpiderLoader.list()>
<zope.interface.interface.Method object at 0x720bd289d7f0 scrapy.interfaces.ISpiderLoader.find_by_request(request)>

writes×4

getSignatureInfo

calls×8 [#398]

_incompat

calls×4 [#402]

mess

(4 writes)
None

writes×4

func
<function SpiderLoader.from_settings at 0x720bd28ac220>

writes

calls [#395]

writes×4 passed to

calls×4 [#396]

method
(11 writes, 11 distinct)
<zope.interface.interface.Method object at 0x720bd289d5e0 from_settings()>
<zope.interface.interface.Method object at 0x720bd289d5e0 from_settings(settings)>
<zope.interface.interface.Method object at 0x720bd289d5e0 scrapy.interfaces.ISpiderLoader.from_settings(settings)>
<zope.interface.interface.Method object at 0x720bd289d7f0 load()>
<zope.interface.interface.Method object at 0x720bd289d7f0 load(spider_name)>
<zope.interface.interface.Method object at 0x720bd289d7f0 scrapy.interfaces.ISpiderLoader.load(spider_name)>
… +5 more values

writes×11

defaults
(4 writes)
()

writes×4

na

(4 writes, 2 distinct)
1
0

writes×4

names

(4 writes, 4 distinct)
('settings',)
('spider_name',)
()
('request', 'name', 'cls')

writes×4

opt
(4 writes)
{}

writes×4

defaults_count
(4 writes)
0

writes×4

nr

(4 writes, 2 distinct)
1
0

writes×4

_set_optional

calls×4 [#397]

argno
(4 writes, 2 distinct)
1
0

writes×4

passed to

passed to

_get_optional

calls×8 [#399]

calls [#431]

calls [#432]

calls [#434]

calls [#476]

calls [#436]

setdict
__init__.py:262

calls [#447]

calls [#448]

calls×3 [#458] calls×9 [#468]

safeRef

calls×2 [#469]

receiver
(9 writes, 9 distinct)
<weakref at 0x720bd2955940; to 'function' at 0x720bd46da660 (<lambda>)>
BoundMethodWeakref(CoreStats.spider_opened)
BoundMethodWeakref(CoreStats.spider_closed)
BoundMethodWeakref(CoreStats.item_scraped)
BoundMethodWeakref(CoreStats.item_dropped)
BoundMethodWeakref(CoreStats.response_received)
… +3 more values

writes×9

senderkey
(9 writes)
125395135662128

writes×9

remove

(9 writes, 4 distinct)
<function connect.<locals>.remove at 0x720bd28acf40>
<function connect.<locals>.remove at 0x720bd28ad760>
<function connect.<locals>.remove at 0x720bd27e0fe0>
<function connect.<locals>.remove at 0x720bd2831f80>

writes×9

weakSender
(9 writes, 9 distinct)
<weakref at 0x720bd2956610; to 'Crawler' at 0x720bd4848830>
<weakref at 0x720bd29664d0; to 'Crawler' at 0x720bd4848830>
<weakref at 0x720bd29662f0; to 'Crawler' at 0x720bd4848830>
<weakref at 0x720bd2966250; to 'Crawler' at 0x720bd4848830>
<weakref at 0x720bd2966430; to 'Crawler' at 0x720bd4848830>
<weakref at 0x720bd2966840; to 'Crawler' at 0x720bd4848830>
… +3 more values

writes×9

receiverID
(9 writes, 9 distinct)
125395103209792
125395102455408
125395102995696
125395160610672
125395102458672
125395150224416
… +3 more values

writes×9

calls [#556]

passed to

passed to passed to

writes×2

calls×9 [#489]

calls [#475] calls [#514] calls×7 [#490]

raises (caught)

calls [#529]

interval
60.0

writes

calls [#538]

jobdir
None

writes

calls [#550]

spider
<Spider 'foo' at 0x720bd3aa43b0>

writes

_set_crawler
__init__.py:63

calls [#552]

getwithbase
Get a composition of a dictionary-like setting and its …
__init__.py:195

calls [#477]

calls [#478]

calls [#480] calls [#479]

compbs
(2 writes, 2 distinct)
<scrapy.settings.BaseSettings object at 0x720bd29349b0>
<scrapy.settings.BaseSettings object at 0x720bd2a7cdd0>

writes

_check_components
<function build_component_list.<locals>._check_components at 0x720bd28ad800>

writes

_map_keys
<function build_component_list.<locals>._map_keys at 0x720bd28ad580>

writes

passed to

writes

writes writes

prio
0

writes

writes×2 writes passed to passed to

passed to passed to

calls×2 [#566] calls [#530]

passed to

calls [#539]

process_response
chunked.py:9

passed to

_redirect
redirect.py:28

passed to

calls [#553]

ValueError
<weakref at 0x720bd2805080; to 'function' at 0x720bd3b3ab60 (close)> is not in list

raises (caught)

test_latin1_location
test_downloadermiddleware_redirect.py:159

calls×2 [#578]

calls×2 [#577]

req

<GET http://scrapytest.org/first>

writes

latin1_location
b'/axe7xe3o'

writes

resp

<302 http://scrapytest.org/first>

calls [#600] writes

req_result
<GET http://scrapytest.org/a%C3%A7%C3%A3o>

writes

perc_encoded_utf8_url
'http://scrapytest.org/a%E7%E3o'

writes

AttributeError
'RedirectMiddlewareTest' object has no attribute 'assertEquals'. Did you mean: 'assertEqual'?

raises (caught)

encoding
text.py:54

calls×2 [#580]

safe_url_string

calls×2 [#581]

s

(2 writes, 2 distinct)
'http://scrapytest.org/first'
'http://scrapytest.org/a%C3%A7%C3%A3o'

calls×2 [#585] writes×2

calls [#584] writes writes writes writes writes×4 writes writes writes writes×2 writes writes writes writes writes writes writes writes writes

writes

writes

to_unicode
Return the unicode representation of a bytes object `te…
python.py:99

calls×2 [#582]

decoded
(2 writes, 2 distinct)
'http://scrapytest.org/first'
'http://scrapytest.org/ação'

writes×2

_strip

calls×2 [#583]

parts
(2 writes, 2 distinct)
SplitResult(scheme='http', netloc='scrapytest.org', path='/first', query='', fragment='')
SplitResult(scheme='http', netloc='scrapytest.org', path='/ação', query='', fragment='')

writes×2

username

(2 writes)
None

writes×2

password
(2 writes)
None

writes×2

hostname
(2 writes)
'scrapytest.org'

writes×2

port
(2 writes)
None

writes×2

netloc_bytes
(4 writes, 2 distinct)
b''
b'scrapytest.org'

writes×4

netloc
(2 writes)
'scrapytest.org'

writes×2

query
(2 writes)

''

writes×2

defrag
(2 writes, 2 distinct)
'http://scrapytest.org/first'
'http://scrapytest.org/a%C3%A7%C3%A3o'

writes×2

frag
(2 writes)

''

writes×2

calls [#629]

to_bytes
Return the binary representation of `text`. If `text`
python.py:112

calls [#630]

passed to

_tobytes
headers.py:29

calls×5 [#595]

calls [#597]

calls [#621]

calls [#607] calls [#604]

calls [#620]

calls [#619]

loops(×7)

meta

__init__.py:25

calls×4 [#601] allowed_status

(301, 302, 303, 307)

writes

to_native_str
Return str representation of `text`
python.py:125

calls [#611] location

'/ação'

writes

_get_url
__init__.py:34

calls [#613] redirected_url

'http://scrapytest.org/ação'

writes

_redirect_request_using_get
redirect.py:48

calls [#614]

_get_body
__init__.py:46

calls [#617] cls

<class 'scrapy.http.request.Request'>

writes

redirected
(2 writes)
<GET http://scrapytest.org/a%C3%A7%C3%A3o>

writes×2

calls×2 [#633] calls [#639]

calls [#615] calls [#616] calls [#612]

passed to

passed to

calls×2 [#634]

calls×6 [#640]

calls [#645]

ttl
20

writes

redirects
1

writes