test_from_content_disposition
test_responsetypes.py:25
loops (×21)
writes×2
writes×3
writes×6
writes×15
writes×4
writes
calls×4 [#4]
calls×3 [#1]
cls
(2 writes, 2 distinct)
<class 'scrapy.http.response.xml.XmlResponse'>
<class 'scrapy.http.response.Response'>
p
(3 writes)
'/'
optimization
(6 writes)
''
source_path
(3 writes, 3 distinct)
'/usr/lib/python3.12/encodings/gbk.py'
'/usr/lib/python3.12/encodings/cp720.py'
'/usr/lib/python3.12/encodings/iso2022_jp.py'
exc_details
(3 writes, 3 distinct)
{'name': 'encodings.gbk', 'path': '/usr/lib/python3.12/encodings/__pycache__/gbk.cpython-312.pyc'}
{'name': 'encodings.cp720', 'path': '/usr/lib/python3.12/encodings/__pycache__/cp720.cpython-312.pyc'}
{'name': 'encodings.iso2022_jp', 'path': '/usr/lib/python3.12/encodings/__pycache__/iso2022_jp.cpython-312.pyc'}
loader
(6 writes, 3 distinct)
<_frozen_importlib_external.SourceFileLoader object at 0x76f56d1ebb60>
<_frozen_importlib_external.SourceFileLoader object at 0x76f56d1f78f0>
<_frozen_importlib_external.SourceFileLoader object at 0x76f56d1e8380>
source_mtime
(6 writes, 2 distinct)
None
1772540118
data
(3 writes, 3 distinct)
bytes(len=1988)
bytes(len=3204)
bytes(len=2007)
loader_class
(6 writes, 2 distinct)
<class '_frozen_importlib_external.ExtensionFileLoader'>
<class '_frozen_importlib_external.SourceFileLoader'>
bytecode_path
(3 writes, 3 distinct)
'/usr/lib/python3.12/encodings/__pycache__/gbk.cpython-312.pyc'
'/usr/lib/python3.12/encodings/__pycache__/cp720.cpython-312.pyc'
'/usr/lib/python3.12/encodings/__pycache__/iso2022_jp.cpython-312.pyc'
finder
(15 writes, 4 distinct)
<class '_frozen_importlib.BuiltinImporter'>
<class '_frozen_importlib.FrozenImporter'>
<class '_frozen_importlib_external.PathFinder'>
FileFinder('/usr/lib/python3.12/encodings')
info
(3 writes)
None
namespace_path
(3 writes)
[]
entry
(3 writes)
'/usr/lib/python3.12/encodings'
is_namespace
(3 writes)
False
tail_module
(3 writes, 3 distinct)
'gbk'
'cp720'
'iso2022_jp'
mtime
(3 writes)
1775119204.8187785
cache
(3 writes)
set(len=123)
cache_module
(3 writes, 3 distinct)
'gbk'
'cp720'
'iso2022_jp'
suffix
(6 writes, 2 distinct)
'.cpython-312-x86_64-linux-gnu.so'
'.py'
full_path
(6 writes, 6 distinct)
'/usr/lib/python3.12/encodings/gbk.cpython-312-x86_64-linux-gnu.so'
'/usr/lib/python3.12/encodings/gbk.py'
'/usr/lib/python3.12/encodings/cp720.cpython-312-x86_64-linux-gnu.so'
'/usr/lib/python3.12/encodings/cp720.py'
'/usr/lib/python3.12/encodings/iso2022_jp.cpython-312-x86_64-linux-gnu.so'
'/usr/lib/python3.12/encodings/iso2022_jp.py'
stat_info
(3 writes, 3 distinct)
os.stat_result(st_mode=33188, st_ino=527615, st_dev=66309, st_nlink=1, st_uid=0, st_gid=0, st_size=1015, st_atime=177511...
os.stat_result(st_mode=33188, st_ino=527526, st_dev=66309, st_nlink=1, st_uid=0, st_gid=0, st_size=13686, st_atime=17751...
os.stat_result(st_mode=33188, st_ino=527620, st_dev=66309, st_nlink=1, st_uid=0, st_gid=0, st_size=1053, st_atime=177511...
head
(6 writes)
'/usr/lib/python3.12/encodings'
tail
(6 writes, 3 distinct)
'gbk.py'
'cp720.py'
'iso2022_jp.py'
base
(6 writes, 3 distinct)
'gbk'
'cp720'
'iso2022_jp'
sep
(6 writes)
'.'
rest
(6 writes)
'py'
tag
(6 writes)
'cpython-312'
almost_filename
(6 writes, 3 distinct)
'gbk.cpython-312'
'cp720.cpython-312'
'iso2022_jp.cpython-312'
source_bytes
(3 writes)
None
source_hash
(3 writes)
None
hash_based
(3 writes)
False
check_source
(3 writes)
True
i
(3 writes)
29
st
(6 writes, 6 distinct)
os.stat_result(st_mode=33188, st_ino=527615, st_dev=66309, st_nlink=1, st_uid=0, st_gid=0, st_size=1015, st_atime=177511...
{'mtime': 1772540118.0, 'size': 1015}
os.stat_result(st_mode=33188, st_ino=527526, st_dev=66309, st_nlink=1, st_uid=0, st_gid=0, st_size=13686, st_atime=17751...
{'mtime': 1772540118.0, 'size': 13686}
os.stat_result(st_mode=33188, st_ino=527620, st_dev=66309, st_nlink=1, st_uid=0, st_gid=0, st_size=1053, st_atime=177511...
{'mtime': 1772540118.0, 'size': 1053}
file
(3 writes, 3 distinct)
<_io.BufferedReader name='/usr/lib/python3.12/encodings/__pycache__/gbk.cpython-312.pyc'>
<_io.BufferedReader name='/usr/lib/python3.12/encodings/__pycache__/cp720.cpython-312.pyc'>
<_io.BufferedReader name='/usr/lib/python3.12/encodings/__pycache__/iso2022_jp.cpython-312.pyc'>
magic
(3 writes)
b'\xcb
.
flags
(6 writes)
0
bytes_data
(3 writes, 2 distinct)
<memory at 0x76f56d338940>
<memory at 0x76f56d338a00>
code
(6 writes, 3 distinct)
<code object <module> at 0xa5b5280, file "/usr/lib/python3.12/encodings/gbk.py", line 1>
<code object <module> at 0x76f56d591e30, file "/usr/lib/python3.12/encodings/cp720.py", line 1>
<code object <module> at 0xa5b5280, file "/usr/lib/python3.12/encodings/iso2022_jp.py", line 1>
mappings
[(b'attachment; filename="data.xml"', <class 'scrapy.http.response.xml.XmlResponse'>), (b'attachment; filename=data.xml'...
source
(4 writes, 4 distinct)
bytes(len=31)
bytes(len=29)
bytes(len=33)
bytes(len=32)
retcls
(2 writes, 2 distinct)
<class 'scrapy.http.response.xml.XmlResponse'>
<class 'scrapy.http.response.Response'>
passed to
from_content_disposition
responsetypes.py:60
find_spec
filename
(10 writes, 6 distinct)
'gbk.cpython-312.pyc'
'cp720.cpython-312.pyc'
'iso2022_jp.cpython-312.pyc'
'"data.xml"'
'data.xml'
'data£.tar.gz'
raises (caught)
calls×4 [#5]
calls×3 [#7]
to_native_str
Return str representation of `text`
python.py:125
from_filename
Return the most appropriate Response class from a file ...
responsetypes.py:81
calls×4 [#6]
calls×2 [#8]
mimetype
(3 writes, 2 distinct)
'application/xml'
'application/x-tar'
to_unicode
Return the unicode representation of a bytes object `te...
python.py:99
from_mimetype
Return the most appropriate Response class for the give...
responsetypes.py:42
UnicodeDecodeError
'utf-8' codec can't decode byte 0xb5 in position 24: invalid start byte
encoding
(7 writes, 3 distinct)
'utf-8'
None
'gzip'