setUp
test_stats.py:9

get_crawler
Return an unconfigured Crawler object. If settings_dict…
test.py:23

calls [#1]

_create_spider
<function Crawler._create_spider at 0x7e5d704698a0>

calls [#211]

from_crawler
extensions.py:9

calls [#220]

loops(×173)

KeyError
'scrapy.crawler'

raises (caught)

lock
(2 writes, 2 distinct)
None

_ModuleLock('scrapy.crawler') at 138939797562112

writes×2

cb
<function _get_module_lock.<locals>.cb at 0x7e5d71485da0>

writes

tid
(3 writes)
138939851845760

writes×2

o

(3 writes, 3 distinct)
None

<scrapy.extensions.corestats.CoreStats object at 0x7e5d704cd670>
<scrapy.extensions.logstats.LogStats object at 0x7e5d703ffb00>

writes

parent
(9 writes, 5 distinct)
'scrapy'
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__'
'zope.interface'
'scrapy.core'
'scrapy.utils'

writes×9

parent_module
(8 writes, 4 distinct)
<module 'scrapy' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__init__.py'>
<module 'zope.interface' from '/home/shashwat/BTP/.venv/lib/python3.12/site-packages/zope/interface/__init__.py'>
<module 'scrapy.core' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/core/__init__.py'>
<module 'scrapy.utils' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/utils/__init__.py'>

writes×8

child
(8 writes, 8 distinct)
'crawler'
'verify'
'engine'
'resolver'
'interfaces'
'extension'
… +2 more values

writes×8

meta_path
[<_distutils_hack.DistutilsMetaFinder object at 0x7e5d73d704a0>, <class '_frozen_importlib.BuiltinImporter'>, <class '_f…

writes

is_reload
False

writes

finder
(10 writes, 6 distinct)
<_distutils_hack.DistutilsMetaFinder object at 0x7e5d73d704a0>
<class '_frozen_importlib.BuiltinImporter'>
<class '_frozen_importlib.FrozenImporter'>
<class '_frozen_importlib_external.PathFinder'>
FileFinder('/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy')
FileFinder('/usr/lib/python3.12/encodings')

writes×6

find_spec
(7 writes, 4 distinct)
<bound method DistutilsMetaFinder.find_spec of <_distutils_hack.DistutilsMetaFinder object at 0x7e5d73d704a0>>
<bound method BuiltinImporter.find_spec of <class '_frozen_importlib.BuiltinImporter'>>
<bound method FrozenImporter.find_spec of <class '_frozen_importlib.FrozenImporter'>>
<bound method PathFinder.find_spec of <class '_frozen_importlib_external.PathFinder'>>

writes×4

info
(2 writes)
None

writes

namespace_path
(2 writes)
[]

writes

entry
(2 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy'
'/usr/lib/python3.12/encodings'

writes

is_namespace
False

writes

tail_module
'crawler'

writes

mtime
1780556959.6750202

writes

cache
set(len=55)

writes

cache_module
'crawler'

writes

suffix
(2 writes, 2 distinct)
'.cpython-312-x86_64-linux-gnu.so'
'.py'

writes×2

loader_class
(2 writes, 2 distinct)
<class '_frozen_importlib_external.ExtensionFileLoader'>
<class '_frozen_importlib_external.SourceFileLoader'>

writes×2

part
(6 writes, 4 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy'
'crawler.cpython-312-x86_64-linux-gnu.so'
'crawler.py'
'crawler.cpython-312.pyc'

writes×6

full_path
(2 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.cpython-312-x86_64-linux-gnu.so'
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py'

writes×2

stat_info
os.stat_result(st_mode=33204, st_ino=3555188, st_dev=66309, st_nlink=1, st_uid=1000, st_gid=1000, st_size=11182, st_atim…

writes

loader
(3 writes, 2 distinct)
<_frozen_importlib_external.SourceFileLoader object at 0x7e5d7158ef90>
<_frozen_importlib_external.SourceFileLoader object at 0x7e5d704c8920>

writes×2

head
(2 writes)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy'

writes×2

tail
(2 writes)
'crawler.py'

writes×2

base
(3 writes, 2 distinct)
'crawler'
<InterfaceClass zope.interface.Interface>

writes×2

sep
(2 writes)
'.'

writes×2

rest

(2 writes)
'py'

writes×2

tag
(2 writes)
'cpython-312'

writes×2

almost_filename
(2 writes)
'crawler.cpython-312'

writes×2

optimization
(2 writes)

''

writes×2

filename
(3 writes)
'crawler.cpython-312.pyc'

writes×3

source_path
(2 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py'
'/usr/lib/python3.12/encodings/idna.py'

writes

source_mtime
(4 writes, 3 distinct)
None
1780556959
1772540118

writes×2

source_bytes
(3 writes, 2 distinct)
None

bytes(len=11182)

writes×2

source_hash
(2 writes)
None

writes

hash_based
(2 writes)
False

writes

check_source
(2 writes)
True

writes

p
'/'

writes

i
(2 writes, 2 distinct)
51
63

writes×2

bytecode_path
(2 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.pyc'
'/usr/lib/python3.12/encodings/__pycache__/idna.cpython-312.pyc'

writes

st

(3 writes, 3 distinct)
os.stat_result(st_mode=33204, st_ino=3555188, st_dev=66309, st_nlink=1, st_uid=1000, st_gid=1000, st_size=11182, st_atim…
{'mtime': 1780556959.6730201, 'size': 11182}
{'mtime': 1772540118.0, 'size': 9710}

writes×2

file
(4 writes, 4 distinct)
<_io.BufferedReader name='/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.pyc'>
<_io.BufferedReader name='/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py'>
<_io.FileIO name=3 mode='wb' closefd=True>
<_io.FileIO [closed]>

writes×4

data
(8 writes, 7 distinct)
bytes(len=17750)
bytearray(b'xcb

')
bytearray(b'xcb

x00x00x00x00')
bytearray(b'xcb

x00x00x00x00x9f$!j')
bytearray(b'xcb

x00x00x00x00x9f$!jxae+x00x00')
bytearray(b'xcb

x00x00x00x00x9f$!jxae+x00x00xe3x00x00x00x00x00x00x00x00x00x00x00x00x05x00x…
… +1 more values

writes×7

exc_details
(2 writes, 2 distinct)
{'name': 'scrapy.crawler', 'path': '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.…
{'name': 'encodings.idna', 'path': '/usr/lib/python3.12/encodings/__pycache__/idna.cpython-312.pyc'}

writes

magic
b'xcb

'

writes

flags
(3 writes)
0

writes×2

bytes_data
(2 writes, 2 distinct)
<memory at 0x7e5d71582440>
<memory at 0x7e5d705934c0>

writes

message

"bytecode is stale for 'scrapy.crawler'"

writes

ImportError
bytecode is stale for 'scrapy.crawler'

raises (caught)

code_object
<code object <module> at 0x7e5d7154b630, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py", line 1>

writes

mode
(2 writes)
33204

writes×2

path_parts
[]

writes

path_tmp
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.pyc.138939797658416'

writes

fd
3

writes

code
(6 writes, 6 distinct)
<code object <module> at 0x7e5d7154b630, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py", line 1>
<code object from_settings at 0x7e5d71442a30, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py"…
<code object load at 0x7e5d715eb340, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py", line 32…
<code object list at 0x7e5d70650be0, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py", line 49…
<code object find_by_request at 0x7e5d706ae790, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.p…
<code object <module> at 0x27a93c40, file "/usr/lib/python3.12/encodings/idna.py", line 1>

writes

six

<module 'six' from '/home/shashwat/BTP/.venv/lib/python3.12/site-packages/six.py'>

writes

signal
<module 'signal' from '/usr/lib/python3.12/signal.py'>

writes

logging
<module 'logging' from '/usr/lib/python3.12/logging/__init__.py'>

writes

warnings
<module 'warnings' from '/usr/lib/python3.12/warnings.py'>

writes

from_name
'twisted.internet.reactor'

writes

reactor

<twisted.internet.epollreactor.EPollReactor object at 0x7e5d7213f7d0>

writes

defer
<module 'twisted.internet.defer' from '/home/shashwat/BTP/.venv/lib/python3.12/site-packages/twisted/internet/defer.py'>

writes

verifyClass
<function verifyClass at 0x7e5d7057e8e0>

writes

DoesNotImplement
<class 'zope.interface.exceptions.DoesNotImplement'>

writes

ExecutionEngine
<class 'scrapy.core.engine.ExecutionEngine'>

writes

CachingThreadedResolver
<class 'scrapy.resolver.CachingThreadedResolver'>

writes

ISpiderLoader
<InterfaceClass scrapy.interfaces.ISpiderLoader>

writes

ExtensionManager
<class 'scrapy.extension.ExtensionManager'>

writes

Settings
(2 writes)
<class 'scrapy.settings.Settings'>

writes×2

SignalManager
<class 'scrapy.signalmanager.SignalManager'>

writes

ScrapyDeprecationWarning
<class 'scrapy.exceptions.ScrapyDeprecationWarning'>

writes

install_shutdown_handlers
<function install_shutdown_handlers at 0x7e5d704693a0>

writes

signal_names
dict(len=34)

writes

load_object
<function load_object at 0x7e5d715537e0>

writes

LogCounterHandler
<class 'scrapy.utils.log.LogCounterHandler'>

writes

configure_logging
<function configure_logging at 0x7e5d7057eb60>

writes

log_scrapy_info
<function log_scrapy_info at 0x7e5d705f7ba0>

writes

logger
<Logger scrapy.crawler (WARNING)>

writes

__module__
(3 writes)
'scrapy.crawler'

writes×3

__qualname__
(3 writes, 3 distinct)
'Crawler'
'CrawlerRunner'
'CrawlerProcess'

writes×3

__init__
(3 writes, 3 distinct)
<function Crawler.__init__ at 0x7e5d704694e0>
<function CrawlerRunner.__init__ at 0x7e5d70469b20>
<function CrawlerProcess.__init__ at 0x7e5d7046a020>

writes×3

spiders
(2 writes, 2 distinct)
<property object at 0x7e5d70572930>
<property object at 0x7e5d70490e50>

writes×2

inlineCallbacks

calls×3 [#3]

crawl
(2 writes, 2 distinct)
<function Crawler.crawl at 0x7e5d70469800>
<function CrawlerRunner.crawl at 0x7e5d70469c60>

writes×2

writes

_create_engine
<function Crawler._create_engine at 0x7e5d70469940>

writes

stop
(2 writes, 2 distinct)
<function Crawler.stop at 0x7e5d70469a80>
<function CrawlerRunner.stop at 0x7e5d70469e40>

writes×2

Crawler
<class 'scrapy.crawler.Crawler'>

writes

__doc__
(2 writes, 2 distinct)
"

This is a convenient helper class that keeps track of, manages and runs
crawlers inside an already setup Twi…

"

A class to run multiple scrapy crawlers in a process simultaneously.

This class extends :class:`~scrapy.cr…

writes×2

crawlers
<property object at 0x7e5d70490b80>

writes

_crawl
<function CrawlerRunner._crawl at 0x7e5d70469d00>

writes

_create_crawler
<function CrawlerRunner._create_crawler at 0x7e5d70469da0>

writes join <function CrawlerRunner.join at 0x7e5d70469f80>

writes

CrawlerRunner
(2 writes)
<class 'scrapy.crawler.CrawlerRunner'>

writes×2

_signal_shutdown
<function CrawlerProcess._signal_shutdown at 0x7e5d7046a0c0>

writes

_signal_kill
<function CrawlerProcess._signal_kill at 0x7e5d7046a160>

writes

start
<function CrawlerProcess.start at 0x7e5d7046a200>

writes

_get_dns_resolver
<function CrawlerProcess._get_dns_resolver at 0x7e5d7046a2a0>

writes

_graceful_stop_reactor
<function CrawlerProcess._graceful_stop_reactor at 0x7e5d7046a340>

writes

_stop_reactor
<function CrawlerProcess._stop_reactor at 0x7e5d7046a3e0>

writes

__classcell__
<cell at 0x7e5d705ab310: empty>

writes

CrawlerProcess
<class 'scrapy.crawler.CrawlerProcess'>

writes

_get_spider_loader
<function _get_spider_loader at 0x7e5d70469440>

writes

args
(2 writes, 2 distinct)
(<code object <module> at 0x7e5d7154b630, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py", line 1>…
(<code object <module> at 0x27a93c40, file "/usr/lib/python3.12/encodings/idna.py", line 1>, {'__name__': 'encodings.idn…

writes

Spider
<class 'scrapy.spiders.Spider'>

writes

key
(4 writes, 4 distinct)
'AJAXCRAWL_ENABLED'
'USER_AGENT'
'__builtins__'
'sys'

writes×3

set

Sets value if priority is higher or equal than current …
__init__.py:35

calls [#12]

freeze
__init__.py:120

calls [#210] runner <scrapy.crawler.CrawlerRunner object at 0x7e5d704ca180>

writes

iteritems

headers.py:72

calls×2 [#109]

calls×9 [#117]

_map_keys
<function build_component_list.<locals>._map_keys at 0x7e5d7046b740>

calls [#112]

c

(3 writes, 3 distinct)
'scrapy.extensions.corestats.CoreStats'
'scrapy.telnet.TelnetConsole'
'scrapy.extensions.throttle.AutoThrottle'

writes

update_classpath
Update a deprecated path from an object with its new lo…
deprecate.py:149

calls×2 [#110]

k
(3 writes, 3 distinct)
'scrapy.extensions.corestats.CoreStats'
'scrapy.extensions.throttle.AutoThrottle'
'Location'

writes×2

v

(2 writes, 2 distinct)
0
'http://www.example.com/redirected'

writes

compdict
{'scrapy.extensions.corestats.CoreStats': 0, 'scrapy.telnet.TelnetConsole': 0, 'scrapy.extensions.memusage.MemoryUsage':…

writes items <generator object build_component_list.<locals>.<genexpr> at 0x7e5d73c335e0>

writes

mwlist
['scrapy.extensions.corestats.CoreStats', 'scrapy.telnet.TelnetConsole', 'scrapy.extensions.memusage.MemoryUsage', 'scra…

writes

middlewares
(6 writes, 6 distinct)
[]
[<scrapy.extensions.corestats.CoreStats object at 0x7e5d704cd670>]
[<scrapy.extensions.corestats.CoreStats object at 0x7e5d704cd670>, <scrapy.telnet.TelnetConsole object at 0x7e5d704c8e30…
[<scrapy.extensions.corestats.CoreStats object at 0x7e5d704cd670>, <scrapy.telnet.TelnetConsole object at 0x7e5d704c8e30…
[<scrapy.extensions.corestats.CoreStats object at 0x7e5d704cd670>, <scrapy.telnet.TelnetConsole object at 0x7e5d704c8e30…
[<scrapy.extensions.corestats.CoreStats object at 0x7e5d704cd670>, <scrapy.telnet.TelnetConsole object at 0x7e5d704c8e30…

writes×6

clspath
(9 writes, 9 distinct)
'scrapy.extensions.corestats.CoreStats'
'scrapy.telnet.TelnetConsole'
'scrapy.extensions.memusage.MemoryUsage'
'scrapy.extensions.memdebug.MemoryDebugger'
'scrapy.extensions.closespider.CloseSpider'
'scrapy.extensions.feedexport.FeedExporter'
… +3 more values

writes×9

mwcls
(9 writes, 9 distinct)
<class 'scrapy.extensions.corestats.CoreStats'>
<class 'scrapy.telnet.TelnetConsole'>
<class 'scrapy.extensions.memusage.MemoryUsage'>
<class 'scrapy.extensions.memdebug.MemoryDebugger'>
<class 'scrapy.extensions.closespider.CloseSpider'>
<class 'scrapy.extensions.feedexport.FeedExporter'>
… +3 more values

writes×9

mw

(7 writes, 5 distinct)
<scrapy.extensions.corestats.CoreStats object at 0x7e5d704cd670>
<scrapy.telnet.TelnetConsole object at 0x7e5d704c8e30>
<scrapy.extensions.closespider.CloseSpider object at 0x7e5d7034d670>
<scrapy.extensions.logstats.LogStats object at 0x7e5d703ffb00>
<scrapy.extensions.spiderstate.SpiderState object at 0x7e5d70338a70>

writes×6

scrapy.exceptions.NotConfigured

raises (caught)

e

(4 writes)
NotConfigured()

writes×4

enabled
['CoreStats', 'TelnetConsole', 'CloseSpider', 'LogStats', 'SpiderState']

writes

_add_middleware
middleware.py:21

calls [#209]

passed to

passed to passed to

passed to

build_component_list
Compose a component list based on a custom and base dic…
conf.py:13

passed to

passed to passed to

passed to passed to

passed to

passed to passed to passed to

passed to

passed to

passed to

escape_ajax
Return the crawleable url according to:
url.py:87

passed to

passed to passed to

passed to

connect

Connect a receiver function to a signal.
signalmanager.py:11

passed to

_removeOldBackRefs

passed to

_verify

calls [#26]

dot
(12 writes, 7 distinct)
19
22
27
13
26
29
… +1 more values

writes×12

mod
(12 writes, 12 distinct)
<module 'scrapy.spiderloader' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py'>
<module 'scrapy.statscollectors' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/statscollectors.py'>
<module 'scrapy.logformatter' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/logformatter.py'>
<module 'scrapy.extensions.corestats' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/extensions/corestats.py'…
<module 'scrapy.telnet' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/telnet.py'>
<module 'scrapy.extensions.memusage' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/extensions/memusage.py'>
… +6 more values

writes×12

calls×2 [#84]

calls×8 [#82]

calls [#16]

setmodule
__init__.py:105

calls [#7]

get
headers.py:44

calls [#91]

__getitem__
headers.py:38

calls×4 [#83]

copy

Return a copy of this Response
__init__.py:67

calls [#77]

getlist
headers.py:50

calls×2 [#71]

update_settings
__init__.py:79

calls [#78]

getbool
True is: 1, '1', True
__init__.py:66

calls×5 [#87]

handler
<LogCounterHandler (DEBUG)>

writes

calls×4 [#95]

lf_cls
<class 'scrapy.logformatter.LogFormatter'>

writes

calls×2 [#100]

writes raises (caught)

getfloat
__init__.py:76

calls [#160]

getint
__init__.py:73

calls×5 [#162]

calls [#208]

_set_url
text.py:30

calls×2 [#236]

_set_body
text.py:39

calls×2 [#245]

update
memusage.py:75

calls [#253]

unwindGenerator
(3 writes, 3 distinct)
<function Crawler.crawl at 0x7e5d70469800>
<function Crawler.stop at 0x7e5d70469a80>
<function CrawlerRunner.join at 0x7e5d70469f80>

writes×3

calls [#212]

passed to

calls [#76]

calls [#25] calls [#24]

calls×3 [#17]

cls_path
'scrapy.spiderloader.SpiderLoader'

writes

loader_cls
<class 'scrapy.spiderloader.SpiderLoader'>

writes

frozencopy
__init__.py:123

calls [#66]

from_settings
Return an instance of the class for the given settings
interfaces.py:5

calls [#69]

passed to

passed to

passed to

__new__
item.py:27

passed to

passed to

_assert_mutability
__init__.py:113

calls [#8]

writes

calls [#9]

passed to

normkey
Normalize key to bytes
headers.py:13

passed to

__contains__
datatypes.py:181

passed to

calls×2 [#11]

calls×2 [#10]

priority
(2 writes)
0

writes×2

passed to

passed to

setdict
__init__.py:100

passed to

calls×20 [#18]

calls [#267]

calls [#268]

tester

<built-in method implementedBy of InterfaceClass object at 0x7e5d705795d0>

writes

excs

[]

writes

namesAndDescriptions

calls [#27]

desc
(4 writes, 4 distinct)
<zope.interface.interface.Method object at 0x7e5d7058dd90 scrapy.interfaces.ISpiderLoader.from_settings(settings)>
<zope.interface.interface.Method object at 0x7e5d7058dcd0 scrapy.interfaces.ISpiderLoader.load(spider_name)>
<zope.interface.interface.Method object at 0x7e5d7058dd60 scrapy.interfaces.ISpiderLoader.list()>
<zope.interface.interface.Method object at 0x7e5d7058dca0 scrapy.interfaces.ISpiderLoader.find_by_request(request)>

writes×4

_verify_element

calls×4 [#29]

writes

calls [#28]

r

(3 writes, 2 distinct)
{}
{'from_settings': <zope.interface.interface.Method object at 0x7e5d7058dd90 scrapy.interfaces.ISpiderLoader.from_setting…

writes×3

passed to

attr

(4 writes, 4 distinct)
<bound method SpiderLoader.from_settings of <class 'scrapy.spiderloader.SpiderLoader'>>
<function SpiderLoader.load at 0x7e5d7054d3a0>
<function SpiderLoader.list at 0x7e5d7046a5c0>
<function SpiderLoader.find_by_request at 0x7e5d71486480>

writes×4

fromMethod

calls [#30]

fromFunction

calls×3 [#40]

meth
(4 writes, 4 distinct)
<zope.interface.interface.Method object at 0x7e5d705ced50 scrapy.interfaces.ISpiderLoader.from_settings(settings)>
<zope.interface.interface.Method object at 0x7e5d705abb00 scrapy.interfaces.ISpiderLoader.load(spider_name)>
<zope.interface.interface.Method object at 0x7e5d705ceea0 scrapy.interfaces.ISpiderLoader.list()>
<zope.interface.interface.Method object at 0x7e5d705abb00 scrapy.interfaces.ISpiderLoader.find_by_request(request)>

writes×4

getSignatureInfo

calls×8 [#34]

_incompat

calls×4 [#38]

mess

(4 writes)
None

writes×4

func
<function SpiderLoader.from_settings at 0x7e5d7054d760>

writes

calls [#31]

writes×4 passed to

calls×4 [#32]

method
(11 writes, 11 distinct)
<zope.interface.interface.Method object at 0x7e5d705ced50 from_settings()>
<zope.interface.interface.Method object at 0x7e5d705ced50 from_settings(settings)>
<zope.interface.interface.Method object at 0x7e5d705ced50 scrapy.interfaces.ISpiderLoader.from_settings(settings)>
<zope.interface.interface.Method object at 0x7e5d705abb00 load()>
<zope.interface.interface.Method object at 0x7e5d705abb00 load(spider_name)>
<zope.interface.interface.Method object at 0x7e5d705abb00 scrapy.interfaces.ISpiderLoader.load(spider_name)>
… +5 more values

writes×11

defaults
(4 writes)
()

writes×4

na

(4 writes, 2 distinct)
1
0

writes×4

names

(4 writes, 4 distinct)
('settings',)
('spider_name',)
()
('request', 'name', 'cls')

writes×4

opt
(4 writes)
{}

writes×4

defaults_count
(4 writes)
0

writes×4

nr

(4 writes, 2 distinct)
1
0

writes×4

_set_optional

calls×4 [#33]

argno
(4 writes, 2 distinct)
1
0

writes×4

passed to

passed to

_get_optional

calls×8 [#35]

calls [#67]

calls [#68]

calls [#70]

_get_mwlist_from_settings
extension.py:14

calls [#103]

calls×2 [#72]

calls [#79]

calls [#80]

calls [#81]

calls×6 [#88]

calls×14 [#96]

kwargs
(14 writes)
{'sender': <scrapy.crawler.Crawler object at 0x7e5d705cff80>}

writes×14

safeRef

calls×11 [#97]

receiver
(14 writes, 14 distinct)
<weakref at 0x7e5d7038ff60; to 'function' at 0x7e5d721a1da0 (<lambda>)>
BoundMethodWeakref(CoreStats.spider_opened)
BoundMethodWeakref(CoreStats.spider_closed)
BoundMethodWeakref(CoreStats.item_scraped)
BoundMethodWeakref(CoreStats.item_dropped)
BoundMethodWeakref(CoreStats.response_received)
… +8 more values

writes×14

senderkey
(14 writes)
138939782201216

writes×14

remove

(14 writes, 6 distinct)
<function connect.<locals>.remove at 0x7e5d721a13a0>
<function connect.<locals>.remove at 0x7e5d7046bd80>
<function connect.<locals>.remove at 0x7e5d7046b740>
<function connect.<locals>.remove at 0x7e5d7021e660>
<function connect.<locals>.remove at 0x7e5d702605e0>
<function connect.<locals>.remove at 0x7e5d70260cc0>

writes×14

weakSender
(14 writes, 14 distinct)
<weakref at 0x7e5d7038ff10; to 'Crawler' at 0x7e5d705cff80>
<weakref at 0x7e5d7039f330; to 'Crawler' at 0x7e5d705cff80>
<weakref at 0x7e5d7039f150; to 'Crawler' at 0x7e5d705cff80>
<weakref at 0x7e5d7039ef70; to 'Crawler' at 0x7e5d705cff80>
<weakref at 0x7e5d7039f290; to 'Crawler' at 0x7e5d705cff80>
<weakref at 0x7e5d7039f6a0; to 'Crawler' at 0x7e5d705cff80>
… +8 more values

writes×14

receiverID
(14 writes, 14 distinct)
138939779841888
138939782201072
138939782049392
138939781130544
138939781135776
138939781131120
… +8 more values

writes×14

calls×5 [#184]

passed to

passed to

passed to

passed to passed to

passed to

reference
(9 writes, 9 distinct)
BoundMethodWeakref(CoreStats.spider_opened)
BoundMethodWeakref(CoreStats.spider_closed)
BoundMethodWeakref(CoreStats.item_scraped)
BoundMethodWeakref(CoreStats.item_dropped)
BoundMethodWeakref(CoreStats.response_received)
BoundMethodWeakref(LogStats.spider_opened)
… +3 more values

writes×9

passed to

passed to passed to

writes×2

calls×10 [#118]

calls [#102]

calls×9 [#119] calls [#153]

raises (caught)

calls [#176]

interval
60.0

writes

job_dir
job.py:3

calls [#191]

calls [#213]

spider
<Spider 'foo' at 0x7e5d714c5a90>

writes

_set_crawler
__init__.py:63

calls [#215]

calls×2 [#104]

calls [#106]

_check_components
<function build_component_list.<locals>._check_components at 0x7e5d7046b920>

writes

writes

passed to

writes×2

calls [#114]

calls×2 [#108]

passed to passed to

passed to

passed to

passed to

calls×5 [#163] calls×2 [#161]

passed to

ValueError
BoundMethodWeakref(LogStats.spider_opened) is not in list

raises (caught)

calls [#192]

process_response
chunked.py:9

passed to

calls [#216]

test_request_meta_handling
test_downloadermiddleware_redirect.py:146

calls [#235]

calls [#234]

url
'http://www.example.com/301'

writes

url2
'http://www.example.com/redirected'

writes

_test_passthrough
<function RedirectMiddlewareTest.test_request_meta_handling.<locals>._test_passthrough at 0x7e5d702613a0>

writes

TypeError
Cannot mix str and non-str arguments

raises (caught)

passed to

passed to

passed to

safe_url_string

passed to

_strip

passed to

passed to

passed to

calls [#250]

calls [#249]

rsp

<301 http://www.example.com/301>

writes

calls [#260]

raises (caught)

encoding
text.py:54

calls [#237]

to_native_str
Return str representation of `text`
python.py:125

calls [#240] calls [#244] calls [#238]

to_unicode
Return the unicode representation of a bytes object `te…
python.py:99

calls [#239]

calls [#243] writes writes writes×2 writes writes writes writes writes writes×4 writes writes writes writes writes writes writes writes writes

writes

writes

calls [#241] decoded

'http://www.example.com/301'

writes

calls [#242] parts

SplitResult(scheme='http', netloc='www.example.com', path='/301', query='', fragment='')

writes

username

None

writes

password
None

writes

hostname
'www.example.com'

writes

port
None

writes

netloc_bytes
(2 writes, 2 distinct)
b''
b'www.example.com'

writes×2

netloc
'www.example.com'

writes

query
''

writes

defrag
'http://www.example.com/301'

writes

frag

''

writes

writes writes

seq

dict_items([('Location', 'http://www.example.com/redirected')])

writes

iseq
<generator object CaselessDict.update.<locals>.<genexpr> at 0x7e5d703cf3d0>

writes

calls [#254]

normvalue
Normalize values to bytes
headers.py:17

calls [#256]

_tobytes
headers.py:28

calls×3 [#255]

calls [#257]

calls [#266]

meta

__init__.py:25

calls [#262] calls [#261]

_get_url
__init__.py:34

calls [#265]

raises (caught)

calls [#263]