setUp
test_closespider.py:10

get_crawler
Return an unconfigured Crawler object. If settings_dict…
test.py:64

calls [#1]

_create_spider
<function Crawler._create_spider at 0x71db1bf1fc40>

calls [#544]

from_crawler
extensions.py:9

calls [#553]

loops(×556)

KeyError
'scrapy.crawler'

raises (caught)

lock
(2 writes, 2 distinct)
None

_ModuleLock('scrapy.crawler') at 125185898649200

writes×2

cb
<function _get_module_lock.<locals>.cb at 0x71db1d0604a0>

writes

tid
(3 writes)
125185952071808

writes×2

o

(3 writes, 3 distinct)
None

<scrapy.extensions.corestats.CoreStats object at 0x71db1bfb7350>
<scrapy.extensions.logstats.LogStats object at 0x71db1bfb6990>

writes

parent
(9 writes, 5 distinct)
'scrapy'
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__'
'zope.interface'
'scrapy.core'
'scrapy.utils'

writes×9

parent_module
(8 writes, 4 distinct)
<module 'scrapy' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__init__.py'>
<module 'zope.interface' from '/home/shashwat/BTP/.venv/lib/python3.12/site-packages/zope/interface/__init__.py'>
<module 'scrapy.core' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/core/__init__.py'>
<module 'scrapy.utils' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/utils/__init__.py'>

writes×8

child
(8 writes, 8 distinct)
'crawler'
'verify'
'engine'
'resolver'
'interfaces'
'extension'
… +2 more values

writes×8

meta_path
[<_distutils_hack.DistutilsMetaFinder object at 0x71db1f8745c0>, <class '_frozen_importlib.BuiltinImporter'>, <class '_f…

writes

is_reload
False

writes

finder
(10 writes, 6 distinct)
<_distutils_hack.DistutilsMetaFinder object at 0x71db1f8745c0>
<class '_frozen_importlib.BuiltinImporter'>
<class '_frozen_importlib.FrozenImporter'>
<class '_frozen_importlib_external.PathFinder'>
FileFinder('/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy')
FileFinder('/usr/lib/python3.12/encodings')

writes×6

find_spec
(7 writes, 4 distinct)
<bound method DistutilsMetaFinder.find_spec of <_distutils_hack.DistutilsMetaFinder object at 0x71db1f8745c0>>
<bound method BuiltinImporter.find_spec of <class '_frozen_importlib.BuiltinImporter'>>
<bound method FrozenImporter.find_spec of <class '_frozen_importlib.FrozenImporter'>>
<bound method PathFinder.find_spec of <class '_frozen_importlib_external.PathFinder'>>

writes×4

info
(2 writes)
None

writes

namespace_path
(2 writes)
[]

writes

entry
(2 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy'
'/usr/lib/python3.12/encodings'

writes

is_namespace
False

writes

tail_module
'crawler'

writes

mtime
1780556369.9745893

writes

cache
set(len=43)

writes

cache_module
'crawler'

writes

suffix
(2 writes, 2 distinct)
'.cpython-312-x86_64-linux-gnu.so'
'.py'

writes×2

loader_class
(2 writes, 2 distinct)
<class '_frozen_importlib_external.ExtensionFileLoader'>
<class '_frozen_importlib_external.SourceFileLoader'>

writes×2

part
(6 writes, 4 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy'
'crawler.cpython-312-x86_64-linux-gnu.so'
'crawler.py'
'crawler.cpython-312.pyc'

writes×6

full_path
(2 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.cpython-312-x86_64-linux-gnu.so'
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py'

writes×2

stat_info
os.stat_result(st_mode=33204, st_ino=3555193, st_dev=66309, st_nlink=1, st_uid=1000, st_gid=1000, st_size=13435, st_atim…

writes

loader
(3 writes, 2 distinct)
<_frozen_importlib_external.SourceFileLoader object at 0x71db1d074d40>
<_frozen_importlib_external.SourceFileLoader object at 0x71db1c0ecf20>

writes×2

head
(2 writes)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy'

writes×2

tail
(2 writes)
'crawler.py'

writes×2

base
(3 writes, 2 distinct)
'crawler'
<InterfaceClass zope.interface.Interface>

writes×2

sep
(2 writes)
'.'

writes×2

rest

(2 writes)
'py'

writes×2

tag
(2 writes)
'cpython-312'

writes×2

almost_filename
(2 writes)
'crawler.cpython-312'

writes×2

optimization
(2 writes)

''

writes×2

filename
(3 writes)
'crawler.cpython-312.pyc'

writes×3

source_path
(2 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py'
'/usr/lib/python3.12/encodings/idna.py'

writes

source_mtime
(4 writes, 3 distinct)
None
1780556350
1772540118

writes×2

source_bytes
(3 writes, 2 distinct)
None

bytes(len=13435)

writes×2

source_hash
(2 writes)
None

writes

hash_based
(2 writes)
False

writes

check_source
(2 writes)
True

writes

p
'/'

writes

i
(2 writes, 2 distinct)
51
63

writes×2

bytecode_path
(2 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.pyc'
'/usr/lib/python3.12/encodings/__pycache__/idna.cpython-312.pyc'

writes

st

(3 writes, 3 distinct)
os.stat_result(st_mode=33204, st_ino=3555193, st_dev=66309, st_nlink=1, st_uid=1000, st_gid=1000, st_size=13435, st_atim…
{'mtime': 1780556350.9183884, 'size': 13435}
{'mtime': 1772540118.0, 'size': 9710}

writes×2

file
(4 writes, 4 distinct)
<_io.BufferedReader name='/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.pyc'>
<_io.BufferedReader name='/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py'>
<_io.FileIO name=3 mode='wb' closefd=True>
<_io.FileIO [closed]>

writes×4

data
(8 writes, 7 distinct)
bytes(len=19104)
bytearray(b'xcb

')
bytearray(b'xcb

x00x00x00x00')
bytearray(b'xcb

x00x00x00x00>"!j')
bytearray(b'xcb

x00x00x00x00>"!j{4x00x00')
bytearray(b'xcb

x00x00x00x00>"!j{4x00x00xe3x00x00x00x00x00x00x00x00x00x00x00x00x05x00x00x00…
… +1 more values

writes×7

exc_details
(2 writes, 2 distinct)
{'name': 'scrapy.crawler', 'path': '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.…
{'name': 'encodings.idna', 'path': '/usr/lib/python3.12/encodings/__pycache__/idna.cpython-312.pyc'}

writes

magic
b'xcb

'

writes

flags
(3 writes)
0

writes×2

bytes_data
(2 writes, 2 distinct)
<memory at 0x71db1d1528c0>
<memory at 0x71db1c0e7d00>

writes

message

"bytecode is stale for 'scrapy.crawler'"

writes

ImportError
bytecode is stale for 'scrapy.crawler'

raises (caught)

code_object
<code object <module> at 0x25c992a0, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py", line 1>

writes

mode
(2 writes)
33204

writes×2

path_parts
[]

writes

path_tmp
'/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/__pycache__/crawler.cpython-312.pyc.125185898762928'

writes

fd
3

writes

code
(6 writes, 6 distinct)
<code object <module> at 0x25c992a0, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py", line 1>
<code object from_settings at 0x71db1c0ce950, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py"…
<code object load at 0x71db1d1b76d0, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py", line 63…
<code object list at 0x71db1c0b98a0, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py", line 80…
<code object find_by_request at 0x71db1c1ba790, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.p…
<code object <module> at 0x25f343f0, file "/usr/lib/python3.12/encodings/idna.py", line 1>

writes

six

<module 'six' from '/home/shashwat/BTP/.venv/lib/python3.12/site-packages/six.py'>

writes

signal
<module 'signal' from '/usr/lib/python3.12/signal.py'>

writes

logging
<module 'logging' from '/usr/lib/python3.12/logging/__init__.py'>

writes

warnings
<module 'warnings' from '/usr/lib/python3.12/warnings.py'>

writes

sys

<module 'sys' (built-in)>

writes

from_name
'twisted.internet.reactor'

writes

reactor

<twisted.internet.epollreactor.EPollReactor object at 0x71db1d075d60>

writes

defer
<module 'twisted.internet.defer' from '/home/shashwat/BTP/.venv/lib/python3.12/site-packages/twisted/internet/defer.py'>

writes

verifyClass
<function verifyClass at 0x71db1c098e00>

writes

DoesNotImplement
<class 'zope.interface.exceptions.DoesNotImplement'>

writes

Spider
(2 writes)
<class 'scrapy.spiders.Spider'>

writes×2

ExecutionEngine
<class 'scrapy.core.engine.ExecutionEngine'>

writes

CachingThreadedResolver
<class 'scrapy.resolver.CachingThreadedResolver'>

writes

ISpiderLoader
<InterfaceClass scrapy.interfaces.ISpiderLoader>

writes

ExtensionManager
<class 'scrapy.extension.ExtensionManager'>

writes

overridden_settings
<function overridden_settings at 0x71db1bf19120>

writes

Settings
<class 'scrapy.settings.Settings'>

writes

SignalManager
<class 'scrapy.signalmanager.SignalManager'>

writes

ScrapyDeprecationWarning
<class 'scrapy.exceptions.ScrapyDeprecationWarning'>

writes

install_shutdown_handlers
<function install_shutdown_handlers at 0x71db1bf1dbc0>

writes

signal_names
dict(len=33)

writes

load_object
<function load_object at 0x71db1d171120>

writes

LogCounterHandler
<class 'scrapy.utils.log.LogCounterHandler'>

writes

configure_logging
<function configure_logging at 0x71db1c0f7560>

writes

log_scrapy_info
<function log_scrapy_info at 0x71db1bf199e0>

writes

get_scrapy_root_handler
<function get_scrapy_root_handler at 0x71db1bf198a0>

writes

install_scrapy_root_handler
<function install_scrapy_root_handler at 0x71db1bf19800>

writes

signals
(5 writes, 5 distinct)
<module 'scrapy.signals' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/signals.py'>
{}
{<object object at 0x71db202bd330>: []}
{<object object at 0x71db202bd330>: [<weakref at 0x71db1be75030; to 'function' at 0x71db1c047880 (<lambda>)>]}
{<object object at 0x71db202bd330>: [<weakref at 0x71db1be75030; to 'function' at 0x71db1c047880 (<lambda>)>, BoundMetho…

writes

logger
<Logger scrapy.crawler (WARNING)>

writes

__module__
(3 writes)
'scrapy.crawler'

writes×3

__qualname__
(3 writes, 3 distinct)
'Crawler'
'CrawlerRunner'
'CrawlerProcess'

writes×3

__init__
(3 writes, 3 distinct)
<function Crawler.__init__ at 0x71db1bf1f880>
<function CrawlerRunner.__init__ at 0x71db1bf1fec0>
<function CrawlerProcess.__init__ at 0x71db1bf844a0>

writes×3

spiders
(2 writes, 2 distinct)
<property object at 0x71db1d096750>
<property object at 0x71db1d096b10>

writes×2

inlineCallbacks

calls×3 [#3]

crawl
(2 writes, 2 distinct)
<function Crawler.crawl at 0x71db1bf1fba0>
<function CrawlerRunner.crawl at 0x71db1bf84040>

writes×2

writes

_create_engine
<function Crawler._create_engine at 0x71db1bf1fce0>

writes

stop
(2 writes, 2 distinct)
<function Crawler.stop at 0x71db1bf1fe20>
<function CrawlerRunner.stop at 0x71db1bf842c0>

writes×2

Crawler
<class 'scrapy.crawler.Crawler'>

writes

__doc__
(2 writes, 2 distinct)

"

This is a convenient helper class that keeps track of, manages and runs
crawlers inside an already setup Twi…

"

A class to run multiple scrapy crawlers in a process simultaneously.

This class extends :class:`~scrapy.cr…

writes×2 crawlers
<property object at 0x71db1bf4b470>

writes

_crawl
<function CrawlerRunner._crawl at 0x71db1bf840e0>

writes

create_crawler
<function CrawlerRunner.create_crawler at 0x71db1bf84180>

writes

_create_crawler
<function CrawlerRunner._create_crawler at 0x71db1bf84220>

writes join
<function CrawlerRunner.join at 0x71db1bf84400>

writes

CrawlerRunner
(2 writes)
<class 'scrapy.crawler.CrawlerRunner'>

writes×2

_signal_shutdown
<function CrawlerProcess._signal_shutdown at 0x71db1bf84540>

writes

_signal_kill
<function CrawlerProcess._signal_kill at 0x71db1bf845e0>

writes

start
<function CrawlerProcess.start at 0x71db1bf84680>

writes

_get_dns_resolver
<function CrawlerProcess._get_dns_resolver at 0x71db1bf84720>

writes

_graceful_stop_reactor
<function CrawlerProcess._graceful_stop_reactor at 0x71db1bf847c0>

writes

_stop_reactor
<function CrawlerProcess._stop_reactor at 0x71db1bf84860>

writes

__classcell__
<cell at 0x71db1d077550: empty>

writes

CrawlerProcess
<class 'scrapy.crawler.CrawlerProcess'>

writes

_get_spider_loader
<function _get_spider_loader at 0x71db1bf1f740>

writes

args
(2 writes, 2 distinct)
(<code object <module> at 0x25c992a0, file "/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/crawler.py", line 1>, {'…
(<code object <module> at 0x25f343f0, file "/usr/lib/python3.12/encodings/idna.py", line 1>, {'__name__': 'encodings.idn…

writes

update
memusage.py:74

calls×2 [#374]

set

Sets value if priority is higher or equal than current …
__init__.py:53

calls×36 [#23]

iteritems

headers.py:73

calls×2 [#83]

__iter__
sitemap.py:23

calls [#84]

__getitem__
[closure inside test_init_mapping]
test_utils_datatypes.py:36

calls×31 [#85] settings

<scrapy.settings.Settings object at 0x71db1c0cbb60>

writes

freeze
Disable further changes to the current settings.
__init__.py:358

calls [#543] runner
<scrapy.crawler.CrawlerRunner object at 0x71db1d0511c0>

writes

defvalue
(2 writes, 2 distinct)
False
'Scrapy/1.8.0 (+https://scrapy.org)'

writes

d
{}

writes

connect

Connect a receiver function to a signal.
signalmanager.py:11

calls [#475] lf_cls

<class 'scrapy.logformatter.LogFormatter'>

writes

calls×2 [#481]

build_component_list
Compose a component list from a { class: order } dictio…
conf.py:18

calls [#491]

_map_keys
<function build_component_list.<locals>._map_keys at 0x71db1bf86840>

calls [#493]

k
(12 writes, 7 distinct)
'scrapy.extensions.corestats.CoreStats'
'scrapy.extensions.throttle.AutoThrottle'
'scrapy.extensions.telnet.TelnetConsole'
'scrapy.extensions.memusage.MemoryUsage'
'scrapy.extensions.memdebug.MemoryDebugger'
'scrapy.extensions.spiderstate.SpiderState'
… +1 more values

writes×8

v

(4 writes, 2 distinct)
0
'///i8n.example2.com/302'

writes

without_none_values
Return a copy of ``iterable`` with all ``None`` entries…
python.py:349

calls [#494] compdict

{'scrapy.extensions.corestats.CoreStats': 0, 'scrapy.extensions.telnet.TelnetConsole': 0, 'scrapy.extensions.memusage.Me…

writes

mwlist
['scrapy.extensions.corestats.CoreStats', 'scrapy.extensions.telnet.TelnetConsole', 'scrapy.extensions.memusage.MemoryUs…

writes

middlewares
(5 writes, 5 distinct)
[]
[<scrapy.extensions.corestats.CoreStats object at 0x71db1bfb7350>]
[<scrapy.extensions.corestats.CoreStats object at 0x71db1bfb7350>, <scrapy.extensions.telnet.TelnetConsole object at 0x7…
[<scrapy.extensions.corestats.CoreStats object at 0x71db1bfb7350>, <scrapy.extensions.telnet.TelnetConsole object at 0x7…
[<scrapy.extensions.corestats.CoreStats object at 0x71db1bfb7350>, <scrapy.extensions.telnet.TelnetConsole object at 0x7…

writes×5

enabled
(5 writes, 5 distinct)
[]
['scrapy.extensions.corestats.CoreStats']
['scrapy.extensions.corestats.CoreStats', 'scrapy.extensions.telnet.TelnetConsole']
['scrapy.extensions.corestats.CoreStats', 'scrapy.extensions.telnet.TelnetConsole', 'scrapy.extensions.memusage.MemoryUs…
['scrapy.extensions.corestats.CoreStats', 'scrapy.extensions.telnet.TelnetConsole', 'scrapy.extensions.memusage.MemoryUs…

writes×5

clspath
(9 writes, 9 distinct)
'scrapy.extensions.corestats.CoreStats'
'scrapy.extensions.telnet.TelnetConsole'
'scrapy.extensions.memusage.MemoryUsage'
'scrapy.extensions.memdebug.MemoryDebugger'
'scrapy.extensions.closespider.CloseSpider'
'scrapy.extensions.feedexport.FeedExporter'
… +3 more values

writes×9

mwcls
(9 writes, 9 distinct)
<class 'scrapy.extensions.corestats.CoreStats'>
<class 'scrapy.extensions.telnet.TelnetConsole'>
<class 'scrapy.extensions.memusage.MemoryUsage'>
<class 'scrapy.extensions.memdebug.MemoryDebugger'>
<class 'scrapy.extensions.closespider.CloseSpider'>
<class 'scrapy.extensions.feedexport.FeedExporter'>
… +3 more values

writes×9

create_instance
Construct a class instance using its ``from_crawler`` o…
misc.py:124

calls×9 [#497]

mw

(6 writes, 4 distinct)
<scrapy.extensions.corestats.CoreStats object at 0x71db1bfb7350>
<scrapy.extensions.telnet.TelnetConsole object at 0x71db1be37fb0>
<scrapy.extensions.memusage.MemoryUsage object at 0x71db1beb7950>
<scrapy.extensions.logstats.LogStats object at 0x71db1bfb6990>

writes×5

scrapy.exceptions.NotConfigured

raises (caught)

e

(5 writes)
NotConfigured()

writes×5

_add_middleware
__init__.py:18

calls [#542]

passed to

passed to passed to

passed to

passed to passed to

passed to passed to

passed to

passed to passed to passed to

passed to

passed to

passed to

escape_ajax
Return the crawleable url according to:
url.py:48

passed to

passed to passed to

passed to

passed to

_removeOldBackRefs

passed to

_verify

calls [#384]

calls [#470]

iter_default_settings
Return the default settings as an iterator of (name, va…
__init__.py:460

calls [#469]

writes

dot
(12 writes, 7 distinct)
19
22
27
24
26
29
… +1 more values

writes×12

mod
(12 writes, 12 distinct)
<module 'scrapy.spiderloader' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/spiderloader.py'>
<module 'scrapy.statscollectors' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/statscollectors.py'>
<module 'scrapy.logformatter' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/logformatter.py'>
<module 'scrapy.extensions.corestats' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/extensions/corestats.py'…
<module 'scrapy.extensions.telnet' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/extensions/telnet.py'>
<module 'scrapy.extensions.memusage' from '/home/shashwat/BTP/BugsInPy/workspace/scrapy/scrapy/extensions/memusage.py'>
… +6 more values

writes×12

calls [#455] calls [#468]

calls×12 [#7]

calls×19 [#9]

setmodule
Store settings from a module with a given priority.
__init__.py:277

calls [#11]

calls [#453]

get
headers.py:45

calls [#462]

copy

Return a copy of this Response
__init__.py:71

calls [#446]

getlist
headers.py:51

calls [#429]

getbool
Get a setting value as a boolean.
__init__.py:115

calls×3 [#435] _load_all_spiders

spiderloader.py:44

calls [#441]

update_settings
__init__.py:83

calls [#447]

handler
<LogCounterHandler (DEBUG)>

writes writes raises (caught)

calls [#541]

getint
Get a setting value as an int.
__init__.py:143

calls×2 [#561]

_set_url
text.py:34

calls×3 [#575]

_set_body
text.py:43

calls×3 [#582]

unwindGenerator
(3 writes, 3 distinct)
<function Crawler.crawl at 0x71db1bf1fba0>
<function Crawler.stop at 0x71db1bf1fe20>
<function CrawlerRunner.join at 0x71db1bf84400>

writes×3

calls [#545]

passed to

calls [#444]

calls [#445]

calls [#383]

calls [#382]

calls [#377]

cls_path
'scrapy.spiderloader.SpiderLoader'

writes

loader_cls
<class 'scrapy.spiderloader.SpiderLoader'>

writes

frozencopy
Return an immutable copy of the current settings.
__init__.py:368

calls [#424]

from_settings
Return an instance of the class for the given settings
interfaces.py:5

calls [#427]

passed to

passed to

passed to

passed to

__new__
trackref.py:30

passed to

passed to

replace
json_request.py:39

passed to

_assert_mutability
__init__.py:342

calls×20 [#10]

calls×9 [#95]

calls×18 [#94]

writes writes

seq

dict_items([('Location', '///i8n.example2.com/302')])

writes

iseq
<generator object CaselessDict.update.<locals>.<genexpr> at 0x71db1be8ff10>

writes

normkey
Normalize key to bytes
headers.py:14

calls [#590]

normvalue
Normalize values to bytes
headers.py:18

calls [#592] calls [#12]

calls×2 [#13]

calls×30 [#17]

calls×47 [#14]

calls×17 [#109]

get_settings_priority
Small helper function that looks up a given string prio…
__init__.py:26

calls×47 [#15]

__contains__
pqueues.py:89

calls×47 [#16]

calls [#601]

calls×46 [#86]

calls [#604]

calls [#605]

passed to

passed to

passed to

passed to

passed to

_get_mwlist_from_settings
extension.py:14

passed to

passed to

job_dir
job.py:3

passed to calls×16 [#378]

tester

<built-in method implementedBy of InterfaceClass object at 0x71db1d06ee50>

writes

excs

[]

writes

namesAndDescriptions

calls [#385]

desc
(4 writes, 4 distinct)
<zope.interface.interface.Method object at 0x71db1c0ae360 scrapy.interfaces.ISpiderLoader.from_settings(settings)>
<zope.interface.interface.Method object at 0x71db1c0ae0f0 scrapy.interfaces.ISpiderLoader.load(spider_name)>
<zope.interface.interface.Method object at 0x71db1c0ae330 scrapy.interfaces.ISpiderLoader.list()>
<zope.interface.interface.Method object at 0x71db1c0ae270 scrapy.interfaces.ISpiderLoader.find_by_request(request)>

writes×4

_verify_element

calls×4 [#387]

writes

calls [#386]

r

(3 writes, 2 distinct)
{}
{'from_settings': <zope.interface.interface.Method object at 0x71db1c0ae360 scrapy.interfaces.ISpiderLoader.from_setting…

writes×3

passed to

attr

(4 writes, 4 distinct)
<bound method SpiderLoader.from_settings of <class 'scrapy.spiderloader.SpiderLoader'>>
<function SpiderLoader.load at 0x71db1bf85300>
<function SpiderLoader.list at 0x71db1bf85440>
<function SpiderLoader.find_by_request at 0x71db1bf853a0>

writes×4

fromMethod

calls [#388]

fromFunction

calls×3 [#398]

meth
(4 writes, 4 distinct)
<zope.interface.interface.Method object at 0x71db1c0adbe0 scrapy.interfaces.ISpiderLoader.from_settings(settings)>
<zope.interface.interface.Method object at 0x71db1bf13b30 scrapy.interfaces.ISpiderLoader.load(spider_name)>
<zope.interface.interface.Method object at 0x71db1bf9bb30 scrapy.interfaces.ISpiderLoader.list()>
<zope.interface.interface.Method object at 0x71db1bf13b30 scrapy.interfaces.ISpiderLoader.find_by_request(request)>

writes×4

getSignatureInfo

calls×8 [#392]

_incompat

calls×4 [#396]

mess

(4 writes)
None

writes×4

func
<function SpiderLoader.from_settings at 0x71db1bf85260>

writes

calls [#389]

passed to writes×4

calls×4 [#390]

method
(11 writes, 11 distinct)
<zope.interface.interface.Method object at 0x71db1c0adbe0 from_settings()>
<zope.interface.interface.Method object at 0x71db1c0adbe0 from_settings(settings)>
<zope.interface.interface.Method object at 0x71db1c0adbe0 scrapy.interfaces.ISpiderLoader.from_settings(settings)>
<zope.interface.interface.Method object at 0x71db1bf13b30 load()>
<zope.interface.interface.Method object at 0x71db1bf13b30 load(spider_name)>
<zope.interface.interface.Method object at 0x71db1bf13b30 scrapy.interfaces.ISpiderLoader.load(spider_name)>
… +5 more values

writes×11

defaults
(4 writes)
()

writes×4

na

(4 writes, 2 distinct)
1
0

writes×4

names

(4 writes, 4 distinct)
('settings',)
('spider_name',)
()
('request', 'name', 'cls')

writes×4

opt
(4 writes)
{}

writes×4

defaults_count
(4 writes)
0

writes×4

nr

(4 writes, 2 distinct)
1
0

writes×4

_set_optional

calls×4 [#391]

argno
(4 writes, 2 distinct)
1
0

writes×4

passed to passed to

_get_optional

calls×8 [#393]

calls [#425]

calls [#426]

calls [#428]

calls [#484]

calls [#430]

calls×3 [#436]

got
(4 writes, 2 distinct)
False
True

writes×4

_check_name_duplicates
spiderloader.py:27

calls [#442]

dupes
[]

writes

setdict
__init__.py:274

calls [#448]

calls [#449]

passed to

writes×4

calls×2 [#476]

safeRef

calls×2 [#477]

receiver
(2 writes, 2 distinct)
<weakref at 0x71db1be75030; to 'function' at 0x71db1c047880 (<lambda>)>
<weakref at 0x71db1bd11b20; to 'function' at 0x71db1d1707c0 (close)>

writes×2

senderkey
(2 writes)
125185879669936

writes×2

remove

(2 writes, 2 distinct)
<function connect.<locals>.remove at 0x71db1bf85f80>
<function connect.<locals>.remove at 0x71db1bd4b600>

writes×2

weakSender
(2 writes, 2 distinct)
<weakref at 0x71db1be75d00; to 'Crawler' at 0x71db1be37cb0>
<weakref at 0x71db1bd6afc0; to 'Crawler' at 0x71db1be37cb0>

writes×2

receiverID
(2 writes, 2 distinct)
125185879920688
125185878465312

writes×2

receivers
(4 writes, 4 distinct)
[]
[<weakref at 0x71db1be75030; to 'function' at 0x71db1c047880 (<lambda>)>]
[BoundMethodWeakref(CoreStats.spider_closed), BoundMethodWeakref(LogStats.spider_closed)]
[BoundMethodWeakref(CoreStats.spider_closed), BoundMethodWeakref(LogStats.spider_closed), <weakref at 0x71db1bd11b20…

writes×4

current

(6 writes, 3 distinct)
None
[]
[125185879669936]

writes×6

calls [#552]

passed to

passed to

passed to

passed to

writes×2

calls×9 [#499]

calls [#516] calls [#483]

calls×7 [#500]

raises (caught)

getfloat
Get a setting value as a float.
__init__.py:155

calls [#528]

interval
60.0

writes

calls [#535]

jobdir
None

writes

calls [#546]

spider
<Spider 'foo' at 0x71db1c0adb20>

writes

_set_crawler
__init__.py:54

calls [#548]

getwithbase
Get a composition of a dictionary-like setting and its …
__init__.py:207

calls [#485]

calls [#486]

calls [#488] calls [#487]

compbs
(2 writes, 2 distinct)
<scrapy.settings.BaseSettings object at 0x71db1bfb5010>
<scrapy.settings.BaseSettings object at 0x71db1bfb7290>

writes

_check_components
<function build_component_list.<locals>._check_components at 0x71db1bf867a0>

writes

writes _validate_values
<function build_component_list.<locals>._validate_values at 0x71db1bf86700>

writes

passed to

writes

writes writes

prio
0

writes

writes×2 passed to writes passed to

passed to

calls×9 [#498]

passed to raises (caught)

passed to

process_response
chunked.py:17

passed to

_redirect
redirect.py:29

passed to

calls [#549]

ValueError
<weakref at 0x71db1bd11b20; to 'function' at 0x71db1d1707c0 (close)> is not in list

raises (caught)

calls×2 [#562]

test_redirect_302_relative
test_downloadermiddleware_redirect.py:113

calls×2 [#574]

calls×2 [#573]

url
'http://www.example.com/302'

writes url2
'///i8n.example2.com/302'

writes

url3
'http://i8n.example2.com/302'

writes

req

<HEAD http://www.example.com/302>

writes

rsp

<302 http://www.example.com/302>

writes calls [#596]

_get_url
__init__.py:38

calls [#640]

req2
<HEAD http://www.example.com/i8n.example2.com/302>

writes

AssertionError
'http://www.example.com/i8n.example2.com/302' != 'http://i8n.example2.com/302'

raises

passed to

passed to

safe_url_string

passed to

_strip

passed to passed to

encoding
text.py:58

calls×2 [#576]

calls×2 [#577]

s

(2 writes, 2 distinct)
'http://www.example.com/302'
'http://www.example.com/i8n.example2.com/302'

writes×2

calls×2 [#581]

calls [#580] writes writes writes writes writes writes×2 writes×4 writes writes writes writes writes writes writes writes writes writes writes

writes

writes

to_unicode
Return the unicode representation of a bytes object ``t…
python.py:89

calls×3 [#578]

decoded
(3 writes, 3 distinct)
'http://www.example.com/302'
'///i8n.example2.com/302'
'http://www.example.com/i8n.example2.com/302'

writes×3

calls×3 [#579]

parts
(3 writes, 3 distinct)
SplitResult(scheme='http', netloc='www.example.com', path='/302', query='', fragment='')
SplitResult(scheme='', netloc='', path='/i8n.example2.com/302', query='', fragment='')
SplitResult(scheme='http', netloc='www.example.com', path='/i8n.example2.com/302', query='', fragment='')

writes×3

username

(3 writes)
None

writes×3

password
(3 writes)
None

writes×3

hostname
(3 writes, 2 distinct)
'www.example.com'
None

writes×3

port
(3 writes)
None

writes×3

netloc_bytes
(5 writes, 2 distinct)
b''
b'www.example.com'

writes×5

netloc
(3 writes, 2 distinct)
'www.example.com'

''

writes×3

query
(3 writes)

''

writes×3

defrag
(2 writes, 2 distinct)
'http://www.example.com/302'
'http://www.example.com/i8n.example2.com/302'

writes×2

frag
(2 writes)

''

writes×2

calls [#626]

to_bytes
Return the binary representation of ``text``. If ``text…
python.py:102

calls [#627]

passed to

_tobytes
headers.py:29

calls×3 [#591]

calls [#593]

calls [#618]

calls [#603] calls [#600]

calls [#617]

calls [#607] calls [#615]

loops(×8)

meta

__init__.py:29

calls×4 [#597] allowed_status

(301, 302, 303, 307, 308)

writes

location
'/i8n.example2.com/302'

writes

calls [#610]

redirected_url
'http://www.example.com/i8n.example2.com/302'

writes

calls [#611]

_get_body
__init__.py:50

calls [#613]

cb_kwargs
__init__.py:48

calls [#616] cls

<class 'scrapy.http.request.Request'>

writes

redirected
<HEAD http://www.example.com/i8n.example2.com/302>

writes

calls [#612] calls [#630]

passed to

passed to

calls×8 [#631]

calls [#636]

ttl
20

writes

redirects
1

writes