setUp
test_closespider.py:10

__init__
extensions.py:5

calls [#1]

loops(×3)

contract

(6 writes, 4 distinct)
<class 'scrapy.contracts.default.UrlContract'>
<class 'scrapy.contracts.default.ScrapesContract'>
<scrapy.contracts.default.UrlContract object at 0x75a8fb373cb0>
<scrapy.contracts.default.ReturnsContract object at 0x75a8fb373830>

writes×2

self
(4 writes, 3 distinct)
HttpError('Ignoring non-200 response')
<twisted.python.failure.Failure scrapy.spidermiddlewares.httperror.HttpError: Ignoring non-200 response>
<GET http://scrapy.org>

writes×3

tb
(2 writes, 2 distinct)
None

<traceback object at 0x75a8fb365180>

writes×2

_create_testcase
__init__.py:153

calls×4 [#9] IndexError

tuple index out of range

raises (caught)

_set_url
text.py:34

calls [#21]

_set_body
text.py:43

calls [#28]

test_errback
test_contracts.py:195

calls×3 [#3]

__new__
item.py:27

calls [#2]

spider
(6 writes, 2 distinct)
<TestSpider 'demo_spider' at 0x75a8fb370680>
'demo_spider'

writes

response

<tests.test_contracts.ResponseMock object at 0x75a8fb371130>

writes

scrapy.spidermiddlewares.httperror.HttpError
Ignoring non-200 response

raises (caught)

failure_mock
<twisted.python.failure.Failure scrapy.spidermiddlewares.httperror.HttpError: Ignoring non-200 response>

writes

from_method
__init__.py:48

calls [#6]

request
(2 writes)
<GET http://scrapy.org>

writes

eb_wrapper
<function ContractsManager._clean_req.<locals>.eb_wrapper at 0x75a8fb2a9120>

calls [#36]

AttributeError
'getset_descriptor' object has no attribute '__traceback__'

raises (caught)

obj
(2 writes, 2 distinct)
<TestSpider 'demo_spider' at 0x75a8fb370680>
REPR FAILED

writes×2

passed to

passed to passed to

extract_contracts
__init__.py:27

passed to

adjust_request_args
default.py:16

passed to

passed to

encoding
text.py:58

passed to

find_spec

passed to

escape_ajax
Return the crawleable url according to:
url.py:48

passed to

passed to add_pre_hook

__init__.py:102

passed to

add_post_hook
__init__.py:125

passed to

_clean_req
stop the request from returning objects and records any…
__init__.py:71

passed to

getTracebackObject

passed to

calls [#20]

writes×4

calls [#19]

calls [#7]

contracts

(4 writes, 3 distinct)
[]
[<scrapy.contracts.default.UrlContract object at 0x75a8fb373cb0>]
[<scrapy.contracts.default.UrlContract object at 0x75a8fb373cb0>, <scrapy.contracts.default.ReturnsContract object at 0x…

writes

args
(8 writes, 7 distinct)
'http://scrapy.org'
['http://scrapy.org']
'requests 1'
['requests', '1']
['self', 'url']
{'callback': <bound method TestSpider.returns_request of <TestSpider 'demo_spider' at 0x75a8fb370680>>, 'method': 'GET',…
… +1 more values

writes×2

get_spec
Returns (args, kwargs) tuple for a function
python.py:249

calls [#15]

kwargs
(4 writes, 3 distinct)
{'callback': None, 'method': 'GET', 'headers': None, 'body': None, 'cookies': None, 'meta': None, 'encoding': 'utf-8', '…
{'callback': <bound method TestSpider.returns_request of <TestSpider 'demo_spider' at 0x75a8fb370680>>, 'method': 'GET',…
{'callback': <bound method TestSpider.returns_request of <TestSpider 'demo_spider' at 0x75a8fb370680>>, 'method': 'GET',…

writes×3

calls×2 [#17]

writes

calls [#35] calls×2 [#33] calls×2 [#31] calls×2 [#8]

writes×3

line
(8 writes, 8 distinct)
' method which returns request'
'method which returns request'
' @url http://scrapy.org'
'@url http://scrapy.org'
' @returns requests 1'
'@returns requests 1'
… +2 more values

writes×8

name

(7 writes, 3 distinct)
'url'
'demo_spider_returns_request'
'returns'

writes×4 writes×2

passed to

passed to passed to

passed to

passed to

writes×5 writes×5

__module__
(5 writes)
'scrapy.contracts'

writes×5

__qualname__
(5 writes)
'_create_testcase.<locals>.ContractTestCase'

writes×5

__str__
(5 writes, 5 distinct)
<function _create_testcase.<locals>.ContractTestCase.__str__ at 0x75a8fb352e80>
<function _create_testcase.<locals>.ContractTestCase.__str__ at 0x75a8fb352f20>
<function _create_testcase.<locals>.ContractTestCase.__str__ at 0x75a8fb353100>
<function _create_testcase.<locals>.ContractTestCase.__str__ at 0x75a8fb353240>
<function _create_testcase.<locals>.ContractTestCase.__str__ at 0x75a8fb2a91c0>

writes×5

ContractTestCase
(5 writes)
<class 'scrapy.contracts._create_testcase.<locals>.ContractTestCase'>

writes writes×5

_getargspec_py23
_getargspec_py23(function) -> named tuple ArgSpec(args,…
python.py:202

calls [#16]

spec
(5 writes, 3 distinct)
ArgSpec(args=['self', 'url', 'callback', 'method', 'headers', 'body', 'cookies', 'meta', 'encoding', 'priority', 'dont_f…
None

ModuleSpec(name='encodings.idna', loader=<_frozen_importlib_external.SourceFileLoader object at 0x75a8fb216690>, origin=…

writes

defaults
(None, 'GET', None, None, None, None, 'utf-8', 0, False, None, None)

writes

firstdefault
2

writes writes

passed to

passed to

passed to

writes

writes

calls [#22]

safe_url_string

calls [#23]

s

'http://scrapy.org'

calls [#27] writes

writes×4

to_unicode
Return the unicode representation of a bytes object `te…
python.py:101

calls [#24]

decoded
'http://scrapy.org'

writes

_strip

calls [#25]

parts
SplitResult(scheme='http', netloc='scrapy.org', path='', query='', fragment='')

writes

username

None

writes

password
None

writes

hostname
'scrapy.org'

writes

port
None

writes

netloc_bytes
(2 writes, 2 distinct)
b''
b'scrapy.org'

writes×2 calls [#26]

finder
(3 writes, 3 distinct)
<class '_frozen_importlib.BuiltinImporter'>
<class '_frozen_importlib.FrozenImporter'>
<class '_frozen_importlib_external.PathFinder'>

writes×3

info
None

writes

module
(5 writes, 3 distinct)
None

<module 'encodings.idna'>
<module 'encodings.idna' from '/usr/lib/python3.12/encodings/idna.py'>

writes×5

code
<code object <module> at 0x3188f170, file "/usr/lib/python3.12/encodings/idna.py", line 1>

writes

tid
129368700076160

writes

netloc
'scrapy.org'

writes

path

''

writes

query
''

passed to passed to writes

defrag
'http://scrapy.org'

writes

frag

''

writes

passed to passed to passed to

cb
(2 writes, 2 distinct)
<bound method TestSpider.returns_request of <TestSpider 'demo_spider' at 0x75a8fb370680>>
<function TestSpider.returns_request at 0x75a8fb2a8f40>

writes

wrapper

<function TestSpider.returns_request at 0x75a8fb2a8f40>

writes writes

cb_wrapper
<function TestSpider.returns_request at 0x75a8fb2a8fe0>

writes writes calls [#37]

case

<scrapy.contracts._create_testcase.<locals>.ContractTestCase testMethod=demo_spider_returns_request>

writes

calls [#38]

exc_info
(HttpError('Ignoring non-200 response'), <class 'scrapy.spidermiddlewares.httperror.HttpError'>, <traceback object at 0x…

writes raises (caught)