test_render_message
websocket_test.py:241

wrapper
[closure inside administrator]
blog.py:43

calls [#1]

__init__
stack_context_test.py:17

calls×5 [#2]

future
(13 writes, 7 distinct)
<tornado.concurrent.Future object at 0x7d269dd09700>
<tornado.concurrent.Future object at 0x7d269dd0b860>
<tornado.concurrent.Future object at 0x7d269e98e420>
None

<tornado.concurrent.Future object at 0x7d269dd567b0>
<tornado.concurrent.Future object at 0x7d269dd13860>
… +1 more values

writes×7

result
(6 writes, 6 distinct)
<generator object WebSocketBaseTestCase.ws_connect at 0x7d269de47d30>
<generator object TCPClient.connect at 0x7d269dd6e260>
<generator object HTTPServer.close_all_connections at 0x7d269ddd2880>
<tornado.concurrent.Future object at 0x7d269dd11610>
b'x'
None

writes×3

orig_stack_contexts
(4 writes, 2 distinct)
((), <tornado.stack_context.ExceptionStackContext object at 0x7d269df683e0>)
((), <tornado.stack_context.ExceptionStackContext object at 0x7d269dd12ae0>)

writes×3

ws_connect
websocket_test.py:143

calls [#3]

current

Returns the current thread's `IOLoop`.
ioloop.py:194

calls [#59]

kwargs
{'af': <AddressFamily.AF_UNSPEC: 0>, 'ssl_options': None, 'max_buffer_size': 104857600}

writes

callback
(5 writes, 5 distinct)
<bound method _HTTPConnection._on_connect of <tornado.websocket.WebSocketClientConnection object at 0x7d269dd117c0>>
<function wrap.<locals>.wrapped at 0x7d269db344a0>
None

<function wrap.<locals>.wrapped at 0x7d269db349a0>
<function wrap.<locals>.wrapped at 0x7d269db347c0>

writes×2

add_future
Schedules a callback on the ``IOLoop`` when the given
ioloop.py:587

calls [#60]

connect

Connect to the given host and port.
tcpclient.py:157

calls [#64] submit

concurrent.py:360

calls [#66]

yielded
(6 writes, 4 distinct)
<tornado.concurrent.Future object at 0x7d269e98e420>
<tornado.concurrent.Future object at 0x7d269dd54680>
None

<tornado.concurrent.Future object at 0x7d269dd114c0>

writes×5

set_result
Sets the result of a ``Future``.
concurrent.py:272

calls [#134]

close_all_connections
httpserver.py:180

calls [#132]

StopIteration

raises (caught)

e

StopIteration()

writes

_value_from_stopiteration
gen.py:161

calls [#133]

calls [#57]

calls×4 [#22]

calls×2 [#68]

headers
httpclient.py:472

calls [#8]

body
httpclient.py:483

calls [#10]

body_producer
[closure inside test_100_continue_early_response]
simple_httpclient_test.py:452

calls [#12]

wrap

Returns a callable object that will restore the current…
stack_context.py:255

calls [#51]

streaming_callback
[closure inside test_streaming_callback]
iostream_test.py:291

calls [#14]

header_callback
[closure inside test_header_callback]
httpclient_test.py:319

calls [#16]

prepare_curl_callback
httpclient.py:515

calls [#18]

__getattr__
util.py:90

calls×5 [#23]

scheme
(2 writes, 2 distinct)
'ws'
'http'

writes×2

sep
':'

writes

rest
'//127.0.0.1:38719/render'

writes

key
(4 writes, 4 distinct)
'Upgrade'
'Connection'
'Sec-WebSocket-Key'
'Sec-WebSocket-Version'

writes×4

__setitem__
options.py:143

calls×4 [#26]

__new__
httpclient.py:159

calls [#35]

time

ioloop_test.py:33

calls [#42] __enter__

http1connection.py:49

calls [#44]

to_unicode
Converts a string argument to a unicode string.
escape.py:206

calls [#45] netloc

'127.0.0.1:38719'

writes

split_host_and_port
Returns ``(host, port)`` tuple from ``netloc``.
httputil.py:924

calls [#46]

host
(2 writes)
'127.0.0.1'

writes

port
(2 writes)
38719

writes

af
<AddressFamily.AF_UNSPEC: 0>

writes

_get_ssl_options
simple_httpclient.py:248

calls [#48]

ssl_options
None

writes

timeout
(4 writes, 4 distinct)
20.0

<tornado.ioloop._Timeout object at 0x7d269dcf9d80>
<tornado.ioloop._Timeout object at 0x7d269db9f1c0>
None

writes

add_timeout
Runs the ``callback`` at the time ``deadline`` from the…
ioloop.py:475

calls [#52]

handle_yield
gen.py:1104

calls×2 [#69]

gen
None

writes

result_future
None

writes

first_yielded
None

writes

run

benchmark.py:66

calls [#72]

__exit__
http1connection.py:52

calls [#76]

wrapped
(6 writes, 6 distinct)
<function wrap.<locals>.wrapped at 0x7d269dd3fba0>
<function wrap.<locals>.wrapped at 0x7d269db344a0>
<function wrap.<locals>.wrapped at 0x7d269db349a0>
<function wrap.<locals>.wrapped at 0x7d269db34cc0>
<function wrap.<locals>.wrapped at 0x7d269db351c0>
<function wrap.<locals>.wrapped at 0x7d269db347c0>

passed to

passed to

stop
tcpclient_test.py:49

passed to

passed to

_clear_tb_log
concurrent.py:219

calls [#156]

_check_done
concurrent.py:317

calls [#157]

get_http_port
Returns the port used by the server.
testing.py:414

calls [#4]

websocket_connect
Client-side websocket support.
websocket.py:1169

calls [#5]

calls×3 [#7]

calls [#6]

io_loop
<tornado.platform.epoll.EPollIOLoop object at 0x7d269de1f7d0>

writes

request
(2 writes, 2 distinct)
<tornado.httpclient.HTTPRequest object at 0x7d269dd0b0e0>
<tornado.httpclient._RequestProxy object at 0x7d269dd09ac0>

writes×2

conn

<tornado.websocket.WebSocketClientConnection object at 0x7d269dd117c0>

writes

writes×4

passed to passed to

initialize
auth_test.py:19

passed to

calls [#9]

utf8
Converts a string argument to a byte string.
escape.py:187

calls [#11]

calls [#13]

cap_contexts
(6 writes, 2 distinct)
[((), <tornado.stack_context.ExceptionStackContext object at 0x7d269dd12ae0>)]
[((), <tornado.stack_context.ExceptionStackContext object at 0x7d269df683e0>)]

writes×6

writes×6

calls [#17] calls [#19] calls [#15]

passed to

calls [#25]

request_attr
(5 writes, 3 distinct)
'ws://127.0.0.1:38719/render'
<tornado.httputil.HTTPHeaders object at 0x7d269dd0b740>
None

writes×5

passed to

__missing__
httputil.py:90

passed to

run_sync

Starts the `IOLoop`, runs the given function, and stops…
ioloop.py:405

passed to

calls×4 [#27]

norm_name
(4 writes, 4 distinct)
'Upgrade'
'Connection'
'Sec-Websocket-Key'
'Sec-Websocket-Version'

writes×4

w

(8 writes, 6 distinct)
'Upgrade'
'Connection'
'Sec'
'WebSocket'
'Key'
'Version'

writes×8

normalized
(4 writes, 4 distinct)
'Upgrade'
'Connection'

'Sec-Websocket-Key'
'Sec-Websocket-Version'

writes×4

self
(4 writes, 4 distinct)
{'Upgrade': 'Upgrade'}
{'Upgrade': 'Upgrade', 'Connection': 'Connection'}
{'Upgrade': 'Upgrade', 'Connection': 'Connection', 'Sec-WebSocket-Key': 'Sec-Websocket-Key'}
{'Upgrade': 'Upgrade', 'Connection': 'Connection', 'Sec-WebSocket-Key': 'Sec-Websocket-Key', 'Sec-WebSocket-Version': 'S…

writes×4

passed to passed to

passed to

passed to passed to

passed to

passed to

passed to

passed to passed to

passed to

passed to

call_at
asyncio.py:131

passed to

__lt__
ioloop.py:971

passed to passed to

add_done_callback
Attaches the given callback to the `Future`.
concurrent.py:259

passed to

passed to

passed to

passed to

done
Returns True if the future has finished running.
concurrent.py:215

passed to

passed to passed to

write_message
Sends the given message to the client of this Web Socke…
websocket.py:231

passed to

_write_frame
websocket.py:735

passed to

write
wsgi.py:122

passed to

_check_closed
iostream.py:923

passed to

closed
Returns true if the stream has been closed.
iostream.py:486

passed to

_handle_write
iostream.py:845

passed to

start
0

passed to

write_to_fd
Attempts to write ``data`` to the underlying file.
iostream.py:209

passed to passed to

_set_done
concurrent.py:321

passed to

exception
If the operation raised an exception, return the `Excep…
concurrent.py:244

passed to

_maybe_add_error_listener
iostream.py:927

passed to

__del__
httpclient.py:81

passed to

read_message
Reads a message from the WebSocket server.
websocket.py:1128

passed to

tearDown

locale_test.py:28

passed to

passed to

remove_handler
asyncio.py:100

passed to

split_fd
Returns an (fd, obj) pair from an ``fd`` parameter.
ioloop.py:640

passed to

passed to

add_callback
[closure inside test_add_callback_return_sequence]
ioloop_test.py:73

passed to

_setup_logging
The IOLoop catches and logs exceptions, so it's
ioloop.py:365

passed to

write_fileno
Returns the write file descriptor for this waker.
interface.py:49

passed to

_run_callback
simple_httpclient.py:439

passed to

passed to

consume

Called after the listen has woken up to do any necessar…
interface.py:57

passed to

wake
Triggers activity on the waker's file descriptor.
interface.py:53

passed to

remove_timeout
asyncio.py:139

passed to

passed to passed to

close
select.py:35

passed to

fileno
kqueue.py:32

passed to

__rethrow
testing.py:268

passed to

configurable_base
util_test.py:41

calls [#36]

base
(2 writes)
<class 'tornado.netutil.Resolver'>

writes

init_kwargs
(2 writes, 2 distinct)
{}
{'io_loop': <tornado.platform.epoll.EPollIOLoop object at 0x7d269de1f7d0>}

writes×2

configured_class
Returns the currently configured class.
util.py:342

calls [#37]

impl
<class 'tornado.netutil.BlockingResolver'>

writes

instance

<tornado.netutil.BlockingResolver object at 0x7d269dd0a870>

writes

calls [#39]

calls [#38]

writes

passed to

passed to passed to

passed to

passed to

calls [#40]

passed to

match
<re.Match object; span=(0, 15), match='127.0.0.1:38719'>

writes writes writes

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

calls [#129]

calls [#150]

ret

(5 writes)
None

writes×3

current_state
(3 writes)
((), <tornado.stack_context.ExceptionStackContext object at 0x7d269df683e0>)

writes×3

_remove_deactivated
Remove deactivated handlers from the chain
stack_context.py:229

calls×3 [#128]

contexts

(3 writes)
((), <tornado.stack_context.ExceptionStackContext object at 0x7d269df683e0>)

writes×3

exc

(3 writes)
(None, None, None)

writes×3

top
(3 writes)
None

writes×3

last_ctx
(3 writes)
0

writes×3

stack
(3 writes)
()

writes×3

calls [#145]

calls×2 [#53]

calls×2 [#55]

calls×2 [#54]

writes×2

calls×3 [#56]

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to passed to

passed to

passed to

passed to

passed to

calls×3 [#62]

writes×3

is_future
concurrent.py:355

calls×3 [#61]

calls×3 [#63]

calls [#65]

writes

passed to

convert_yielded
Convert a yielded object into a `.Future`.
gen.py:1259

passed to

calls [#84]

_contains_yieldpoint
Returns True if ``children`` contains any YieldPoints.
gen.py:659

calls×2 [#70]

calls×2 [#71]

inner
(2 writes, 2 distinct)
<function Runner.handle_yield.<locals>.inner at 0x7d269db347c0>
<function Runner.handle_yield.<locals>.inner at 0x7d269db34180>

calls [#81] writes×2

passed to passed to passed to

calls [#130]

writes×2

calls [#74]

writes

calls [#139]

calls [#138]

writes

calls [#75] calls [#73]

exc_info
None

writes

value
[(<AddressFamily.AF_INET: 2>, ('127.0.0.1', 38719))]

writes

addrinfo
[(<AddressFamily.AF_INET: 2>, ('127.0.0.1', 38719))]

writes

connector

<tornado.tcpclient._Connector object at 0x7d269dd56840>

writes

writes

future_cell
(3 writes, 2 distinct)
[None]
[<tornado.concurrent.Future object at 0x7d269dd11610>]

writes passed to

passed to

passed to

final_contexts
((), <tornado.stack_context.ExceptionStackContext object at 0x7d269dd12ae0>)

writes

calls×2 [#82]

calls [#89]

calls [#88]

opcode
1

writes

message
b'hello'

writes

flags
0

writes

calls [#90]

frame
(3 writes, 3 distinct)
b'x81'
b'x81x85'
b'x81x85xb1Wxd6xc4xd92xbaxa8xde'

writes

unmasked_arr
(3 writes, 3 distinct)
array('B', [104, 101, 108, 108, 111])
array('B', [217, 101, 108, 108, 111])
array('B', [217, 50, 186, 168, 222])

writes

i
(4 writes, 2 distinct)
0
4

writes

data
b'xb1Wxd6xc4xd92xbaxa8xde'

writes

calls [#92]

passed to

passed to

finbit
128

writes writes×2

l
5

writes

mask_bit
128

writes

mask
b'xb1Wxd6xc4'

writes

_websocket_mask_python
Websocket masking function.
util.py:436

calls [#91]

passed to

mask_arr
array('B', [177, 87, 214, 196])

writes writes×2

writes

passed to

passed to

calls [#95]

writes

calls [#97] calls [#96] calls [#102] calls [#93]

calls [#94]

writes

writes

size
11

writes

calls [#98]

num_bytes
11

writes

index
194

writes

calls [#99]

calls×3 [#122]

writes

calls [#143]

calls×3 [#123]

writes

fd
(2 writes, 2 distinct)
6
4

writes

calls [#120]

old_current
<tornado.platform.epoll.EPollIOLoop object at 0x7d269de1f7d0>

writes

old_wakeup_fd
(2 writes, 2 distinct)
None
- 1

writes×2

calls [#121]

ncallbacks
1

writes

due_timeouts
(4 writes, 2 distinct)
[]
None

writes×4

now

(2 writes, 2 distinct)
1779889477.3333201
1779889477.340694

writes×2

calls×2 [#126]

poll_timeout
(2 writes, 2 distinct)
0.0
4.987168788909912

writes×2

event_pairs
[(4, 1)]

writes

events
1

writes

fd_obj
(2 writes, 2 distinct)
4
None

writes×2

handler_func
(2 writes, 2 distinct)
<function wrap.<locals>.wrapped at 0x7d269ea6f1a0>
None

writes×2

calls×2 [#100]

cb
<function BaseIOStream.write.<locals>.<lambda> at 0x7d269db358a0>

writes

calls [#101]

calls [#103]

writes

calls [#158] calls×2 [#104]

calls [#105]

get_async_test_timeout
Get the global timeout setting for async tests.
testing.py:110

calls [#109] calls [#108]

initialized
Returns true if the singleton instance has been created…
ioloop.py:166

calls×2 [#160] calls×2 [#159]

uninitialize
Removes the ``SIGCHLD`` handler.
process.py:326

calls [#165]

clear_current
ioloop.py:233

calls [#174] calls [#166]

writes

sock
(2 writes, 2 distinct)
<socket.socket fd=6, family=2, type=1, proto=6, laddr=('127.0.0.1', 38719)>
<socket.socket [closed] fd=-1, family=2, type=1, proto=6>

writes×2

calls [#106]

calls [#151]

passed to

passed to

passed to

calls×2 [#107]

obj
(2 writes, 2 distinct)
6
4

writes×2

AttributeError
'int' object has no attribute 'fileno'

raises (caught)

KeyError
b'ASYNC_TEST_TIMEOUT'

raises (caught)

TypeError
float() argument must be a string or a real number, not 'NoneType'

raises (caught)

calls [#155]

calls [#113] calls [#112] calls [#154]

writes

writes×2 calls [#119]

calls [#110]

timeout_handle
<tornado.ioloop._Timeout object at 0x7d269db9f1c0>

writes

calls [#153]

passed to calls [#111]

calls×2 [#127]

writes×2

stack_contexts
(3 writes)
()

writes×3

head
(3 writes)
<tornado.stack_context.ExceptionStackContext object at 0x7d269df683e0>

writes×3

ctx

(6 writes, 2 distinct)
<tornado.stack_context.ExceptionStackContext object at 0x7d269df683e0>
None

writes×6

parent
(3 writes)
None

writes×3

passed to

passed to

passed to

writes×2

calls [#170]

calls×4 [#161]

calls [#169]

try_close
common.py:12

calls [#173]

writes

f

<_io.FileIO [closed]>

writes