setUp
http1connection_test.py:14 calls×2 [#1]

get_new_ioloop
Creates a new `.IOLoop` for this test. May be overridd…
testing.py:252

calls [#3]

module
(3 writes, 2 distinct)
<object object at 0x77e4da8f4060>
<module 'tornado.platform.epoll' from '/home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/platform/epoll.py'>

writes×2

tid
(2 writes)
131824803623040

writes

finder
(2 writes, 2 distinct)
<_distutils_hack.DistutilsMetaFinder object at 0x77e4d9e742f0>
<class '_frozen_importlib_external.PathFinder'>

writes

find_spec
(2 writes, 2 distinct)
<bound method DistutilsMetaFinder.find_spec of <_distutils_hack.DistutilsMetaFinder object at 0x77e4d9e742f0>>
<bound method PathFinder.find_spec of <class '_frozen_importlib_external.PathFinder'>>

writes

spec
(5 writes, 4 distinct)
None

ModuleSpec(name='tornado.platform.epoll', loader=<_frozen_importlib_external.SourceFileLoader object at 0x77e4d8e00ad0>,…
('/echo', <class 'tornado.test.httpserver_test.EchoHandler'>)
URLSpec('/echo$', <class 'tornado.test.httpserver_test.EchoHandler'>, kwargs={}, name=None)

writes×2

EPollIOLoop
<class 'tornado.platform.epoll.EPollIOLoop'>

writes

impl
(4 writes, 4 distinct)
<class 'tornado.platform.epoll.EPollIOLoop'>
<class 'tornado.simple_httpclient.SimpleAsyncHTTPClient'>
<class 'tornado.netutil.BlockingResolver'>
<class 'tornado.httpserver.HTTPServer'>

writes

instance
(5 writes, 4 distinct)
<tornado.platform.epoll.EPollIOLoop object at 0x77e4d8fae510>
<tornado.simple_httpclient.SimpleAsyncHTTPClient object at 0x77e4d8fae720>
<tornado.netutil.BlockingResolver object at 0x77e4d8e3eab0>
<tornado.httpserver.HTTPServer object at 0x77e4d8e3fce0>

writes

initialize
auth_test.py:19

calls [#9]

make_current
Makes this the `IOLoop` for the current thread.
ioloop.py:216

calls [#24]

__init__
stack_context_test.py:17

calls [#70]

bind_unused_port
Binds a server socket to an available port on localhost…
testing.py:95

calls [#25]

sock
(7 writes, 3 distinct)
<socket.socket fd=6, family=2, type=1, proto=6, laddr=('0.0.0.0', 0)>
<socket.socket fd=6, family=2, type=1, proto=6, laddr=('127.0.0.1', 35555)>
<socket.socket [closed] fd=-1, family=2, type=1, proto=6>

writes

port
(2 writes)
35555

writes

get_http_client
curl_httpclient_test.py:26

calls [#28]

get_app
wsgi_test.py:21

calls [#46]

get_http_server
testing.py:387

calls [#54]

add_sockets
Makes this server start accepting connections on the gi…
tcpserver.py:129

calls [#65]

get_http_port
Returns the port used by the server.
testing.py:414

calls [#73]

connect

Connect to the given host and port.
tcpclient.py:157

calls [#74]

wait

Wait for `.notify`.
locks.py:116

calls [#85]

__new__
httpclient.py:159

calls [#4]

calls [#31]

configurable_base
util_test.py:41

calls×4 [#5]

base
(8 writes, 4 distinct)
<class 'tornado.ioloop.IOLoop'>
<class 'tornado.httpclient.AsyncHTTPClient'>
<class 'tornado.netutil.Resolver'>
<class 'tornado.httpserver.HTTPServer'>

writes×4

init_kwargs
(7 writes, 2 distinct)
{}
{'io_loop': <tornado.platform.epoll.EPollIOLoop object at 0x77e4d8fae510>}

writes×7

configured_class
Returns the currently configured class.
util.py:327

calls×4 [#6]

writes×4 writes×3

calls×3 [#36]

_async_clients
httpclient.py:153

calls [#30] instance_cache

<WeakKeyDictionary at 0x77e4d8e3e390>

writes

calls×4 [#7]

writes×4

configurable_default
util_test.py:45

calls×4 [#8]

writes

KeyError
'tornado.platform.epoll'

raises (caught)

lock
(2 writes, 2 distinct)
None

_ModuleLock('tornado.platform.epoll') at 131824776572576

writes×2

cb
(8 writes, 8 distinct)
<function _get_module_lock.<locals>.cb at 0x77e4d8d41260>
<function BaseIOStream.write.<locals>.<lambda> at 0x77e4d8d41f80>
<function chain_future.<locals>.copy at 0x77e4d8d42c00>
<function with_timeout.<locals>.<lambda> at 0x77e4d8d42e80>
<function IOLoop.add_future.<locals>.<lambda> at 0x77e4d8d43240>
<function IOLoop.add_future.<locals>.<lambda> at 0x77e4d8d436a0>
… +2 more values

writes

writes

path
(3 writes, 3 distinct)
None

['/home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/platform']
'/echo'

writes×2

parent
(14 writes, 2 distinct)
'tornado.platform'
None

writes

parent_spec
(2 writes, 2 distinct)
None

ModuleSpec(name='tornado.platform', loader=<_frozen_importlib_external.SourceFileLoader object at 0x77e4d9a31f70>, origi…

writes×2

parent_module
<module 'tornado.platform' from '/home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/platform/__init__.py'>

writes

child
'epoll'

writes

meta_path
[<_distutils_hack.DistutilsMetaFinder object at 0x77e4d9e742f0>, <class '_frozen_importlib.BuiltinImporter'>, <class '_f…

writes

is_reload
False

writes writes writes writes

SimpleAsyncHTTPClient
<class 'tornado.simple_httpclient.SimpleAsyncHTTPClient'>

writes

passed to

_can_keep_alive
http1connection.py:481

passed to passed to

passed to

current

Returns the current thread's `IOLoop`.
ioloop.py:193

passed to

call_at
asyncio.py:131

passed to

start

Starts the mock S3 server on the given port at the give…
s3server.py:46

passed to

_server_request_loop
http1connection.py:714

passed to

_read_message
http1connection.py:154

passed to

__lt__
ioloop.py:986

passed to

close_all_connections
httpserver.py:167

passed to

calls [#38]

calls×4 [#10]

calls [#12]

calls [#13]

set_close_exec
windows.py:17

calls [#14]

calls×4 [#15]

fileno
kqueue.py:32

calls [#20]

add_handler
asyncio.py:65

calls [#21]

writes×3

flags
(7 writes, 3 distinct)
1
0

<AddressInfo.AI_PASSIVE: 1>

writes×4

bind_sockets
Creates listening sockets bound to the given port and a…
netutil.py:111

passed to

calls×2 [#72]

calls×2 [#18]

calls×4 [#71]

r

4

writes

w

5

writes

_set_nonblocking
posix.py:32

calls×2 [#16]

io
(2 writes)
<module 'io' (frozen)>

writes×2

_load_ui_modules
web.py:1913

calls [#48]

_load_ui_methods
web.py:1900

calls [#49]

add_handlers
Appends the given handlers to our handler list.
web.py:1853

calls [#50]

pattern
(3 writes, 2 distinct)
'/echo$'
'/echo'

writes

self
(5 writes, 3 distinct)
URLSpec('/echo$', <class 'tornado.test.httpserver_test.EchoHandler'>, kwargs={}, name=None)
Return()
Return(True)

writes×5

_find_groups
Returns a tuple (reverse string, group count) for a url…
web.py:3035

calls [#52]

params

<tornado.http1connection.HTTP1ConnectionParameters object at 0x77e4d9f01f70>

writes

_clear_callbacks
Clears the callback attributes.
http1connection.py:263

calls [#167]

handle_yield
gen.py:1058

calls [#193]

writes×2

split_fd
Returns an (fd, obj) pair from an ``fd`` parameter.
ioloop.py:635

calls×3 [#22]

obj
(9 writes, 5 distinct)
4

<socket.socket fd=6, family=2, type=1, proto=6, laddr=('127.0.0.1', 35555)>
<socket.socket fd=7, family=2, type=1, proto=0, laddr=('127.0.0.1', 41506), raddr=('127.0.0.1', 35555)>
<socket.socket fd=8, family=2, type=1, proto=6, laddr=('127.0.0.1', 35555), raddr=('127.0.0.1', 41506)>
6

writes×3

wrap

Returns a callable object that will restore the current…
stack_context.py:253

calls×3 [#23]

fd
(13 writes, 4 distinct)
6
7
8
4

writes×2

AttributeError
'int' object has no attribute 'fileno'

raises (caught)

wrapped
(13 writes, 12 distinct)
<function wrap.<locals>.wrapped at 0x77e4d8d41580>
<function wrap.<locals>.wrapped at 0x77e4d8d420c0>
<function wrap.<locals>.wrapped at 0x77e4d8d41f80>
<function wrap.<locals>.wrapped at 0x77e4d8d423e0>
<function wrap.<locals>.wrapped at 0x77e4d8d434c0>
<function wrap.<locals>.wrapped at 0x77e4d8d42980>
… +6 more values

writes×13

null_wrapper
(3 writes, 3 distinct)
<function wrap.<locals>.null_wrapper at 0x77e4d8d422a0>
<function wrap.<locals>.null_wrapper at 0x77e4d8d42a20>
<function wrap.<locals>.null_wrapper at 0x77e4d8d439c0>

writes×3

accept_handler
<function add_accept_handler.<locals>.accept_handler at 0x77e4d8d42160>

calls [#117]

_remove_deactivated
Remove deactivated handlers from the chain
stack_context.py:227

calls×13 [#116]

contexts

(13 writes)
((), <tornado.stack_context.ExceptionStackContext object at 0x77e4d9006780>)

writes×13

exc

(13 writes)
(None, None, None)

writes×13

top
(13 writes)
None

writes×13

last_ctx
(13 writes)
0

writes×13

stack
(13 writes)
()

writes×13

result
(11 writes, 8 distinct)
<generator object HTTP1ServerConnection._server_request_loop at 0x77e4d8e15240>
None

<generator object HTTP1Connection._read_message at 0x77e4d8d38540>
b'x'
<generator object HTTP1Connection._read_fixed_body at 0x77e4d8e16040>
(<tornado.httputil.HTTPHeaders object at 0x77e4d8fe7c20>, b'{}')
… +2 more values

calls [#466]

stop
tcpclient_test.py:46

calls×2 [#140]

__del__
httpclient.py:81

calls [#428]

consume

Called after the listen has woken up to do any necessar…
interface.py:57

calls×2 [#244]

run

benchmark.py:66

calls×6 [#249]

_on_connection_close
http1connection.py:283

calls [#434]

calls [#26]

writes writes

calls [#27]

writes

sockets
(2 writes, 2 distinct)
[]
[<socket.socket fd=6, family=2, type=1, proto=6, laddr=('127.0.0.1', 35555)>]

writes×2

bound_port
(2 writes, 2 distinct)
None
35555

writes×2

res

(<AddressFamily.AF_INET: 2>, <SocketKind.SOCK_STREAM: 1>, 6, '', ('127.0.0.1', 0))

writes

af
<AddressFamily.AF_INET: 2>

writes

socktype
<SocketKind.SOCK_STREAM: 1>

writes

proto
6

writes

canonname
''

writes

sockaddr
('127.0.0.1', 0)

writes

writes×2

host
'127.0.0.1'

writes

requested_port
0

writes

passed to

add_accept_handler
Adds an `.IOLoop` event handler to accept new connectio…
netutil.py:231

passed to

passed to

calls [#29]

attr_name
'_async_client_dict_AsyncHTTPClient'

writes

calls [#47]

writes×2

calls [#51]

handlers
(2 writes, 2 distinct)
[]
[URLSpec('/echo$', <class 'tornado.test.httpserver_test.EchoHandler'>, kwargs={}, name=None)]

writes×2

passed to

passed to

passed to

passed to passed to

passed to

passed to

passed to

get_httpserver_options
May be overridden by subclasses to return additional
testing.py:408

passed to

passed to

passed to passed to

_add_io_state
Adds `state` (IOLoop.{READ,WRITE} flags) to our event h…
iostream.py:903

passed to

closed
Returns true if the stream has been closed.
iostream.py:478

passed to

__enter__
http1connection.py:49

passed to

__exit__
http1connection.py:52

passed to

passed to

time

ioloop_test.py:32

passed to

add_timeout
Runs the ``callback`` at the time ``deadline`` from the…
ioloop.py:474

passed to

passed to

passed to

_setup_logging
The IOLoop catches and logs exceptions, so it's
ioloop.py:364

passed to

write_fileno
Returns the write file descriptor for this waker.
interface.py:49

passed to

_handle_events
caresresolver.py:43

passed to

_handle_connect
iostream.py:1176

passed to

_run_callback
Runs the given callback with exception handling.
websocket.py:406

passed to

wrapper
(2 writes, 2 distinct)
<function BaseIOStream._run_callback.<locals>.wrapper at 0x77e4d8d42980>
<function BaseIOStream._run_callback.<locals>.wrapper at 0x77e4d8d422a0>

passed to

add_callback
asyncio.py:142

passed to

_handle_write
iostream.py:827

passed to

reading
Returns true if we are currently reading from the strea…
iostream.py:470

passed to

writing
Returns true if we are currently writing to the stream.
iostream.py:474

passed to

update_handler
asyncio.py:79

passed to

_handle_connection
tcpserver.py:237

passed to

handle_stream
[closure inside test_handle_stream_coroutine_logging]
tcpserver_test.py:19

passed to

start_serving
Starts serving requests on this connection.
http1connection.py:702

passed to

passed to

passed to

add_future
Schedules a callback on the ``IOLoop`` when the given
ioloop.py:586

passed to

add_done_callback
Attaches the given callback to the `Future`.
concurrent.py:256

passed to passed to

wake
Triggers activity on the waker's file descriptor.
interface.py:53

passed to

_maybe_add_error_listener
iostream.py:887

passed to

remove_timeout
asyncio.py:139

passed to

__rethrow
testing.py:268

passed to

test_chunked_request_uppercase
httpserver_test.py:449

passed to

write
wsgi.py:122

passed to

_check_closed
iostream.py:883

passed to

write_to_fd
Attempts to write ``data`` to the underlying file.
iostream.py:202

passed to

set_result
Sets the result of a ``Future``.
concurrent.py:269

passed to

_set_done
concurrent.py:318

passed to

exception
If the operation raised an exception, return the `Excep…
concurrent.py:241

passed to

_clear_tb_log
concurrent.py:219

passed to

_check_done
concurrent.py:314

passed to

passed to

headers_received
<function read_stream_body.<locals>.Delegate.headers_received at 0x77e4d8d41f80>

passed to

finish
<function read_stream_body.<locals>.Delegate.finish at 0x77e4d8d43560>

passed to

passed to

set_close_callback
wsgi.py:101

passed to

read_response
Read a single HTTP response.
http1connection.py:138

passed to

passed to

read_until_regex
Asynchronously read until we have matched the given reg…
iostream.py:229

passed to

_set_read_callback
iostream.py:660

passed to

_try_inline_read
Attempt to complete the current read operation from buf…
iostream.py:688

passed to

_run_streaming_callback
iostream.py:754

passed to

_find_read_pos
Attempts to find a position in the read buffer that sat…
iostream.py:772

passed to

_read_to_buffer_loop
iostream.py:585

passed to

_read_to_buffer
Reads from the socket and appends the result to the rea…
iostream.py:721

passed to

read_from_fd
Attempts to read from the underlying file.
iostream.py:209

passed to

passed to

done
Returns True if the future has finished running.
concurrent.py:215

passed to

passed to

_handle_read
iostream.py:645

passed to

_check_max_bytes
iostream.py:820

passed to

_read_from_buffer
Attempts to complete the currently-pending read from th…
iostream.py:762

passed to

_run_read_callback
iostream.py:669

passed to

_consume
iostream.py:876

passed to

passed to

passed to

_parse_headers
http1connection.py:508

passed to

passed to

__getitem__
options.py:140

passed to

_read_body
http1connection.py:525

passed to

_cleanup
httpserver.py:299

passed to

_deactivate_stack_context
gen.py:1121

passed to

tearDown

locale_test.py:28

passed to

close
select.py:35

passed to

remove_handler
asyncio.py:100

passed to

close_fd
Closes the file underlying this stream.
iostream.py:194

passed to

_maybe_run_close_callback
iostream.py:440

passed to

run_sync

Starts the `IOLoop`, runs the given function, and stops…
ioloop.py:404

passed to

start_request
httpserver.py:181

passed to

on_close
websocket_test.py:44

passed to

passed to passed to

writes×2

pieces
(2 writes, 2 distinct)
[]
['/echo']

writes×2

fragment
'/echo'

writes

re_unescape

Unescape a string escaped by `re.escape`.
util.py:228

calls [#53] unescaped_fragment

'/echo'

writes

calls [#56]

calls [#64]

calls [#55]

writes

calls [#66]

calls [#67]

writes

BlockingIOError
[Errno 115] Operation now in progress

raises (caught)

e

(7 writes, 4 distinct)
BlockingIOError(115, 'Operation now in progress')
BlockingIOError(11, 'Resource temporarily unavailable')
Return(True)
StopIteration()

writes

errno_from_exception
Provides the errno from an Exception object.
util.py:195

calls [#133]

i
(3 writes, 2 distinct)
0
1

writes×2

connection

<socket.socket fd=8, family=2, type=1, proto=6, laddr=('127.0.0.1', 35555), raddr=('127.0.0.1', 41506)>

writes

address
('127.0.0.1', 41506)

writes

calls [#118]

passed to passed to

passed to

passed to

passed to

passed to

calls [#75] passed to

raises (caught)

writes

calls [#77] calls [#76]

passed to

_value_from_stopiteration
gen.py:160

passed to

calls [#80]

calls [#81]

calls×2 [#78]

calls [#79]

calls [#84]

calls×3 [#98]

calls×2 [#137]

calls×2 [#335] calls×2 [#337] calls×2 [#334] calls [#357]

loops(×4)

get_async_test_timeout
Get the global timeout setting for async tests.
testing.py:110

calls×2 [#86]

timeout
(8 writes, 5 distinct)
5

<tornado.ioloop._Timeout object at 0x77e4d8c9e980>
None

<tornado.ioloop._Timeout object at 0x77e4d8cf6680>
<tornado.ioloop._Timeout object at 0x77e4d8bd7dc0>

writes×2

timeout_func
(2 writes, 2 distinct)
<function AsyncTestCase.wait.<locals>.timeout_func at 0x77e4d8d42340>
<function AsyncTestCase.wait.<locals>.timeout_func at 0x77e4d8d43880>

writes×2

calls×2 [#88] calls×2 [#92] calls×2 [#87]

callbacks
(14 writes, 7 distinct)
[]
None

[functools.partial(<function wrap.<locals>.null_wrapper at 0x77e4d8d42a20>)]
[functools.partial(<function wrap.<locals>.wrapped at 0x77e4d8d42fc0>, <tornado.concurrent.Future object at 0x77e4d8e848…
[functools.partial(<function wrap.<locals>.wrapped at 0x77e4d8d431a0>, <tornado.concurrent.Future object at 0x77e4d8e3f8…
[functools.partial(<function wrap.<locals>.wrapped at 0x77e4d8d42fc0>, <tornado.concurrent.Future object at 0x77e4d9a939…
… +1 more values

writes

due_timeouts
(14 writes, 2 distinct)
[]
None

writes

writes×2

yielded
(7 writes, 7 distinct)
<tornado.concurrent.Future object at 0x77e4d8e3f890>
<tornado.concurrent.Future object at 0x77e4d8e405c0>
<tornado.concurrent.Future object at 0x77e4d9a93980>
<tornado.concurrent.Future object at 0x77e4d8e3fa10>
<tornado.concurrent.Future object at 0x77e4d8fae630>
<tornado.concurrent.Future object at 0x77e4d8e40650>
… +1 more values

writes×2

calls×2 [#146] calls×2 [#145]

calls [#336]

calls [#353]

calls [#358]

need_delegate_close
(5 writes, 2 distinct)
False
True

writes×2

header_future
(3 writes, 2 distinct)
<tornado.concurrent.Future object at 0x77e4d8e405c0>
None

writes

calls×2 [#343] calls×2 [#347]

value
(7 writes, 5 distinct)
bytes(len=100)
True

bytes(len=149)
None
False

writes

start_line
(6 writes, 4 distinct)
'POST /echo HTTP/1.1'
RequestStartLine(method='POST', path='/echo', version='HTTP/1.1')
'HTTP/1.1 200 OK'
ResponseStartLine(version='HTTP/1.1', code=200, reason='OK')

writes×2

line
(8 writes, 5 distinct)

''

'Transfer-Encoding: Chunked'
'Content-Type: application/x-www-form-urlencoded'
'Server: TornadoServer/4.4'
'Content-Length: 2'

writes×2

headers
(5 writes, 2 distinct)
<tornado.httputil.HTTPHeaders object at 0x77e4d8e86000>
<tornado.httputil.HTTPHeaders object at 0x77e4d8fe7c20>

writes×2

calls [#333]

skip_body
(2 writes)
False

writes

calls [#338]

body_future
(2 writes, 2 distinct)
None

<tornado.concurrent.Future object at 0x77e4d8fae630>

writes

parse_response_start_line
Returns a (version, code, reason) tuple for an HTTP 1.x…
httputil.py:814

calls [#331]

code
200

writes

raises (caught)

TypeError
float() argument must be a string or a real number, not 'NoneType'

raises (caught)

passed to

passed to

passed to

passed to

passed to

calls×3 [#89]

calls×3 [#91]

calls×3 [#90]

writes×3

calls×2 [#209]

calls×3 [#115]

calls×3 [#97] writes×6

writes×3

calls×11 [#95]

calls×3 [#93]

old_current
(3 writes)
<tornado.platform.epoll.EPollIOLoop object at 0x77e4d8fae510>

writes×3

old_wakeup_fd
(6 writes, 2 distinct)
None
- 1

writes×6

calls×3 [#94]

writes×13 writes×13

now

(7 writes, 7 distinct)
1779889514.3716683
1779889514.3885593
1779889514.406704
1779889514.415333
1779889514.440755
1779889514.4971635
… +1 more values

writes×7

poll_timeout
(6 writes, 5 distinct)
4.990877151489258
4.971426486968994
4.996448278427124
0.0
4.970541477203369

writes×6

event_pairs
(4 writes, 4 distinct)
[(6, 1), (7, 4)]
[(4, 1), (8, 1)]
[(7, 1)]
[(4, 1)]

writes×4

events

(4 writes, 2 distinct)
4
1

writes×4

fd_obj
(10 writes, 5 distinct)
<socket.socket fd=7, family=2, type=1, proto=0, laddr=('127.0.0.1', 41506), raddr=('127.0.0.1', 35555)>
<socket.socket fd=6, family=2, type=1, proto=6, laddr=('127.0.0.1', 35555)>
None

<socket.socket fd=8, family=2, type=1, proto=6, laddr=('127.0.0.1', 35555), raddr=('127.0.0.1', 41506)>
4

writes×10

handler_func
(10 writes, 5 distinct)
<function wrap.<locals>.null_wrapper at 0x77e4d8d422a0>
<function wrap.<locals>.wrapped at 0x77e4d8d420c0>
None

<function wrap.<locals>.null_wrapper at 0x77e4d8d42b60>
<function wrap.<locals>.wrapped at 0x77e4d8d41580>

writes×10

calls×10 [#135] calls×2 [#214]

passed to

passed to

passed to

passed to

calls×3 [#112] calls×12 [#99]

calls [#100]

calls [#108]

state

(4 writes, 2 distinct)
24
25

writes×4 calls×3 [#110] calls×3 [#111] calls×2 [#220] calls×3 [#113]

err

0

writes

calls [#101]

calls×8 [#247]

calls×2 [#102]

calls×2 [#136]

calls×2 [#105]

writes×2

calls×2 [#103]

calls×5 [#126]

calls×2 [#138]

writes

writes×4

orig_stack_contexts
(9 writes)
((), <tornado.stack_context.ExceptionStackContext object at 0x77e4d9006780>)

writes×3 writes×4 calls [#127]

calls×2 [#143]

calls [#450]

calls [#174]

calls [#449]

StopIteration

raises (caught)

calls [#448]

calls×3 [#104]

_merge_prefix
Replace the first entries in a deque of strings with a …
iostream.py:1510

calls [#154] calls×2 [#153]

num_bytes
122

writes

calls [#156]

passed to

calls×3 [#114]

writes×3 writes×3

writes×13

stack_contexts
(13 writes)
()

writes×13

head
(13 writes)
<tornado.stack_context.ExceptionStackContext object at 0x77e4d9006780>

writes×13

passed to

passed to

passed to

passed to

passed to

calls [#119]

stream

<tornado.iostream.IOStream object at 0x77e4d8e43c50>

writes

calls [#121]

passed to

passed to

read_stream_body
Reads an HTTP response from `stream` and runs callback …
httpserver_test.py:32

passed to

calls×2 [#122]

context

<tornado.httpserver._HTTPRequestContext object at 0x77e4d8e43e60>

writes

conn

(4 writes, 4 distinct)
<tornado.http1connection.HTTP1ServerConnection object at 0x77e4d8e03f80>
<tornado.http1connection.HTTP1Connection object at 0x77e4d8e3c3e0>
<tornado.http1connection.HTTP1Connection object at 0x77e4d8e02180>
<tornado.http1connection.HTTP1Connection object at 0x77e4d8e87a10>

writes

calls [#124]

passed to

passed to

passed to

passed to

calls [#125]

calls [#129]

passed to calls×9 [#252] calls×5 [#350]

writes

request_delegate
(2 writes, 2 distinct)
<tornado.httpserver._ServerRequestAdapter object at 0x77e4d9c57ef0>
<tornado.httpserver._ServerRequestAdapter object at 0x77e4d8e3fdd0>

writes

passed to

passed to

passed to

passed to

convert_yielded
Convert a yielded object into a `.Future`.
gen.py:1207

passed to

calls×5 [#131]

is_future
concurrent.py:351

calls×5 [#130]

calls×5 [#132]

writes×2 writes

calls [#141]

calls×2 [#142]

calls [#440] calls [#439] calls [#388]

calls [#202] calls [#163] calls [#147] calls [#162]

writes

response
b'{}'

writes

json_decode
Returns Python objects for the given JSON string.
escape.py:85

calls [#371]

AssertionError
{} != {'foo': ['bar']}

raises

calls [#150]

calls [#152]

writes

calls [#151] calls [#161] calls [#148]

WRITE_BUFFER_CHUNK_SIZE
131072

writes

calls×2 [#149]

chunk
(9 writes, 5 distinct)
None

bytes(len=122)
bytes(len=100)
bytes(len=151)
bytes(len=149)

writes×4

prefix
(4 writes, 3 distinct)
[]
[b'POST /echo HTTP/1.1

Transfer-Encoding: Chunked

Content-Type: application/x-www-form-urlencoded

']
[b'HTTP/1.1 200 OK

Server: TornadoServer/4.4

Content-Type: application/json; charset=UTF-8

Date: Wed, 27 May 20…

writes×4

remaining
(4 writes, 3 distinct)
100
0
149

writes×4

deque
(6 writes, 5 distinct)
deque([])
deque([b'4

foo=

3

bar

0

'])
deque([b'POST /echo HTTP/1.1

Transfer-Encoding: Chunked

Content-Type: application/x-www-form-urlencoded

', …
deque([b'{}'])
deque([b'HTTP/1.1 200 OK

Server: TornadoServer/4.4

Content-Type: application/json; charset=UTF-8

Date: Wed, 27 …

writes×6

calls×7 [#157]

writes×6

calls [#158]

calls [#159] calls [#160]

calls [#164]

writes

chunks
[]

writes

__module__
'tornado.test.httpserver_test'

writes

__qualname__
'read_stream_body.<locals>.Delegate'

writes

writes

data_received
<function read_stream_body.<locals>.Delegate.data_received at 0x77e4d8d43420>

writes

writes Delegate
<class 'tornado.test.httpserver_test.read_stream_body.<locals>.Delegate'>

writes

calls [#171]

passed to

calls [#261]

calls [#354]

calls [#268]

calls [#269]

passed to

calls×2 [#168]

calls×2 [#170] calls×2 [#169]

calls [#172]

writes

calls [#175]

writes

passed to

passed to

passed to

calls [#176] calls [#178]

calls [#177]

calls [#189] calls [#181] calls [#188]

calls [#180] calls [#179]

pos
(5 writes, 3 distinct)
None
100
149

writes

calls [#183]

m

(2 writes, 2 distinct)
<re.Match object; span=(96, 100), match=b'

'>

<re.Match object; span=(145, 149), match=b'

'>

writes×2

calls×2 [#227]

passed to

calls×3 [#184]

calls×3 [#187] calls×2 [#225]

writes×2

target_bytes
(3 writes)
65536

writes×3

next_find_pos
(3 writes)
0

writes×3

calls×3 [#185]

calls×3 [#186]

writes×3

raises (caught)

writes

writes×2

passed to

passed to

passed to

calls×3 [#198]

_contains_yieldpoint
Returns True if ``children`` contains any YieldPoints.
gen.py:624

calls×5 [#194] calls×4 [#195]

calls×5 [#197]

calls×2 [#196]

writes×2

calls×2 [#221] calls×2 [#228]

calls×2 [#229]

calls×2 [#234]

calls×2 [#232]

calls×2 [#230]

calls×2 [#231]

passed to

writes×4

raises (caught) calls×5 [#258]

writes×3

calls×2 [#259] calls×2 [#262]

calls [#446]

writes calls×6 [#251]

writes×5

writes

writes×2

calls [#455]

calls [#454]

calls×3 [#276]

calls×2 [#423]

calls [#260]

calls [#267]

calls×2 [#272]

calls [#415]

writes writes×2

calls×2 [#313]

writes

calls×7 [#250]

exc_info
(5 writes)
None

writes×5

writes×6

header_data
(2 writes, 2 distinct)
bytes(len=100)
bytes(len=149)

writes×2

calls×2 [#253]

writes writes×2

parse_request_start_line
Returns a (method, path, version) tuple for an HTTP 1.x…
httputil.py:792

calls [#256]

calls [#257]

writes

calls [#263]

calls [#264]

writes

tornado.gen.Return
True

raises (caught)

calls×3 [#275] calls×3 [#278]

future_cell
(3 writes, 2 distinct)
[None]
[<tornado.concurrent.Future object at 0x77e4d8e43e60>]

writes

calls [#422] calls [#414]

raises (caught)

passed to

passed to

passed to

to_unicode
Converts a string argument to a unicode string.
escape.py:205

passed to

passed to

to_basestring
Converts a string argument to a subclass of basestring.
escape.py:233

passed to passed to

passed to

passed to

calls×2 [#254]

data
(2 writes, 2 distinct)
'POST /echo HTTP/1.1

Transfer-Encoding: Chunked

Content-Type: application/x-www-form-urlencoded

'

'HTTP/1.1 200 OK

Server: TornadoServer/4.4

Content-Type: application/json; charset=UTF-8

Date: Wed, 27 May 2026…

writes×2

eol
(2 writes, 2 distinct)
20
16

writes×2 writes×2

parse

Returns a dictionary from HTTP header text.
httputil.py:193

calls×2 [#255]

writes passed to

passed to

passed to

passed to

passed to

h
(2 writes, 2 distinct)
<tornado.httputil.HTTPHeaders object at 0x77e4d8e86000>
<tornado.httputil.HTTPHeaders object at 0x77e4d8fe7c20>

writes×6 writes×2

passed to

passed to

passed to

passed to

passed to

passed to

passed to passed to

writes

method
'POST'

writes

version
'HTTP/1.1'

writes

passed to passed to

raises (caught)

connection_header
(2 writes)
None

writes×2

passed to

passed to

raises (caught)

raises (caught)

calls [#341]

calls [#342]

calls×2 [#339]

content_length
(2 writes, 2 distinct)
None
2

writes×2

passed to

passed to

calls [#332]

match
<re.Match object; span=(0, 15), match='HTTP/1.1 200 OK'>

writes

passed to

passed to

passed to

calls [#372]

calls [#390] calls [#510] calls [#387]

calls [#495]

calls×2 [#386]

calls×3 [#373]

calls [#391]

initialized
Returns true if the singleton instance has been created…
ioloop.py:165

calls×2 [#496]

uninitialize
Removes the ``SIGCHLD`` handler.
process.py:326

calls [#502]

clear_current
ioloop.py:232

calls [#503]

calls×2 [#375] calls [#374]

calls×4 [#498]

calls [#379] calls [#378] calls×2 [#376]

calls×3 [#377]

writes writes×3 writes

calls×2 [#380]

calls [#381]

futures
(2 writes)
[]

writes×2

calls [#395] calls [#400] calls [#394]

calls [#392]

calls [#492]

calls [#490]

calls [#491]

writes

writes×2

timeout_handle
<tornado.ioloop._Timeout object at 0x77e4d8bd7dc0>

writes

passed to

calls [#437] calls [#436]

calls [#435]