test_facebook_login
auth_test.py:402

fetch

Executes a request, returning an `HTTPResponse`.
httpclient.py:91

calls×2 [#1]

__getitem__
options.py:134

calls [#367]

response
(5 writes, 5 distinct)
HTTPResponse(_body=None,buffer=<_io.BytesIO object at 0x7670a52c8bd0>,code=302,effective_url='http://localhost:33959/fac…
HTTPResponse(_body=None,buffer=<_io.BytesIO object at 0x7670a52b6ed0>,code=200,effective_url='http://localhost:33959/fac…
HTTPResponse(_body=b'access_token=asdf',buffer=<_io.BytesIO object at 0x7670a52b6ed0>,code=200,effective_url='http://loc…
HTTPResponse(_body=None,buffer=<_io.BytesIO object at 0x7670a52b6ed0>,code=200,effective_url='http://localhost:33959/fac…
HTTPResponse(_body=b'{}',buffer=<_io.BytesIO object at 0x7670a52b6ed0>,code=200,effective_url='http://localhost:33959/fa…

writes AssertionError
Async operation timed out after 5 seconds

raises (caught)

calls×2 [#5]

get_url
[closure inside test_multi_process]
process_test.py:68

calls×2 [#2]

__init__
stack_context_test.py:17

calls×12 [#6]

headers
httpclient.py:459

calls×4 [#19]

utf8
Converts a string argument to a byte string.
escape.py:193

calls×8 [#185]

wrap

Returns a callable object that will restore the current…
stack_context.py:253

calls×2 [#25]

request
(8 writes, 4 distinct)
<tornado.httpclient.HTTPRequest object at 0x7670a55d4170>
<tornado.httpclient._RequestProxy object at 0x7670a55d73b0>
<tornado.httpclient.HTTPRequest object at 0x7670a542e1b0>
<tornado.httpclient._RequestProxy object at 0x7670a55d59a0>

writes×4

handle_future
(2 writes, 2 distinct)
<function AsyncHTTPClient.fetch.<locals>.handle_future at 0x7670a530f1a0>
<function AsyncHTTPClient.fetch.<locals>.handle_future at 0x7670a530f100>

writes×2

add_done_callback
Attaches the given callback to the `Future`.
concurrent.py:251

calls×6 [#26]

handle_response
(2 writes, 2 distinct)
<function AsyncHTTPClient.fetch.<locals>.handle_response at 0x7670a530f100>
<function AsyncHTTPClient.fetch.<locals>.handle_response at 0x7670a5208400>

writes×2

fetch_impl
curl_httpclient.py:77

calls×2 [#27]

key
(12 writes, 4 distinct)
<object object at 0x7670a6578de0>
'network_interface'
'proxy_password'
<object object at 0x7670a6578e50>

writes×4

time

ioloop_test.py:32

calls×28 [#198]

__getattr__
util.py:37

calls×76 [#142]

result
(11 writes, 11 distinct)
<generator object TCPClient.connect at 0x7670a54d4af0>
<generator object HTTP1ServerConnection._server_request_loop at 0x7670a53f5640>
HTTPResponse(_body=None,buffer=<_io.BytesIO object at 0x7670a52c8bd0>,code=302,effective_url='http://localhost:33959/fac…
<generator object TCPClient.connect at 0x7670a54d63e0>
<generator object HTTP1ServerConnection._server_request_loop at 0x7670a53f6240>
b'x'
… +5 more values

writes

__del__
httpclient.py:81

calls×4 [#191]

wait

Wait for `.notify`.
locks.py:116

calls×2 [#65]

KeyError
b'ASYNC_TEST_TIMEOUT'

raises (caught)

__lt__
ioloop.py:965

calls×14 [#482]

events

(8 writes, 2 distinct)
4
1

writes×4

null_wrapper
[closure inside wrap]
stack_context.py:271

calls×9 [#199]

closed
Returns true if the stream has been closed.
iostream.py:478

calls×4 [#187]

_run_callback
Runs the given callback with exception handling.
websocket.py:412

calls×32 [#221]

remove_timeout
asyncio.py:139

calls×2 [#365]

calls×8 [#145]

__setitem__
httputil.py:203

calls×12 [#148]

username

(4 writes)
None

writes×4

password
(4 writes)
None

writes×4

body_expected
(4 writes)
False

writes×4

body_present
(4 writes)
False

writes×4

req_path
(4 writes, 4 distinct)
'/facebook/client/login'
'/facebook/client/login?code=1234'
'/facebook/server/access_token?redirect_uri=http%3A%2F%2Flocalhost%3A33959%2Ffacebook%2Fclient%2Flogin%3Fcode%3D1234&cod…
'/facebook/server/me?access_token=asdf&fields=picture%2Clink%2Cname%2Clocale%2Clast_name%2Cfirst_name%2Cid'

writes×4

_create_connection
simple_httpclient.py:377

calls×4 [#172]

write_headers
wsgi.py:106

calls×4 [#180]

lines
(12 writes, 9 distinct)
[]
[b'GET /facebook/client/login HTTP/1.1']
[b'GET /facebook/client/login HTTP/1.1', b'Connection: close', b'Host: localhost:33959', b'Accept-Encoding: gzip']
[b'GET /facebook/client/login?code=1234 HTTP/1.1']
[b'GET /facebook/client/login?code=1234 HTTP/1.1', b'Connection: close', b'Host: localhost:33959', b'Accept-Encoding: gz…
[b'GET /facebook/server/access_token?redirect_uri=http%3A%2F%2Flocalhost%3A33959%2Ffacebook%2Fclient%2Flogin%3Fcode%3D12…
… +3 more values

writes×4

name

(8 writes, 2 distinct)
'Connection'
'Accept-Encoding'

writes×4

values
(8 writes, 2 distinct)
['close']
['gzip']

writes×4

n

(8 writes, 2 distinct)
'Connection'
'Accept-Encoding'

writes×4

v

(9 writes, 3 distinct)
'close'
'gzip'
['asdf']

writes×4

line
(4 writes, 4 distinct)
bytes(len=35)
bytes(len=45)
bytes(len=205)
bytes(len=118)

writes×4

data
(11 writes, 11 distinct)
bytes(len=104)
'GET /facebook/client/login HTTP/1.1

Connection: close

Host: localhost:33959

Accept-Encoding: gzip

'

'HTTP/1.1 302 Found

Server: TornadoServer/4.3.dev1

Content-Type: text/html; charset=UTF-8

Date: Wed, 27 May 202…
bytes(len=114)
'GET /facebook/client/login?code=1234 HTTP/1.1

Connection: close

Host: localhost:33959

Accept-Encoding: gzip
…

bytes(len=274)
… +5 more values

writes×4

write
wsgi.py:122

calls×4 [#189]

_write_body
simple_httpclient.py:389

calls×4 [#193]

__rethrow
testing.py:257

calls×2 [#366]

args
(4 writes, 4 distinct)
{'access_token': [b'asdf']}
[<tornado.test.auth_test.FacebookClientLoginHandler object at 0x7670a542c680>, 'http://localhost:33959/facebook/server/m…
(HTTPResponse(_body=b'access_token=asdf',buffer=<_io.BytesIO object at 0x7670a52b6ed0>,code=200,effective_url='http://lo…
(HTTPResponse(_body=b'{}',buffer=<_io.BytesIO object at 0x7670a52b6ed0>,code=200,effective_url='http://localhost:33959/f…

writes

_on_oauth2_request
auth.py:672

calls [#1204]

raises (caught)

get_protocol
testing.py:410

calls×2 [#3]

get_http_port
Returns the port used by the server.
testing.py:403

calls×2 [#4]

calls×6 [#35]

calls×2 [#7]

body
httpclient.py:470

calls×2 [#9]

body_producer
[closure inside test_100_continue_early_response]
simple_httpclient_test.py:414

calls×2 [#11] calls×2 [#44]

streaming_callback
[closure inside test_streaming_callback]
iostream_test.py:291

calls×2 [#13]

header_callback
[closure inside test_header_callback]
httpclient_test.py:310

calls×2 [#15]

prepare_curl_callback
httpclient.py:502

calls×2 [#17]

get_all
Returns an iterable of all (name, value) pairs.
httputil.py:160

calls×2 [#21]

__enter__
http1connection.py:49

calls×2 [#36]

calls×2 [#34] calls×8 [#37]

to_unicode
Converts a string argument to a unicode string.
escape.py:210

calls×2 [#38]

netloc
(2 writes)
'localhost:33959'

writes×2

split_host_and_port
Returns ``(host, port)`` tuple from ``netloc``.
httputil.py:883

calls×2 [#39]

host
(4 writes)
'localhost'

writes×2

port
(4 writes)
33959

writes×2

af
(6 writes, 2 distinct)
<AddressFamily.AF_UNSPEC: 0>
<AddressFamily.AF_INET: 2>

writes×2

_get_ssl_options
simple_httpclient.py:238

calls×2 [#41]

ssl_options
(2 writes)
None

writes×2

add_timeout
Runs the ``callback`` at the time ``deadline`` from the…
ioloop.py:462

calls×2 [#45]

wrapper
[closure inside administrator]
blog.py:43

calls×2 [#49]

current

Returns the current thread's `IOLoop`.
ioloop.py:189

calls×2 [#59]

handle_yield
gen.py:1032

calls×2 [#60]

run

runtests.py:64

calls×2 [#61]

calls×2 [#62]

__exit__
http1connection.py:52

calls×2 [#63]

passed to passed to

_can_keep_alive
http1connection.py:474

passed to

headers_received
[closure inside read_stream_body]
httpserver_test.py:37

passed to

_read_body
http1connection.py:516

passed to

calls×2 [#10]

calls×2 [#12]

defines

calls×2 [#16] calls×2 [#18] calls×2 [#14]

passed to

passed to

passed to

passed to

_handle_request
simple_httpclient.py:153

passed to

writes×4 writes×4

writes×2

set_result
Sets the result of a ``Future``.
concurrent.py:264

calls×2 [#886]

set_exception
Sets the exception of a ``Future.``
concurrent.py:273

calls [#342]

writes×2

timeout_handle
(4 writes)
None

writes×2

_process_queue
simple_httpclient.py:139

calls×2 [#28]

passed to

_remove_timeout
simple_httpclient.py:163

passed to

passed to

passed to

__missing__
httputil.py:86

passed to

writes×2 passed to

writes×2

calls×2 [#29] calls×2 [#30]

release_callback
(2 writes, 2 distinct)
functools.partial(<bound method SimpleAsyncHTTPClient._release_fetch of <tornado.simple_httpclient.SimpleAsyncHTTPClient…
functools.partial(<bound method SimpleAsyncHTTPClient._release_fetch of <tornado.simple_httpclient.SimpleAsyncHTTPClient…

writes×2

calls×2 [#64] calls×2 [#31]

writes×2 writes×2

calls×4 [#134]

passed to

passed to

calls×2 [#33]

_connection_class
simple_httpclient.py:150

calls×2 [#32]

calls×24 [#144] calls×8 [#160] calls×4 [#162]

passed to

match
(5 writes, 3 distinct)
<re.Match object; span=(0, 15), match='localhost:33959'>
<re.Match object; span=(0, 18), match='HTTP/1.1 302 Found'>
<re.Match object; span=(0, 15), match='HTTP/1.1 200 OK'>

writes×2 writes×2 writes×2

passed to

connect

Connect to the given host and port.
tcpclient.py:157

passed to

passed to

passed to

passed to

passed to on_connect_done

tcpclient.py:100

passed to

passed to

passed to

call_at
asyncio.py:131

calls×8 [#46]

calls×4 [#48]

calls×4 [#47]

calls×3 [#72]

calls [#912] calls×6 [#50]

calls [#914]

kwargs
(4 writes, 2 distinct)
{'af': <AddressFamily.AF_UNSPEC: 0>, 'ssl_options': None, 'max_buffer_size': 104857600}
{'path': '/me', 'callback': <tornado.concurrent.Future object at 0x7670a54710a0>, 'access_token': b'asdf', 'fields': 'pi…

writes×3

calls×2 [#51]

add_future
Schedules a callback on the ``IOLoop`` when the given
ioloop.py:574

calls×2 [#52]

writes×6

calls×2 [#56]

calls [#917]

writes

replace
Replace the named argument in ``args, kwargs`` with ``n…
util.py:323

calls [#911]

handle_exception
(2 writes, 2 distinct)
<function _auth_return_future.<locals>.wrapper.<locals>.handle_exception at 0x7670a5208900>
<function _auth_return_future.<locals>.wrapper.<locals>.handle_exception at 0x7670a520ab60>

writes×2

facebook_request
Fetches the given relative API path, e.g., "/btaylor/pi…
auth.py:1015

calls [#915]

passed to

passed to

passed to

passed to

passed to

passed to

stop
tcpclient_test.py:46

passed to

passed to

writes×4

calls×2 [#54]

calls×2 [#55]

is_future
concurrent.py:346

calls×2 [#53]

passed to

_clear_tb_log
concurrent.py:214

calls×33 [#117]

_check_done
concurrent.py:309

calls×9 [#301]

tornado.iostream.StreamClosedError
Stream is closed

raises (caught)

calls×2 [#57]

calls×4 [#279]

done
Returns True if the future has finished running.
concurrent.py:210

calls×10 [#278]

_contains_yieldpoint
Returns True if ``children`` contains any YieldPoints.
gen.py:609

calls×10 [#277]

calls×27 [#118]

writes×7

calls×14 [#232]

calls×23 [#116] writes×4

calls×10 [#276] calls×14 [#234]

raises (caught)

calls [#613]

calls×13 [#120]

stream

(12 writes, 8 distinct)
<tornado.iostream.IOStream object at 0x7670a55d42c0>
<tornado.iostream.IOStream object at 0x7670a542cf80>
<tornado.iostream.IOStream object at 0x7670a542ffe0>
<tornado.iostream.IOStream object at 0x7670a55877d0>
<tornado.iostream.IOStream object at 0x7670a54709e0>
<tornado.iostream.IOStream object at 0x7670a55d7680>
… +2 more values

writes×4

conn

(7 writes, 7 distinct)
<tornado.http1connection.HTTP1ServerConnection object at 0x7670a55d54f0>
<tornado.http1connection.HTTP1Connection object at 0x7670a5411730>
<tornado.http1connection.HTTP1ServerConnection object at 0x7670a542f140>
<tornado.http1connection.HTTP1ServerConnection object at 0x7670a55e0f80>
<tornado.http1connection.HTTP1Connection object at 0x7670a542fa70>
<tornado.http1connection.HTTP1ServerConnection object at 0x7670a5411730>
… +1 more values

writes×3

calls×30 [#115]

addr
(4 writes)
('127.0.0.1', 33959)

writes×4

tornado.gen.Return
<tornado.iostream.IOStream object at 0x7670a55d42c0>

raises (caught)

_value_from_stopiteration
gen.py:145

calls×13 [#119]

_deactivate_stack_context
gen.py:1095

calls×13 [#122]

set_close_callback
wsgi.py:101

calls [#614]

finish
[closure inside read_stream_body]
httpserver_test.py:43

calls×7 [#238]

header_data
(7 writes, 7 distinct)
bytes(len=104)
bytes(len=368)
bytes(len=114)
bytes(len=274)
bytes(len=198)
bytes(len=187)
… +1 more values

writes×7

_parse_headers
http1connection.py:499

calls×7 [#228]

parse_request_start_line
Returns a (method, path, version) tuple for an HTTP 1.x…
httputil.py:778

calls×7 [#230] calls×4 [#229]

need_delegate_close
(14 writes, 2 distinct)
True
False

writes×14

calls×7 [#233]

header_future
(7 writes)
None

writes×7

skip_body
(7 writes)
False

writes×7

calls×7 [#235]

body_future
(7 writes, 4 distinct)
None

<tornado.concurrent.Future object at 0x7670a542f4a0>
<tornado.concurrent.Future object at 0x7670a54710a0>
<tornado.concurrent.Future object at 0x7670a55e0650>

writes×7

_clear_callbacks
Clears the callback attributes.
http1connection.py:263

calls×6 [#241]

parse_response_start_line
Returns a (version, code, reason) tuple for an HTTP 1.x…
httputil.py:800

calls×3 [#288]

code
(3 writes, 2 distinct)
302
200

writes×3

close
select.py:35

calls×3 [#307]

start_request
httpserver.py:181

calls×3 [#325]

request_delegate
(3 writes, 3 distinct)
<tornado.httpserver._ServerRequestAdapter object at 0x7670a542e960>
<tornado.httpserver._ServerRequestAdapter object at 0x7670a5471220>
<tornado.httpserver._ServerRequestAdapter object at 0x7670a5470fe0>

writes×3

read_response
Read a single HTTP response.
http1connection.py:138

calls×3 [#326]

raises (caught)

on_close
websocket_test.py:45

calls×3 [#333]

StopIteration

raises (caught)

final_contexts
(3 writes, 3 distinct)
((), <tornado.stack_context.ExceptionStackContext object at 0x7670a55d6db0>)
((), <tornado.stack_context.ExceptionStackContext object at 0x7670a542e930>)
((), <tornado.stack_context.ExceptionStackContext object at 0x7670a54716d0>)

writes×3

calls×2 [#67]

calls×2 [#68]

get_async_test_timeout
Get the global timeout setting for async tests.
testing.py:99

calls×2 [#66]

timeout_func
(2 writes, 2 distinct)
<function AsyncTestCase.wait.<locals>.timeout_func at 0x7670a5208360>
<function AsyncTestCase.wait.<locals>.timeout_func at 0x7670a5208b80>

writes×2

start

Starts the mock S3 server on the given port at the give…
s3server.py:46

calls×2 [#73]

raises (caught)

TypeError
float() argument must be a string or a real number, not 'NoneType'

raises (caught)

calls [#1225]

raises (caught)

calls×4 [#109] calls×7 [#76]

_setup_logging
The IOLoop catches and logs exceptions, so it's
ioloop.py:360

calls×2 [#74]

old_current
(2 writes)
<tornado.platform.epoll.EPollIOLoop object at 0x7670a550fb00>

writes×2

old_wakeup_fd
(4 writes, 2 distinct)
None
- 1

writes×4

write_fileno
Returns the write file descriptor for this waker.
interface.py:49

calls×2 [#75]

writes×4

calls×2 [#78] calls×2 [#111]

_handle_events
caresresolver.py:43

passed to

update_handler
asyncio.py:79

passed to

accept_handler
[closure inside add_accept_handler]
netutil.py:248

passed to

consume

Called after the listen has woken up to do any necessar…
interface.py:57

passed to

calls×11 [#79] calls×44 [#80] calls×4 [#85]

_handle_connect
iostream.py:1176

calls×4 [#81]

_handle_write
iostream.py:827

calls×4 [#88]

reading
Returns true if we are currently reading from the strea…
iostream.py:470

calls×11 [#90]

writing
Returns true if we are currently writing to the stream.
iostream.py:474

calls×11 [#91]

fileno
kqueue.py:32

calls×6 [#93] calls×6 [#92]

_handle_read
iostream.py:645

calls×7 [#203]

err

(4 writes)
0

writes×4

calls×4 [#82]

_set_done
concurrent.py:313

calls×20 [#83]

calls×2 [#888]

raises (caught)

calls×4 [#84]

_auth_future_to_callback
auth.py:107

calls [#1210]

writes×4

passed to

handle_stream
[closure inside test_handle_stream_coroutine_logging]
tcpserver_test.py:18

passed to _on_connect

simple_httpclient.py:297

passed to

passed to

split_fd
Returns an (fd, obj) pair from an ``fd`` parameter.
ioloop.py:614

calls×6 [#94]

obj
(6 writes, 4 distinct)
<socket.socket fd=7, family=2, type=1, proto=0, laddr=('127.0.0.1', 42814), raddr=('127.0.0.1', 33959)>
<socket.socket fd=7, family=2, type=1, proto=0, laddr=('127.0.0.1', 42816), raddr=('127.0.0.1', 33959)>
<socket.socket fd=9, family=2, type=1, proto=0, laddr=('127.0.0.1', 42830), raddr=('127.0.0.1', 33959)>
<socket.socket fd=9, family=2, type=1, proto=0, laddr=('127.0.0.1', 42836), raddr=('127.0.0.1', 33959)>

writes×6

_remove_deactivated
Remove deactivated handlers from the chain
stack_context.py:227

i
(13 writes, 3 distinct)
0
1
'asdf'

writes×8

connection
(8 writes, 8 distinct)
<socket.socket fd=8, family=2, type=1, proto=6, laddr=('127.0.0.1', 33959), raddr=('127.0.0.1', 42814)>
<tornado.http1connection.HTTP1Connection object at 0x7670a542e9c0>
<socket.socket fd=8, family=2, type=1, proto=6, laddr=('127.0.0.1', 33959), raddr=('127.0.0.1', 42816)>
<tornado.http1connection.HTTP1Connection object at 0x7670a5587920>
<socket.socket fd=10, family=2, type=1, proto=6, laddr=('127.0.0.1', 33959), raddr=('127.0.0.1', 42830)>
<tornado.http1connection.HTTP1Connection object at 0x7670a5471880>
… +2 more values

writes×4

address
(4 writes, 4 distinct)
('127.0.0.1', 42814)
('127.0.0.1', 42816)
('127.0.0.1', 42830)
('127.0.0.1', 42836)

writes×4

_handle_connection
tcpserver.py:232

calls×4 [#98]

BlockingIOError
[Errno 11] Resource temporarily unavailable

raises (caught)

errno_from_exception
Provides the errno from an Exception object.
util.py:166

calls×4 [#107]

passed to

passed to

passed to

passed to

calls×4 [#99]

writes×4

calls×4 [#101]

calls×8 [#102]

context

(4 writes, 4 distinct)
<tornado.httpserver._HTTPRequestContext object at 0x7670a542d3d0>
<tornado.httpserver._HTTPRequestContext object at 0x7670a542f860>
<tornado.httpserver._HTTPRequestContext object at 0x7670a542f800>
<tornado.httpserver._HTTPRequestContext object at 0x7670a542fc20>

writes×4

writes×4

start_serving
Starts serving requests on this connection.
http1connection.py:674

calls×4 [#104]

passed to

passed to

passed to passed to

calls×4 [#105]

calls×4 [#106]

calls×3 [#350]

passed to

calls×4 [#137]

writes×4

calls×4 [#133]

calls×16 [#135]

calls×4 [#138]

calls×4 [#130]

calls×4 [#131]

_maybe_add_error_listener
iostream.py:887

calls×4 [#132]

raises (caught)

norm_name
(12 writes, 3 distinct)
'Connection'
'Host'

'Accept-Encoding'

writes×12 calls [#171]

w

(2 writes, 2 distinct)
'Accept'
'Encoding'

writes×2

normalized
'Accept-Encoding'

writes

calls×8 [#175] calls×4 [#174]

writes×4

set_nodelay
Set the no-delay flag for this stream.
websocket.py:348

calls×4 [#173]

calls×12 [#181]

calls×4 [#182]

raises (caught)

writes×8 writes×4

writes×4

passed to passed to passed to

passed to

passed to passed to passed to

passed to passed to

passed to

passed to

writes×4

WRITE_BUFFER_CHUNK_SIZE
(4 writes)
131072

writes×4

calls×8 [#194]

calls×4 [#196]

_read_response
simple_httpclient.py:406

calls×4 [#197]

_read_to_buffer_loop
iostream.py:585

calls×7 [#204]

pos
(14 writes, 7 distinct)
104
368
114
274
198
187
… +1 more values

writes×7

_read_from_buffer
Attempts to complete the currently-pending read from th…
iostream.py:762

calls×7 [#211]

calls×7 [#205]

target_bytes
(7 writes)
65536

writes×7

next_find_pos
(7 writes)
0

writes×7

_read_to_buffer
Reads from the socket and appends the result to the rea…
iostream.py:721

calls×7 [#206]

_run_streaming_callback
iostream.py:754

calls×7 [#208]

_find_read_pos
Attempts to find a position in the read buffer that sat…
iostream.py:772

calls×7 [#209]

writes×7

read_from_fd
Attempts to read from the underlying file.
iostream.py:209

calls×7 [#207]

chunk
(14 writes, 7 distinct)
bytes(len=104)
bytes(len=368)
bytes(len=114)
bytes(len=274)
bytes(len=215)
bytes(len=187)
… +1 more values

writes×7

writes×7

passed to

m

(7 writes, 7 distinct)
<re.Match object; span=(100, 104), match=b'

'>

<re.Match object; span=(364, 368), match=b'

'>

<re.Match object; span=(110, 114), match=b'

'>

<re.Match object; span=(270, 274), match=b'

'>

<re.Match object; span=(194, 198), match=b'

'>

<re.Match object; span=(183, 187), match=b'

'>
… +1 more values

writes×7

_check_max_bytes
iostream.py:820

calls×7 [#210]

passed to

_run_read_callback
iostream.py:669

calls×7 [#212]

calls×7 [#214]

calls×7 [#215]

_consume
iostream.py:876

calls×7 [#213]

passed to

writes×7

writes×7

eol
(7 writes, 6 distinct)
36
19
46
206
16
119

writes×7

method
(4 writes)
'GET'

writes×4

path
(4 writes, 4 distinct)
'/facebook/client/login'
'/facebook/client/login?code=1234'
'/facebook/server/access_token?redirect_uri=http%3A%2F%2Flocalhost%3A33959%2Ffacebook%2Fclient%2Flogin%3Fcode%3D1234&cod…
'/facebook/server/me?access_token=asdf&fields=picture%2Clink%2Cname%2Clocale%2Clast_name%2Cfirst_name%2Cid'

writes×4

version
(4 writes)
'HTTP/1.1'

writes×4

passed to passed to

passed to

passed to passed to

passed to

passed to

connection_header
(4 writes)
'close'

writes×4

passed to

passed to

passed to

passed to

passed to

content_length
(7 writes, 4 distinct)
None
0
17
2

writes×7

passed to

writes×3

passed to

passed to

passed to

passed to passed to

set_exc_info
Sets the exception information of a ``Future.``
concurrent.py:288

calls [#343]

calls [#344]

calls×2 [#362]

wake
Triggers activity on the waker's file descriptor.
interface.py:53

calls×2 [#363]

raises (caught) failure

(<class 'AssertionError'>, AssertionError('Async operation timed out after 5 seconds'), <traceback object at 0x7670a50f7…

writes

passed to

_on_access_token
auth.py:481

passed to

passed to

writes×2

calls [#907] calls [#909]

writes

_get_body
httpclient.py:570

calls [#906]

parse_qs_bytes
Parses a query string like urlparse.parse_qs, but retur…
escape.py:172

calls [#908]

writes

session

{'access_token': b'asdf', 'expires': None}

writes

writes

writes writes

encoded
(2 writes, 2 distinct)
{}
{'access_token': [b'asdf']}

writes×2

k

'access_token'

writes

passed to

passed to

passed to

passed to

passed to

passed to passed to

writes

old_value
functools.partial(<bound method FacebookGraphMixin._on_get_user_info of <tornado.test.auth_test.FacebookClientLoginHandl…

writes

calls [#916]

url
'http://localhost:33959/facebook/server/me'

writes

calls [#1208]

writes

calls [#1205]

json_decode
Returns Python objects for the given JSON string.
escape.py:91

calls [#1206]

to_basestring
Converts a string argument to a subclass of basestring.
escape.py:238

calls [#1207]

raises (caught) writes