setUp
http1connection_test.py:17 calls [#1]

get_new_ioloop
Creates a new `.IOLoop` for this test. May be overridd…
testing.py:248

calls [#2]

make_current
Makes this the `IOLoop` for the current thread.
ioloop.py:212

calls [#24]

post_coroutine
[closure inside wrap]
testing.py:521

calls [#25]

__new__
httpclient.py:159

calls [#3]

configurable_base
util_test.py:41

calls [#4]

base
(2 writes)
<class 'tornado.ioloop.IOLoop'>

writes

init_kwargs
{}

writes

configured_class
Returns the currently configured class.
util.py:286

calls [#5] impl

<class 'tornado.platform.epoll.EPollIOLoop'>

writes

instance

<tornado.platform.epoll.EPollIOLoop object at 0x7ce510200470>

writes

initialize
auth_test.py:19

calls [#9]

calls [#6]

writes

configurable_default
util_test.py:45

calls [#7]

module
(6 writes, 4 distinct)
<object object at 0x7ce511378060>
None
<module 'tornado.platform.epoll'>
<module 'tornado.platform.epoll' from '/home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/platform/epoll.py'>

writes×6

KeyError
'tornado.platform.epoll'

raises (caught)

lock
(2 writes, 2 distinct)
None

_ModuleLock('tornado.platform.epoll') at 137323259891536

writes×2

self
(7 writes, 7 distinct)
_ModuleLock('tornado.platform.epoll') at 137323259891536
<_frozen_importlib._WeakValueDictionary object at 0x7ce51139b2c0>
<Event set>
<Event clear>
{'Connection': 'Connection'}
{'Connection': 'Connection', 'Content-Length': 'Content-Length'}
… +1 more values

writes×2

cb
(5 writes, 4 distinct)
<function _get_module_lock.<locals>.cb at 0x7ce5102d0860>
<function multi_future.<locals>.callback at 0x7ce5102d1440>
<function IOLoop.add_future.<locals>.<lambda> at 0x7ce5102d1760>
<function BaseIOStream.write.<locals>.<lambda> at 0x7ce5102d13a0>

writes

tid
(2 writes)
137323287388288

writes×2

path
(2 writes, 2 distinct)
None

['/home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/platform']

writes×2

parent
(6 writes, 2 distinct)
'tornado.platform'
None

writes

parent_spec
(2 writes, 2 distinct)
None

ModuleSpec(name='tornado.platform', loader=<_frozen_importlib_external.SourceFileLoader object at 0x7ce510c23ce0>, origi…

writes×2

parent_module
<module 'tornado.platform' from '/home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/platform/__init__.py'>

writes

child
'epoll'

writes

meta_path
[<_distutils_hack.DistutilsMetaFinder object at 0x7ce511170440>, <class '_frozen_importlib.BuiltinImporter'>, <class '_f…

writes

is_reload
False

writes

finder
(4 writes, 4 distinct)
<_distutils_hack.DistutilsMetaFinder object at 0x7ce511170440>
<class '_frozen_importlib.BuiltinImporter'>
<class '_frozen_importlib.FrozenImporter'>
<class '_frozen_importlib_external.PathFinder'>

writes×4

find_spec
(4 writes, 4 distinct)
<bound method DistutilsMetaFinder.find_spec of <_distutils_hack.DistutilsMetaFinder object at 0x7ce511170440>>
<bound method BuiltinImporter.find_spec of <class '_frozen_importlib.BuiltinImporter'>>
<bound method FrozenImporter.find_spec of <class '_frozen_importlib.FrozenImporter'>>
<bound method PathFinder.find_spec of <class '_frozen_importlib_external.PathFinder'>>

writes×4

spec
(4 writes, 2 distinct)
None

ModuleSpec(name='tornado.platform.epoll', loader=<_frozen_importlib_external.SourceFileLoader object at 0x7ce5102037a0>,…

writes×4

info
None

writes

code
<code object <module> at 0x7ce5102fc690, file "/home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/platform/epoll.py",…

writes

EPollIOLoop
<class 'tornado.platform.epoll.EPollIOLoop'>

writes

passed to

passed to passed to

passed to

passed to

__init__
stack_context_test.py:17

passed to

fileno
kqueue.py:32

passed to

add_handler
asyncio.py:65

passed to

split_fd
Returns an (fd, obj) pair from an ``fd`` parameter.
ioloop.py:631

passed to

passed to

run_sync

Starts the `IOLoop`, runs the given function, and stops…
ioloop.py:400

passed to

run

<function IOLoop.run_sync.<locals>.run at 0x7ce5102d07c0>

passed to

add_callback
asyncio.py:142

passed to

wake
Triggers activity on the waker's file descriptor.
interface.py:53

passed to

time

ioloop_test.py:32

passed to

add_timeout
Runs the ``callback`` at the time ``deadline`` from the…
ioloop.py:470

passed to

call_at
asyncio.py:131

passed to

start

Starts the mock S3 server on the given port at the give…
s3server.py:46

passed to

_setup_logging
The IOLoop catches and logs exceptions, so it's
ioloop.py:360

passed to

write_fileno
Returns the write file descriptor for this waker.
interface.py:49

passed to

_run_callback
Runs the given callback with exception handling.
websocket.py:410

passed to

pre_coroutine
[closure inside wrap]
testing.py:507

passed to

result
(6 writes, 6 distinct)
<generator object HTTP1ConnectionTest.asyncSetUp at 0x7ce51012c400>
<types._GeneratorWrapper object at 0x7ce5102cf5c0>
<tornado.concurrent.Future object at 0x7ce5102cede0>
b'x'
None

<generator object HTTP1Connection._read_message at 0x7ce51029d580>

passed to

asyncSetUp
http1connection_test.py:22

passed to

accept_callback
<function HTTP1ConnectionTest.asyncSetUp.<locals>.accept_callback at 0x7ce5102d1080>

passed to

handle_yield
gen.py:1051

passed to

add_future
Schedules a callback on the ``IOLoop`` when the given
ioloop.py:582

passed to

add_done_callback
Attaches the given callback to the `Future`.
concurrent.py:256

passed to

_handle_events
caresresolver.py:43

passed to

closed
Returns true if the stream has been closed.
iostream.py:478

passed to

_handle_connect
iostream.py:1176

passed to

set_result
Sets the result of a ``Future``.
concurrent.py:269

passed to

_set_done
concurrent.py:318

passed to

_handle_write
iostream.py:827

passed to

reading
Returns true if we are currently reading from the strea…
iostream.py:470

passed to

writing
Returns true if we are currently writing to the stream.
iostream.py:474

passed to

update_handler
asyncio.py:79

passed to

set

Set the internal flag to ``True``. All waiters are awak…
locks.py:204

passed to

done
Returns True if the future has finished running.
concurrent.py:215

passed to

__del__
httpclient.py:81

passed to

consume

Called after the listen has woken up to do any necessar…
interface.py:57

passed to

_clear_tb_log
concurrent.py:219

passed to

_deactivate_stack_context
gen.py:1114

passed to

stop
tcpclient_test.py:46

passed to

remove_timeout
asyncio.py:139

passed to

_check_done
concurrent.py:314

passed to

test_http10_no_content_length
http1connection_test.py:41

passed to

_clear_callbacks
Clears the callback attributes.
http1connection.py:263

passed to

set_close_callback
wsgi.py:101

passed to

_maybe_add_error_listener
iostream.py:887

passed to

write
wsgi.py:122

passed to

_check_closed
iostream.py:883

passed to

write_to_fd
Attempts to write ``data`` to the underlying file.
iostream.py:202

passed to

exception
If the operation raised an exception, return the `Excep…
concurrent.py:241

passed to

close
select.py:35

passed to

close_fd
Closes the file underlying this stream.
iostream.py:194

passed to

_maybe_run_close_callback
iostream.py:440

passed to

read_response
Read a single HTTP response.
http1connection.py:138

passed to

_read_message
http1connection.py:154

passed to

read_until_regex
Asynchronously read until we have matched the given reg…
iostream.py:229

passed to

_set_read_callback
iostream.py:660

passed to

_try_inline_read
Attempt to complete the current read operation from buf…
iostream.py:688

passed to

_run_streaming_callback
iostream.py:754

passed to

_find_read_pos
Attempts to find a position in the read buffer that sat…
iostream.py:772

passed to

_read_to_buffer_loop
iostream.py:585

passed to

_read_to_buffer
Reads from the socket and appends the result to the rea…
iostream.py:721

passed to

read_from_fd
Attempts to read from the underlying file.
iostream.py:209

passed to

_check_max_bytes
iostream.py:820

passed to

_read_from_buffer
Attempts to complete the currently-pending read from th…
iostream.py:762

passed to

_run_read_callback
iostream.py:669

passed to

_consume
iostream.py:876

passed to

_parse_headers
http1connection.py:499

passed to

parse_response_start_line
Returns a (version, code, reason) tuple for an HTTP 1.x…
httputil.py:800

passed to

_can_keep_alive
http1connection.py:474

passed to

__getitem__
options.py:140

passed to

__missing__
httputil.py:86

passed to

set_exc_info
Sets the exception information of a ``Future.``
concurrent.py:293

passed to

passed to

passed to passed to

passed to

passed to

current

Returns the current thread's `IOLoop`.
ioloop.py:189

passed to passed to

passed to

passed to

passed to

calls×2 [#10]

calls [#12]

calls [#13]

set_close_exec
windows.py:17

calls [#14]

calls [#15]

calls [#21] calls [#20]

writes×4

flags
(5 writes, 2 distinct)
1
0

writes×3

writes

calls×3 [#48]

calls×2 [#18]

calls×4 [#79]

r

4

writes

w

(6 writes, 6 distinct)
5
'Connection'
'Content'
'Length'
'Transfer'
'Encoding'

writes

_set_nonblocking
posix.py:32

calls×2 [#16]

io
(2 writes)
<module 'io' (frozen)>

calls [#180] writes×2

calls×2 [#49]

params

<tornado.http1connection.HTTP1ConnectionParameters object at 0x7ce5102f4500>

writes

calls [#119]

writes×2

calls [#22]

obj
(2 writes, 2 distinct)
4

<socket.socket fd=7, family=2, type=1, proto=0, laddr=('127.0.0.1', 47356), raddr=('127.0.0.1', 38817)>

writes

wrap

Returns a callable object that will restore the current…
stack_context.py:253

calls [#23]

AttributeError
'int' object has no attribute 'fileno'

raises (caught)

cap_contexts
(4 writes)
[((), <tornado.stack_context.ExceptionStackContext object at 0x7ce510f50590>)]

writes×4

wrapped
(4 writes, 4 distinct)
<function wrap.<locals>.wrapped at 0x7ce5102d0900>
<function wrap.<locals>.wrapped at 0x7ce5102d0a40>
<function wrap.<locals>.wrapped at 0x7ce5102d0540>
<function wrap.<locals>.wrapped at 0x7ce5102d16c0>

writes×4

defines

defines

null_wrapper
[closure inside wrap]
stack_context.py:271

defines

passed to

passed to

calls×2 [#42]

ret

(8 writes)
None

writes×5

current_state
(6 writes)
((), <tornado.stack_context.ExceptionStackContext object at 0x7ce510f50590>)

writes×5

_remove_deactivated
Remove deactivated handlers from the chain
stack_context.py:227

calls×5 [#41]

contexts

(5 writes)
((), <tornado.stack_context.ExceptionStackContext object at 0x7ce510f50590>)

writes×5

exc

(5 writes)
(None, None, None)

writes×5

top
(5 writes)
None

writes×5

last_ctx
(5 writes)
0

writes×5

stack
(5 writes)
()

writes×5

accept_handler
[closure inside add_accept_handler]
netutil.py:246

calls [#76] calls [#89]

calls [#107]

calls [#26]

calls [#115]

future_cell
(3 writes, 2 distinct)
[None]
[<tornado.concurrent.Future object at 0x7ce5102cede0>]

writes×2

writes

calls [#27] calls [#31] calls [#30]

timeout_handle
<tornado.ioloop._Timeout object at 0x7ce510c897c0>

writes calls [#35]

calls [#112]

calls [#111] calls [#110]

passed to writes

wrapper
[closure inside administrator]
blog.py:43

calls [#43]

future
(11 writes, 7 distinct)
<tornado.concurrent.Future object at 0x7ce5102cede0>
None

<tornado.concurrent.Future object at 0x7ce510200380>
<tornado.concurrent.Future object at 0x7ce5102cf8f0>
<tornado.concurrent.Future object at 0x7ce5102bd970>
<tornado.concurrent.Future object at 0x7ce5102cdc70>
… +1 more values

writes×2

writes

orig_stack_contexts
(4 writes)
((), <tornado.stack_context.ExceptionStackContext object at 0x7ce510f50590>)

writes×2

listener
(2 writes, 2 distinct)
<socket.socket fd=6, family=2, type=1, proto=6, laddr=('127.0.0.1', 38817)>
<socket.socket [closed] fd=-1, family=2, type=1, proto=6>

writes

convert_yielded
<function convert_yielded at 0x7ce510cb2ca0>

writes

is_future
concurrent.py:351

calls [#52]

calls [#53]

calls×2 [#95] calls [#100]

calls [#98]

e

(2 writes, 2 distinct)
BlockingIOError(11, 'Resource temporarily unavailable')
StopIteration()

writes

exc_info
(2 writes)
None

writes×2

value
(2 writes, 2 distinct)
[<tornado.iostream.IOStream object at 0x7ce5102bc7a0>, None]
bytes(len=29)

writes×2

StopIteration

raises (caught)

_value_from_stopiteration
gen.py:157

calls [#99]

calls [#102]

header_data
bytes(len=29)

writes

calls [#184]

calls [#28] list_empty

True

writes

calls [#32] calls [#29]

calls [#34]

calls [#33]

timeout
(2 writes, 2 distinct)
<tornado.ioloop._Timeout object at 0x7ce510c897c0>
None

writes

passed to

passed to

passed to

calls×2 [#74]

calls×5 [#38]

writes

calls [#36] old_current

<tornado.platform.epoll.EPollIOLoop object at 0x7ce510200470>

writes

old_wakeup_fd
(2 writes, 2 distinct)
None
- 1

writes×2

calls [#37]

callbacks
(6 writes, 4 distinct)
[functools.partial(<function wrap.<locals>.wrapped at 0x7ce5102d0a40>)]
None

[functools.partial(<function wrap.<locals>.wrapped at 0x7ce5102d14e0>, <tornado.concurrent.Future object at 0x7ce5102cf8…
[functools.partial(<function wrap.<locals>.wrapped at 0x7ce5102d16c0>, <tornado.concurrent.Future object at 0x7ce5102ced…

writes×6

due_timeouts
(6 writes, 2 distinct)
[]
None

writes×6

now

(3 writes, 3 distinct)
1779889604.281327
1779889604.3022616
1779889604.306968

writes×3

callback
(8 writes, 5 distinct)
functools.partial(<function wrap.<locals>.wrapped at 0x7ce5102d0a40>)
<function wrap.<locals>.wrapped at 0x7ce5102d16c0>
None

functools.partial(<function wrap.<locals>.wrapped at 0x7ce5102d14e0>, <tornado.concurrent.Future object at 0x7ce5102cf8f…
functools.partial(<function wrap.<locals>.wrapped at 0x7ce5102d16c0>, <tornado.concurrent.Future object at 0x7ce5102cede…

writes×6

calls×3 [#39]

poll_timeout
(3 writes, 3 distinct)
4.982671499252319
0.0
4.963762521743774

writes×3

event_pairs
(2 writes, 2 distinct)
[(4, 1), (6, 1), (7, 4)]
[]

writes×2

fd
(4 writes, 3 distinct)
7
6
4

writes×3

events

(2 writes, 2 distinct)
4
1

writes×2

fd_obj
(4 writes, 4 distinct)
<socket.socket fd=7, family=2, type=1, proto=0, laddr=('127.0.0.1', 47356), raddr=('127.0.0.1', 38817)>
<socket.socket fd=6, family=2, type=1, proto=6, laddr=('127.0.0.1', 38817)>
4
None

writes×4

handler_func
(4 writes, 4 distinct)
<function wrap.<locals>.null_wrapper at 0x7ce5102d0fe0>
<function wrap.<locals>.wrapped at 0x7ce5102d1260>
<function wrap.<locals>.wrapped at 0x7ce5102d0900>
None

writes×4

calls [#58]

passed to

passed to

unfinished_children
{<tornado.concurrent.Future object at 0x7ce510200cb0>}

writes

passed to

passed to

passed to

passed to

passed to

calls×3 [#40]

writes×3

writes×5

stack_contexts
(5 writes)
()

writes×5

head
(5 writes)
<tornado.stack_context.ExceptionStackContext object at 0x7ce510f50590>

writes×5

ctx

(10 writes, 2 distinct)
<tornado.stack_context.ExceptionStackContext object at 0x7ce510f50590>
None

writes×10

passed to

calls×4 [#44]

calls [#45] writes×3

writes×2

writes×2

calls [#46]

yielded
(2 writes, 2 distinct)
[<tornado.concurrent.Future object at 0x7ce510200380>, <tornado.concurrent.Future object at 0x7ce510200cb0>]
<tornado.concurrent.Future object at 0x7ce5102cdca0>

writes×2

calls [#150]

passed to

passed to

passed to

writes

passed to

calls×3 [#97] calls [#114]

writes

port
38817

writes

event

(3 writes, 2 distinct)
<Event clear>
<Event set>

writes

writes

passed to passed to

passed to

passed to

calls [#78]

writes

calls [#81]

passed to

passed to

passed to

calls [#177]

calls [#179]

_contains_yieldpoint
Returns True if ``children`` contains any YieldPoints.
gen.py:621

calls [#176]

calls×2 [#51]

calls [#55]

writes

calls [#54]

calls [#56]

passed to

passed to

passed to

passed to passed to

passed to

passed to

passed to passed to

writes

calls [#59]

calls [#71]

calls×4 [#60]

calls [#61]

calls [#67]

state

(2 writes, 2 distinct)
24
25

writes×2

calls [#72] calls [#70] calls [#69]

writes

err

0

writes

calls [#62]

calls×5 [#63]

calls [#85]

writes×4

calls [#64]

calls [#134]

writes

calls [#132]

_merge_prefix
Replace the first entries in a deque of strings with a …
iostream.py:1510

calls [#130] calls×2 [#129]

num_bytes
34

writes

calls [#73]

writes writes

calls [#77]

i
(3 writes, 2 distinct)
0
1

writes×2

connection

<socket.socket fd=8, family=2, type=1, proto=6, laddr=('127.0.0.1', 38817), raddr=('127.0.0.1', 47356)>

writes

address
('127.0.0.1', 47356)

writes

BlockingIOError
[Errno 11] Resource temporarily unavailable

raises (caught)

writes

errno_from_exception
Provides the errno from an Exception object.
util.py:163

calls [#86]

writes

calls [#82] calls [#83]

passed to

passed to

writes×2

passed to

passed to

to_unicode
Converts a string argument to a unicode string.
escape.py:200

passed to

calls [#108]

calls×2 [#116]

writes

calls [#139]

conn

<tornado.http1connection.HTTP1Connection object at 0x7ce5102bf5c0>

writes

calls [#123] calls [#140]

test

<tornado.test.http1connection_test.HTTP1ConnectionTest testMethod=test_http10_no_content_length>

writes

body
[]

writes

__module__
'tornado.test.http1connection_test'

writes

__qualname__
'HTTP1ConnectionTest.test_http10_no_content_length.<locals>.Delegate'

writes

headers_received
<function HTTP1ConnectionTest.test_http10_no_content_length.<locals>.Delegate.headers_received at 0x7ce5102d1080>

writes

data_received
<function HTTP1ConnectionTest.test_http10_no_content_length.<locals>.Delegate.data_received at 0x7ce5102d1440>

writes

finish
<function HTTP1ConnectionTest.test_http10_no_content_length.<locals>.Delegate.finish at 0x7ce5102d1760>

writes

Delegate
<class 'tornado.test.http1connection_test.HTTP1ConnectionTest.test_http10_no_content_length.<locals>.Delegate'>

writes

calls [#147]

calls×2 [#120]

calls×2 [#121]

calls×2 [#122]

calls [#138]

calls [#126]

writes

calls [#128] calls [#127]

writes

calls [#137] calls [#124]

WRITE_BUFFER_CHUNK_SIZE
131072

writes

calls×2 [#125]

chunk
(4 writes, 2 distinct)
bytes(len=34)
bytes(len=29)

writes×2

prefix
(2 writes, 2 distinct)
[]
[b'HTTP/1.0 200 Not Modified

']

writes×2

remaining
(2 writes, 2 distinct)
29
0

writes×2

deque
(3 writes, 3 distinct)
deque([])
deque([b'hello'])
deque([b'HTTP/1.0 200 Not Modified

', b'hello'])

writes×3

calls [#135] calls [#136] calls [#143] calls [#142] calls [#141]

calls [#144]

futures
[]

writes

raises (caught)

calls [#148]

writes

calls [#203] calls [#197]

loops(×3)

start_line
(3 writes, 2 distinct)
'HTTP/1.0 200 Not Modified'
ResponseStartLine(version='HTTP/1.0', code=200, reason='Not Modified')

writes×2

headers
(2 writes)
<tornado.httputil.HTTPHeaders object at 0x7ce5102cf710>

writes×2

calls [#190] calls [#201] calls [#188]

need_delegate_close
False

writes

calls [#151]

header_future
<tornado.concurrent.Future object at 0x7ce5102cdca0>

writes

passed to

writes

calls [#152] calls [#154]

calls [#153]

calls [#157]

calls [#156] calls [#155]

pos
(3 writes, 2 distinct)
None
29

writes×2

calls [#159] calls [#166]

m

<re.Match object; span=(25, 29), match=b'

'>

writes

calls [#165]

passed to

calls [#160]

calls [#163]

calls [#164]

writes

target_bytes
65536

writes

next_find_pos
0

writes

calls [#161]

calls [#162]

writes

writes

calls [#167]

writes

writes

calls [#170]

calls [#172]

calls [#168]

calls [#169]

passed to

calls [#185]

data
'HTTP/1.0 200 Not Modified

'

writes

eol
26

writes

writes

parse

Returns a dictionary from HTTP header text.
httputil.py:188

calls [#186]

passed to

calls [#187]

h
<tornado.httputil.HTTPHeaders object at 0x7ce5102cf710>

writes

line
''

writes

passed to

passed to

calls [#189]

match
<re.Match object; span=(0, 25), match='HTTP/1.0 200 Not Modified'>

writes

raises (caught)

raises (caught)

calls×3 [#191]

connection_header
None

writes

raises (caught)

calls×3 [#192]

writes×3

writes×5

normalized
(3 writes, 3 distinct)
'Connection'
'Content-Length'
'Transfer-Encoding'

writes×3

calls [#202]