test_path_traversal_protection
web_test.py:1188

__init__
stack_context_test.py:17

calls [#1]

__enter__
http1connection.py:49

calls [#2]

get_and_head
Performs a GET and HEAD request and returns the GET res…
web_test.py:1016

calls [#3]

calls×4 [#39]

calls×2 [#40]

headers
httpclient.py:459

calls×2 [#10]

update
httputil.py:228

calls×2 [#12]

body
httpclient.py:470

calls×2 [#13]

body_producer
[closure inside test_100_continue_early_response]
simple_httpclient_test.py:411

calls×2 [#15]

wrap

Returns a callable object that will restore the current…
stack_context.py:253

calls×2 [#48]

streaming_callback
[closure inside test_streaming_callback]
iostream_test.py:280

calls×2 [#17]

header_callback
[closure inside test_header_callback]
httpclient_test.py:308

calls×2 [#19]

prepare_curl_callback
httpclient.py:502

calls×2 [#21]

get_all
Returns an iterable of all (name, value) pairs.
httputil.py:164

calls×2 [#25]

time

ioloop_test.py:32

calls×2 [#38]

__getattr__
util.py:31

calls×8 [#41]

to_unicode
Converts a string argument to a unicode string.
escape.py:210

calls×2 [#42]

netloc
(2 writes)
'localhost:37607'

writes×2

split_host_and_port
Returns ``(host, port)`` tuple from ``netloc``.
httputil.py:897

calls×2 [#43]

host
(4 writes)
'localhost'

writes×2

port
(4 writes)
37607

writes×2

af
(4 writes, 2 distinct)
<AddressFamily.AF_UNSPEC: 0>
<AddressFamily.AF_INET: 2>

writes×2

_get_ssl_options
simple_httpclient.py:238

calls×2 [#45]

ssl_options
(2 writes)
None

writes×2

timeout
(10 writes, 7 distinct)
20.0

<tornado.ioloop._Timeout object at 0x742832dcd0c0>
5

<tornado.ioloop._Timeout object at 0x742832d4b800>
None

<tornado.ioloop._Timeout object at 0x742832c2f8c0>
… +1 more values

writes×2

add_timeout
Runs the ``callback`` at the time ``deadline`` from the…
ioloop.py:462

calls×2 [#49]

wrapper
[closure inside administrator]
blog.py:43

calls×2 [#51]

__del__
httpclient.py:81

calls×2 [#57]

__exit__
http1connection.py:52

calls×2 [#58]

loops(×9)

fetch

Executes a request, returning an `HTTPResponse`.
httpclient.py:91

calls [#4]

key
(7 writes, 4 distinct)
<object object at 0x742834910e00>
'network_interface'
'proxy_password'
<object object at 0x742834910da0>

writes

calls×19 [#126] calls×2 [#154] calls [#151]

callbacks
(10 writes, 6 distinct)
[]
None

[functools.partial(<function wrap.<locals>.wrapped at 0x742832ec7100>, <tornado.concurrent.Future object at 0x742832f5a7…
[functools.partial(<function wrap.<locals>.wrapped at 0x742832ec6ca0>, <tornado.concurrent.Future object at 0x742832f90e…
[functools.partial(<function wrap.<locals>.wrapped at 0x742832ec7b00>, <tornado.concurrent.Future object at 0x742832f925…
[functools.partial(<function wrap.<locals>.wrapped at 0x742832ec7100>, <tornado.concurrent.Future object at 0x742832f92a…

writes×2

due_timeouts
(10 writes, 2 distinct)
[]
None

writes×2

now

(6 writes, 6 distinct)
1779889655.0324252
1779889655.049084
1779889655.0541866
1779889655.078681
1779889655.1496358
1779889655.158556

writes

poll_timeout
(4 writes, 4 distinct)
0.2864995002746582
0.0
4.949565172195435
0.29527997970581055

writes

event_pairs
(4 writes, 4 distinct)
[(6, 1), (7, 4)]
[]
[(8, 1)]
[(4, 1), (6, 1), (7, 4)]

writes

fd
(9 writes, 4 distinct)
7
6
8
4

writes

fd_obj
(9 writes, 6 distinct)
<socket.socket fd=7, family=2, type=1, proto=0, laddr=('127.0.0.1', 42454), raddr=('127.0.0.1', 37607)>
<socket.socket fd=6, family=2, type=1, proto=6, laddr=('127.0.0.1', 37607)>
None

<socket.socket fd=8, family=2, type=1, proto=6, laddr=('127.0.0.1', 37607), raddr=('127.0.0.1', 42454)>
<socket.socket fd=7, family=2, type=1, proto=0, laddr=('127.0.0.1', 42458), raddr=('127.0.0.1', 37607)>
4

writes×2

handler_func
(9 writes, 6 distinct)
<function wrap.<locals>.null_wrapper at 0x742832ec6e80>
<function wrap.<locals>.wrapped at 0x742832ec58a0>
None

<function wrap.<locals>.null_wrapper at 0x742832ec7740>
<function wrap.<locals>.null_wrapper at 0x742832ec6520>
<function wrap.<locals>.wrapped at 0x742833b10900>

writes×2

null_wrapper
[closure inside wrap]
stack_context.py:271

calls [#155]

_run_callback
Runs the given callback with exception handling.
websocket.py:409

calls [#172]

__contains__
httputil.py:221

calls×2 [#128]

__setitem__
httputil.py:208

calls×3 [#130]

username

None

writes

password
None

writes

body_expected
False

writes

body_present
False

writes

req_path
'/static/../static_foo.txt'

writes

_create_connection
simple_httpclient.py:377

calls [#147]

start_line
(9 writes, 7 distinct)
RequestStartLine(method='HEAD', path='/static/../static_foo.txt', version='')
'HEAD /static/../static_foo.txt HTTP/1.1'
RequestStartLine(method='HEAD', path='/static/../static_foo.txt', version='HTTP/1.1')
'HTTP/1.1 404 Not Found'
ResponseStartLine(version='HTTP/1.1', code=404, reason='Not Found')
'GET /static/../static_foo.txt HTTP/1.1'
… +1 more values

writes

write_headers
wsgi.py:106

calls [#150]

data
bytes(len=108)

writes

_write_body
simple_httpclient.py:389

calls×8 [#9] calls [#153]

calls×2 [#8]

get_url
[closure inside test_multi_process]
process_test.py:68

calls×2 [#5]

calls×4 [#23] calls×2 [#29]

request
(8 writes, 4 distinct)
<tornado.httpclient.HTTPRequest object at 0x742832f58f50>
<tornado.httpclient._RequestProxy object at 0x742832f5a2a0>
<tornado.httpclient.HTTPRequest object at 0x742832f59130>
<tornado.httpclient._RequestProxy object at 0x742832f5b740>

writes×4

handle_future
(2 writes, 2 distinct)
<function AsyncHTTPClient.fetch.<locals>.handle_future at 0x742832ec6520>
<function AsyncHTTPClient.fetch.<locals>.handle_future at 0x742832ec63e0>

writes×2

add_done_callback
Attaches the given callback to the `Future`.
concurrent.py:234

calls×2 [#30]

handle_response
(2 writes, 2 distinct)
<function AsyncHTTPClient.fetch.<locals>.handle_response at 0x742832ec6480>
<function AsyncHTTPClient.fetch.<locals>.handle_response at 0x742832ec7ec0>

writes×2

fetch_impl
curl_httpclient.py:77

calls×2 [#31]

wait

Wait for `.notify`.
locks.py:119

calls×2 [#60]

get_protocol
testing.py:396

calls×2 [#6]

get_http_port
Returns the port used by the server.
testing.py:389

passed to calls×2 [#7]

set_result
Sets the result of a ``Future``.
concurrent.py:247

passed to passed to

utf8
Converts a string argument to a byte string.
escape.py:193

calls×2 [#14]

calls×2 [#16]

cap_contexts
(8 writes, 3 distinct)
[((), <tornado.stack_context.ExceptionStackContext object at 0x742833daed20>)]
[((), <tornado.stack_context.ExceptionStackContext object at 0x7428339360c0>)]
[((), <tornado.stack_context.ExceptionStackContext object at 0x742832f5b170>)]

writes×8

wrapped
(8 writes, 5 distinct)
<function wrap.<locals>.wrapped at 0x742832ec63e0>
<function wrap.<locals>.wrapped at 0x742832ec6980>
<function wrap.<locals>.wrapped at 0x742832ec72e0>
<function wrap.<locals>.wrapped at 0x742832ec7e20>
<function wrap.<locals>.wrapped at 0x742832ec7c40>

writes×8

defines

passed to calls×2 [#18] calls×2 [#20] calls×2 [#22]

passed to

passed to

_handle_request
simple_httpclient.py:153

passed to

passed to

passed to

calls×2 [#218]

result
(4 writes, 4 distinct)
<generator object TCPClient.connect at 0x742832fd4fb0>
<generator object TCPClient.connect at 0x742832fd5340>
b'x'
None

calls×6 [#115]

calls [#411]

_remove_deactivated
Remove deactivated handlers from the chain
stack_context.py:227

calls×23 [#90]

accept_handler
[closure inside add_accept_handler]
netutil.py:239

calls×2 [#91]

run

runtests.py:64

calls×10 [#106]

_on_connect
simple_httpclient.py:297

calls×2 [#117]

stop
tcpclient_test.py:46

calls×2 [#233]

consume

Called after the listen has woken up to do any necessar…
interface.py:57

calls [#333]

set_exception
Sets the exception of a ``Future.``
concurrent.py:256

calls×2 [#219]

writes×2

timeout_handle
(4 writes)
None

writes×2

_process_queue
simple_httpclient.py:139

calls×2 [#32]

_remove_timeout
simple_httpclient.py:163

passed to

passed to

calls×2 [#33]

writes×2 writes×2

calls×2 [#34]

release_callback
(2 writes, 2 distinct)
functools.partial(<bound method SimpleAsyncHTTPClient._release_fetch of <tornado.simple_httpclient.SimpleAsyncHTTPClient…
functools.partial(<bound method SimpleAsyncHTTPClient._release_fetch of <tornado.simple_httpclient.SimpleAsyncHTTPClient…

writes×2

calls×2 [#35]

calls×2 [#59]

writes×2 writes×2

passed to

passed to

calls×2 [#37]

_connection_class
simple_httpclient.py:150

passed to calls×2 [#36]

match
(2 writes)
<re.Match object; span=(0, 15), match='localhost:37607'>

writes×2 writes×2 writes×2

connect

Connect to the given host and port.
tcpclient.py:157

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

remove_timeout
asyncio.py:122

passed to

call_at
asyncio.py:114

calls×4 [#50]

calls×2 [#66]

calls×2 [#65]

writes×4

__lt__
ioloop.py:963

calls×2 [#67]

calls×4 [#52]

kwargs
(2 writes)
{'af': <AddressFamily.AF_UNSPEC: 0>, 'ssl_options': None, 'max_buffer_size': 104857600}

writes×2

current

Returns the current thread's `IOLoop`.
ioloop.py:189

calls×2 [#53]

add_future
Schedules a callback on the ``IOLoop`` when the given
ioloop.py:574

calls×2 [#54]

writes×2

orig_stack_contexts
(12 writes, 3 distinct)
((), <tornado.stack_context.ExceptionStackContext object at 0x7428339360c0>)
((), <tornado.stack_context.ExceptionStackContext object at 0x742833daed20>)
((), <tornado.stack_context.ExceptionStackContext object at 0x742832f5b170>)

writes×2

calls×2 [#55]

yielded
(7 writes, 6 distinct)
<tornado.concurrent.Future object at 0x742832f59100>
<tornado.concurrent.Future object at 0x742833bccb90>
<tornado.concurrent.Future object at 0x742832f92720>
<tornado.concurrent.Future object at 0x742832f91ac0>
<tornado.concurrent.Future object at 0x742832f924e0>
<tornado.concurrent.Future object at 0x742832f920c0>

writes×2

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

writes×2

passed to

_clear_tb_log
concurrent.py:197

calls×6 [#116]

tornado.iostream.StreamClosedError
Stream is closed

raises (caught)

_check_done
concurrent.py:292

calls×2 [#230]

handle_yield
gen.py:913

passed to

final_contexts
(2 writes, 2 distinct)
((), <tornado.stack_context.ExceptionStackContext object at 0x7428339360c0>)
((), <tornado.stack_context.ExceptionStackContext object at 0x742832f5b170>)

writes×2

Exception
did not get expected log message

raises (caught)

calls×2 [#62]

writes×2

calls×2 [#63]

get_async_test_timeout
Get the global timeout setting for async tests.
testing.py:94

calls×2 [#61]

timeout_func
(2 writes, 2 distinct)
<function AsyncTestCase.wait.<locals>.timeout_func at 0x742832ec7240>
<function AsyncTestCase.wait.<locals>.timeout_func at 0x742832ec6e80>

writes×2

start

Starts the mock S3 server on the given port at the give…
s3server.py:46

calls×2 [#68]

KeyError
b'ASYNC_TEST_TIMEOUT'

raises (caught)

TypeError
float() argument must be a string or a real number, not 'NoneType'

raises (caught)

calls×3 [#89]

calls×7 [#71]

writes×2

calls×4 [#101]

_setup_logging
The IOLoop catches and logs exceptions, so it's
ioloop.py:360

calls×2 [#69]

old_current
(2 writes)
<tornado.platform.epoll.EPollIOLoop object at 0x742833864e30>

writes×2

old_wakeup_fd
(4 writes, 2 distinct)
None
- 1

writes×4

write_fileno
Returns the write file descriptor for this waker.
interface.py:49

calls×2 [#70]

writes×5 writes×3 writes×8 writes×5 writes×3 writes×8

events

(4 writes, 2 distinct)
4
1

writes×4 writes×7 writes×7

calls×2 [#73] calls×2 [#103]

_handle_events
caresresolver.py:43

passed to update_handler

asyncio.py:70

passed to

split_fd
Returns an (fd, obj) pair from an ``fd`` parameter.
ioloop.py:614

passed to

passed to passed to

passed to

passed to

passed to passed to

calls×2 [#79] calls×6 [#74]

closed
Returns true if the stream has been closed.
iostream.py:475

calls×24 [#75]

_handle_connect
iostream.py:1160

calls×2 [#76]

_handle_write
iostream.py:820

calls×2 [#82]

state

(11 writes, 2 distinct)
24
25

writes×11

reading
Returns true if we are currently reading from the strea…
iostream.py:467

calls×6 [#84]

writing
Returns true if we are currently writing to the stream.
iostream.py:471

calls×6 [#85]

fileno
kqueue.py:32

calls×3 [#87] calls×3 [#86]

_handle_read
iostream.py:642

calls×4 [#159]

err

(2 writes)
0

writes×2

calls×2 [#77]

_set_done
concurrent.py:296

calls×2 [#78]

cb
(2 writes, 2 distinct)
functools.partial(<bound method _Connector.on_connect_done of <tornado.tcpclient._Connector object at 0x742832f59160>>, …
functools.partial(<bound method _Connector.on_connect_done of <tornado.tcpclient._Connector object at 0x742832f92f60>>, …

writes×2

writes×3

calls×3 [#88]

obj
(3 writes, 2 distinct)
<socket.socket fd=7, family=2, type=1, proto=0, laddr=('127.0.0.1', 42454), raddr=('127.0.0.1', 37607)>
<socket.socket fd=7, family=2, type=1, proto=0, laddr=('127.0.0.1', 42458), raddr=('127.0.0.1', 37607)>

writes×3

i
(4 writes, 2 distinct)
0
1

writes×4

connection
(4 writes, 4 distinct)
<socket.socket fd=8, family=2, type=1, proto=6, laddr=('127.0.0.1', 37607), raddr=('127.0.0.1', 42454)>
<tornado.http1connection.HTTP1Connection object at 0x742832f59610>
<socket.socket fd=8, family=2, type=1, proto=6, laddr=('127.0.0.1', 37607), raddr=('127.0.0.1', 42458)>
<tornado.http1connection.HTTP1Connection object at 0x742832f93260>

writes×2

address
(2 writes, 2 distinct)
('127.0.0.1', 42454)
('127.0.0.1', 42458)

writes×2

_handle_connection
tcpserver.py:232

calls×2 [#92] BlockingIOError

[Errno 11] Resource temporarily unavailable

raises (caught)

e

(8 writes, 3 distinct)
BlockingIOError(11, 'Resource temporarily unavailable')
Return()
StopIteration()

writes×2

errno_from_exception
Provides the errno from an Exception object.
util.py:160

calls×2 [#99]

passed to

passed to

passed to

handle_stream
[closure inside test_handle_stream_coroutine_logging]
tcpserver_test.py:18

passed to

calls×2 [#93]

stream

(4 writes, 4 distinct)
<tornado.iostream.IOStream object at 0x742832f91d90>
<tornado.iostream.IOStream object at 0x742832f91220>
<tornado.iostream.IOStream object at 0x742832f5aa20>
<tornado.iostream.IOStream object at 0x742832f929f0>

writes×2

calls×2 [#95]

passed to

passed to

passed to

passed to

calls×4 [#96]

context

(2 writes, 2 distinct)
<tornado.httpserver._HTTPRequestContext object at 0x742832f92390>
<tornado.httpserver._HTTPRequestContext object at 0x742832f5adb0>

writes×2

conn

(4 writes, 4 distinct)
<tornado.http1connection.HTTP1ServerConnection object at 0x742832fa2330>
<tornado.http1connection.HTTP1Connection object at 0x742832f93140>
<tornado.http1connection.HTTP1ServerConnection object at 0x742832f92540>
<tornado.http1connection.HTTP1Connection object at 0x742832f5b440>

writes×2

start_serving
Starts serving requests on this connection.
http1connection.py:674

calls×2 [#98]

passed to

passed to

passed to

passed to

calls×20 [#104]

is_future
concurrent.py:329

calls×2 [#225]

writes×4

writes×2

calls×13 [#108]

writes×5 writes×10

calls×6 [#109]

writes×2

writes×2

writes×6

done
Returns True if the future has finished running.
concurrent.py:193

calls×13 [#107]

exc_info
(12 writes, 3 distinct)
None

(<class 'tornado.iostream.StreamClosedError'>, StreamClosedError('Stream is closed'), <traceback object at 0x742832fc36c…
(<class 'tornado.iostream.StreamClosedError'>, StreamClosedError('Stream is closed'), <traceback object at 0x742832c5bc8…

writes×12

value
(11 writes, 7 distinct)
(<AddressFamily.AF_INET: 2>, ('127.0.0.1', 37607), <tornado.iostream.IOStream object at 0x742832f91220>)
bytes(len=108)
True

bytes(len=150)
None

(<AddressFamily.AF_INET: 2>, ('127.0.0.1', 37607), <tornado.iostream.IOStream object at 0x742832f929f0>)
… +1 more values

writes×11

addr
(2 writes)
('127.0.0.1', 37607)

writes×2

tornado.gen.Return

raises (caught)

_deactivate_stack_context
gen.py:980

calls×6 [#110]

writes×8

header_data
(4 writes, 3 distinct)
bytes(len=108)
bytes(len=150)
bytes(len=107)

writes×4

need_delegate_close
(8 writes, 2 distinct)
True
False

writes×8

header_future
(4 writes)
None

writes×4

skip_body
(5 writes, 2 distinct)
False
True

writes×5

body_future
(3 writes, 2 distinct)
None

<tornado.concurrent.Future object at 0x742832f924e0>

writes×3

calls×5 [#198]

code
(2 writes)
404

writes×2

request_delegate
(2 writes, 2 distinct)
<tornado.httpserver._ServerRequestAdapter object at 0x742832f5a690>
<tornado.httpserver._ServerRequestAdapter object at 0x742832f5b590>

writes×2

raises (caught)

StopIteration

raises (caught)

set_exc_info
Sets the exception information of a ``Future.``
concurrent.py:271

passed to

passed to

passed to

passed to

passed to passed to passed to passed to

passed to

passed to

passed to passed to

calls×2 [#122]

writes×2

calls×2 [#119]

calls×8 [#120]

calls×2 [#123]

set_close_callback
wsgi.py:101

calls×2 [#118]

norm_name
(10 writes, 3 distinct)
'Connection'
'Host'

'Accept-Encoding'

writes×6 writes×4

self
(6 writes, 3 distinct)
{'Connection': 'close'}
{'Connection': 'close', 'Host': 'localhost:37607'}
{'Connection': 'close', 'Host': 'localhost:37607', 'Accept-Encoding': 'gzip'}

writes×6

passed to passed to

passed to

passed to

passed to passed to passed to

passed to

passed to passed to passed to passed to passed to passed to

passed to passed to

passed to passed to

passed to

passed to

passed to passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to passed to

passed to

passed to

passed to

passed to passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to passed to passed to passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to passed to passed to passed to passed to

passed to

_read_to_buffer_loop
iostream.py:582

passed to

_read_to_buffer
Reads from the socket and appends the result to the rea…
iostream.py:718

passed to

_run_streaming_callback
iostream.py:747

passed to

_find_read_pos
Attempts to find a position in the read buffer that sat…
iostream.py:765

passed to

_read_from_buffer
Attempts to complete the currently-pending read from th…
iostream.py:755

passed to

_run_read_callback
iostream.py:666

passed to

passed to passed to

passed to

passed to

passed to

wake
Triggers activity on the waker's file descriptor.
interface.py:53

passed to

passed to

__rethrow
testing.py:252

passed to

passed to

get
red_test.py:15

passed to

writes×2

passed to passed to

lines
(6 writes, 5 distinct)
[]
[b'HEAD /static/../static_foo.txt HTTP/1.1']
[b'HEAD /static/../static_foo.txt HTTP/1.1', b'Connection: close', b'Host: localhost:37607', b'Accept-Encoding: gzip']
[b'GET /static/../static_foo.txt HTTP/1.1']
[b'GET /static/../static_foo.txt HTTP/1.1', b'Connection: close', b'Host: localhost:37607', b'Accept-Encoding: gzip']

writes×6

n

(6 writes, 3 distinct)
'Connection'
'Host'

'Accept-Encoding'

writes×6

v

(6 writes, 3 distinct)
'close'
'localhost:37607'
'gzip'

writes×6

line
(2 writes, 2 distinct)
bytes(len=39)
bytes(len=38)

writes×2

calls×4 [#160]

pos
(8 writes, 3 distinct)
108
150
107

writes×4

calls×4 [#161] calls×4 [#165]

target_bytes
(4 writes)
65536

writes×4

next_find_pos
(4 writes)
0

writes×4

calls×4 [#164] calls×4 [#162] calls×4 [#163]

writes×4

chunk
(4 writes, 4 distinct)
bytes(len=108)
bytes(len=150)
bytes(len=107)
bytes(len=219)

writes×4

passed to

m

(4 writes, 3 distinct)
<re.Match object; span=(104, 108), match=b'

'>

<re.Match object; span=(146, 150), match=b'

'>

<re.Match object; span=(103, 107), match=b'

'>

writes×4

passed to

calls×4 [#166]

passed to passed to

passed to

passed to

passed to

passed to passed to passed to passed to

passed to

calls×2 [#220]

calls×2 [#234]

calls×2 [#235]

writes×2