test_redirect_put_without_body
httpclient_test.py:319

fetch
[closure inside test_multi_process]
process_test.py:96

calls [#1]

tornado.util.TimeoutError
Operation timed out after 5 seconds

loops(×26) raises (caught)

get_url
[closure inside test_multi_process]
process_test.py:61

calls [#2]

url
'http://127.0.0.1:46185/redirect?url=/put&status=307'

writes

get_async_test_timeout
Get the global timeout setting for async tests.
testing.py:64

calls [#5]

KeyError
b'ASYNC_TEST_TIMEOUT'

raises (caught)

run_sync

Starts the `IOLoop`, runs the given function, and stops…
ioloop.py:459

calls [#6]

future_cell
(5 writes, 4 distinct)
[None]
[<Future pending>]
[<Future pending cb=[IOLoop.add_future.<locals>.<lambda>() at /home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/iolo…
[<Future cancelled>]

writes

add_callback
[closure inside test_add_callback_return_sequence]
ioloop_test.py:37

calls×3 [#168]

time

Returns the current time according to the `IOLoop`'s cl…
ioloop.py:533

calls [#207]

add_timeout
Runs the ``callback`` at the time ``deadline`` from the…
ioloop.py:547

calls×2 [#177]

timeout_handle
(6 writes, 6 distinct)
<TimerHandle when=8183.954758374662 IOLoop._run_callback(functools.par...7c606ddbc4a0>))>
<TimerHandle when=11779.018564276546 IOLoop._run_callback(functools.par...7c606ddbde40>))>
<TimerHandle cancelled when=11779.018564276546>
<TimerHandle when=11779.14349955085 IOLoop._run_callback(functools.par...7c606ddbe0c0>))>
<TimerHandle cancelled when=11779.14349955085>
<TimerHandle cancelled when=8183.954758374662>

writes×3

start

Starts the mock S3 server on the given port at the give…
s3server.py:57

calls [#183]

_run_callback
simple_httpclient.py:529

calls×4 [#180]

ret

(7 writes, 2 distinct)
None
True

writes

result
(7 writes, 4 distinct)
<Future pending>
<Future pending cb=[IOLoop.add_future.<locals>.<lambda>() at /home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/ioloo…
[(<AddressFamily.AF_INET: 2>, ('127.0.0.1', 46185))]
None

writes×2

__getattr__
util.py:80

calls×44 [#71]

to_unicode
escape.py:203

calls [#170]

netloc
(2 writes)
'127.0.0.1:46185'

writes

split_host_and_port
Returns ``(host, port)`` tuple from ``netloc``.
httputil.py:1032

calls [#171]

host
(4 writes)
'127.0.0.1'

writes

port
(4 writes)
46185

writes

af
(4 writes, 2 distinct)
<AddressFamily.AF_UNSPEC: 0>
<AddressFamily.AF_INET: 2>

writes×2

_get_ssl_options
simple_httpclient.py:443

calls [#173]

ssl_options
(2 writes)
None

writes

source_ip
(2 writes)
None

writes

timeout
(9 writes, 8 distinct)
20.0
<TimerHandle cancelled when=8179.300517967836>
<TimerHandle cancelled when=8198.968204548015>
<TimerHandle cancelled when=11779.018564276546>
<TimerHandle cancelled when=8179.429670600625>
<TimerHandle cancelled when=8199.103976779621>
… +2 more values

writes

StopIteration
[(<AddressFamily.AF_INET: 2>, ('127.0.0.1', 46185))]

raises (caught)

addrinfo
(2 writes)
[(<AddressFamily.AF_INET: 2>, ('127.0.0.1', 46185))]

writes

__init__
options_test.py:20

calls×6 [#132]

connector

(2 writes, 2 distinct)
<tornado.tcpclient._Connector object at 0x7c606df388f0>
<tornado.tcpclient._Connector object at 0x7c606df3b440>

writes

_handle_events
caresresolver.py:48

calls×5 [#116]

stream

(8 writes, 4 distinct)
<tornado.iostream.IOStream object at 0x7c606dda8bc0>
<tornado.iostream.IOStream object at 0x7c606dda8920>
<tornado.iostream.IOStream object at 0x7c606df0b860>
<tornado.iostream.IOStream object at 0x7c606df3bfe0>

writes×2

closed
Returns true if the stream has been closed.
iostream.py:667

calls×3 [#107]

_clear_callbacks
Clears the callback attributes.
http1connection.py:302

calls×2 [#148]

conn

(3 writes, 3 distinct)
<tornado.http1connection.HTTP1Connection object at 0x7c606df393d0>
<tornado.http1connection.HTTP1Connection object at 0x7c606df3b230>
<tornado.http1connection.HTTP1Connection object at 0x7c606df3bd40>

writes×2

start_request
routing_test.py:165

calls×2 [#162]

request_delegate
(3 writes, 3 distinct)
<tornado.routing._RoutingDelegate object at 0x7c606dda9850>
<tornado.routing._RoutingDelegate object at 0x7c606ddab320>
<tornado.routing._RoutingDelegate object at 0x7c606df38920>

writes×2

read_response
Read a single HTTP response.
http1connection.py:165

calls×4 [#114]

need_delegate_close
(10 writes, 2 distinct)
False
True

writes×9

read_until_regex
Asynchronously read until we have matched the given reg…
iostream.py:350

calls×2 [#165]

header_future
(9 writes, 3 distinct)
<Future pending>
<Future pending cb=[chain_future.<locals>.copy() at /home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/concurrent.py:…
None

writes×7

with_timeout
Wraps a `.Future` (or other yieldable object) in a time…
gen.py:547

calls [#208]

on_connect_done
tcpclient.py:134

calls [#209]

remove_timeout
asyncio.py:167

calls×3 [#128]

addr
(2 writes)
('127.0.0.1', 46185)

writes

set_close_callback
Sets a callback that will be run when the connection is…
http1connection.py:314

calls×2 [#142]

_remove_timeout
simple_httpclient.py:222

calls [#215]

key
(4 writes, 2 distinct)
'proxy_host'
'proxy_auth_mode'

writes×3

headers
httpclient.py:546

writes×3 __getitem__ options.py:160

calls×4 [#74]

__setitem__
options.py:163

calls×5 [#77]

username

(2 writes)
None

writes×2

password
(2 writes)
None

writes×2

req_path
(2 writes, 2 distinct)
'/redirect?url=/put&status=307'
'/put'

writes×2

_create_connection
simple_httpclient.py:493

calls×2 [#96]

start_line
(7 writes, 7 distinct)
RequestStartLine(method='PUT', path='/redirect?url=/put&status=307', version='')
'PUT /redirect?url=/put&status=307 HTTP/1.1'
RequestStartLine(method='PUT', path='/redirect?url=/put&status=307', version='HTTP/1.1')
ResponseStartLine(version='HTTP/1.1', code=307, reason='Temporary Redirect')
RequestStartLine(method='PUT', path='/put', version='')
'PUT /put HTTP/1.1'
… +1 more values

writes×5

write_headers
Implements `.HTTPConnection.write_headers`.
http1connection.py:376

calls×2 [#104]

lines
(6 writes, 5 distinct)
[]
[b'PUT /redirect?url=/put&status=307 HTTP/1.1']
[b'PUT /redirect?url=/put&status=307 HTTP/1.1', b'Connection: close', b'Host: 127.0.0.1:46185', b'Accept-Encoding: gzip'…
[b'PUT /put HTTP/1.1']
[b'PUT /put HTTP/1.1', b'Connection: close', b'Accept-Encoding: gzip', b'Transfer-Encoding: chunked', b'Host: 127.0.0.1:…

writes×2

l
(4 writes, 3 distinct)
'Connection: close'
'Transfer-Encoding: chunked'
'Host: 127.0.0.1:46185'

writes×2

line
(4 writes, 4 distinct)
bytes(len=42)
bytes(len=26)
b'PUT /put HTTP/1.1'
bytes(len=21)

writes×4

data
(2 writes, 2 distinct)
bytes(len=139)
bytes(len=114)

writes×2

write
runtests.py:106

calls×2 [#108]

future_add_done_callback
concurrent.py:235

calls×2 [#109]

finish
[closure inside find_handler]
routing_test.py:40

calls×3 [#113]

_on_write_complete
http1connection.py:530

calls [#115]

copy

[closure inside chain_future]
concurrent.py:154

calls×2 [#127]

header_data
(3 writes, 3 distinct)
bytes(len=139)
bytes(len=222)
bytes(len=114)

writes×3

_parse_headers
http1connection.py:574

calls×2 [#129]

start_line_str
(3 writes, 3 distinct)
'PUT /redirect?url=/put&status=307 HTTP/1.1'
'HTTP/1.1 307 Temporary Redirect'
'PUT /put HTTP/1.1'

writes×3

parse_request_start_line
Returns a (method, path, version) tuple for an HTTP 1.x…
httputil.py:892

calls×2 [#130]

req_start_line
(2 writes, 2 distinct)
RequestStartLine(method='PUT', path='/redirect?url=/put&status=307', version='HTTP/1.1')
RequestStartLine(method='PUT', path='/put', version='HTTP/1.1')

writes×2

_can_keep_alive
http1connection.py:543

calls×2 [#131]

__enter__
http1connection.py:56

calls×3 [#133]

headers_received
[closure inside test_http10_no_content_length]
http1connection_test.py:46

calls×2 [#134]

header_recv_future
(3 writes, 2 distinct)
None

<coroutine object _HTTPConnection.headers_received at 0x7c606ddedd40>

writes×3

__exit__
http1connection.py:59

calls×3 [#135]

skip_body
(3 writes)
False

writes×3

_read_body
http1connection.py:586

calls×2 [#136]

body_future
(3 writes, 2 distinct)
<coroutine object HTTP1Connection._read_chunked_body at 0x7c606df779a0>
<coroutine object HTTP1Connection._read_fixed_body at 0x7c606ddeed40>

writes×3

total_size
(2 writes)
0

writes×2

chunk_len_str
b'0

'

writes

chunk_len
0

writes

crlf
b'

'

writes

prepare

httpclient_test.py:60

calls [#143]

tornado.iostream.StreamClosedError
Stream is closed

raises (caught)

on_close
websocket_test.py:55

calls [#167] resp_start_line

ResponseStartLine(version='HTTP/1.1', code=307, reason='Temporary Redirect')

writes

code
307

writes raises (caught)

get_protocol
testing.py:453

calls [#3]

get_http_port
Returns the port used by the server.
testing.py:446

calls [#4]

is_future
concurrent.py:52

passed to

redirect
Sends a redirect to the given (optionally relative) URL…
web.py:791

passed to

raises (caught)

env

None

writes

writes

run

<function IOLoop.run_sync.<locals>.run at 0x7c606ddbc0e0>

writes

calls [#7]

timeout_callback
(3 writes, 3 distinct)
<function IOLoop.run_sync.<locals>.timeout_callback at 0x7c606ddbc4a0>
<function with_timeout.<locals>.timeout_callback at 0x7c606ddbde40>
<function with_timeout.<locals>.timeout_callback at 0x7c606ddbe0c0>

writes

calls [#9] calls [#8]

writes

calls [#12]

passed to

passed to

writes×2

writes×2

convert_yielded
<function convert_yielded at 0x7c606df940e0>

calls [#18] writes

add_future
Schedules a callback on the ``IOLoop`` when the given
ioloop.py:664

calls [#19]

call_soon
(4 writes, 2 distinct)
<bound method BaseEventLoop.call_soon_threadsafe of <_UnixSelectorEventLoop running=False closed=False debug=False>>
<bound method BaseEventLoop.call_soon of <_UnixSelectorEventLoop running=True closed=False debug=False>>

writes×4

writes

call_at
asyncio.py:155

calls [#11] calls×5 [#10]

passed to

calls×2 [#28] calls [#55]

calls [#31]

old_loop
<_UnixSelectorEventLoop running=False closed=False debug=False>

writes

_setup_logging
The IOLoop catches and logs exceptions, so it's
ioloop.py:426

calls [#13]

calls×2 [#14]

writes

calls×9 [#20] calls [#21]

writes

calls [#22]

writes×2 writes writes

calls [#24]

raises (caught) writes writes writes writes

calls×2 [#30]

writes

calls×2 [#32]

writes×2

writes

calls [#51]

writes

calls [#53]

writes

calls [#54]

writes×2

calls [#56]

calls [#57]

writes

calls [#63] calls [#61]

writes

calls [#17]

calls [#282]

assign_thread_identity
[closure inside initialize]
asyncio.py:71

calls [#15] writes×6

stop
tcpclient_test.py:53

calls [#285]

passed to

calls×11 [#73]

body
httpclient.py:560

calls×2 [#89]

passed to passed to passed to passed to

match
(2 writes)
<re.Match object; span=(0, 15), match='127.0.0.1:46185'>

passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to writes×2 writes×2 writes×2 passed to passed to passed to passed to passed to passed to passed to

calls×3 [#50]

passed to

calls×5 [#38]

fileobj
(11 writes, 5 distinct)
<socket.socket fd=9, family=2, type=1, proto=6, laddr=('127.0.0.1', 46185)>
<socket.socket fd=10, family=2, type=1, proto=0, laddr=('127.0.0.1', 36240), raddr=('127.0.0.1', 46185)>
<socket.socket fd=11, family=2, type=1, proto=6, laddr=('127.0.0.1', 46185), raddr=('127.0.0.1', 36240)>
<socket.socket fd=10, family=2, type=1, proto=0, laddr=('127.0.0.1', 36250), raddr=('127.0.0.1', 46185)>
<socket.socket fd=11, family=2, type=1, proto=6, laddr=('127.0.0.1', 46185), raddr=('127.0.0.1', 36250)>

writes×7

handler_func
(7 writes, 5 distinct)
<function add_accept_handler.<locals>.accept_handler at 0x7c606dddfb00>
<bound method BaseIOStream._handle_events of <tornado.iostream.IOStream object at 0x7c606dda8920>>
<bound method BaseIOStream._handle_events of <tornado.iostream.IOStream object at 0x7c606dda8bc0>>
<bound method BaseIOStream._handle_events of <tornado.iostream.IOStream object at 0x7c606df3bfe0>>
<bound method BaseIOStream._handle_events of <tornado.iostream.IOStream object at 0x7c606df0b860>>

writes×7

accept_handler
[closure inside add_accept_handler]
netutil.py:243

calls×2 [#33]

calls×20 [#39]

_handle_connect
iostream.py:686

calls×2 [#40]

_handle_write
iostream.py:947

calls×2 [#43]

state

(8 writes, 2 distinct)
24
25

writes×8

reading
Returns true if we are currently reading from the strea…
iostream.py:659

calls×5 [#45]

writing
Returns true if we are currently writing to the stream.
iostream.py:663

calls×5 [#46]

fileno
ioloop.py:66

calls×4 [#47]

update_handler
asyncio.py:105

calls×4 [#48]

_handle_read
iostream.py:783

calls×3 [#120]

i
(4 writes, 2 distinct)
0
1

writes×4

connection
(4 writes, 4 distinct)
<socket.socket fd=11, family=2, type=1, proto=6, laddr=('127.0.0.1', 46185), raddr=('127.0.0.1', 36240)>
<tornado.http1connection.HTTP1Connection object at 0x7c606ddaa8a0>
<socket.socket fd=11, family=2, type=1, proto=6, laddr=('127.0.0.1', 46185), raddr=('127.0.0.1', 36250)>
<tornado.http1connection.HTTP1Connection object at 0x7c606ddad640>

writes×2

address
(2 writes, 2 distinct)
('127.0.0.1', 36240)
('127.0.0.1', 36250)

writes×2

set_close_exec
windows.py:19

calls×2 [#34]

_handle_connection
tcpserver.py:274

calls×2 [#35] BlockingIOError

[Errno 11] Resource temporarily unavailable

raises (caught)

e

(2 writes)
BlockingIOError(11, 'Resource temporarily unavailable')

writes×2

errno_from_exception
Provides the errno from an Exception object.
util.py:188

calls×2 [#36]

passed to passed to

flags
(2 writes)
1

writes×2 writes×2

passed to passed to passed to

passed to

err

(2 writes)
0

writes×2

size
(2 writes)
0

writes×4 writes×2

fd
(4 writes, 2 distinct)
10
11

writes×4

passed to

passed to

passed to passed to

passed to passed to passed to

calls×3 [#52]

delegate
(5 writes, 5 distinct)
<tornado.routing._RoutingDelegate object at 0x7c606dda9850>
<tornado.http1connection._GzipMessageDelegate object at 0x7c606df39280>
<tornado.routing._RoutingDelegate object at 0x7c606ddab320>
<tornado.routing._RoutingDelegate object at 0x7c606df38920>
<tornado.http1connection._GzipMessageDelegate object at 0x7c606ddab440>

passed to passed to passed to writes×2 writes×3 passed to passed to raises (caught) passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to

writes×2

writes×2

writes×2

future_converted
(6 writes, 3 distinct)
<Future pending>
<Future pending cb=[chain_future.<locals>.copy() at /home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/concurrent.py:…
<Future pending cb=[chain_future.<locals>.copy() at /home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/concurrent.py:…

writes×6

io_loop
(2 writes)
<tornado.platform.asyncio.AsyncIOLoop object at 0x7c606effe120>

writes×2

error_callback
(2 writes, 2 distinct)
<function with_timeout.<locals>.error_callback at 0x7c606ddbdd00>
<function with_timeout.<locals>.error_callback at 0x7c606ddbe700>

writes×2 passed to

writes×2

clear_timeouts
tcpclient.py:192

calls×2 [#58]

close_streams
tcpclient.py:198

calls×2 [#59] calls×2 [#60]

writes×7 passed to

_maybe_add_error_listener
iostream.py:1011

calls×2 [#62]

calls×2 [#64]

passed to passed to passed to passed to

__missing__
httputil.py:87

passed to

passed to

passed to passed to passed to passed to passed to

raises (caught)

norm_name
(6 writes, 4 distinct)
'Connection'
'Host'

'Accept-Encoding'
'Transfer-Encoding'

writes×6

calls [#95]

passed to passed to

w

(2 writes, 2 distinct)
'Accept'
'Encoding'

writes×2

normalized
'Accept-Encoding'

writes

self
{'Connection': 'Connection', 'Host': 'Host', 'Accept-Encoding': 'Accept-Encoding'}

writes

passed to

passed to

passed to passed to

passed to

passed to passed to passed to passed to passed to passed to

passed to

passed to

passed to passed to passed to passed to passed to passed to

passed to passed to passed to passed to passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to passed to

passed to

passed to

set_nodelay
Set the no-delay flag for this stream.
websocket.py:547

passed to

passed to passed to passed to passed to

passed to

passed to passed to passed to passed to passed to passed to passed to

get_argument
web.py:424

passed to passed to

passed to

passed to

calls×4 [#99] calls×2 [#98] passed to

writes×2

calls×2 [#97]

passed to passed to passed to passed to passed to raises (caught)

calls [#106]

writes×4

utf8
escape.py:172

calls×2 [#105]

header_lines
(2 writes, 2 distinct)
<generator object HTTP1Connection.write_headers.<locals>.<genexpr> at 0x7c606ddf3ca0>
<generator object HTTP1Connection.write_headers.<locals>.<genexpr> at 0x7c606dc74120>

writes×2 writes×2 passed to

passed to passed to passed to

chunk
bytes(len=29)

writes

exc

None

writes

pos
(3 writes, 3 distinct)
139
222
114

writes×3

b
(2 writes, 2 distinct)
<Future finished result=b'PUT /redire...unked

'>

<Future finished result=b'PUT /put HT...46185

'>

writes×2 passed to

passed to

writes×2

writes×2

data_str
(2 writes, 2 distinct)
'PUT /redirect?url=/put&status=307 HTTP/1.1

Connection: close

Host: 127.0.0.1:46185

Accept-Encoding: gzip

Tr…
'PUT /put HTTP/1.1

Connection: close

Accept-Encoding: gzip

Transfer-Encoding: chunked

Host: 127.0.0.1:46185…

writes×2

eol
(2 writes, 2 distinct)
43
18

writes×2

passed to

method
(2 writes)
'PUT'

writes×2

path
(2 writes, 2 distinct)
'/redirect?url=/put&status=307'
'/put'

writes×2

version
(2 writes)
'HTTP/1.1'

passed to passed to passed to writes×2

passed to

connection_header
(2 writes)
'close'

writes×2

request
(2 writes, 2 distinct)
HTTPServerRequest(protocol='http', host='127.0.0.1:46185', method='PUT', uri='/redirect?url=/put&status=307', version='H…
HTTPServerRequest(protocol='http', host='127.0.0.1:46185', method='PUT', uri='/put', version='HTTP/1.1', remote_ip='127.…

writes×2

passed to passed to

content_length
(2 writes)
None

writes×2

calls [#144] passed to

calls [#147] calls×2 [#145]

passed to

passed to