test_static_with_range_neg_past_start
web_test.py:1287

get_and_head
Performs a GET and HEAD request and returns the GET res…
web_test.py:1140

calls [#1]

loops(×11)

fetch
[closure inside test_multi_process]
process_test.py:96

calls [#2]

KeyError
b'ASYNC_TEST_TIMEOUT'

raises (caught)

timeout_handle
(3 writes, 3 distinct)
<TimerHandle when=8274.819843643752 IOLoop._run_callback(functools.par...773dd783da80>))>
<TimerHandle cancelled when=11869.873502215158>
<TimerHandle when=8274.977782545513 IOLoop._run_callback(functools.par...773dd783d760>))>

writes

result
(6 writes, 4 distinct)
<Future pending>
<Future pending cb=[IOLoop.add_future.<locals>.<lambda>() at /home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/ioloo…
None

<coroutine object StaticFileHandler.get at 0x773dd79fb380>

writes×2

__getattr__
util.py:80

calls×19 [#44]

StopIteration
[(<AddressFamily.AF_INET: 2>, ('127.0.0.1', 36233))]

raises (caught)

_handle_events
caresresolver.py:48

calls [#68]

need_delegate_close
(4 writes, 2 distinct)
False
True

writes×2

key
(3 writes, 2 distinct)
'network_interface'
'proxy_auth_mode'

writes

__setitem__
options.py:163

calls×3 [#47]

username

None

writes

password
None

writes

body_expected
False

writes

body_present
False

writes

req_path
'/static/robots.txt'

writes

_create_connection
simple_httpclient.py:478

calls [#63]

start_line
(2 writes, 2 distinct)
RequestStartLine(method='HEAD', path='/static/robots.txt', version='')
RequestStartLine(method='HEAD', path='/static/robots.txt', version='HTTP/1.1')

writes×2

write_headers
Implements `.HTTPConnection.write_headers`.
http1connection.py:376

calls [#66]

future
(6 writes, 4 distinct)
None

<Future pending>
<Future finished result=None>
<Future finished result=HTTPResponse(...,time_info={})>

writes×3

data
bytes(len=124)

writes

copy

[closure inside chain_future]
concurrent.py:154

calls [#70]

remove_timeout
asyncio.py:167

calls [#71]

header_data
bytes(len=124)

writes

start_line_str
'HEAD /static/robots.txt HTTP/1.1'

writes

headers
<tornado.httputil.HTTPHeaders object at 0x773dd7855ac0>

writes

req_start_line
RequestStartLine(method='HEAD', path='/static/robots.txt', version='HTTP/1.1')

writes

header_recv_future
None

writes

skip_body
False

writes

body_future
None

writes

decode_argument
Decodes an argument from the request.
web.py:559

calls [#72]

arg
b'robots.txt'

writes

prepare

httpclient_test.py:56

calls [#73]

_has_stream_request_body
web.py:1856

calls [#74]

method
<bound method StaticFileHandler.head of <tornado.web.StaticFileHandler object at 0x773dd7992360>>

writes

head
simple_httpclient_test.py:84

calls [#75]

absolute_path
'/home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/test/static/robots.txt'

writes

get_url
[closure inside test_multi_process]
process_test.py:61

calls×2 [#3]

url
(2 writes)
'http://127.0.0.1:36233/static/robots.txt'

writes×2

get_async_test_timeout
Get the global timeout setting for async tests.
testing.py:63

calls×2 [#6]

run_sync

Starts the `IOLoop`, runs the given function, and stops…
ioloop.py:463

calls×2 [#7]

handle_response
[closure inside fetch]
httpclient.py:290

defines

get_protocol
testing.py:422

calls×2 [#4]

get_http_port
Returns the port used by the server.
testing.py:415

calls×2 [#5]

raises (caught)

env

(2 writes)
None

writes×2

future_cell
(6 writes, 3 distinct)
[None]
[<Future pending>]
[<Future pending cb=[IOLoop.add_future.<locals>.<lambda>() at /home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/iolo…

writes×2

run

(2 writes, 2 distinct)
<function IOLoop.run_sync.<locals>.run at 0x773dd783d760>
<function IOLoop.run_sync.<locals>.run at 0x773dd783e200>

writes×2

add_callback
[closure inside test_add_callback_return_sequence]
ioloop_test.py:37

calls×2 [#8]

timeout_callback
(2 writes, 2 distinct)
<function IOLoop.run_sync.<locals>.timeout_callback at 0x773dd783da80>
<function IOLoop.run_sync.<locals>.timeout_callback at 0x773dd783d760>

writes×2

time

Returns the current time according to the `IOLoop`'s cl…
ioloop.py:537

calls×2 [#9]

add_timeout
Runs the ``callback`` at the time ``deadline`` from the…
ioloop.py:552

calls×2 [#10]

writes×2

start

Starts the mock S3 server on the given port at the give…
s3server.py:57

calls×2 [#13] writes×4 passed to

writes×4

convert_yielded
(2 writes)
<function convert_yielded at 0x773dd804d080>

writes×2

call_soon
(8 writes, 3 distinct)
<bound method BaseEventLoop.call_soon_threadsafe of <_UnixSelectorEventLoop running=False closed=False debug=False>>
<bound method BaseEventLoop.call_soon of <_UnixSelectorEventLoop running=True closed=False debug=False>>
<bound method BaseEventLoop.call_soon of <_UnixSelectorEventLoop running=False closed=False debug=False>>

writes×8

call_at
asyncio.py:155

calls×2 [#11] calls×2 [#12]

passed to

calls×4 [#26]

old_loop
(2 writes)
<_UnixSelectorEventLoop running=False closed=False debug=False>

writes×2

_setup_logging
The IOLoop catches and logs exceptions, so it's
ioloop.py:430

calls×2 [#14]

_run_callback
simple_httpclient.py:514

calls×3 [#15] calls×16 [#19]

to_unicode
escape.py:200

calls×2 [#20]

netloc
(2 writes)
'127.0.0.1:36233'

writes×2

split_host_and_port
Returns ``(host, port)`` tuple from ``netloc``.
httputil.py:1032

calls×2 [#21]

host
(4 writes)
'127.0.0.1'

writes×2

port
(4 writes)
36233

writes×2

af
(4 writes, 2 distinct)
<AddressFamily.AF_UNSPEC: 0>
<AddressFamily.AF_INET: 2>

writes×4

_get_ssl_options
simple_httpclient.py:428

calls×2 [#23]

ssl_options
(2 writes)
None

writes×2

timeout
(6 writes, 5 distinct)
20.0
<TimerHandle cancelled when=11869.873502215158>
<TimerHandle cancelled when=8274.819843643752>
<TimerHandle cancelled when=11870.011352627738>
<TimerHandle cancelled when=8274.977782545513>

writes×2 raises (caught)

addrinfo
(2 writes)
[(<AddressFamily.AF_INET: 2>, ('127.0.0.1', 36233))]

writes×2

connector

(2 writes, 2 distinct)
<tornado.tcpclient._Connector object at 0x773dd7856b70>
<tornado.tcpclient._Connector object at 0x773dd784ecf0>

writes×2

calls×4 [#27]

__init__
options_test.py:20

calls×2 [#31]

conn

(2 writes, 2 distinct)
<tornado.http1connection.HTTP1Connection object at 0x773dd7854050>
<tornado.http1connection.HTTP1Connection object at 0x773dd784ef90>

writes×2

start_request
routing_test.py:165

calls×2 [#32]

request_delegate
(2 writes, 2 distinct)
<tornado.routing._RoutingDelegate object at 0x773dd784efc0>
<tornado.routing._RoutingDelegate object at 0x773dd7857e60>

writes×2

read_response
Read a single HTTP response.
http1connection.py:165

calls×2 [#33]

writes×2

header_future
(4 writes, 2 distinct)
<Future pending>
<Future pending cb=[chain_future.<locals>.copy() at /home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/concurrent.py:…

writes×4

on_connect_done
tcpclient.py:134

calls×2 [#34]

stream

(6 writes, 2 distinct)
<tornado.iostream.IOStream object at 0x773dd78548f0>
<tornado.iostream.IOStream object at 0x773dd78b1010>

writes×4

addr
(2 writes)
('127.0.0.1', 36233)

writes×2

set_close_callback
Sets a callback that will be run when the connection is…
http1connection.py:314

calls×2 [#37]

_remove_timeout
simple_httpclient.py:217

calls×2 [#38]

writes×2

calls×2 [#18]

assign_thread_identity
[closure inside initialize]
asyncio.py:71

calls [#16]

ret

(11 writes)
None

passed to writes×11 calls×2 [#77]

passed to

passed to

passed to

passed to

match
(2 writes)
<re.Match object; span=(0, 15), match='127.0.0.1:36233'>

writes×2

writes×2 writes×2

passed to passed to

passed to

passed to passed to

passed to

passed to passed to

passed to passed to

passed to passed to

passed to

passed to

passed to passed to

passed to

passed to

passed to passed to

calls×6 [#30]

fileobj
(8 writes, 5 distinct)
<socket.socket fd=9, family=2, type=1, proto=6, laddr=('127.0.0.1', 36233)>
<socket.socket fd=10, family=2, type=1, proto=0, laddr=('127.0.0.1', 48504), raddr=('127.0.0.1', 36233)>
<socket.socket fd=11, family=2, type=1, proto=6, laddr=('127.0.0.1', 36233), raddr=('127.0.0.1', 48504)>
<socket.socket fd=10, family=2, type=1, proto=0, laddr=('127.0.0.1', 48514), raddr=('127.0.0.1', 36233)>
<socket.socket fd=11, family=2, type=1, proto=6, laddr=('127.0.0.1', 36233), raddr=('127.0.0.1', 48514)>

writes×8

handler_func
(8 writes, 5 distinct)
<function add_accept_handler.<locals>.accept_handler at 0x773dd783d080>
<bound method BaseIOStream._handle_events of <tornado.iostream.IOStream object at 0x773dd78548f0>>
<bound method BaseIOStream._handle_events of <tornado.iostream.IOStream object at 0x773dd784ecf0>>
<bound method BaseIOStream._handle_events of <tornado.iostream.IOStream object at 0x773dd78b1010>>
<bound method BaseIOStream._handle_events of <tornado.iostream.IOStream object at 0x773dd784f800>>

writes×8

accept_handler
[closure inside add_accept_handler]
netutil.py:243

calls×2 [#28]

state

(11 writes, 2 distinct)
24
25

writes×11

i
(4 writes, 2 distinct)
0
1

writes×4

connection
(4 writes, 4 distinct)
<socket.socket fd=11, family=2, type=1, proto=6, laddr=('127.0.0.1', 36233), raddr=('127.0.0.1', 48504)>
<tornado.http1connection.HTTP1Connection object at 0x773dd78298e0>
<socket.socket fd=11, family=2, type=1, proto=6, laddr=('127.0.0.1', 36233), raddr=('127.0.0.1', 48514)>
<tornado.http1connection.HTTP1Connection object at 0x773dd7829dc0>

writes×2

address
(2 writes, 2 distinct)
('127.0.0.1', 48504)
('127.0.0.1', 48514)

writes×2

BlockingIOError
[Errno 11] Resource temporarily unavailable

raises (caught)

e

(2 writes)
BlockingIOError(11, 'Resource temporarily unavailable')

writes×2

_handle_request_exception
web.py:1746

passed to passed to passed to passed to

delegate
(4 writes, 4 distinct)
<tornado.routing._RoutingDelegate object at 0x773dd784efc0>
<tornado.routing._RoutingDelegate object at 0x773dd7857d70>
<tornado.routing._RoutingDelegate object at 0x773dd7857e60>
<tornado.routing._RoutingDelegate object at 0x773dd78b1f70>

passed to passed to writes×4 passed to

passed to

passed to

on_close
websocket_test.py:52

passed to

passed to passed to passed to passed to passed to passed to passed to

writes×2 clear_timeouts
tcpclient.py:192

calls×2 [#35]

close_streams
tcpclient.py:198

calls×2 [#36]

passed to passed to passed to

passed to

passed to

passed to passed to

__getitem__
options.py:160

passed to

norm_name
(6 writes, 3 distinct)
'Connection'
'Host'

'Accept-Encoding'

writes×6

passed to passed to passed to passed to passed to

writes×2

passed to passed to passed to

lines
(6 writes, 5 distinct)
[]
[b'HEAD /static/robots.txt HTTP/1.1']
[b'HEAD /static/robots.txt HTTP/1.1', b'Range: bytes=-1000000', b'Connection: close', b'Host: 127.0.0.1:36233', b'Accept…
[b'GET /static/robots.txt HTTP/1.1']
[b'GET /static/robots.txt HTTP/1.1', b'Range: bytes=-1000000', b'Connection: close', b'Host: 127.0.0.1:36233', b'Accept-…

writes×6

header_lines
(2 writes, 2 distinct)
<generator object HTTP1Connection.write_headers.<locals>.<genexpr> at 0x773dd8559700>
<generator object HTTP1Connection.write_headers.<locals>.<genexpr> at 0x773dd78c3e60>

writes×2

line
(2 writes, 2 distinct)
bytes(len=32)
bytes(len=31)

writes×2

passed to

passed to

passed to passed to

passed to

b
(2 writes, 2 distinct)
<Future finished result=b'HEAD /stati... gzip

'>

<Future finished result=b'GET /static... gzip

'>

passed to writes×2

writes×4

passed to passed to passed to passed to passed to passed to passed to passed to passed to

finish
[closure inside find_handler]
routing_test.py:40

writes

writes×2

__iter__
options.py:153