test_missing_websocket_key
websocket_test.py:200

fetch

Executes a request, returning an `HTTPResponse`.
httpclient.py:94

calls [#1]

calls [#5]

get_url
[closure inside test_multi_process]
process_test.py:73

calls [#2]

__init__
stack_context_test.py:18

calls×4 [#6]

headers
httpclient.py:475

calls×2 [#18]

wrap

Returns a callable object that will restore the current…
stack_context.py:255

calls [#29]

request
(4 writes, 2 distinct)
<tornado.httpclient.HTTPRequest object at 0x7f423f1cb650>
<tornado.httpclient._RequestProxy object at 0x7f423f1cba70>

writes×2

future
(6 writes, 4 distinct)
<tornado.concurrent.Future object at 0x7f423f013f20>
<tornado.concurrent.Future object at 0x7f423f0796a0>
<tornado.concurrent.Future object at 0x7f423f079b80>
None

writes

callback
(6 writes, 5 distinct)
<function wrap.<locals>.wrapped at 0x7f423ef0c720>
<function AsyncHTTPClient.fetch.<locals>.handle_response at 0x7f423ef0ca40>
<bound method _HTTPConnection._on_connect of <tornado.simple_httpclient._HTTPConnection object at 0x7f423f0357f0>>
<function wrap.<locals>.wrapped at 0x7f423ef0d760>
None

writes

handle_future
<function AsyncHTTPClient.fetch.<locals>.handle_future at 0x7f423ef0c900>

writes

add_done_callback
Attaches the given callback to the `Future`.
concurrent.py:259

calls [#30]

handle_response
<function AsyncHTTPClient.fetch.<locals>.handle_response at 0x7f423ef0ca40>

writes

fetch_impl
curl_httpclient.py:83

calls [#31]

wait

Wait for `.notify`.
locks.py:116

calls [#69]

get_protocol
testing.py:405

calls [#3]

get_http_port
Returns the port used by the server.
testing.py:398

calls [#4]

calls [#40]

calls [#7]

body
httpclient.py:486

calls [#8]

body_producer
[closure inside test_100_continue_early_response]
simple_httpclient_test.py:451

calls [#10]

calls [#49]

streaming_callback
[closure inside test_streaming_callback]
iostream_test.py:290

calls [#12]

header_callback
[closure inside test_header_callback]
httpclient_test.py:319

calls [#14]

prepare_curl_callback
httpclient.py:518

calls [#16]

key
(5 writes, 4 distinct)
'Connection'

'Upgrade'
'Sec-WebSocket-Version'
<object object at 0x7f4240ad4e90>

writes×3 __setitem__
options.py:143

calls×3 [#20]

__enter__
http1connection.py:49

calls [#41]

current

Returns the current thread's `IOLoop`.
ioloop.py:228

calls×2 [#38]

time

ioloop_test.py:45

calls [#39]

__getattr__
util.py:100

calls×4 [#42]

to_unicode
Converts a string argument to a unicode string.
escape.py:206

calls [#43]

netloc
'localhost:35979'

writes

split_host_and_port
Returns ``(host, port)`` tuple from ``netloc``.
httputil.py:927

calls [#44]

host
(2 writes)
'localhost'

writes

port
(2 writes)
35979

writes

af
<AddressFamily.AF_UNSPEC: 0>

writes

_get_ssl_options
simple_httpclient.py:248

calls [#46]

ssl_options
None

writes

timeout
(4 writes, 4 distinct)
20.0
5
<TimerHandle cancelled when=8398.065403015951>
<TimerHandle cancelled when=8398.173423078719>

writes

add_timeout
twisted.py:488

calls [#50]

wrapper
[closure inside administrator]
blog.py:43

calls [#54]

handle_yield
gen.py:1098

calls [#65]

gen
(2 writes, 2 distinct)
None

<module 'tornado.gen' from '/home/shashwat/BTP/BugsInPy/workspace/tornado/tornado/gen.py'>

writes

result_future
None

writes

first_yielded
None

writes

run

benchmark.py:66

calls [#66]

__exit__
http1connection.py:52

calls [#67]

utf8
Converts a string argument to a byte string.
escape.py:187

calls [#9]

calls [#11]

cap_contexts
(6 writes, 2 distinct)
[((), <tornado.stack_context.ExceptionStackContext object at 0x7f423f1a8380>)]
[((), <tornado.stack_context.ExceptionStackContext object at 0x7f423f0365a0>)]

writes×6

wrapped
(6 writes, 6 distinct)
<function wrap.<locals>.wrapped at 0x7f423ef0c720>
<function wrap.<locals>.wrapped at 0x7f423ef0d3a0>
<function wrap.<locals>.wrapped at 0x7f423ef0d760>
<function wrap.<locals>.wrapped at 0x7f423ef0de40>
<function wrap.<locals>.wrapped at 0x7f423ef0c0e0>
<function wrap.<locals>.wrapped at 0x7f423ef0c180>

writes×6

null_wrapper
[closure inside wrap]
stack_context.py:273

defines

calls [#13] calls [#15] calls [#17]

passed to passed to

_handle_request
simple_httpclient.py:154

passed to

__missing__
httputil.py:90

passed to

_remove_timeout
simple_httpclient.py:164

passed to

passed to

run_sync

Starts the `IOLoop`, runs the given function, and stops…
ioloop.py:444

passed to

calls×3 [#21]

norm_name
(3 writes, 3 distinct)
'Connection'

'Upgrade'
'Sec-Websocket-Version'

writes×3

w

(5 writes, 5 distinct)
'Connection'
'Upgrade'
'Sec'
'WebSocket'
'Version'

writes×5

normalized
(3 writes, 3 distinct)
'Connection'
'Upgrade'
'Sec-Websocket-Version'

writes×3

self
(3 writes, 3 distinct)
{'Connection': 'Connection'}
{'Connection': 'Connection', 'Upgrade': 'Upgrade'}
{'Connection': 'Connection', 'Upgrade': 'Upgrade', 'Sec-WebSocket-Version': 'Sec-Websocket-Version'}

writes×3

passed to passed to

passed to

passed to

passed to passed to

_process_queue
simple_httpclient.py:140

passed to

passed to passed to passed to

_connection_class
simple_httpclient.py:151

passed to

passed to

passed to passed to

passed to

call_at
asyncio.py:130

passed to

passed to

add_future
Schedules a callback on the ``IOLoop`` when the given
ioloop.py:626

passed to

result
(2 writes, 2 distinct)
<generator object TCPClient.connect at 0x7f423ef59fc0>
<tornado.concurrent.Future object at 0x7f423f07e5a0>

passed to

connect

[closure inside test_stop_in_callback]
tcpserver_test.py:93

passed to

passed to

passed to

passed to

passed to

start

Starts the mock S3 server on the given port at the give…
s3server.py:46

passed to

_setup_logging
The IOLoop catches and logs exceptions, so it's
ioloop.py:404

passed to

make_current
Makes this the `IOLoop` for the current thread.
ioloop.py:257

passed to

_handle_events
caresresolver.py:43

passed to

_run_callback
simple_httpclient.py:439

passed to

inner

[closure inside find_circular_references]
circlerefs.py:19

passed to

stop
tcpclient_test.py:50

passed to

remove_timeout
asyncio.py:138

passed to

__rethrow
testing.py:247

passed to

tearDown

locale_test.py:28

passed to remove_handler

asyncio.py:99

passed to

split_fd
Returns an (fd, obj) pair from an ``fd`` parameter.
ioloop.py:679

passed to

passed to

add_callback
[closure inside test_add_callback_return_sequence]
ioloop_test.py:85

passed to

done
Returns True if the future has finished running.
concurrent.py:215

passed to

_clear_tb_log
concurrent.py:219

passed to

_check_done
concurrent.py:317

passed to

close
select.py:35

passed to

passed to

passed to

passed to passed to

passed to

passed to

calls [#114]

calls [#151]

_remove_deactivated
Remove deactivated handlers from the chain
stack_context.py:229

calls×15 [#82]

contexts

(15 writes, 2 distinct)
((), <tornado.stack_context.ExceptionStackContext object at 0x7f423f1a8380>)
((), <tornado.stack_context.ExceptionStackContext object at 0x7f423f0365a0>)

writes×15

exc

(15 writes)
(None, None, None)

writes×15

top
(15 writes)
None

writes×15

last_ctx
(15 writes)
0

writes×15

stack
(15 writes)
()

writes×15

accept_handler
[closure inside add_accept_handler]
netutil.py:244

calls [#83]

calls [#122] calls×7 [#90]

passed to passed to

passed to

passed to

passed to

passed to

passed to

passed to

writes

timeout_handle
(4 writes, 3 distinct)
None

<TimerHandle when=8398.173423078719 IOLoop._run_callback(functools.par...7f423ef0c180>))>
<TimerHandle cancelled when=8398.173423078719>

writes

calls [#32]

writes

writes

writes

calls [#33] calls [#34] release_callback

functools.partial(<bound method SimpleAsyncHTTPClient._release_fetch of <tornado.simple_httpclient.SimpleAsyncHTTPClient…

writes

calls [#35] calls [#68]

writes

writes

writes

passed to

passed to

calls [#37]

calls [#36]

writes×5

request_attr
(4 writes, 2 distinct)
'http://localhost:35979/echo'
None

writes×4

passed to

match
<re.Match object; span=(0, 15), match='localhost:35979'>

writes writes writes

passed to passed to

passed to

passed to

passed to

passed to

passed to

passed to

passed to

calls×3 [#52] calls×3 [#51] calls×3 [#53]

calls×2 [#55]

writes×3

writes×2

calls [#56]

kwargs
{'af': <AddressFamily.AF_UNSPEC: 0>, 'ssl_options': None, 'max_buffer_size': 104857600}

writes

calls [#57]

writes

orig_stack_contexts
(2 writes)
((), <tornado.stack_context.ExceptionStackContext object at 0x7f423f0365a0>)

writes

calls [#61]

yielded
(3 writes, 3 distinct)
<tornado.concurrent.Future object at 0x7f423f079b80>
<tornado.concurrent.Future object at 0x7f423f0362d0>
None

writes×2

passed to

passed to

passed to

passed to

passed to

passed to

passed to

calls [#59]

writes

calls [#60]

is_future
concurrent.py:355

calls [#58]

calls [#162] calls [#62] calls [#163]

passed to

convert_yielded
Convert a yielded object into a `.Future`.
gen.py:1253

passed to

writes writes writes writes×2

exc_info
None

writes

value
[(<AddressFamily.AF_INET: 2>, ('127.0.0.1', 35979))]

writes

writes

future_cell
(3 writes, 2 distinct)
[None]
[<tornado.concurrent.Future object at 0x7f423f07e5a0>]

writes

passed to

passed to

passed to final_contexts

((), <tornado.stack_context.ExceptionStackContext object at 0x7f423f0365a0>)

writes

calls [#71]

writes

calls [#72]

get_async_test_timeout
Get the global timeout setting for async tests.
testing.py:92

calls [#70]

timeout_func
<function AsyncTestCase.wait.<locals>.timeout_func at 0x7f423ef0dd00>

writes

calls [#76] KeyError

b'ASYNC_TEST_TIMEOUT'

raises (caught)

TypeError
float() argument must be a string or a real number, not 'NoneType'

raises (caught)

calls×2 [#77]

old_current
(2 writes)
<tornado.platform.asyncio.AsyncIOLoop object at 0x7f423fc7f080>

writes×2 calls×2 [#78]

calls×3 [#79] calls×3 [#80] calls×7 [#87]

calls [#81]

fileobj
(7 writes, 4 distinct)
<socket.socket fd=6, family=2, type=1, proto=6, laddr=('127.0.0.1', 35979)>
<socket.socket fd=7, family=2, type=1, proto=0, laddr=('127.0.0.1', 34448), raddr=('127.0.0.1', 35979)>
<socket.socket fd=8, family=2, type=1, proto=6, laddr=('127.0.0.1', 35979), raddr=('127.0.0.1', 34448)>
<socket.socket [closed] fd=-1, family=2, type=1, proto=6>

writes×6

handler_func
(5 writes, 3 distinct)
<function wrap.<locals>.wrapped at 0x7f423ef0c180>
<function wrap.<locals>.null_wrapper at 0x7f423ef0d8a0>
<function wrap.<locals>.null_wrapper at 0x7f423ef0e520>

writes×5 calls×4 [#85]

state

(5 writes, 2 distinct)
24
25

writes×5

fd
(3 writes, 2 distinct)
<socket.socket [closed] fd=-1, family=2, type=1, proto=6>
6

writes

stack_contexts
(15 writes)
()

writes×15

head
(15 writes, 2 distinct)
<tornado.stack_context.ExceptionStackContext object at 0x7f423f1a8380>
<tornado.stack_context.ExceptionStackContext object at 0x7f423f0365a0>

writes×15

parent
(15 writes)
None

writes×15

passed to

i
(2 writes, 2 distinct)
0
1

writes×2

connection

<socket.socket fd=8, family=2, type=1, proto=6, laddr=('127.0.0.1', 35979), raddr=('127.0.0.1', 34448)>

writes

address
('127.0.0.1', 34448)

writes

BlockingIOError
[Errno 11] Resource temporarily unavailable

raises (caught)

e

BlockingIOError(11, 'Resource temporarily unavailable')

writes

calls×4 [#86]

args

(<socket.socket [closed] fd=-1, family=2, type=1, proto=6>, 1)

writes

calls×14 [#88]

writes

x

'gen'

calls [#117] writes

tornado.gen.BadYieldError
yielded unknown object True

raises (caught)

f
(7 writes)
None

writes×7

passed to

passed to

passed to

raises (caught)

passed to

passed to

passed to

passed to

passed to

writes passed to

sock
(2 writes, 2 distinct)
<socket.socket fd=6, family=2, type=1, proto=6, laddr=('127.0.0.1', 35979)>
<socket.socket [closed] fd=-1, family=2, type=1, proto=6>

writes×2

calls [#128]

writes×2

calls [#127] calls [#131]

calls [#172]

calls×2 [#126]

calls [#132] calls×2 [#164]

uninitialize
Removes the ``SIGCHLD`` handler.
process.py:325

calls [#169]

clear_current
Clears the `IOLoop` for the current thread.
ioloop.py:273

calls [#170]

passed to

writes writes

calls [#129]

calls [#130]

removed
[True]

writes

writes×2

calls [#135] calls [#136]

calls [#161]

writes

calls [#140]

calls [#159]

writes×2

calls [#160] calls [#133]

passed to

calls [#134]

calls×3 [#165]