test_do_not_override_ie_key_in_url_transparent
test_YoutubeDL.py:757

__init__
metadatafromtitle.py:9

calls×4 [#1]

ydl
<test.test_YoutubeDL.YDL object at 0x759b4e457e00>

writes

__module__
(4 writes, 2 distinct)
'test.test_YoutubeDL'
'youtube_dl.YoutubeDL'

writes×3

__qualname__
(4 writes, 4 distinct)
'TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo1IE'
'TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo2IE'
'TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo3IE'
'YoutubeDL.build_format_selector.<locals>.TokenIterator'

writes×3

_VALID_URL
(3 writes, 3 distinct)
'foo1:'
'foo2:'
'foo3:'

writes×3

_real_extract
(3 writes, 3 distinct)
<function TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo1IE._real_extract at 0x759b4cfeb560>
<function TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo2IE._real_extract at 0x759b4cfeb6a0>
<function TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo3IE._real_extract at 0x759b4cfeb880>

writes×3

Foo1IE

<class 'test.test_YoutubeDL.TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo1IE'>

writes

Foo2IE

<class 'test.test_YoutubeDL.TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo2IE'>

writes

Foo3IE

<class 'test.test_YoutubeDL.TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo3IE'>

writes

add_info_extractor
Add an InfoExtractor object to the end of the list.
YoutubeDL.py:436

calls×3 [#19]

extract_info
[closure inside _real_extract]
animeondemand.py:118

calls [#32]

downloaded
{'formats': [{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol':…

writes

AssertionError

'foo1_id' != 'testid'

raises

calls×3 [#2]

get_params
helper.py:24

calls [#3]

params
dict(len=41)

writes

check_deprecated
<function YoutubeDL.__init__.<locals>.check_deprecated at 0x759b4cfea0c0>

writes

_setup_opener
YoutubeDL.py:2220

calls [#10]

type
(7 writes, 6 distinct)
'http'
'https'
67
1
4
0

writes×2

register_socks_protocols
utils.py:71

calls [#16]

scheme
(2 writes, 2 distinct)
'socks'
'socks5'

writes

set_downloader
Sets the downloader for this PP.
common.py:37

calls×3 [#18]

sep
(6 writes)
'/'

writes×6

i
(3 writes, 2 distinct)
54
0

writes×2

head
(4 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test/'
'/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test'

writes×4

path
(7 writes, 4 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test'
'/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test/parameters.json'
'/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test/local_parameters.json'

''

writes×4

b
(2 writes, 2 distinct)
'parameters.json'
'local_parameters.json'

writes×2

PARAMETERS_FILE
'/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test/parameters.json'

writes

LOCAL_PARAMETERS_FILE
'/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test/local_parameters.json'

writes

pf
<_io.TextIOWrapper name='/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test/parameters.json' mode='r' encoding='utf-8…

writes

parameters
dict(len=41)

writes

FileNotFoundError

[Errno 2] No such file or directory: '/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test/local_parameters.json'

raises (caught)

passed to

passed to

make_HTTPS_handler
utils.py:681

passed to

calls×3 [#11]

timeout_val
20

writes

opts_cookiefile
None

writes

opts_proxy
None

writes

cookie_processor
<youtube_dl.utils.YoutubeDLCookieProcessor object at 0x759b4d229520>

writes

proxies
{}

writes

proxy_handler
<youtube_dl.utils.PerRequestProxyHandler object at 0x759b4f0fb710>

writes

debuglevel
0

calls [#13] writes

https_handler
<youtube_dl.utils.YoutubeDLHTTPSHandler object at 0x759b4d082ed0>

writes

ydlh
<youtube_dl.utils.YoutubeDLHandler object at 0x759b4d082960>

writes

data_handler
<urllib.request.DataHandler object at 0x759b4d414ce0>

writes

file_handler
<urllib.request.FileHandler object at 0x759b4d228fb0>

writes

file_open
<function YoutubeDL._setup_opener.<locals>.file_open at 0x759b4cfeb600>

writes

opener

<urllib.request.OpenerDirector object at 0x759b4d228da0>

writes

passed to

passed to

__next__
<function YoutubeDL.build_format_selector.<locals>.TokenIterator.__next__ at 0x759b4cee6160>

passed to

calls [#14]

opts_no_check_certificate
False

writes

context

<ssl.SSLContext object at 0x759b4ce94cd0>

writes

writes

defines

extract

[closure inside _real_extract]
ustudio.py:38

defines

_make_result
test_YoutubeDL.py:40

calls [#78]

calls×3 [#21]

ie_key
lazy_load_template.py:11

calls×3 [#20]

writes

calls×3 [#34]

loops(×99)

ies
(3 writes, 3 distinct)
[<test.test_YoutubeDL.TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo1IE object at 0x759b4e30b…
[<test.test_YoutubeDL.TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo2IE object at 0x759b4d61d…
[<test.test_YoutubeDL.TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo3IE object at 0x759b4d1fd…

writes×3

ie
(8 writes, 3 distinct)
<test.test_YoutubeDL.TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo1IE object at 0x759b4e30bd…
<test.test_YoutubeDL.TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo2IE object at 0x759b4d61d8…
<test.test_YoutubeDL.TestYoutubeDL.test_do_not_override_ie_key_in_url_transparent.<locals>.Foo3IE object at 0x759b4d1fda…

writes×3

suitable
tvanouvelles.py:47

calls×3 [#33]

get_info_extractor
Returns the info extractor class with the given ie_name
__init__.py:44

calls×5 [#35]

working
Getter method for _WORKING.
common.py:382

calls×3 [#36] calls×3 [#37]

ie_result
(13 writes, 7 distinct)
{'_type': 'url_transparent', 'url': 'foo2:', 'ie_key': 'Foo2', 'title': 'foo1 title', 'id': 'foo1_id'}
{'_type': 'url_transparent', 'url': 'foo2:', 'ie_key': 'Foo2', 'title': 'foo1 title', 'id': 'foo1_id', 'extractor': 'Foo…
{'_type': 'url', 'url': 'foo3:', 'ie_key': 'Foo3'}
{'_type': 'url', 'url': 'foo3:', 'ie_key': 'Foo3', 'extractor': 'Foo2', 'webpage_url': 'foo2:', 'webpage_url_basename': …
{'formats': [{'url': 'http://localhost/sample.mp4'}], 'id': 'testid', 'title': 'foo3 title', 'extractor': 'testex', 'ext…
{'formats': [{'url': 'http://localhost/sample.mp4'}], 'id': 'testid', 'title': 'foo3 title', 'extractor': 'testex', 'ext…
… +1 more values

writes×10

add_default_extra_info
YoutubeDL.py:812

calls×3 [#42]

key
(6 writes, 2 distinct)
'extractor'

'extractor_key'

writes×3

value
(7 writes, 4 distinct)
'Foo1'
'Foo2'
'Foo3'
(1, 'best', (1, 0), (1, 4), None)

writes×3

info_dict
(14 writes, 14 distinct)
{'_type': 'url_transparent', 'url': 'foo2:', 'ie_key': 'Foo2', 'title': 'foo1 title', 'id': 'foo1_id', 'extractor': 'Foo…
{'_type': 'url_transparent', 'url': 'foo2:', 'ie_key': 'Foo2', 'title': 'foo1 title', 'id': 'foo1_id', 'extractor': 'Foo…
{'_type': 'url', 'url': 'foo3:', 'ie_key': 'Foo3', 'extractor': 'Foo2'}
{'_type': 'url', 'url': 'foo3:', 'ie_key': 'Foo3', 'extractor': 'Foo2', 'webpage_url': 'foo2:', 'webpage_url_basename': …
{'formats': [{'url': 'http://localhost/sample.mp4'}], 'id': 'foo1_id', 'title': 'foo1 title', 'extractor': 'Foo1', 'extr…
{'formats': [{'url': 'http://localhost/sample.mp4'}], 'id': 'foo1_id', 'title': 'foo1 title', 'extractor': 'Foo1', 'extr…
… +8 more values

writes×12

process_ie_result
Take the result of the ie(may be modified) and resolve …
YoutubeDL.py:820

calls×3 [#47]

sanitize_url
utils.py:540

calls [#93]

info
(3 writes, 3 distinct)
{'_type': 'url', 'url': 'foo3:', 'ie_key': 'Foo3', 'extractor': 'Foo2', 'webpage_url': 'foo2:', 'webpage_url_basename': …
{'formats': [{'url': 'http://localhost/sample.mp4'}], 'id': 'testid', 'title': 'foo3 title', 'extractor': 'testex', 'ext…
{'formats': [{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol':…

writes×3

k
(4 writes, 3 distinct)
'_type'
'extractor_key'
'id'

writes×4

v

(4 writes, 3 distinct)
'url_transparent'
'Foo1'

'foo1_id'

writes×4

force_properties
(6 writes, 6 distinct)
{'_type': 'url_transparent', 'url': 'foo2:', 'ie_key': 'Foo2', 'title': 'foo1 title', 'id': 'foo1_id', 'extractor': 'Foo…
{'url': 'foo2:', 'ie_key': 'Foo2', 'title': 'foo1 title', 'id': 'foo1_id', 'extractor': 'Foo1', 'webpage_url': 'foo1:', …
{'title': 'foo1 title', 'id': 'foo1_id', 'extractor': 'Foo1', 'webpage_url': 'foo1:', 'webpage_url_basename': '', 'extra…
{'_type': 'url_transparent', 'url': 'foo3:', 'ie_key': 'Foo3', 'extractor': 'Foo1', 'webpage_url': 'foo1:', 'webpage_url…
{'url': 'foo3:', 'ie_key': 'Foo3', 'extractor': 'Foo1', 'webpage_url': 'foo1:', 'webpage_url_basename': '', 'extractor_k…
{'extractor': 'Foo1', 'webpage_url': 'foo1:', 'webpage_url_basename': '', 'extractor_key': 'Foo1', 'title': 'foo1 title'…

writes×6

f
(8 writes, 4 distinct)
'_type'
'ie_key'
{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol': 'http', 'htt…
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x759b4cee63e0>

writes×6

new_result
(6 writes, 6 distinct)
{'_type': 'url', 'url': 'foo3:', 'ie_key': 'Foo3', 'extractor': 'Foo2', 'webpage_url': 'foo2:', 'webpage_url_basename': …
{'_type': 'url', 'url': 'foo3:', 'ie_key': 'Foo3', 'extractor': 'Foo1', 'webpage_url': 'foo1:', 'webpage_url_basename': …
{'_type': 'url_transparent', 'url': 'foo3:', 'ie_key': 'Foo3', 'extractor': 'Foo1', 'webpage_url': 'foo1:', 'webpage_url…
{'formats': [{'url': 'http://localhost/sample.mp4'}], 'id': 'testid', 'title': 'foo3 title', 'extractor': 'testex', 'ext…
{'formats': [{'url': 'http://localhost/sample.mp4'}], 'id': 'foo1_id', 'title': 'foo1 title', 'extractor': 'Foo1', 'extr…
{'formats': [{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol':…

writes×6

sanitize_string_field
<function YoutubeDL.process_video_result.<locals>.sanitize_string_field at 0x759b4cee5300>

calls [#91]

sanitize_numeric_fields
<function YoutubeDL.process_video_result.<locals>.sanitize_numeric_fields at 0x759b4cee4fe0>

calls [#92]

field
(6 writes, 4 distinct)
'foo1_id'
None
'chapter'
'episode'

writes×2

numeric_field
(4 writes, 2 distinct)
'asr'
'tbr'

writes×2

thumbnails
None

writes

thumbnail
None

writes

subtitles
None

writes

process_subtitles
Select the requested subtitles and their format
YoutubeDL.py:1589

calls [#89]

formats
(7 writes, 6 distinct)
[{'url': 'http://localhost/sample.mp4'}]
[{'url': 'http://localhost/sample.mp4', 'format_id': '0'}]
[{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown'}]
[{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4'}]
[{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol': 'http'}]
[{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol': 'http', 'ht…

writes×6

is_wellformed
<function YoutubeDL.process_video_result.<locals>.is_wellformed at 0x759b4cee5080>

writes

formats_dict
(7 writes, 7 distinct)
{}
{'0': []}
{'0': [{'url': 'http://localhost/sample.mp4', 'format_id': '0'}]}
{'0': [{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown'}]}
{'0': [{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4'}]}
{'0': [{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol': 'http…
… +1 more values

writes×7

format
(7 writes, 6 distinct)
{'url': 'http://localhost/sample.mp4'}
{'url': 'http://localhost/sample.mp4', 'format_id': '0'}
{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown'}
{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4'}
{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol': 'http'}
{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol': 'http', 'htt…

writes×6

format_id
'0'

writes

ambiguous_formats
(5 writes, 5 distinct)
[{'url': 'http://localhost/sample.mp4', 'format_id': '0'}]
[{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown'}]
[{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4'}]
[{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol': 'http'}]
[{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol': 'http', 'ht…

writes×5

format_resolution
YoutubeDL.py:2038

calls [#94]

determine_ext
utils.py:1210

calls [#95]

determine_protocol
utils.py:2436

calls [#96]

full_format_info
(3 writes, 3 distinct)
{'formats': [{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol':…
{'formats': [{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol':…
{'formats': [{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol':…

writes×3

_calc_headers
YoutubeDL.py:1332

calls [#98]

req_format
'best'

writes

build_format_selector
YoutubeDL.py:1067

calls [#102]

selector_function
(2 writes, 2 distinct)
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.selector_function at 0x759b4cee6840…
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.selector_function at 0x759b4cee5e40…

calls [#112]

format_selector
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.selector_function at 0x759b4cee5e40…

writes

GeneratorExit

raises (caught)

incomplete_formats
False

writes

ctx

{'formats': [{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol':…

writes formats_to_download
[{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol': 'http', 'ht…

writes

new_info
(2 writes, 2 distinct)
{'formats': [{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol':…
{'formats': [{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol':…

writes×2

process_info
test_YoutubeDL.py:33

calls [#115]

writes×5 passed to calls×3 [#41]

_

(4 writes, 2 distinct)
0
None

writes×3

initialize
Initializes an instance (authentication, etc).
common.py:386

calls×3 [#38]

writes×3

_initialize_geo_bypass
Initialize geo restriction bypass mechanism.
common.py:393

calls×3 [#39]

_real_initialize
viu.py:18

calls×3 [#40]

country_code
(3 writes)
None

writes×3

passed to passed to

calls×3 [#45]

IE_NAME
common.py:481

calls×3 [#43]

url_basename
utils.py:1749

calls×3 [#44]

add_extra_info
Set the keys from extra_info in info dict if they are m…
YoutubeDL.py:745

calls×3 [#46]

writes×3 writes×3

writes×3

passed to writes×2

process_video_result
YoutubeDL.py:1355

passed to

passed to passed to

_calc_cookies
YoutubeDL.py:1350

passed to

passed to

calls×2 [#49]

calls [#85]

result_type
(3 writes, 2 distinct)
'url_transparent'
'video'

writes×3

calls×2 [#48]

extract_flat
(2 writes)
False

writes×2

calls [#86]

passed to passed to

passed to passed to

passed to

passed to

passed to

res

(4 writes, 4 distinct)
{'formats': [{'url': 'http://localhost/sample.mp4'}], 'id': 'testid', 'title': 'testttitle', 'extractor': 'testex', 'ext…
{'formats': [{'url': 'http://localhost/sample.mp4'}], 'id': 'testid', 'title': 'foo3 title', 'extractor': 'testex', 'ext…
'unknown'
{'User-Agent': 'Mozilla/5.0 (X11; Linux x86_64; rv:10.0) Gecko/20150101 Firefox/47.0 (Chrome)', 'Accept-Charset': 'ISO-8…

writes×2

report_force_conversion
<function YoutubeDL.process_video_result.<locals>.report_force_conversion at 0x759b4cfeb920>

writes

writes writes

passed to passed to

writes×2 writes×2 writes×2

available_subs
{}

writes

passed to

url
(2 writes)
'http://localhost/sample.mp4'

writes

valid_url
True

writes

passed to passed to

sanitized_Request
utils.py:544

passed to

passed to passed to

writes

guess
(2 writes)
'mp4'

writes×2

writes

calls [#97]

protocol
None

writes

ext

'mp4'

writes

writes

add_headers
None

writes

calls [#99]

cookies
None

writes

x_forwarded_for_ip
None

writes

calls [#100]

pr

<urllib.request.Request object at 0x759b4d1fd970>

writes

calls [#101]

writes

writes writes

syntax_error
<function YoutubeDL.build_format_selector.<locals>.syntax_error at 0x759b4cee54e0>

writes

PICKFIRST
'PICKFIRST'

writes

MERGE
'MERGE'

writes

SINGLE
'SINGLE'

writes

GROUP
'GROUP'

writes

FormatSelector
<class 'youtube_dl.YoutubeDL.FormatSelector'>

writes

_parse_filter
<function YoutubeDL.build_format_selector.<locals>._parse_filter at 0x759b4cee58a0>

writes

_remove_unused_ops
<function YoutubeDL.build_format_selector.<locals>._remove_unused_ops at 0x759b4cee5b20>

writes

_parse_format_selection
<function YoutubeDL.build_format_selector.<locals>._parse_format_selection at 0x759b4cee5bc0>

writes

_build_selector_function
<function YoutubeDL.build_format_selector.<locals>._build_selector_function at 0x759b4cee5d00>

writes stream
<_io.BytesIO object at 0x759b4cd6c720>

writes

tokens
[(1, 'best', (1, 0), (1, 4), None)]

writes

__iter__
<function YoutubeDL.build_format_selector.<locals>.TokenIterator.__iter__ at 0x759b4cee60c0>

writes

writes

next

<function YoutubeDL.build_format_selector.<locals>.TokenIterator.__next__ at 0x759b4cee6160>

writes

restore_last_token
<function YoutubeDL.build_format_selector.<locals>.TokenIterator.restore_last_token at 0x759b4cee6520>

writes

TokenIterator
<class 'youtube_dl.YoutubeDL.YoutubeDL.build_format_selector.<locals>.TokenIterator'>

writes

parsed_selector
[FormatSelector(type='SINGLE', selector='best', filters=[])]

writes

passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to

writes×4 ALLOWED_OPS ('/', '+', ',', '(', ')')

writes

last_string
(2 writes, 2 distinct)
None
'best'

writes×2

last_start
(2 writes, 2 distinct)
None
(1, 0)

writes×2

last_end
(2 writes, 2 distinct)
None
(1, 4)

writes×2

last_line
None

writes

string
(4 writes, 3 distinct)
'utf-8'
'best'
''

writes×3

start

(5 writes, 4 distinct)
(0, 0)
(1, 0)
(1, 4)
(2, 0)

writes×4

end
(4 writes, 4 distinct)
(0, 0)
(1, 4)
(1, 5)
(2, 0)

writes×4

line
(3 writes, 2 distinct)

''

'best'

writes×3

writes writes

passed to

writes writes calls [#107]

calls×2 [#108]

selectors
(2 writes, 2 distinct)
[]
[FormatSelector(type='SINGLE', selector='best', filters=[])]

writes×2

current_selector
(2 writes, 2 distinct)
None

FormatSelector(type='SINGLE', selector='best', filters=[])

writes×2

StopIteration

raises (caught)

passed to

format_spec
'best'

writes

writes×2

filters
[]

writes

final_selector
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x759b4cee63e0>

writes

s

FormatSelector(type='SINGLE', selector='best', filters=[])

writes

fs

[<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x759b4cee63e0>]

writes

passed to passed to passed to passed to passed to

passed to passed to

passed to passed to

passed to

passed to

raises (caught) writes

passed to

passed to

writes writes×2 writes

calls [#114]

passed to

format_idx
- 1

writes

audiovideo_formats
[{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol': 'http', 'ht…

writes

passed to

ctx_copy
{'formats': [{'url': 'http://localhost/sample.mp4', 'format_id': '0', 'format': '0 - unknown', 'ext': 'mp4', 'protocol':…

writes

passed to

passed to passed to

passed to

passed to

passed to passed to