test_call
test_jsinterp.py:110
calls [#1]
writes
calls [#2]
raises (caught)
__init__
metadatafromtitle.py:9
jsi
<youtube_dl.jsinterp.JSInterpreter object at 0x7bd3a219e7e0>
call_function
jsinterp.py:246
loops(×59)
writes
calls×2 [#3]
writes
calls [#13]
raises (caught)
writes×3
writes
writes
writes
raises (caught)
objects
{}
extract_function
jsinterp.py:232
f
<function JSInterpreter.build_function.<locals>.resf at 0x7bd3a1f88860>
interpret_statement
jsinterp.py:37
var_m
(3 writes)
None
json.decoder.JSONDecodeError
Expecting value: line 1 column 1 (char 0)
fname
'y'
v
'3'
argvals
(3,)
youtube_dl.utils.ExtractorError
Unsupported JS expression 'x()'; please report this issue on https://yt-dl.org/bug . Make sure you are using the latest version; see https://yt-dl.org/update on how to update. Be sure to call youtub...
writes×2
writes×2
writes×5
writes×3
writes×3
func_m
(2 writes, 2 distinct)
<re.Match object; span=(86, 115), match='function z() { return y(3); }'>
<re.Match object; span=(44, 77), match='function y(a) { return x() + a; }'>
argnames
(2 writes, 2 distinct)
['']
['a']
calls×2 [#4]
calls×2 [#5]
should_abort
(5 writes, 2 distinct)
False
True
stmt_m
(3 writes)
None
return_m
(3 writes, 2 distinct)
<re.Match object; span=(0, 7), match='return '>
None
calls×3 [#7]
writes×10
writes×10
writes×2
calls×2 [#6]
passed to
writes×2
passed to
passed to
writes×3
passed to
build_function
jsinterp.py:250
interpret_expression
jsinterp.py:58
writes×2
writes
passed to
writes×3
writes×3
writes×3
passed to
resf
(2 writes, 2 distinct)
<function JSInterpreter.build_function.<locals>.resf at 0x7bd3a1f88860>
<function JSInterpreter.build_function.<locals>.resf at 0x7bd3a1f88900>
expr
(4 writes, 4 distinct)
'y(3)'
'x() + a'
'x() '
'x()'
op
(13 writes, 6 distinct)
'|='
'='
'|'
'*'
'-'
'+'
opfunc
(13 writes, 5 distinct)
<built-in function or_>
<function <lambda> at 0x7bd3a29d3ce0>
<built-in function mul>
<built-in function sub>
<built-in function add>
m
(5 writes, 3 distinct)
None
<re.Match object; span=(0, 4), match='y(3)'>
<re.Match object; span=(0, 7), match='x() + a'>
writes×2
writes×2
local_vars
(2 writes, 2 distinct)
{}
{'a': 3}
stmt
(4 writes, 4 distinct)
' return y(3)'
'return y(3)'
' return x() + a'
'return x() + a'