test_youtube_format_selection
test_YoutubeDL.py:221 loops(×47)

order
list(len=47)

writes

format_info
<function TestFormatSelection.test_youtube_format_selection.<locals>.format_info at 0x73a5401f9760>

writes

f_id
(2 writes, 2 distinct)
'38'
'139'

writes×2

formats_order
list(len=47)

writes

_make_result
test_YoutubeDL.py:38

calls×3 [#3]

__init__
execafterdownload.py:11

calls×6 [#4]

ydl
(3 writes, 3 distinct)
<test.test_YoutubeDL.YDL object at 0x73a540303680>
<test.test_YoutubeDL.YDL object at 0x73a5403037a0>
<test.test_YoutubeDL.YDL object at 0x73a540189fa0>

writes×3

yie
(3 writes, 3 distinct)
<youtube_dl.extractor.youtube.YoutubeIE object at 0x73a540340f80>
<youtube_dl.extractor.youtube.YoutubeIE object at 0x73a541f537a0>
<youtube_dl.extractor.youtube.YoutubeIE object at 0x73a540728f80>

writes×3

_sort_formats
common.py:708

calls×3 [#17]

process_ie_result
Take the result of the ie(may be modified) and resolve …
YoutubeDL.py:692

calls×3 [#26]

downloaded
(2 writes, 2 distinct)
dict(len=21)
{'formats': [{'ext': 'm4a', 'format_note': 'DASH audio', 'acodec': 'aac', 'vcodec': 'none', 'abr': 48, 'preference': -50…

writes×2

AttributeError
'NoneType' object has no attribute 'type'

raises (caught)

info
(6 writes, 6 distinct)
{'ext': 'mp4', 'width': 4096, 'height': 3072}
{'ext': 'mp4', 'width': 4096, 'height': 3072, 'format_id': '38'}
{'ext': 'mp4', 'width': 4096, 'height': 3072, 'format_id': '38', 'url': 'url:38'}
{'ext': 'm4a', 'format_note': 'DASH audio', 'acodec': 'aac', 'vcodec': 'none', 'abr': 48, 'preference': -50, 'container'…
{'ext': 'm4a', 'format_note': 'DASH audio', 'acodec': 'aac', 'vcodec': 'none', 'abr': 48, 'preference': -50, 'container'…
{'ext': 'm4a', 'format_note': 'DASH audio', 'acodec': 'aac', 'vcodec': 'none', 'abr': 48, 'preference': -50, 'container'…

writes×6

passed to

calls×12 [#5]

get_params
helper.py:21

calls×3 [#6]

params
(3 writes)
dict(len=41)

writes×3

_setup_opener
YoutubeDL.py:1909

calls×3 [#9]

set_downloader
Sets the downloader for this PP.
common.py:33

calls×3 [#16]

sep
(9 writes)
'/'

writes×9

head
(6 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test/'
'/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test'

writes×6

path
(6 writes, 2 distinct)
'/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test'
'/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test/parameters.json'

writes×6

b
(3 writes)
'parameters.json'

writes×3

PARAMETERS_FILE
(3 writes)
'/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test/parameters.json'

writes×3

pf
(3 writes)
<_io.TextIOWrapper name='/home/shashwat/BTP/BugsInPy/workspace/youtube-dl/test/parameters.json' mode='r' encoding='utf-8…

writes×3

parameters
(3 writes)
dict(len=41)

writes×3

passed to

passed to

make_HTTPS_handler
utils.py:443

passed to

calls×6 [#10]

timeout_val
(3 writes)
20

writes×3

opts_cookiefile
(3 writes)
None

writes×3

opts_proxy
(3 writes)
None

writes×3

cookie_processor
(3 writes, 3 distinct)
<urllib.request.HTTPCookieProcessor object at 0x73a540303cb0>
<urllib.request.HTTPCookieProcessor object at 0x73a5401caba0>
<urllib.request.HTTPCookieProcessor object at 0x73a5401cb7d0>

writes×3

proxies
(3 writes)
{}

writes×3

proxy_handler
(3 writes, 3 distinct)
<youtube_dl.utils.PerRequestProxyHandler object at 0x73a540845df0>
<youtube_dl.utils.PerRequestProxyHandler object at 0x73a540342a20>
<youtube_dl.utils.PerRequestProxyHandler object at 0x73a540343110>

writes×3

debuglevel
(3 writes)
0

writes×3 calls×3 [#11]

https_handler
(3 writes, 3 distinct)
<youtube_dl.utils.YoutubeDLHTTPSHandler object at 0x73a5403430b0>
<youtube_dl.utils.YoutubeDLHTTPSHandler object at 0x73a54018b320>
<youtube_dl.utils.YoutubeDLHTTPSHandler object at 0x73a5401cab70>

writes×3

ydlh
(3 writes, 3 distinct)
<youtube_dl.utils.YoutubeDLHandler object at 0x73a540342000>
<youtube_dl.utils.YoutubeDLHandler object at 0x73a54018be90>
<youtube_dl.utils.YoutubeDLHandler object at 0x73a540189a60>

writes×3

opener
(3 writes, 3 distinct)
<urllib.request.OpenerDirector object at 0x73a541270b90>
<urllib.request.OpenerDirector object at 0x73a54072b890>
<urllib.request.OpenerDirector object at 0x73a540343440>

writes×3

passed to calls×3 [#12]

opts_no_check_certificate
(3 writes)
False

writes×3

context

(3 writes, 3 distinct)
<ssl.SSLContext object at 0x73a540129ad0>
<ssl.SSLContext object at 0x73a53ff39b50>
<ssl.SSLContext object at 0x73a53ff39ed0>

writes×3

passed to

loops(×141)

_formats_key
(3 writes, 3 distinct)
<function InfoExtractor._sort_formats.<locals>._formats_key at 0x73a5401fb380>
<function InfoExtractor._sort_formats.<locals>._formats_key at 0x73a53fe87ec0>
<function InfoExtractor._sort_formats.<locals>._formats_key at 0x73a53fe874c0>

writes×3

ValueError
'3gp' is not in list

raises (caught)

raises (caught)

loops(×659)

result_type
(3 writes)
'video'

writes×3

add_extra_info
Set the keys from extra_info in info dict if they are m…
YoutubeDL.py:626

calls×3 [#27]

process_video_result
YoutubeDL.py:1149

calls×3 [#28]

formats
(4 writes, 2 distinct)
list(len=47)
[]

writes

formats_dict
(12 writes, 5 distinct)
{}
{'139': []}
{'139': [{'ext': 'm4a', 'format_note': 'DASH audio', 'acodec': 'aac', 'vcodec': 'none', 'abr': 48, 'preference': -50, 'c…
dict(len=47)
{'139': [{'ext': 'm4a', 'format_note': 'DASH audio', 'acodec': 'aac', 'vcodec': 'none', 'abr': 48, 'preference': -50, 'c…

writes×3

format_id
(12 writes, 2 distinct)
'139'
'38'

writes×9

ambiguous_formats
(8 writes, 5 distinct)
[{'ext': 'm4a', 'format_note': 'DASH audio', 'acodec': 'aac', 'vcodec': 'none', 'abr': 48, 'preference': -50, 'container…
[{'ext': 'mp4', 'width': 4096, 'height': 3072, 'format_id': '38', 'url': 'url:38'}]
[{'ext': 'mp4', 'width': 4096, 'height': 3072, 'format_id': '38', 'url': 'url:38', 'format': '38 - 4096x3072'}]
[{'ext': 'mp4', 'width': 4096, 'height': 3072, 'format_id': '38', 'url': 'url:38', 'format': '38 - 4096x3072', 'http_hea…
[{'ext': 'm4a', 'format_note': 'DASH audio', 'acodec': 'aac', 'vcodec': 'none', 'abr': 48, 'preference': -50, 'container…

writes×8

format_resolution
YoutubeDL.py:1711

calls×7 [#30]

_calc_headers
YoutubeDL.py:1131

calls×11 [#31]

req_format
(3 writes, 3 distinct)
'bestvideo+bestaudio'
'bestvideo[height>=999999]+bestaudio/best'
'bestvideo/best,bestaudio'

writes×3

build_format_selector
YoutubeDL.py:913

calls×3 [#51]

_parse_format_selection
(3 writes, 3 distinct)
<function YoutubeDL.build_format_selector.<locals>._parse_format_selection at 0x73a53fe87920>
<function YoutubeDL.build_format_selector.<locals>._parse_format_selection at 0x73a53fe876a0>
<function YoutubeDL.build_format_selector.<locals>._parse_format_selection at 0x73a53ff4c7c0>

calls×2 [#125]

_build_selector_function
(3 writes, 3 distinct)
<function YoutubeDL.build_format_selector.<locals>._build_selector_function at 0x73a53fe879c0>
<function YoutubeDL.build_format_selector.<locals>._build_selector_function at 0x73a53fe87560>
<function YoutubeDL.build_format_selector.<locals>._build_selector_function at 0x73a53ff4c900>

calls [#137]

__next__
(3 writes, 3 distinct)
<function YoutubeDL.build_format_selector.<locals>.TokenIterator.__next__ at 0x73a53fe87d80>
<function YoutubeDL.build_format_selector.<locals>.TokenIterator.__next__ at 0x73a53fe87c40>
<function YoutubeDL.build_format_selector.<locals>.TokenIterator.__next__ at 0x73a53fe87ce0>

calls×4 [#123]

video_selector
(4 writes, 4 distinct)
FormatSelector(type='SINGLE', selector='bestvideo', filters=[])
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x73a53ff1c040>
FormatSelector(type='SINGLE', selector='bestvideo', filters=['height>=999999'])
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x73a53ff4c040>

writes

audio_selector
(4 writes, 3 distinct)
[FormatSelector(type='SINGLE', selector='bestaudio', filters=[])]
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.selector_function at 0x73a53ff1c860…
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.selector_function at 0x73a53ff4cb80…

writes

StopIteration

raises (caught)

parsed_selector
(3 writes, 3 distinct)
[FormatSelector(type='MERGE', selector=(FormatSelector(type='SINGLE', selector='bestvideo', filters=[]), [FormatSelector…
[FormatSelector(type='PICKFIRST', selector=(FormatSelector(type='MERGE', selector=(FormatSelector(type='SINGLE', selecto…
[FormatSelector(type='PICKFIRST', selector=(FormatSelector(type='SINGLE', selector='bestvideo', filters=[]), [FormatSele…

writes

_merge
(2 writes, 2 distinct)
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>._merge at 0x73a53ff1c540>
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>._merge at 0x73a53ff4c540>

calls [#78]

format_selector
(2 writes, 2 distinct)
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.selector_function at 0x73a53fe87f60…
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.selector_function at 0x73a53ff4ccc0…

writes×2

video_formats
(2 writes, 2 distinct)
[{'ext': 'mp4', 'height': 144, 'format_note': 'DASH video', 'acodec': 'none', 'preference': -40, 'format_id': '160', 'ur…
[]

writes

audio_formats
(2 writes)
[{'ext': 'm4a', 'format_note': 'DASH audio', 'acodec': 'aac', 'vcodec': 'none', 'abr': 48, 'preference': -50, 'container…

writes×2

pair
({'ext': 'mp4', 'height': 1080, 'format_note': 'DASH video', 'acodec': 'none', 'preference': -40, 'format_id': '137', 'u…

writes

formats_to_download
(2 writes, 2 distinct)
[{'requested_formats': ({'ext': 'mp4', 'height': 1080, 'format_note': 'DASH video', 'acodec': 'none', 'preference': -40,…
[{'ext': 'mp4', 'width': 4096, 'height': 3072, 'format_id': '38', 'url': 'url:38', 'format': '38 - 4096x3072', 'http_hea…

writes×2

new_info
(4 writes, 3 distinct)
{'formats': [{'ext': 'm4a', 'format_note': 'DASH audio', 'acodec': 'aac', 'vcodec': 'none', 'abr': 48, 'preference': -50…
dict(len=21)
{'formats': [{'ext': 'm4a', 'format_note': 'DASH audio', 'acodec': 'aac', 'vcodec': 'none', 'abr': 48, 'preference': -50…

writes×4

process_info
test_YoutubeDL.py:31

calls×2 [#79]

ie_result
(3 writes, 3 distinct)
dict(len=21)
{'formats': [{'ext': 'm4a', 'format_note': 'DASH audio', 'acodec': 'aac', 'vcodec': 'none', 'abr': 48, 'preference': -50…
{'formats': [{'ext': 'm4a', 'format_note': 'DASH audio', 'acodec': 'aac', 'vcodec': 'none', 'abr': 48, 'preference': -50…

writes×3

filter_parts
(3 writes, 3 distinct)
[]
['height']
['height', '>=', '999999']

writes

format_filter
'height>=999999'

writes

first_choice
(2 writes, 2 distinct)
FormatSelector(type='MERGE', selector=(FormatSelector(type='SINGLE', selector='bestvideo', filters=['height>=999999']), …
FormatSelector(type='SINGLE', selector='bestvideo', filters=[])

writes

second_choice
(2 writes)
[FormatSelector(type='SINGLE', selector='best', filters=[])]

writes

_filter
(2 writes)
<function YoutubeDL._build_format_filter.<locals>._filter at 0x73a53ff4c680>

calls×5 [#154]

actual_value
(7 writes, 4 distinct)
None
144
1080
3072

writes×3

picked_formats
(2 writes, 2 distinct)
[]
[{'ext': 'mp4', 'width': 4096, 'height': 3072, 'format_id': '38', 'url': 'url:38', 'format': '38 - 4096x3072', 'http_hea…

writes×2

audiovideo_formats
list(len=29)

writes

raises (caught)

thumbnails
(3 writes)
None

writes×3

thumbnail
(3 writes)
None

writes×3

process_subtitles
Select the requested subtitles and their format
YoutubeDL.py:1289

calls×3 [#29] writes×9 writes×3 writes×3

available_subs
(3 writes)
{}

writes×3

passed to passed to

passed to

final_selector
(11 writes, 10 distinct)
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x73a53ff1c040>
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x73a53ff1c2c0>
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x73a53ff1c400>
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x73a53ff4c040>
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x73a53ff4c7c0>
<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x73a53ff4c400>
… +4 more values

passed to

passed to

add_headers
(11 writes, 2 distinct)
None

{'User-Agent': 'Mozilla/5.0 (X11; Linux x86_64; rv:10.0) Gecko/20150101 Firefox/20.0 (Chrome)', 'Accept-Charset': 'ISO-8…

writes×11

_calc_cookies
YoutubeDL.py:1144

calls×11 [#32]

cookies
(11 writes)
None

writes×11

pr
(11 writes, 6 distinct)
<urllib.request.Request object at 0x73a540343d70>
<urllib.request.Request object at 0x73a54018bd70>
<urllib.request.Request object at 0x73a54070bb90>
<urllib.request.Request object at 0x73a54018bb90>
<urllib.request.Request object at 0x73a540189ac0>
<urllib.request.Request object at 0x73a5401cb860>

writes×11

writes×3

syntax_error
(3 writes, 3 distinct)
<function YoutubeDL.build_format_selector.<locals>.syntax_error at 0x73a53fe87420>
<function YoutubeDL.build_format_selector.<locals>.syntax_error at 0x73a53fe87b00>
<function YoutubeDL.build_format_selector.<locals>.syntax_error at 0x73a53fe87ec0>

writes×3

PICKFIRST
(3 writes)
'PICKFIRST'

writes×3

MERGE
(3 writes)
'MERGE'

writes×3

SINGLE
(3 writes)
'SINGLE'

writes×3

GROUP
(3 writes)
'GROUP'

writes×3

FormatSelector
(3 writes)
<class 'youtube_dl.YoutubeDL.FormatSelector'>

writes×3

_parse_filter
(3 writes, 3 distinct)
<function YoutubeDL.build_format_selector.<locals>._parse_filter at 0x73a53fe874c0>
<function YoutubeDL.build_format_selector.<locals>._parse_filter at 0x73a53fe87a60>
<function YoutubeDL.build_format_selector.<locals>._parse_filter at 0x73a53ff4c9a0>

writes×3

writes×3 writes×3

stream

(3 writes, 3 distinct)
<_io.BytesIO object at 0x73a53ff0dd50>
<_io.BytesIO object at 0x73a53ff0dc10>
<_io.BytesIO object at 0x73a53ff52110>

writes×3

tokens
(3 writes, 3 distinct)
[TokenInfo(type=67 (ENCODING), string='utf-8', start=(0, 0), end=(0, 0), line=''), TokenInfo(type=1 (NAME), string='best…
[TokenInfo(type=67 (ENCODING), string='utf-8', start=(0, 0), end=(0, 0), line=''), TokenInfo(type=1 (NAME), string='best…
[TokenInfo(type=67 (ENCODING), string='utf-8', start=(0, 0), end=(0, 0), line=''), TokenInfo(type=1 (NAME), string='best…

writes×3

__module__
(3 writes)
'youtube_dl.YoutubeDL'

writes×3

__qualname__
(3 writes)
'YoutubeDL.build_format_selector.<locals>.TokenIterator'

writes×3

__iter__
(3 writes, 2 distinct)
<function YoutubeDL.build_format_selector.<locals>.TokenIterator.__iter__ at 0x73a53fe87e20>
<function YoutubeDL.build_format_selector.<locals>.TokenIterator.__iter__ at 0x73a53fe87ba0>

writes×3 writes×3

next

(3 writes, 3 distinct)
<function YoutubeDL.build_format_selector.<locals>.TokenIterator.__next__ at 0x73a53fe87d80>
<function YoutubeDL.build_format_selector.<locals>.TokenIterator.__next__ at 0x73a53fe87c40>
<function YoutubeDL.build_format_selector.<locals>.TokenIterator.__next__ at 0x73a53fe87ce0>

writes×3

restore_last_token
(3 writes, 3 distinct)
<function YoutubeDL.build_format_selector.<locals>.TokenIterator.restore_last_token at 0x73a53ff1c220>
<function YoutubeDL.build_format_selector.<locals>.TokenIterator.restore_last_token at 0x73a53ff4c360>
<function YoutubeDL.build_format_selector.<locals>.TokenIterator.restore_last_token at 0x73a53fe87560>

writes×3

TokenIterator
(3 writes)
<class 'youtube_dl.YoutubeDL.YoutubeDL.build_format_selector.<locals>.TokenIterator'>

writes×2 writes×3

passed to passed to passed to passed to passed to passed to passed to passed to passed to passed to raises (caught)

passed to

calls×2 [#121] calls [#120]

_

(14 writes, 4 distinct)

''

'bestvideo+bestaudio'
'bestvideo[height>=999999]+bestaudio/best'
'bestvideo/best,bestaudio'

writes×2 writes

calls [#119]

passed to

calls×24 [#56] calls×7 [#55]

calls×2 [#129]

writes×13

writes writes

raises (caught)

writes writes

passed to

writes×2 writes×2

writes×2

format_spec
(7 writes, 3 distinct)
'bestvideo'
'bestaudio'
'best'

writes×7

filters
(11 writes, 2 distinct)
[]
[<function YoutubeDL._build_format_filter.<locals>._filter at 0x73a53ff4c680>]

writes×11

writes×11

s

(12 writes, 9 distinct)
FormatSelector(type='SINGLE', selector='bestaudio', filters=[])
FormatSelector(type='MERGE', selector=(FormatSelector(type='SINGLE', selector='bestvideo', filters=[]), [FormatSelector(…
FormatSelector(type='MERGE', selector=(FormatSelector(type='SINGLE', selector='bestvideo', filters=['height>=999999']), …
FormatSelector(type='SINGLE', selector='best', filters=[])
[FormatSelector(type='SINGLE', selector='best', filters=[])]
FormatSelector(type='PICKFIRST', selector=(FormatSelector(type='MERGE', selector=(FormatSelector(type='SINGLE', selector…
… +3 more values

writes×12

fs
(8 writes, 7 distinct)
[<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x73a53ff1c2c0>]
[<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x73a53ff1c400>]
[<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x73a53ff4c7c0>]
[<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x73a53ff4c2c0>]
[<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x73a53ff4c400>,…
[<function YoutubeDL.build_format_selector.<locals>._build_selector_function.<locals>.final_selector at 0x73a53ff4c9a0>]
… +1 more values

writes×8

_build_format_filter
Returns a function to filter the formats according to t…
YoutubeDL.py:856

calls [#141] raises (caught)

passed to

passed to

passed to

raises (caught)

passed to passed to

format_1
'137'

writes

format_2
'141'

writes

output_ext
'mp4'

writes

passed to

passed to

passed to

passed to

passed to passed to

writes

passed to

passed to

passed to passed to

passed to

passed to

OPERATORS

{'<': <built-in function lt>, '<=': <built-in function le>, '>': <built-in function gt>, '>=': <built-in function ge>, '…

writes

operator_rex
re.compile('(?x)\s*
(?P<key>width|height|tbr|abr|vbr|asr|filesize|fps)
\s*(?P<op><|<=|>|>=|=…

writes

m

<re.Match object; span=(0, 14), match='height>=999999'>

writes

comparison_value
999999

writes

op

<built-in function ge>

writes

writes

passed to passed to passed to

writes×4

format_idx
- 1

passed to passed to