Overview

17 tables in 3 groups. Every column is on the next pages.

Catalog

What the shop sells: categories, products, photos, and stock per size × color.

Categories 10 columns
Products 12 columns
ProductVariants 9 columns
ProductImages 6 columns
Colors 4 columns

Details: page 2

Orders & Tailoring

Ready-made and custom orders, their lines (snapshots), status timeline and measurements.

Orders 19 columns
OrderLines 12 columns
TailoringSpecs 18 columns
OrderStatusHistory 7 columns
DeliveryZones 8 columns

Details: page 3

Settings & Owner Login

What the owner edits in the dashboard, duplicate-order protection, and the owner account.

SiteSettings 3 columns
TailoringCatalog 3 columns
PriceRules 3 columns
IdempotencyKeys 6 columns
AspNetUsers 7 columns
AspNetRoles 2 columns
AspNetUserRoles 2 columns

Details: page 4

How the tables connect

From (one)		To (many)	Type	Meaning
Categories	→	**Categories**	one-to-many	a category can contain sub-categories
Categories	→	**Products**	one-to-many	each product belongs to one category
Products	→	**ProductImages**	one-to-many	a product has many photos
Products	→	**ProductVariants**	one-to-many	a product is sold in many size × color variants
Colors	→	**ProductVariants**	one-to-many	each variant has one color
DeliveryZones	→	**Orders**	one-to-many	each order is delivered to one governorate
Orders	→	**OrderLines**	one-to-many	an order has many items
ProductVariants	→	**OrderLines**	one-to-many	each order item is one variant
Orders	→	**OrderStatusHistory**	one-to-many	every status change of an order is recorded
Orders	→	**TailoringSpecs**	one-to-one (optional)	a custom order has one tailoring sheet
AspNetUsers	→	**OrderStatusHistory**	one-to-many	records which account made the change
AspNetUsers	→	**AspNetUserRoles**	one-to-many	a user can have roles
AspNetRoles	→	**AspNetUserRoles**	one-to-many	a role (Owner) is given to users

Catalog

What the shop sells: categories, products, photos, and stock per size × color.

PK primary key · FK foreign key (link) · UK unique · **snapshot** = copied when the order is placed · 🔗 = how this table connects

Categories

Id	int	PK	
ParentId	int	FK	null = main category
NameAr	string		
NameEn	string		
Slug	string	UK	
ImageUrl	string		
SortOrder	int		
IsVisible	bool		
CreatedAt	datetime		
UpdatedAt	datetime		

🔗 **Categories → Categories** · one-to-many · a category can contain sub-categories
🔗 **Categories → Products** · one-to-many · each product belongs to one category

Products

Id	int	PK	
CategoryId	int	FK	
NameAr	string		
NameEn	string		
Slug	string	UK	
DescriptionAr	text		
DescriptionEn	text		
BasePrice	decimal		
IsVisible	bool		
IsDeleted	bool		soft delete
CreatedAt	datetime		
UpdatedAt	datetime		

🔗 **Categories → Products** · one-to-many · each product belongs to one category
🔗 **Products → ProductImages** · one-to-many · a product has many photos
🔗 **Products → ProductVariants** · one-to-many · a product is sold in many size × color variants

ProductVariants

Id	int	PK	
ProductId	int	FK	
ColorId	int	FK	
Size	string		UK with ProductId + ColorId
Sku	string	UK	
Stock	int		
PriceOverride	decimal		null = base price
IsDeleted	bool		
xmin	uint		concurrency token

🔗 **Products → ProductVariants** · one-to-many · a product is sold in many size × color variants
🔗 **Colors → ProductVariants** · one-to-many · each variant has one color
🔗 **ProductVariants → OrderLines** · one-to-many · each order item is one variant

ProductImages

Id	int	PK	
ProductId	int	FK	
StorageKey	string		Supabase Storage key
AltAr	string		
AltEn	string		
SortOrder	int		0 = main photo

🔗 **Products → ProductImages** · one-to-many · a product has many photos

Colors

Id	int	PK	
NameAr	string		
NameEn	string		
Hex	string		#rrggbb

🔗 **Colors → ProductVariants** · one-to-many · each variant has one color

Orders & Tailoring

Ready-made and custom orders, their lines (snapshots), status timeline and measurements.

PK primary key · FK foreign key (link) · UK unique · **snapshot** = copied when the order is placed · 🔗 = how this table connects

Orders

Id	int	PK	
Number	string	UK	ZF-10234
TrackingTokenHash	string		token itself never stored
Type	string		Ready | Custom
Status	string		
CustomerName	string		
Phone	string		+201xxxxxxxxx
Email	string		optional
DeliveryZoneId	int	FK	
City	string		
Address	string		
Notes	string		
Subtotal	decimal		
DeliveryFee	decimal		
Total	decimal		
PaymentMethod	string		
PaymentStatus	string		
CreatedAt	datetime		
UpdatedAt	datetime		

🔗 **DeliveryZones → Orders** · one-to-many · each order is delivered to one governorate
🔗 **Orders → OrderLines** · one-to-many · an order has many items
🔗 **Orders → OrderStatusHistory** · one-to-many · every status change of an order is recorded
🔗 **Orders → TailoringSpecs** · one-to-one (optional) · a custom order has one tailoring sheet

OrderLines

Id	int	PK	
OrderId	int	FK	
VariantId	int	FK	
ProductNameAr	string		snapshot
ProductNameEn	string		snapshot
Size	string		snapshot
ColorNameAr	string		snapshot
ColorNameEn	string		snapshot
UnitPrice	decimal		snapshot
Quantity	int		
LineTotal	decimal		
ImageUrl	string		

🔗 **Orders → OrderLines** · one-to-many · an order has many items
🔗 **ProductVariants → OrderLines** · one-to-many · each order item is one variant

TailoringSpecs

Id	int	PK	
OrderId	int	FK	1 to 1
StyleId	string		null = own design
Garment	string		
Fabric	string		
Color	string		
Fit	string		
SizingMode	string		
StandardSize	string		
Measurements	jsonb		key to cm
HasLining	bool		
Extras	jsonb		embroidery, …
ReferenceImageKey	string		private bucket
EstimatedPrice	decimal		
QuotedPrice	decimal		
QuoteNote	string		
QuoteValidUntil	datetime		
QuoteApprovedAt	datetime		

🔗 **Orders → TailoringSpecs** · one-to-one (optional) · a custom order has one tailoring sheet

OrderStatusHistory

Id	int	PK	
OrderId	int	FK	
FromStatus	string		
ToStatus	string		
ChangedByUserId	string	FK	null = customer or system
ChangedAt	datetime		
Note	string		

🔗 **Orders → OrderStatusHistory** · one-to-many · every status change of an order is recorded
🔗 **AspNetUsers → OrderStatusHistory** · one-to-many · records which account made the change

DeliveryZones

Id	int	PK	
Key	string	UK	cairo, giza, …
NameAr	string		
NameEn	string		
Fee	decimal		
EtaDaysMin	int		
EtaDaysMax	int		
IsActive	bool		

🔗 **DeliveryZones → Orders** · one-to-many · each order is delivered to one governorate

Settings & Owner Login

What the owner edits in the dashboard, duplicate-order protection, and the owner account.

PK primary key · FK foreign key (link) · UK unique · **snapshot** = copied when the order is placed · 🔗 = how this table connects

SiteSettings

Id	int	PK	single row
Content	jsonb		hero, contacts, social
UpdatedAt	datetime		

TailoringCatalog

Id	int	PK	single row
Content	jsonb		garments, styles, fabrics, fields
UpdatedAt	datetime		

PriceRules

Id	int	PK	single row
Content	jsonb		base per style + extras
UpdatedAt	datetime		

IdempotencyKeys

Key	string	PK	
Endpoint	string		
RequestHash	string		
StatusCode	int		
ResponseJson	jsonb		
CreatedAt	datetime		kept 24 h

AspNetUsers

Id	string	PK	
FullName	string		
Email	string	UK	
PasswordHash	string		
MustChangePassword	bool		
LockoutEnd	datetime		
AccessFailedCount	int		

🔗 **AspNetUsers → OrderStatusHistory** · one-to-many · records which account made the change

🔗 **AspNetUsers → AspNetUserRoles** · one-to-many · a user can have roles

AspNetRoles

Id	string	PK	
Name	string	UK	Owner

🔗 **AspNetRoles → AspNetUserRoles** · one-to-many · a role (Owner) is given to users

AspNetUserRoles

UserId	string	PK
RoleId	string	PK

🔗 **AspNetUsers → AspNetUserRoles** · one-to-many · a user can have roles

🔗 **AspNetRoles → AspNetUserRoles** · one-to-many · a role (Owner) is given to users