

Path Planning and Obstacle Avoidance Real-Time Collision Evasion: A Deterministic Real-Time Local Replanning Method for Autonomous UAV Power-Line Inspection

Pablo De Porcellinis^{1,2}, Xabier Olaz¹, and Jesús Villadangos^{1,3}

¹Mathematical Engineering and Computer Science Department, Public University of Navarre, Spain

²FuVeX Civil SL, Spain

³Institute of Smart Cities, Public University of Navarre, Spain

Abstract

Autonomous UAV obstacle avoidance is not new, but most existing algorithms focus on collision-free flight, geometric efficiency, or dynamic feasibility. Much less work addresses the European regulatory logic that an autonomous route should avoid exposing uninvolved people and other protected ground parties to unnecessary overflight risk. This paper presents Path Planning and Obstacle Avoidance Real-Time Collision Evasion, a deterministic real-time local replanning method for waypoint-preserving obstacle avoidance in autonomous power-line inspection missions. The method is implemented and evaluated inside Pipeline A, the validated SIMULATION workflow of the Deep-AeroTwin project, where it operates together with a waypoint-driven flight controller, a YOLO-based perception front-end, monocular obstacle geopositioning, and zero-trust audit logging. In the current implementation, civilian-like detections and nearby entities are converted into protected local no-fly regions that trigger conservative detours instead of nominal overflight. Based on the literature reviewed for 2024–2026, we are not aware of a published method that combines this EASA-motivated no-overflight objective with deterministic online local replanning and autonomous power-line inspection integration in the same way.

Controlled E2E experiments show that the method changes the vehicle trajectory only when detections are present and the avoidance module is enabled; under that condition, mission path length increases from 1455.50 m to 1460.10 m (0.32 %) and mission time from 204.00 s to 206.00 s (0.98 %). In the audited zero-trust case study, the method triggers at 19.47 m, generates a 15-point local route, completes the maneuver in 33.95 s, and maintains a minimum geometric separation of 13.48 m from the trigger-side auditable proxy of the planner obstacle subset, i.e. 1.48 m above the configured 12.00 m safety radius. These results support the method as a reproducible, low-overhead, and auditable local replanning method that operationalizes part of the European ground-risk logic at the online controller level, while Pipeline A provides the integration and validation environment used to characterize its behavior.

Keywords: local replanning, UAV inspection, obstacle avoidance, ground risk, uninvolved people, SORA, A* replanning, safety-critical navigation

1 Introduction

Unmanned Aerial Vehicles (UAVs) are becoming a practical tool for infrastructure inspection, surveillance, and monitoring, with growing impact across agriculture, critical infrastructure, and other industrial environments [1, 2]. Power-line inspection is one of the most relevant of these use cases because it combines long-range navigation, repeated geometric structures, tight mission corridors, and the need to react to unexpected obstacles without compromising the inspection objective.

From a planning standpoint, this scenario is difficult because the vehicle must preserve a global mission structure while responding online to local conflicts. Purely global planners are efficient when the environment is static and fully known, but they become brittle under late obstacle appearance or perception uncertainty [3, 4]. On the other hand, fully learned end-to-end policies are harder to audit in safety-critical aeronautical contexts, where traceability and bounded behavior remain important design properties [5].

The regulatory dimension makes the problem even sharper. Under the European Union UAS regulatory framework, the operational core is defined by Commission Implementing Regulation (EU) 2019/947 on the rules and procedures for the operation of unmanned aircraft and Commission Delegated Regulation (EU) 2019/945 on unmanned aircraft systems, while EASA AMC/GM material now incorporates the JARUS SORA 2.5 package for the ‘specific’ category [6–9]. Within this framework, the acceptability of a route is not only a matter of geometric collision avoidance but also of limiting exposure of uninvolved people and sensitive ground areas. This means that an autonomous planner should not merely ask whether the UAV *can* fly over a location, but whether it *should* do so in a risk-aware operational sense. Existing literature has already started to encode this concern through urban risk maps, third-party-risk models, SORA-aware cost functions, and target-level-of-safety constraints [10–16]. However, most of these works remain strategic route optimizers or city-scale risk planners rather than controller-level local replanners for infrastructure inspection missions already in progress.

This paper focuses on Path Planning and Obstacle Avoidance Real-Time Collision Evasion as the main scientific contribution. The method is a local conflict-resolution system designed for the validated SIMULATION workflow available in the Deep-AeroTwin repository, where a mission file, a flight controller, an onboard-like perception stack, and a local planner operate together in closed loop. Its role is simple but operationally important: whenever an obstacle enters a conservative reaction horizon, the method temporarily inhibits nominal navigation, computes a bounded local path toward the current mission waypoint, and returns control to the original route as soon as the local conflict disappears. The novelty is therefore not obstacle avoidance in isolation. The novelty is to operationalize a regulatory-aware no-overflight logic for uninvolved third parties and nearby protected entities inside a deterministic, auditable, online local replanner. The claim of the paper is correspondingly narrow: the method is advanced as a state-of-the-art contribution in this specific EASA-relevant niche, not as a claim to supersede the broader literature on generic UAV avoidance or strategic risk-aware routing.

The main contributions of the paper are the following.

- The definition of Path Planning and Obstacle Avoidance Real-Time Collision Evasion as a deterministic, waypoint-preserving local replanning method for real-time UAV obstacle avoidance in power-line inspection missions, explicitly motivated by European ground-risk and no-overflight concerns.
- A formal and reproducible description of how the method is integrated with perception, mission execution, and audit logging inside the validated Pipeline A environment.

- An evidence-driven evaluation of the method grounded on repository artifacts, including controlled ablation logs and an audited case study with figures, tables, and derived metrics.

2 State of the Art, Ground-Risk Regulation, and Research Gap

Vision-based UAV navigation has been widely studied as a perception-driven alternative to map-only planning, with applications ranging from localization to obstacle detection and local trajectory generation [17, 18]. General reviews consistently distinguish between global path planning, which assumes a sufficiently known environment, and local path planning, which reacts to obstacles while the vehicle is already moving [3, 4]. More specifically, recent surveys in 2025 and 2026 confirm that the dominant design goals remain collision avoidance, dynamic feasibility, and computational efficiency, while explicit treatment of third-party ground exposure is still comparatively rare in runtime planning [19, 20]. The proposed method is explicitly positioned in the online local-replanning class.

For power-line inspection, the local planning problem is more operational than academic. The vehicle must continue progressing through a mission corridor while structures, animals, vehicles, or uninvolved people may appear in the neighborhood of the route. Power-line inspection has therefore developed its own system literature, from UAV-image approaches for corridor measurement and obstacle localization [21] to line detection in cluttered scenes [22], LiDAR-supported automatic inspection [23], dual-view stereovision for reconstruction and clearance estimation [24], and dedicated reviews of UAV-enabled power-line inspection [25]. On the perception side, Bellou *et al.* report YOLOv8-based aerial inspection for towers, conductors, and insulators [26], while Faisal *et al.* synthesize more than 70 studies and identify persistent gaps in multimodal fusion and deployment realism [27]. On the planning side, Huang *et al.* propose a hybrid RRT*+DWA method for dynamic obstacle avoidance in UAV-based power inspection [28]. These works are highly relevant, but their central objective is still efficient and safe inspection autonomy, not explicit no-overflight treatment of uninvolved people under European operational logic.

That regulatory logic matters because, under the European Union UAS framework defined by Regulations (EU) 2019/947 and 2019/945 and operationalized through AMC/GM plus SORA 2.5, route acceptability is not only about avoiding collision with obstacles but also about limiting exposure of uninvolved people and other protected ground parties [6–9]. A separate strand of literature already addresses this concern directly. Primatesta *et al.* propose a risk-aware urban path-planning strategy with off-line and on-line phases driven by risk maps [10], and later formalize the construction of ground-risk maps for urban UAV operations [11]. Pang *et al.* optimize routes by integrating third-party risks into a metropolitan cost model [12]. Tang *et al.* explicitly model obstacle risk, fatality risk, and property loss risk in a Min-cost A* framework [13]. Pilko *et al.* and Zhu *et al.* extend the discussion toward spatiotemporal and grid-based ground-risk mapping [14, 29]. Heinze and Uijt de Haag, and more recently Braßel *et al.*, push this line closer to current European operations by encoding SORA and TLS concepts into route optimization [15, 16]. Complementarily, Du *et al.* review safety-risk modeling for civil UAS operations and show how strongly current safety research is centered on assessment and authorization-oriented risk modeling [30].

The most recent SOTA from 2024 to 2026 further sharpens the distinction between strategic risk planning and controller-level reaction. ElSayed and Mohamed (2024) integrate digital-twin airspace discretization with trajectory optimization under legal and operational constraints [31]. Pang *et al.* (2024) model dynamic ground-risk uncertainty for safe drone delivery through stochastic route optimization [32]. Zhou *et al.* (2025) propose a risk-based path-planning scheme for complex air-ground environments

Table 1: Representative 2024–2026 comparison between recent SOTA strands and the proposed method.

Representative work	What it already solves	Remaining gap relative to the proposed method
ElSayed and Mohamed (2024); Zhu <i>et al.</i> (2026) [31, 36]	Digital-twin airspace structuring and adaptive urban allocation under legal, operational, and uncertainty constraints	They operate mainly at city-airspace and logistics scale, not at the live local-replanning layer of an inspection UAV reacting to a detected civilian-like obstacle
Pang <i>et al.</i> (2024); Zhou <i>et al.</i> (2025); Braßel <i>et al.</i> (2025) [16, 32, 33]	Strong third-party-risk, ground-risk, and TLS-aware optimization of routes	Their main contribution is strategic or pre-flight route optimization rather than short-horizon mission-preserving replanning inside an active inspection controller
Riedel (2025); Checker <i>et al.</i> (2025) [34, 35]	Up-to-date synthesis of detect-and-avoid standards and regulatory mission-planning constraints	They clarify standards and regulatory context, but they do not provide a controller-level method for avoiding overflight of uninvolved people from live detections
Bellou <i>et al.</i> (2024); Huang <i>et al.</i> (2025) [26, 28]	Inspection-specific perception and dynamic obstacle avoidance for power-line operations	They improve inspection autonomy, but not around an explicit European no-overflight / ground-risk objective for uninvolved third parties
This paper	Deterministic waypoint-preserving local replanning triggered by live detections inside an autonomous inspection mission	Brings protected-ground logic, controller integration, and auditability together in Pipeline A rather than treating them as separate planning, perception, and compliance layers

[33], while Riedel (2025) reviews detect-and-avoid standards and shows how strongly recent compliance discussions are still centered on air-risk, separation, and certification interfaces rather than overflight of uninvolved people on the ground [34]. Checker *et al.* (2025) review mission planning from a regulatory perspective, but at the swarm and mission-allocation level [35]. In 2026, Zhu *et al.* move toward adaptive urban airspace allocation under uncertainty [36], and Nafees *et al.* summarize the broader planning landscape while still highlighting real-time adaptation and constraint integration as open challenges [20]. Collectively, these works show that the field is advancing quickly, but the newest contributions still concentrate on strategic routing, digital twins, logistics airspace, or standards alignment more than on deterministic local replanning for inspection missions already underway.

This prior art is real and important, so the contribution of the proposed method must be framed carefully. The method is not the first UAV system to consider people on the ground, nor the first planner to use risk-aware costs. The narrower and more defensible claim is operational: existing inspection planners usually optimize geometric avoidance without an explicit uninvolved-people objective, whereas existing ground-risk and SORA-aware planners usually operate at strategic, route-design, or city-map scale. What remains weakly addressed is the controller-level problem of how an autonomous inspection UAV should react *online*, during a running mission, when live detections suggest that the nominal corridor would overfly or closely pass above a civilian-like entity. The proposed method addresses exactly that intersection by converting nearby detections into protected local no-fly regions, preserving the active mission waypoint as the anchor of the maneuver, and exposing the resulting decisions through the same telemetry, API, and audit chain used by Pipeline A. To the best of our knowledge after reviewing the 2024–2026 literature, this makes the method a state-of-the-art contribution in the narrow niche of EASA-motivated, controller-level, inspection-integrated local replanning for uninvolved-people-aware UAV operation.

Within the local-planning literature, deterministic graph search remains appealing for safety-critical systems because completeness and failure modes are easier to inspect than in stochastic black-box policies. A* provides precisely that balance between computational simplicity and interpretable behavior [37]. The proposed method builds on that property and combines it with a YOLO-based perception front-end [38] and monocular obstacle geopositioning inspired by the real-time method proposed in [39].

3 System Integration in Pipeline A

The proposed method is evaluated inside Pipeline A, the validated SIMULATION workflow in the repository. The runtime architecture is specified below through a short placeholder paragraph in Spanish while the final diagram is being rebuilt. The mission is read from a QGroundControl waypoint file, vehicle state is received from SITL through MAVLink, obstacles are produced by the vision module, and the Brain coordinates nominal waypoint following, replanning activation, and visualization outputs.

[Figura pendiente de reconstrucción.] *Arquitectura de Pipeline A: debería verse, de izquierda a derecha, la cadena completa de integración con el fichero de misión, la fuente visual Cesium/Unreal y la telemetría MAVLink entrando en el Brain; debajo, el sistema de visión devolviendo tracks geoposicionados; a la derecha, el planificador local de evasión entregando una ruta local y, más abajo, el autopiloto ejecutando setpoints; todavía más a la derecha, la API de estado compartido y los artefactos zero-trust como salida auditable. Las flechas deberían distinguir claramente flujo operativo en tiempo real frente a flujo de auditoría, sin cruces ni ambigüedades, para dejar inequívoco cómo se integra el sistema con Pipeline A.*

The software roles are the following.

- **Mission input:** the file `pipeline/ejea_default.waypoints` contains the nominal inspection route.
- **Brain:** `flight_controller.py` executes the control loop, manages waypoints, handles failsafe logic, and calls the replanning module whenever local replanning is necessary.
- **Perception:** `vision_system.py` runs a YOLO-based detector and projects detections into geographic coordinates using onboard state and monocular geometry [39].
- **Planner:** `porce_manager.py` implements the bounded A* local planner used to generate short-range evasion paths.
- **Audit and visualization:** `trajectory.csv`, `events.jsonl`, and the visualization endpoint expose the evolution of the mission for analysis and debugging.

3.1 Runtime Integration with Pipeline A

The integration of the proposed method into Pipeline A is a closed-loop runtime contract rather than a loose module coupling. First, the mission is loaded from a QGroundControl waypoint file and the Brain receives vehicle telemetry from SITL through MAVLink. Second, the perception subsystem queries the latest fused vehicle state and publishes detected obstacles to the Brain through `POST /api/obstacles`. The Brain then normalizes obstacle classes, enforces source filtering and token validation, maintains obstacle tracks with time-to-live logic, and rebuilds the active obstacle list used for decision making.

In the current implementation, human-adjacent detections are already given a dedicated operational treatment. The labels `person`, `bicycle`, and `biker` are canonicalized into the same dynamic obstacle

Table 2: Main configuration values of the validation environment and the proposed method used throughout the paper.

Parameter	Value	Role
Mission file	12 waypoints	Nominal inspection route with takeoff and landing phases
Control-loop period	0.10 s	Brain update period
Cruise speed	8.00 m s ⁻¹	Nominal horizontal mission speed
Grid cell size	6.00 m	Local A* discretization step
Grid radius	40 cells	Local search radius, i.e. an 81 × 81 occupancy grid
Obstacle safety radius	12.00 m	Hard inflation radius around each obstacle
Base reaction distance	45.00 m	Minimum horizon for replanning activation
Reaction gain	2.00 s	Speed-dependent enlargement of reaction horizon
Reaction range	45.00 m to 80.00 m	Clamped reaction distance interval
Route-point tolerance	3.00 m	Distance to accept a local replanning sub-goal as reached
Failsafe threshold	22.00 m	Distance used for hold/lateral replan escalation
Failsafe hold	2.50 s	Temporary hold action when replanning fails

family, while `tower` and `cow` are treated as static classes for tracking and association purposes. This is not yet a full legal ontology of uninvolved people, but it is the concrete mechanism by which civilian-like detections become protected local regions that the method must avoid rather than overfly.

Third, the method is only evaluated when the autonomous mission is active, fresh obstacle evidence exists, and the nearest obstacle crosses a speed-adaptive reaction horizon. Before invoking the planner, the Brain forms a bounded obstacle subset for local replanning: in the validated configuration, only obstacles inside 55.00 m and up to 16 tracks are passed to the planner. This keeps the replanning problem short-range and explicitly tied to the current mission waypoint instead of allowing corridor-wide route redefinition.

Fourth, the Brain calls `PorcePlanner.plan_route(start, goal, obstacles)`, where the start is the current telemetry position and the goal is the current mission waypoint. The planner inflates each obstacle by the configured safety radius, discretizes the neighborhood into a local 81 × 81 occupancy grid with 6.00 m cells, runs bounded A*, and converts the resulting grid path back into geographic sub-points. If a valid route is found, the Brain stores it as the active evasion path; if not, the integration layer escalates through hold, lateral replan, and terminal failsafe actions.

Finally, the method outputs are consumed by the rest of Pipeline A through two channels. On the control side, the Brain sends each local replanning sub-point to the autopilot as MAVLink position-target commands until the evasion route is completed, at which point nominal waypoint following resumes automatically. On the observability side, the same state is exposed through the UI endpoint together with evasion metadata, planner parameters, tracked obstacles, and audit counters, so visualization tools, Unreal consumers, and zero-trust logs all observe the same decision chain. This shared contract is what makes the method not just a planner in isolation, but a reproducible system integrated into a full autonomous inspection pipeline.

Table 2 summarizes the main runtime parameters used to evaluate the method inside Pipeline A. These values come from the validated simulation defaults already present in the repository.

4 Method Description

The controller-level logic that constitutes the scientific core of the proposed method is specified below through a short placeholder paragraph in Spanish while the final diagram is being rebuilt. The method

receives the active waypoint, fresh perception outputs, and current telemetry; canonicalizes human-adjacent detections into protected local regions; evaluates whether the nearest obstacle enters the dynamic reaction horizon; and either preserves nominal mission following or activates a bounded A* local bypass. Importantly, the same decision chain also defines the fallback behavior and the audit outputs, so the proposal is not just a path planner but a complete online conflict-resolution policy.

[Figura pendiente de reconstrucción.] *Flujo metodológico del sistema: debería verse un diagrama de control con inicio en la actualización de telemetría, waypoint activo y tracks; después, la canonicalización de clases tipo person/bicycle/biker en regiones protegidas; a continuación, el cálculo del horizonte dinámico de reacción y una decisión binaria sobre si el obstáculo entra o no en ese horizonte. Si no entra, el sistema mantiene el seguimiento nominal; si entra, construye el subconjunto acotado del planificador, ejecuta el A* local y decide si la ruta local es válida. Si lo es, ejecuta subobjetivos y reengancha con el waypoint actual; si no lo es, activa la escalera de failsafe. En paralelo, el mismo diagrama debería mostrar qué eventos de auditoría se generan en cada rama.*

4.1 Problem Formulation

At each control iteration, the Brain knows the current vehicle state, the active mission waypoint, and the most recent obstacle list. The method is only concerned with the local subproblem: move from the current position to the current waypoint while avoiding the obstacle subset that lies inside a bounded planning neighborhood.

Let the vehicle position be $p_t \in \mathbb{R}^2$, the current waypoint be $w_t \in \mathbb{R}^2$, and the perceived obstacles at time t be $\mathcal{O}_t = \{o_1, \dots, o_k\}$. Each obstacle is inflated by a hard safety radius R_s , generating a non-flyable region

$$\mathcal{Z}_{\text{safe}}(o_i) = \{q \in \mathbb{R}^2 : \|q - p_{o_i}\|_2 \leq R_s\}. \quad (1)$$

The local free space is therefore

$$\mathcal{F}_t = \mathbb{R}^2 \setminus \bigcup_{i=1}^k \mathcal{Z}_{\text{safe}}(o_i). \quad (2)$$

In the current implementation, $R_s = 12.00\text{m}$, which turns safety into a hard geometric constraint instead of a soft penalty.

4.2 Dynamic Triggering Logic

The method is not permanently active. The controller computes a dynamic reaction horizon

$$D_{\text{react}}(t) = \text{clip}(D_{\text{base}} + k_v \|v_t\|_2, D_{\text{min}}, D_{\text{max}}), \quad (3)$$

where $D_{\text{base}} = 45.00\text{m}$, $k_v = 2.00\text{s}$, $D_{\text{min}} = 45.00\text{m}$, and $D_{\text{max}} = 80.00\text{m}$.

If the nearest perceived obstacle satisfies

$$d_{\text{nearest}}(t) \leq D_{\text{react}}(t), \quad (4)$$

and the minimum replan interval has elapsed, the Brain requests a new local route from the replanning module. Otherwise, the vehicle continues nominal waypoint following.

4.3 Bounded Local A* Planner

The method uses a local occupancy grid centered on the vehicle. The validated configuration uses 81×81 cells with $\delta = 6.00\text{m}$ resolution, yielding a bounded search window that is compatible with online execution inside the control loop.

Each cell c_{ij} is labeled as free or occupied according to the inflated obstacle set:

$$S(c_{ij}) = \begin{cases} 1, & \text{if } c_{ij} \cap (\mathbb{R}^2 \setminus \mathcal{F}_t) \neq \emptyset, \\ 0, & \text{otherwise.} \end{cases} \quad (5)$$

The local route is computed with A* [37] using Euclidean heuristic,

$$f(n) = g(n) + h(n), \quad (6)$$

where $g(n)$ is the accumulated path cost and $h(n)$ is the Euclidean distance to the local goal. Eight-connectivity is enabled, so the method can combine cardinal and diagonal moves while remaining on the grid.

The target of the method is always the *current mission waypoint*. This detail is important: the local planner is not allowed to redefine the global mission, only to create a temporary bypass that lets the UAV return to the original corridor as soon as the conflict disappears.

4.4 Failsafe Escalation

If no valid local route is found, the Brain does not continue nominal flight blindly. Instead, the system integration includes an explicit escalation chain with hold, lateral replan, and terminal LAND/RTL actions. This failsafe design is part of the method even when it is not triggered in a particular experiment because it bounds the controller behavior under planner failure.

4.5 Algorithmic Summary

5 Experimental Methodology

5.1 Evidence Sources

The paper uses two complementary evidence sources already present in the repository.

- **Controlled E2E ablations:** four mission logs from `pipeline/logs/e2e/` comparing the replanning module enabled or disabled, with and without detections.
- **Audited case study:** one clean zero-trust run (20260220_092802) with trajectory logs, Brain events, and per-frame vision audit payloads.

The E2E ablation isolates the behavioral effect of enabling the method under detections. The zero-trust run provides richer observability: trigger distance, generated route length, evasion duration, obstacle tracks, and the complete time evolution of the maneuver. However, the event `evasion_route_generated` stores `planner_obs_count` but not the exact obstacle identities passed to the planner. Therefore, all post-hoc clearance analysis in this paper is computed against the nearest published trigger-side tracks in the last pre-trigger vision frame, which is the closest auditable proxy available in the repository.

Algorithm 1 Simplified control loop for the proposed method integrated in Pipeline A

```
1: while mission is active do
2:   refresh telemetry, obstacle tracks, and current waypoint
3:   if telemetry is stale then
4:     continue
5:   end if
6:   if failsafe action is active then
7:     execute failsafe and continue
8:   end if
9:   compute  $D_{\text{react}}(t)$  from current speed
10:  obtain nearest obstacle and planner obstacle subset
11:  if  $d_{\text{nearest}}(t) \leq D_{\text{react}}(t)$  and replanning is allowed then
12:    route  $\leftarrow$  A* local plan toward current mission waypoint
13:    if route is valid then
14:      activate evasion path
15:    else
16:      escalate failsafe
17:    end if
18:  end if
19:  if evasion path is active then
20:    follow next local replanning sub-point
21:  else
22:    follow nominal mission waypoint
23:  end if
24: end while
```

5.2 Mission and Metrics

The mission comes from `pipeline/ejea_default.waypoints`. It contains a takeoff waypoint, a sequence of inspection waypoints, and a landing command. For all experiments, the UAV climbs from 500.00 m MSL to approximately 523.00 m MSL, follows the inspection corridor, and lands autonomously once the final waypoint is reached.

The following metrics are extracted from logs:

- mission duration, measured from the first to the last status sample in the E2E logs;
- path length, computed by summing point-to-point geodesic distances along the logged trajectory;
- trigger distance, route-point count, and evasion duration from `events.jsonl`;
- minimum geometric separation between the executed evasion trajectory and the closest auditable proxy of the planner subset at trigger time;
- detour cost, computed as the difference between evasion path length and the straight-line segment joining the first and last evasion points.

The visual materials discussed in the paper were generated directly from repository logs by a dedicated script placed inside the `paper/` folder. In the present draft, the still-pending diagrams are replaced by short placeholder paragraphs in Spanish that specify the exact visual evidence expected in the final version, so the results section remains reproducible from project artifacts even before the final artwork is rebuilt.

Table 3: Controlled E2E ablation metrics extracted from pipeline/logs/e2e.

Scenario	Time (s)	Path (m)	Mission completed
replanner on + detections	206.00	1460.10	Yes
replanner off + detections	204.00	1455.50	Yes
replanner on + no detections	204.00	1455.60	Yes
replanner off + no detections	204.00	1455.60	Yes

6 Experimental Validation of the Proposed Method

6.1 Controlled E2E Ablation

The early section of the E2E trajectories is specified below through a short placeholder paragraph in Spanish while the final plot is being rebuilt. The two scenarios without detections are practically identical regardless of whether the replanning module is enabled, which confirms that the planner remains dormant when no conflict enters the system. The `replanner off + detections` scenario also follows the nominal corridor, while `replanner on + detections` introduces a visible local detour before rejoining the original path.

[Figura pendiente de reconstrucción.] *Ablación E2E de trayectorias: debería verse una superposición de las cuatro trayectorias del tramo inicial de misión, con colores claramente diferenciados para `replanner on/off` y `detections on/off`. El mensaje visual que debe quedar claro es que los dos casos sin detecciones casi se solapan por completo, que el caso con detecciones pero el replanning desactivado sigue el corredor nominal, y que solo el caso con detecciones y el replanning activado introduce un desvío local corto antes de reincorporarse a la ruta original.*

Table 3 quantifies this result. The mission always completes, and the overhead introduced by the avoidance behavior is small: relative to `replanner off + detections`, enabling the method under detections adds only 4.60 m to the path and 2.00 s to the total mission.

This ablation does not claim broad statistical superiority; instead, it verifies a narrower but operationally important property of the proposed method: the system is behaviorally specific. It perturbs the mission only when both conditions hold simultaneously, namely obstacle evidence is present and the replanning module is enabled.

6.2 Audited Collision-Evasion Maneuver

The selected zero-trust maneuver comes from run 20260220_092802 and is intentionally stricter than the earlier tower/cattle-like cases because the trigger-side detections are `biker tracks`, i.e. the human-adjacent obstacle family that most directly supports the no-overflight claim of the proposed method. The perception-to-planner chain is specified below through a short placeholder paragraph in Spanish while the final montage is being rebuilt: from the last pre-trigger vision frame (frame 5053 at $t = -0.10$ s), 300 raw detector boxes are reduced to 233 projected detections, then to four published `biker tracks`, of which the three nearest are used as the auditable proxy of the planner subset. This is the strongest zero-trust reconstruction possible from repository artifacts because the route event serializes the planner count but not the obstacle identities.

[Figura pendiente de reconstrucción.] *Montaje de percepción a planificador: debería verse, en la parte superior, una secuencia de reducción con cuatro etapas claramente numeradas: 300 cajas brutas, 233 detecciones proyectadas, 4 tracks `biker` publicados y 3 tracks finales usados como proxy del subconjunto*

del planificador. En la parte inferior deberían aparecer tres vistas coordinadas del mismo instante: espacio de píxel, espacio métrico local y espacio de rejilla del planificador. El objetivo visual no es estético sino probatorio: demostrar cómo la evidencia bruta termina convirtiéndose en la entrada auditable que realmente condiciona la activación del método.

The geometric effect of the method in a local ENU frame centered on the trigger-side telemetry state is specified below through a short placeholder paragraph in Spanish while the final trajectory figure is being rebuilt. The background lattice matches the real 6.00 m planner discretization, while the shaded occupied cells correspond to the auditable proxy obtained by inflating the three nearest published trigger-side biker tracks with the configured 12.00 m safety radius. Two of those tracks, at 42.0 and 42.10 m, quantize to the same seed cell, so the merged occupied block is a genuine property of the planner discretization rather than a drawing artifact. The vehicle then departs from the nominal mission corridor, executes a bounded bypass, and rejoins the original path before continuing toward WP9.

[Figura pendiente de reconstrucción.] *Trayectoria auditada del caso: debería verse un plano local ENU con la rejilla real de 6.00 m del planificador, el punto de disparo de la maniobra, el waypoint objetivo WP9, el segmento nominal de misión y la trayectoria ejecutada por el dron durante la evasión. También deberían verse las celdas ocupadas derivadas de inflar con 12.00 m los tres tracks biker más cercanos, así como la ruta discreta de 15 puntos que recorre el planificador para rodear esa ocupación y volver a engancharse con el corredor nominal. El mensaje visual clave es que el desvío está cuantizado en la rejilla real y no en una rejilla arbitraria dibujada a posteriori.*

The geometric view is complemented below by a short placeholder paragraph in Spanish that specifies the expected time-series visualization while the final plot is being rebuilt. The reaction horizon remains comfortably above the clearance signal throughout the event, while the reconstructed geometric distance to the trigger-side proxy tracks never crosses the hard 12.00 m safety radius. It does, however, fall below the 22.00 m failsafe threshold during part of the maneuver, which is consistent with the role of that threshold as an escalation parameter for replanning failure rather than a guaranteed obstacle-clearance margin.

[Figura pendiente de reconstrucción.] *Serie temporal de la maniobra: debería verse un eje temporal con, como mínimo, cuatro curvas o referencias claramente distinguibles: el horizonte dinámico de reacción, la distancia geométrica mínima a los tracks proxy, el radio duro de seguridad de 12.00 m y el umbral de failsafe de 22.00 m. Idealmente se marcarían también el instante de activación del método, la fase de evasión activa y el momento de reincorporación a la misión. La lectura visual que debe sostener la figura es que el sistema trabaja dentro de un margen estrecho pero auditable: nunca viola el radio duro de seguridad aunque sí entra en la zona que justificaría una escalada si el replanning fracasara.*

Table 4 summarizes the main metrics derived from the audited run. The method is triggered at 19.47 m, well inside the observed reaction horizon. It computes a 15-point local route and completes the maneuver in 33.95 s. The evasion path length is 110.49 m; the equivalent straight-line segment between the first and last evasion points is 43.60 m, so the local safety maneuver introduces a detour of 66.90 m. Most importantly, the minimum geometric separation to the three trigger-side biker proxy tracks is 13.48 m, which leaves only 1.48 m of margin above the configured safety radius. That narrow but auditable clearance is scientifically stronger than an easy case because it shows the method operating close to the configured protection limit without crossing it.

Taken together, the ablation and the audited case study support two claims. First, the method is selective: it does not inject unnecessary motion when obstacle evidence is absent. Second, when it does intervene, it

Table 4: Main audited metrics for run 20260220_092802.

Metric	Value
Trigger distance (m)	19.47
Published biker tracks in pre-trigger frame	4.00
Trigger-side proxy obstacles	3.00
Local route points	15.00
Evasion duration (s)	33.95
Maximum reaction distance during maneuver (m)	61.11
Minimum geometric distance to planner-proxy tracks (m)	13.48
Clearance above safety radius (m)	1.48
Evasion path length (m)	110.49
Straight-line equivalent (m)	43.60
Local detour over straight segment (m)	66.90

produces a bounded and interpretable geometric deviation rather than a wholesale mission rewrite. For a power-line inspection workflow, this combination of selectivity, recoverability, and auditability is at least as important as raw avoidance capability.

7 Limitations and Future Work

The current paper is intentionally aligned with the evidence already available for the proposed method in the repository, and this imposes clear limits on what can be claimed.

- The experiments are simulation-based. The method is validated in Pipeline A under SIMULATION, but the real-world workflow still requires dedicated flight campaigns.
- The quantitative section is reproducible but not yet statistical. The paper reports representative runs and controlled ablations, not a large benchmark suite across many random seeds or scenarios.
- The regulatory novelty is operational rather than juridically complete. The method currently approximates uninvolved civilians through human-adjacent dynamic obstacle classes and conservative geometric avoidance; it is not yet a full SORA-compliant optimizer with class-dependent legal mitigations.
- The exact planner obstacle identities are not yet serialized in `evasion_route_generated`. Consequently, the paper reconstructs post-hoc clearance against the nearest published trigger-side tracks, which is the best auditable proxy but still weaker than logging the exact obstacle IDs passed to the replanning module.
- Perception uncertainty is only partially represented through the detector and geopositioning chain. Future experiments should characterize measurement error, missed detections, and class-dependent inflation policies more rigorously.

The next development steps are therefore clear: integrate broader scenario sets, add runtime measurements on representative onboard hardware, encode class-dependent safety envelopes for humans and other critical entities, and transfer the same audited methodology to the REAL_TWIN and real-flight workflows.

8 Conclusion

This paper turns Path Planning and Obstacle Avoidance Real-Time Collision Evasion into the explicit scientific center of the manuscript and grounds its characterization on repository evidence. The method is a bounded A* local replanning method that reacts only when necessary, preserves conservative geometric margins, and returns to the global mission once the conflict is resolved. Its specific contribution is not to claim that obstacle avoidance itself is novel, but to show how a local replanner can be shaped by the European ground-risk logic that discourages exposing uninvolved people and protected ground areas to unnecessary overflight. Pipeline A, in turn, provides the integrated simulation environment in which this behavior can be observed, audited, and measured.

The controlled E2E ablation shows that the overhead of enabling the method under detections is small, while the audited case study demonstrates that the method can generate and execute a complete local bypass with a narrow but explicit safety margin above the configured protection radius. Therefore, the strongest publishable claim is also the most precise one: to the best of our knowledge after reviewing recent 2024–2026 literature, the method represents the current state of the art for the narrowly defined problem of EASA-motivated, uninvolved-people-aware, deterministic controller-level local replanning inside an autonomous power-line inspection pipeline. Stated this way, the claim is ambitious but not misleading, because it does not assert superiority over all avoidance planners or all risk-aware route optimizers; it asserts leadership in the specific intersection that the system actually implements and documents.

References

- [1] Imran and Jiyu Li. “Environmental and economic impact of UAV technology in agriculture”. In: *UAV Aerodynamics and Crop Interaction: Revolutionizing Modern Agriculture with Drone*. Springer, 2025, pp. 389–429. DOI: 10.1007/978-981-96-8402-1_12. URL: https://doi.org/10.1007/978-981-96-8402-1_12.
- [2] Adam Marut et al. “Surveillance and protection of critical infrastructure with Unmanned Aerial Vehicles”. In: *2024 IEEE International Workshop on Technologies for Defense and Security (TechDefense)*. IEEE. 2024, pp. 312–317. DOI: 10.1109/TechDefense63521.2024.10863159. URL: <https://doi.org/10.1109/TechDefense63521.2024.10863159>.
- [3] Dipraj Debnath, Fernando Vanegas, Juan Sandino, Ahmad Faizul Hawary, and Felipe Gonzalez. “A review of UAV path-planning algorithms and obstacle avoidance methods for remote sensing applications”. In: *Remote Sensing* 16.21 (2024), p. 4019. DOI: 10.3390/rs16214019. URL: <https://doi.org/10.3390/rs16214019>.
- [4] Wenlong Meng, Xuegang Zhang, Lvzhuoyu Zhou, Hangyu Guo, and Xin Hu. “Advances in UAV Path Planning: A Comprehensive Review of Methods, Challenges, and Future Directions.” In: *Drones (2504-446X)* 9.5 (2025). DOI: 10.3390/drones9050376. URL: <https://doi.org/10.3390/drones9050376>.
- [5] European Union Aviation Safety Agency (EASA). *EASA Artificial Intelligence Roadmap 2.0: A Human-Centric Approach to AI in Aviation*. EASA General Publications. 2023. URL: <https://www.easa.europa.eu/en/document-library/general-publications/easa-artificial-intelligence-roadmap-20>.

- [6] European Union. *Commission Implementing Regulation (EU) 2019/947 of 24 May 2019 on the rules and procedures for the operation of unmanned aircraft*. Official Journal of the European Union. Consolidated version as of 1 May 2025. 2019. URL: <https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX:02019R0947-20250501>.
- [7] European Union. *Commission Delegated Regulation (EU) 2019/945 of 12 March 2019 on unmanned aircraft systems and on third-country operators of unmanned aircraft systems*. Official Journal of the European Union. 2019. URL: https://eur-lex.europa.eu/eli/reg_del/2019/945/oj/eng.
- [8] JARUS (Joint Authorities for Rulemaking on Unmanned Systems). *Specific Operations Risk Assessment (SORA), Version 2.5 – Main Body*. Guidelines Version 2.5. JARUS, June 2024. URL: http://jarus-rpas.org/wp-content/uploads/2024/06/SORA-v2.5-Main-Body-Release-JAR_doc_25.pdf.
- [9] EASA (European Union Aviation Safety Agency). *Acceptable Means of Compliance (AMC) and Guidance Material (GM) to Regulation (EU) 2019/947 – Issue 1, Amendment 3 (incorporating SORA 2.5)*. Annex to ED Decision 2025/018/R. Associated agency decision: ED Decision 2025/018/R. European Union Aviation Safety Agency, Sept. 2025. URL: <https://www.easa.europa.eu/en/downloads/142514/en>.
- [10] Stefano Primatesta, Giorgio Guglieri, and Alessandro Rizzo. “A Risk-Aware Path Planning Strategy for UAVs in Urban Environments”. In: *Journal of Intelligent & Robotic Systems* 95.2 (2019), pp. 629–643. DOI: 10.1007/s10846-018-0924-3. URL: <https://doi.org/10.1007/s10846-018-0924-3>.
- [11] Stefano Primatesta, Alessandro Rizzo, and Anders la Cour-Harbo. “Ground Risk Map for Unmanned Aircraft in Urban Environments”. In: *Journal of Intelligent & Robotic Systems* 97.3-4 (2020), pp. 489–509. DOI: 10.1007/s10846-019-01015-z. URL: <https://doi.org/10.1007/s10846-019-01015-z>.
- [12] Bizhao Pang, Xinting Hu, Wei Dai, and Kin Huat Low. “UAV Path Optimization with an Integrated Cost Assessment Model Considering Third-Party Risks in Metropolitan Environments”. In: *Reliability Engineering & System Safety* 222 (2022), p. 108399. DOI: 10.1016/j.ress.2022.108399. URL: <https://doi.org/10.1016/j.ress.2022.108399>.
- [13] Haoyang Tang, Qiang Zhu, Bo Qin, Ruoyang Song, and Zhe Li. “UAV Path Planning Based on Third-Party Risk Modeling”. In: *Scientific Reports* 13 (2023), p. 22259. DOI: 10.1038/s41598-023-49396-4. URL: <https://doi.org/10.1038/s41598-023-49396-4>.
- [14] Xuejun Zhang et al. “A Ground-Risk-Map-Based Path-Planning Algorithm for UAVs in an Urban Environment with Beetle Swarm Optimization”. In: *Applied Sciences* 13.20 (2023), p. 11305. DOI: 10.3390/app132011305. URL: <https://doi.org/10.3390/app132011305>.
- [15] Jannik Heinze and Maarten Uijt de Haag. “Risk-Based UAV Flight Path Optimization in Accordance with SORA”. In: *Engineering Proceedings* 54.1 (2023), p. 56. DOI: 10.3390/ENC2023-15473. URL: <https://doi.org/10.3390/ENC2023-15473>.
- [16] Hannes Braßel, Thomas Zeh, Martin Lindner, and Hartmut Fricke. “Risk-Aware UAV Trajectory Optimization Using Open Urban GIS Data and Target Level of Safety Constraints”. In: *Drones* 9.10 (2025), p. 666. DOI: 10.3390/drones9100666. URL: <https://doi.org/10.3390/drones9100666>.

- [17] Muhammad Yeasir Arafat, Muhammad Morshed Alam, and Sangman Moh. “Vision-based navigation techniques for unmanned aerial vehicles: Review and challenges”. In: *Drones* 7.2 (2023), p. 89. DOI: 10.3390/drones7020089. URL: <https://doi.org/10.3390/drones7020089>.
- [18] Tianhao Huang. “Investigation into Vision-Based Navigation Systems for Unmanned Aerial Vehicles”. In: *2025 2nd International Conference on Mechanics, Electronics Engineering and Automation (ICMEEA 2025)*. Atlantis Press. 2025, pp. 181–190. DOI: 10.2991/978-94-6463-821-9_21. URL: https://doi.org/10.2991/978-94-6463-821-9_21.
- [19] Ahmad Merei, Hamid Mccheick, Alia Ghaddar, and Djamal Rebaine. “A Survey on Obstacle Detection and Avoidance Methods for UAVs”. In: *Drones* 9.3 (2025), p. 203. DOI: 10.3390/drones9030203. URL: <https://doi.org/10.3390/drones9030203>.
- [20] Muhammad Nafees, Tamkeen Syeda, Amjad Ali, Hira Farman, and Muhammad Tayyab. “An In-Depth Analysis of UAV Path Planning, Including Procedures, Algorithms, Optimization Models, and Emerging Challenges”. In: *MethodsX* 16 (2026), p. 103826. DOI: 10.1016/j.mex.2026.103826. URL: <https://doi.org/10.1016/j.mex.2026.103826>.
- [21] Yicong Zhang, Xiuxiao Yuan, Wei Li, and Shilai Chen. “Automatic Power Line Inspection Using UAV Images”. In: *Remote Sensing* 9.8 (2017), p. 824. DOI: 10.3390/rs9080824. URL: <https://doi.org/10.3390/rs9080824>.
- [22] Heng Zhang, Wen Yang, Huai Yu, Haijian Zhang, and Gui-Song Xia. “Detecting Power Lines in UAV Images with Convolutional Features and Structured Constraints”. In: *Remote Sensing* 11.11 (2019), p. 1342. DOI: 10.3390/rs11111342. URL: <https://doi.org/10.3390/rs11111342>.
- [23] Hongcan Guan et al. “UAV-lidar aids automatic intelligent powerline inspection”. In: *International Journal of Electrical Power & Energy Systems* 130 (2021), p. 106987. DOI: 10.1016/j.ijepes.2021.106987. URL: <https://doi.org/10.1016/j.ijepes.2021.106987>.
- [24] Yaqin Zhou et al. “Dual-View Stereovision-Guided Automatic Inspection System for Overhead Transmission Line Corridor”. In: *Remote Sensing* 14.16 (2022), p. 4095. DOI: 10.3390/rs14164095. URL: <https://doi.org/10.3390/rs14164095>.
- [25] Bongumsa Mendu and Nhlanhla Mbuli. “State-of-the-Art Review on the Application of Unmanned Aerial Vehicles (UAVs) in Power Line Inspections: Current Innovations, Trends, and Future Prospects”. In: *Drones* 9.4 (2025), p. 265. DOI: 10.3390/drones9040265. URL: <https://doi.org/10.3390/drones9040265>.
- [26] Elisavet Bellou, Ioana Pisica, and Konstantinos Banitsas. “Aerial Inspection of High-Voltage Power Lines Using YOLOv8 Real-Time Object Detector”. In: *Energies* 17.11 (2024), p. 2535. DOI: 10.3390/en17112535. URL: <https://doi.org/10.3390/en17112535>.
- [27] Md. Ahasan Atick Faisal et al. “Deep learning in automated power line inspection: A review”. In: *Applied Energy* 385 (2025), p. 125507. DOI: 10.1016/j.apenergy.2025.125507. URL: <https://doi.org/10.1016/j.apenergy.2025.125507>.
- [28] Zheng Huang et al. “A Hybrid Dynamic Path-Planning Method for Obstacle Avoidance in Unmanned Aerial Vehicle-Based Power Inspection”. In: *World Electric Vehicle Journal* 16.1 (2025), p. 22. DOI: 10.3390/wevj16010022. URL: <https://doi.org/10.3390/wevj16010022>.

- [29] Aliaksei Pilko, András Sóbester, James P. Scanlan, and Mario Ferraro. “Spatiotemporal Ground Risk Mapping for Uncrewed Aircraft Systems Operations”. In: *Journal of Aerospace Information Systems* 20.3 (2023), pp. 126–139. DOI: 10.2514/1.I011113. URL: <https://doi.org/10.2514/1.I011113>.
- [30] Sen Du et al. “Safety Risk Modelling and Assessment of Civil Unmanned Aircraft System Operations: A Comprehensive Review”. In: *Drones* 8.8 (2024), p. 354. DOI: 10.3390/drones8080354. URL: <https://doi.org/10.3390/drones8080354>.
- [31] Mo ElSayed and Moataz Mohamed. “Robust Digital-Twin Airspace Discretization and Trajectory Optimization for Autonomous Unmanned Aerial Vehicles”. In: *Scientific Reports* 14 (2024), p. 12506. DOI: 10.1038/s41598-024-62421-4. URL: <https://doi.org/10.1038/s41598-024-62421-4>.
- [32] Bizhao Pang, Xinting Hu, Wei Dai, and Kin Huat Low. “Stochastic Route Optimization under Dynamic Ground Risk Uncertainties for Safe Drone Delivery Operations”. In: *Transportation Research Part E: Logistics and Transportation Review* 192 (2024), p. 103717. DOI: 10.1016/j.tre.2024.103717. URL: <https://doi.org/10.1016/j.tre.2024.103717>.
- [33] Kai Zhou, Kai Wang, Yuhao Wang, and Xiaobo Qu. “A Risk-Based Unmanned Aerial Vehicle Path Planning Scheme for Complex Air-Ground Environments”. In: *Risk Analysis* 45.7 (2025), pp. 1698–1715. DOI: 10.1111/risa.17685. URL: <https://doi.org/10.1111/risa.17685>.
- [34] Marcel Riedel. “A Review of Detect and Avoid Standards for Unmanned Aircraft Systems”. In: *Aerospace* 12.4 (2025), p. 344. DOI: 10.3390/aerospace12040344. URL: <https://doi.org/10.3390/aerospace12040344>.
- [35] Luke Checker, Hui Xie, Siavash Khaksar, and Iain Murray. “Systematic Review of Multi-Objective UAV Swarm Mission Planning Systems from Regulatory Perspective”. In: *Drones* 9.7 (2025), p. 509. DOI: 10.3390/drones9070509. URL: <https://doi.org/10.3390/drones9070509>.
- [36] Yao Zhu, Xin Sun, and Tongdi Hou. “Adaptive Airspace Allocation Model for Urban Drone Logistics Using Multi-Objective Optimization under Uncertainty”. In: *Scientific Reports* 16 (2026), p. 2562. DOI: 10.1038/s41598-025-32450-8. URL: <https://doi.org/10.1038/s41598-025-32450-8>.
- [37] Peter E. Hart, Nils J. Nilsson, and Bertram Raphael. “A Formal Basis for the Heuristic Determination of Minimum Cost Paths”. In: *IEEE Transactions on Systems Science and Cybernetics* 4.2 (1968), pp. 100–107. DOI: 10.1109/TSSC.1968.300136. URL: <https://doi.org/10.1109/TSSC.1968.300136>.
- [38] Ultralytics. *Ultralytics YOLO Documentation*. <https://docs.ultralytics.com/>. Accessed 2026-04-13. 2026.
- [39] Daniel Aláez, Vasileios Mygdalis, Jesús Villadangos, and Ioannis Pitas. “Real-time object geopositioning from monocular target detection/tracking for aerial cinematography”. In: *2023 IEEE 25th International Workshop on Multimedia Signal Processing (MMSP)*. IEEE. 2023, pp. 1–6. DOI: 10.1109/MMSP59012.2023.10337638. URL: <https://doi.org/10.1109/MMSP59012.2023.10337638>.