

530 S. Henderson Rd. Suite F King of Prussia, PA 19406 T: 800.215.8563 F: 888.576.8524 jeffL@rosito-bisani.com

Espresso Machine Installation Requirements (Three Group Espresso Machine)

Supplied by Customer

Plumbing

-Cold Water Line

-On/Off Shut-Off Valve with 3/8 inch compression fitting within 6 feet of espresso machine

-Open Floor Sink Drain within 4 feet of espresso machine

Electric

- -Power
 - -220 Volts
 - -30 Amp Dedicated Circuit
- -Wall Receptacle
 - Receptacle (Twist and Lock): NEMA L630R
 - -Within 4 feet of espresso machine

*(If there is an existing 220 volt wall receptacle....we will need the existing plug or NEMA number to match accordingly)

Drilling

-2 to 3 inch diameter hole ONLY on hard surfaces such as marble, granite, stainless steel, polished metal, tile, and other custom finishes.

Supplied by Rosito Bisani

Qualified Installation/Service Technician

Installation Materials

- -All necessary hoses, fittings, pipes to connect machine to shut-off valve
- -Plug to match receptacle
- -Installation of Water Softener (if purchased through Rosito Bisani)

Drilling

-Wood surfaces

Please feel free to have your plumber or electrician contact us with any questions, concerns, or comments, regarding the installation requirements.

East Coast Office: 800-215-8563 West Coast Office: 800-848-4444

Rosito-Bisani.com

East Coast Office: 800-215-8563 West Coast Office: 800-848-4444

SAMPLE SET UP

208/230 Voltage Application

