



Pasta Cooker  
High BTU  
CPG-2



**STANDARD FEATURES**

- Double chamber in 18/10 stainless steel
- 304 and 316 series stainless steel construction.
- 12 gallon water capacity per tank chamber.
- Dual Burners Per Tank Chamber.
- Triple fiberglass insulation on all sides.
- Seamless stainless steel baskets with specially designed perforated holes.
- Multiple basket size configurations.
- Specially designed burner creates a water current flow that lifts starch carrying it out to the overflow drain.
- Automatic pilot.
- Top mount water faucet for continuous clean water flow.
- Low water safety cut-off.
- 80,000 BTU per chamber burners.
- Adjustable legs.

**OPTIONS**

- Single chamber.
- Triple chamber.
- Multiple basket size configuration in stainless steel.
- Casters.




ITEM:

PROJECT:

DATE:

Pasta Cooker  
High BTU  
CPG-2

# Pasta Cooker High BTU CPG-2



MODEL	UNIT DIMENSION W x D x H	TANK DIMENSION W x D x H	CAPACITY (GAL.)	WT.	SHIP WT.	K.W.	V.	PH.	HZ.	AMPS	H <sub>2</sub> O	GAS	DRAIN	BTU	WATER COLUMN
CPG 2 (GAS)	31.5" x 37.25 x 45	12" x 20 x 12	24 gal.	280 lbs.	300 lbs.	X	X	X	X	X	3/4"	3/4" (2 inlets)	1 1/4" (2 outlets)	80,000 (per side)	4 1/2"

**Rosito Bisani Imports, Inc.**  
940 South La Brea Avenue, Los Angeles CA, 90036  
Tel: 323-937-1888 • Fax: 323-938-0728 • Toll Free: 1-800-848-4444  
E-mail: sales@rosito-bisani.com  
**www.rosito-bisani.com**  
530 South Henderson Road, Suite F, King of Prussia PA, 19406  
Tel: 610-265-5950 • Fax: 888-576-8524

