



530 S. Henderson Rd. Suite F King of Prussia, PA 19406
T: 800.215.8563 F: 888.576.8524 jeffL@rosito-bisani.com

Espresso Machine Installation Requirements Two Group Espresso Machine

Supplied by Customer

Plumbing

- Cold Water Line
- On/Off Shut-Off Valve with 3/8 inch compression fitting within 6 feet of espresso machine (#3)

- Open Floor Sink Drain within 4 feet of espresso machine (#4)

Electric

- Power

 - 220 Volts

 - 20 Amp Dedicated Circuit

- Wall Receptacle

 - Receptacle : NEMA 6-20R

 - Within 4 feet of espresso machine (#1)

 - 110v Receptacle within 4 feet of machine for grinder (dedicated circuit) (#5)

*(If there is an existing 220 volt wall receptacle....we will need the existing plug or NEMA number to match accordingly)

Drilling

- 2 to 3 inch diameter hole ONLY on hard surfaces such as marble, granite, stainless steel, polished metal, tile, and other custom finishes. (#2)

Supplied by Rosito Bisani

Qualified Installation/Service Technician

Installation Materials

- All necessary hoses, fittings, pipes to connect machine to shut-off valve

- Plug to match receptacle

- Installation of Water Softener (if purchased through Rosito Bisani)

Drilling

- Wood or laminated surfaces only

Please feel free to have your plumber or electrician contact us with any questions, concerns, or comments, regarding the installation requirements.

East Coast Office: 800-215-8563
West Coast Office: 800-848-4444

Rosito-Bisani.com

East Coast Office: 800-215-8563

West Coast Office: 800-848-4444

SAMPLE SET UP

208/230 Voltage Application

