



309 S. Cloverdale Suite C-41  
Seattle, WA. 98108  
www.synesso.com  
info@synesso.com  
206.764.0600

# HYDRA 3 GROUP INSTALLATION CHECKLIST



## Quick Reference Specifications:

**Dimensions:** 21"(H) 43"(W) 23"(D)

**Weight:** 215 lbs (full)



**Electrical Requirements:** Volts: 208-240/Amps: 40

**Plumbing Requirements:** Flow: 30GPH (minimum) Pressure: 35psi (minimum) Hardness: 3 GPG (maximum) Fitting: 3/8" MPT w/shut-off

**Drainage Requirements:** Open gravity drain of 1.25" ID (min) within 4 feet of machine.

The following information will assist you in preparing your location for the installation of your equipment. Please make sure everything is prepared to these specifications *prior* to scheduling your installation. Once everything is complete, check the appropriate **boxes** and sign the bottom of the form.

### COUNTER SPACE REQUIREMENTS:



### WATER SUPPLY REQUIREMENTS:



\*Machine must be supplied with a minimum of 30 Gallons per hour @ 35 PSI.

\*A 3/8" MPT is required for hook-up. A shut-off valve must be installed.

\*If water hardness levels exceed 3 GPG (Grains per Gallon) a water softener **MUST** be installed.

Exceeding these levels will void the manufacturer's warranty. (Check appropriate box below)

- ☐ I have tested the water hardness and it is 3 GPG or less (see above).
- ☐ I already have a suitable water softener and its output is 3 GPG or less (see above).
- ☐ I have tested the water hardness level and it is written above. Please supply me with the appropriate water softener at time of installation.

### ELECTRICAL REQUIREMENTS:

**208-240V/40AMP/6700WATT**

Dedicated 40 AMP Plug within 4 feet of installation location. **PLEASE NOTE:** The machine will not be supplied with a Cord Cap (Male plug).

### DRAINAGE REQUIREMENTS:

Access to open gravity drain no smaller than 1.25" ID (Inner Diameter). Drain **MUST** be within 4 feet of the machine for proper drainage.