



East Coast Office: 800-215-8563  
West Coast Office: 800-848-4444  
Rosito-Bisani.com

## **Espresso Machine Installation Requirements One Group Espresso Machine**

### **Supplied by Customer**

#### **Plumbing**

- Cold Water Line
  - On/Off Shut-Off Valve with 3/8 inch compression fitting within 6 feet of espresso machine (#3)
- Open Floor Sink Drain within 4 feet of espresso machine (#4)

#### **Electric**

- Power
  - 110 Volts
  - 20 Amp Dedicated Circuit
- Wall Receptacle: NEMA 5-20R
  - Within 4 feet of espresso machine (#1)
  - 110v Receptacle within 4 feet of machine for grinder (dedicated circuit) (#5)

#### **Drilling**

- 2 to 3 inch diameter hole ONLY on hard surfaces such as marble, granite, stainless steel, polished metal, tile, and other custom finishes. (#2)

### **Supplied by Rosito Bisani**

### **Qualified Installation/Service Technician**

#### **Installation Materials**

- All necessary hoses, fittings, pipes to connect machine to shut-off valve
- Plug to match receptacle
- Installation of Water Softener (if purchased through Rosito Bisani)

#### **Drilling**

- Wood surfaces

**Please feel free to have your plumber or electrician contact us with any questions, concerns, or comments, regarding the installation requirements.**

Rosito-Bisani.com

East Coast Office: 800-215-8563

West Coast Office: 800-848-4444

## SAMPLE SET UP

**110**

**Voltage Application**

DIAGRAM DOES NOT REPRESENT ACTUAL DIMENSIONS

