

# Rotary Gas-Fired Oven Cupola Dome Mosaic - CM FGR130 Morello Forni



#### STANDARD FEATURES

- Gas Cupola Mosaic Dome Oven with rotating cooking bedplate chamber.
- Constructed from high refractory premium grade alumina.
- Oven walls average 7" thickness with completely sealed wall enclosures.
- Double gas burner system in stainless steel.
- Internal dome burner and under bedplate gas burner system.
- Thermal insulation made of mineral fibre with high insulating properties; minimum 6" from top to bottom requiring 3" clearance to combustible materials.
- INTELTOUCH-MF10 Touch Screen Electronic Control System.
- Independent intuitive digital safety controls.
- Programmable time, speed, temperature and flame control system.
- Optimized performance and large productivity.
- Emergency Stop push button.
- 220/60/1

$\overline{}$	<b>D</b> -	-1	$\overline{}$	N I
U	М	ш	O	IN

Mosaic Natural Stone Colors

$H \vdash M$	
--------------	--


PROJECT:


DATE:


Rotary Gas-Fired Oven Cupola Dome Mosaic - CM FGR130



## Rotary Gas-Fired Oven Cupola Dome Mosaic - CM FGR130 Morello Forni







#### **FLUE CONNECTION**

**FLUE CONNECTION**All ovens are provided with an exhaust flue collar  $\frac{1}{2}$ " or  $\frac{2}{2}$ " in height and 8" or 10" nominal diameter depending on model. The flue collar  $(\emptyset H)$  is located on oven top to provide a secure connection to the chimney. The oven flue collar is designed to be connected to chimney listed to UL-103HT. When working on gas only ovens, the oven is suitable for connection to Type B Gas Vent when used with the draft hood. When burning wood, an independent Flue evacuation system is required.

## **ELECTRICAL CONNECTION**

Verify the power supply has the same rating as the oven.

These ovens require make-up air to replace combustion air and excess air taken out by the flue. Always check for adequate openings to allow required make-up air flow in. Check table included in operations manual.

Model/	FGR130	Cooking Time				
Specifications	(51)					
Power	220/60/1	Capacity	(10) x 11"			
Gas Fitting (inches)	3/4	Individual Pizza	2 ~ 3 minutes			
BTU	136,000					
			4 ~ 6 minutes			
Weight (lbs.)	5,291	Pan Pizza				

Model/ Dimension (inches)	A	В	С	D	E	F	ØH	ı	L	М	N	0
FGR-130 (51)	75	79	44	12	41	81	10	45.5	32.5	48	10	25.5



#### Rosito Bisani Imports, Inc.

940 South La Brea Avenue, Los Angeles CA, 90036 Tel: 323-937-1888 • Fax: 323-938-0728 • Toll Free: 1-800-848-4444 E-mail: sales@rosito-bisani.com

### www.rosito-bisani.com

530 South Henderson Road, Suite F, King of Prussia PA, 19406 Tel: 610-265-5950 • Fax: 888-576-8524



