



East Coast Office: 800-215-8563  
West Coast Office: 800-848-4444  
Rosito-Bisani.com

## **Espresso Machine Installation Requirements Two Group Espresso Machine**

### **Supplied by Customer**

#### **Plumbing**

- Cold Water Line
- On/Off Shut-Off Valve with 3/8 inch compression fitting within 6 feet of espresso machine (#3)

- Open Floor Sink Drain within 4 feet of espresso machine (#4)

#### **Electric**

- Power

- 220 Volts

- 20 Amp Dedicated Circuit

- Wall Receptacle

- Receptacle : NEMA L6-20R

- Within 4 feet of espresso machine (#1)

- 110v Receptacle within 4 feet of machine for grinder (dedicated circuit) (#5)

\*(If there is an existing 220 volt wall receptacle....we will need the existing plug or NEMA number to match accordingly)

#### **Drilling**

- 2 to 3 inch diameter hole ONLY on hard surfaces such as marble, granite, stainless steel, polished metal, tile, and other custom finishes. (#2)

### **Supplied by Rosito Bisani**

### **Qualified Installation/Service Technician**

#### **Installation Materials**

- All necessary hoses, fittings, pipes to connect machine to shut-off valve

- Plug to match receptacle

- Installation of Water Softener (if purchased through Rosito Bisani )

#### **Drilling**

- Wood or laminated surfaces only

**Please feel free to have your plumber or electrician contact us with any questions, concerns, or comments, regarding the installation requirements.**

Rosito-Bisani.com

East Coast Office: 800-215-8563

West Coast Office: 800-848-4444

# SAMPLE SET UP

**208/230**

**Voltage Application**

