



Rotary Gas-Fired Oven Cupola Dome Basic FGR130CB



STANDARD FEATURES

- Gas Cupola Basic Dome Oven with rotating cooking bedplate chamber.
- Constructed from high refractory premium grade alumina.
- Oven walls average 7" thickness with completely sealed wall enclosures.
- Double gas burner system in stainless steel.
- Internal dome burner and under bedplate gas burner system.
- Thermal insulation made of mineral fibre with high insulating properties; minimum 6" from top to bottom requiring 3" clearance to combustible materials.
- INTELTOUCH-MFI10 Touch Screen Electronic Control System.
- Independent intuitive digital safety controls.
- Programmable time, speed, temperature and flame control system.
- Optimized performance and large productivity.
- Emergency Stop push button.
- 220/60/1

OPTION

Custom Colors RAL




ITEM:

PROJECT:

DATE:

**Rotary Gas-Fired Oven
Cupola Dome Basic
FGR130CB**

Rotary Gas-Fired Oven Cupola Dome Basic FGR130CB



Model/ Specifications	FGR130CB (51)
Power	220/60/1
Gas Fitting (inches)	3/4
BTU	136,000
Weight (lbs.)	5,291

Cooking Time	
Capacity	(10) x 11"
Individual Pizza	2 ~ 3 minutes
Pan Pizza	4 ~ 6 minutes

Model/ Dimension (inches)	A	B	C	D	E	F	ØH	I	L	M	N	O
FGR-130CB (51)	75	79	44	12	41	81	10	45.5	32.5	48	10	25.5



Rosito Bisani Imports, Inc.
940 South La Brea Avenue, Los Angeles CA, 90036
Tel: 323-937-1888 • Fax: 323-938-0728 • Toll Free: 1-800-848-4444
E-mail: sales@rosito-bisani.com

www.rosito-bisani.com

530 South Henderson Road, Suite F, King of Prussia PA, 19406
Tel: 610-265-5950 • Fax: 888-576-8524

GAS-FIRED

