

## Rotary Gas-Fired Oven Standard FGR110ST



- Gas oven with rotating cooking bedplate chamber.
- Constructed from high refractory premium grade alumina with heavy metal enclosure.
- Oven walls average 7" thickness with completely sealed wall enclosures.
- Double gas burner system in stainless steel.
- Internal dome burner and under bedplate gas burner system.
- Thermal insulation made of mineral fibre with high insulating properties; minimum 6" from top to bottom requiring 3" clearance to combustible materials.
- INTELTOUCH-MF10 Touch Screen Electronic Control System.
- Independent intuitive digital safety controls.
- Programmable time, speed, temperature and flame control system.
- Optimized performance and large productivity.
- Emergency Stop push button.
- 220/60/1

4-			
ш	ı ⊢	١N	η.
•	_		•••


PROJECT:


DATE:


**Rotary Gas-Fired Oven** Standard FGR110ST



## Rotary Gas-Fired OvenStandard FGR110ST







Model/	FGR110ST	Cooking Time			
Specifications	(43)				
Power	220/60/1	Capacity	(7) x 11"		
Gas Fitting (inches)	3/4	Individual Pizza	2 ~ 3 minutes		
BTU	136,000	==			
Weight (lbs.)	4,200	Pan Pizza	4 ~ 6 minutes		

Model/ Dimension (inches)	A	В	С	D	E	F	ØH	ı	L	М	Ν	0
FGR-110ST (43)	65.5	70	40.5	12	37	76.5	10	45.5	32.5	48	10	21.5



## Rosito Bisani Imports, Inc.

940 South La Brea Avenue, Los Angeles CA, 90036
Tel: 323-937-1888 • Fax: 323-938-0728 • Toll Free: 1-800-848-4444
E-mail: sales@rosito-bisani.com

## www.rosito-bisani.com

530 South Henderson Road, Suite F, King of Prussia PA, 19406 Tel: 610-265-5950 • Fax: 888-576-8524

