



SYNESSO

Synesso Hydra-Hybrid Specifications

| <u>Model</u> | <u>1 Group</u> | <u>2 Group</u> | <u>3 Group</u> |
|---|-----------------------|-----------------------|-----------------------|
| Voltage, Single Phase | 220 | 220 | 220 |
| Hertz | 50 / 60 | 50 / 60 | 50 / 60 |
| Amps - max draw | 16 | 32 | 40 |
| Brew & Steam Specifications: | | | |
| Watts per Element, Steam Tank | 1000 x 2 | 2000 x 2 | 2500 x 2 |
| Total Steam Element Wattage | 2000 | 4000 | 5000 |
| Steam Tank Capacity (Liters) | 3.2 | 7.7 | 12.3 |
| Watts per Element, Brew Tank | 700 | 700 x 2 | 700 x 3 |
| Brew Tank Capacities (Liters) | 1.9 | 1.9 x 2 | 1.9 x 3 |
| Machine Dimensions: | | | |
| | Inches / mm | Inches / mm | Inches / mm |
| Height (Steam Wand 21", Handle 20.5") | 18" / 457 | 18" / 457 | 18" / 457 |
| Width (Steam Handle to Handle add 3") | 18" / 457 | 29" / 736 | 40" / 1016 |
| Depth | 23" / 584 | 23" / 584 | 23" / 584 |
| Weights & Dimensions: | | | |
| | Lbs / Kgs | Lbs / Kgs | Lbs / Kgs |
| Machine Weight, Empty | 106 / 48 | 154 / 70 | 190 / 86 |
| Shipping Weight (approximate) | 190 / 86 | 260 / 118 | 324 / 147 |
| Boxed Dimensions: L" x W" x H" | 42" x 30" x 31" | 42" x 32" x 31" | 50" x 32" x 31" |
| Boxed Dimensions: L x W x H m/m | 508x762x787 | 1042x762x787 | 1245x813x787 |
| Plumbing (Compression) | 3/8" OD | 3/8" OD | 3/8" OD |

- Certified by ETL for Sanitation to NSF / ANSI Standard 4
- Certified by ETL for Electrical Safety to ANSI / UL Standard 197
- Certified by ETL for Electrical Safety to CSA Standard C22.2 No. 109
- CE Compliant (By request)
- C-Tick Compliant (By request)

