

Rotary Gas-Fired Oven Cupola Dome Basic FGR150CB



- chamber.
- Constructed from high refractory premium grade alumina.
- Oven walls average 7" thickness with completely sealed wall
- Double gas burner system in stainless steel.
- Internal dome burner and under bedplate gas burner system.
- Thermal insulation made of mineral fibre with high insulating properties; minimum 6" from top to bottom requiring 3" clearance to combustible materials.
- INTELTOUCH-MFI0 Touch Screen Electronic Control System.
- Independent intuitive digital safety controls.
- Programmable time, speed, temperature and flame control system.
- Optimized performance and large productivity.
- 220/60/1

OPT	ION
-----	-----


• Emergency Stop push button.


ITEM:
PROJECT:
DATE:


Rotary Gas-Fired Oven Cupola Dome Basic FGR150CB



Rotary Gas-Fired Oven Cupola Dome Basic FGR150CB







FLUE CONNECTION

All ovens are provided with an exhaust flue collar ½" or 2½" in height and 8" or 10" nominal diameter depending on model. The flue collar (ØH) is located on oven top to provide a secure connection to the chimney. The oven flue collar is designed to be connected to chimney listed to UL-103HT. When working on gas only ovens, the oven is suitable for connection to Type B Gas Vent when used with the draft hood. When burning wood, an independent Flue evacuation system is required.

ELECTRICAL CONNECTIONVerify the power supply has the same rating as the oven.

These ovens require make-up air to replace combustion air and excess air taken out by the flue. Always check for adequate openings to allow required make-up air flow in. Check table included in operations manual.

Model/	FGR150CB	Cooking Time			
Specifications	(59)				
Power	220/60/1	Capacity	(14) x 11"		
Gas Fitting (inches)	3/4	Individual Pizza	2 ~ 3 minutes		
BTU	169,000				
	,		4 ~ 6 minutes		
Weight (lbs.)	6,173	Pan Pizza			

Model/ Dimension (inches)	Α	В	С	D	E	F	ØН	I	L	М	Ν	0
FGR-150CB (59)	83.5	83.5	48	12	45	81	10	49.5	32.5	48	10	29.5



Rosito Bisani Imports, Inc.

940 South La Brea Avenue, Los Angeles CA, 90036 Tel: 323-937-1888 • Fax: 323-938-0728 • Toll Free: 1-800-848-4444 E-mail: sales@rosito-bisani.com

www.rosito-bisani.com

530 South Henderson Road, Suite F, King of Prussia PA, 19406 Tel: 610-265-5950 • Fax: 888-576-8524

