

**Rotating Hybrid  
Gas and Wood Fired Oven - ST  
FGRi110 Morello Forni**



**STANDARD FEATURES**

- Hybrid (wood/gas) oven with rotating cooking bedplate chamber.
- Constructed from high refractory premium grade alumina with heavy metal enclosure and stand.
- Oven walls average 7" thickness with completely sealed wall enclosures.
- Operates gas only, wood only, or combination wood and gas.
- Double gas burner system in stainless steel.
- Internal dome burner and under bedplate gas burner system.
- Thermal insulation made of mineral fibre with high insulating properties; minimum 6" from top to bottom requiring 3" clearance to combustible materials.
- INTELTOUCH-MF10 Touch Screen Electronic Control System.
- Independent intuitive digital safety controls.
- Programmable time, speed, temperature and flame control system.
- Optimized performance and large productivity.
- Emergency push button to stop.
- 220/60/1

**ITEM:**

---

**PROJECT:**


---

**DATE:**

---

**Rotating Hybrid  
Gas and Wood Fired Oven - ST  
FGRi110 Morello Forni**

## Rotating Hybrid Gas and Wood Fired Oven - ST FGRi110 Morello Forni



### FLUE CONNECTION

All ovens are provided with an exhaust flue collar  $\frac{1}{2}$ " or  $2\frac{1}{2}$ " in height and 8" or 10" nominal diameter depending on model. The flue collar (ØH) is located on oven top to provide a secure connection to the chimney. The oven flue collar is designed to be connected to chimney listed to UL-103HT. When working on gas only ovens, the oven is suitable for connection to Type B Gas Vent when used with the draft hood. When burning wood, an independent Flue evacuation system is required.

### ELECTRICAL CONNECTION

Verify the power supply has the same rating as the oven.

### AIR SUPPLY

These ovens require make-up air to replace combustion air and excess air taken out by the flue. Always check for adequate openings to allow required make-up air flow in. Check table included in operations manual.

Model/ Specifications	FGRi110 (47)	Cooking Time	
Power	220/60/1	Capacity	(9) x 11"
Gas Fitting (inches)	$\frac{3}{4}$	Individual Pizza	2 ~ 3 minutes
BTU	136,000	Pan Pizza	4 ~ 6 minutes
Weight (lbs.)	5,070		

Model/ Dimension (inches)	A	B	C	D	E	F	ØH	I	L	M	N	O
FGRi110 (47)	73.5	77.5	44	12	41	76.5	10	45.5	32.5	48	10	25.5



**Rosito Bisani Imports, Inc.**  
940 South La Brea Avenue, Los Angeles CA, 90036  
Tel: 323-937-1888 • Fax: 323-938-0728 • Toll Free: 1-800-848-4444  
E-mail: sales@rosito-bisani.com

**www.rosito-bisani.com**

530 South Henderson Road, Suite F, King of Prussia PA, 19406  
Tel: 610-265-5950 • Fax: 888-576-8524

**GAS-FIRED**

