

INDEX

- ABC finite elements, 268
- Accumulators, 330
- AC currents, 129, 206
- Acoustics, 330
- Actuator(s), magnetic, *see also* Magnetic actuators
 - acceleration of, 147–149
 - definition of, 3, 95
 - finite element analysis of, 49–51. *See also* Maxwell software
 - force of, *see* Magnetic force
 - high speed, 235
 - reciprocating, 284–285
 - size of, 147–149
- Airgap, 33, 37–40, 311, 337–343
- Alternator load dump, 250
- Ampere's Law, 14–17, 33–36
- Analogy(ies), 35–36, 289, 293–295, 328–330
- Apertures, 250–255
- Architecture of VHDL-AMS models, 296–299
- Armature, 39, 95
- Automotive brakes and control, 190–191, 329–330, 348–353
- Automotive sensors, 190–192, 201–206, 224
- Axissymmetric geometry, 56–57

- Bessel function(s), 141, 155
- Bessho DC solenoid
 - flux plot of, 276
 - geometry, 56–58
 - transient operation, 149–150, 155–156, 161–164, 235, 275–279, 293–296, 307, 335–354
- B–H curves, 19–21, 361–365
 - ramp, 156–158, 166–167, 365
 - step, 156–165, 363
- Biomolecular separator, 121–125
- Block diagram, 3–5, 295, 301–304

- Boundary conditions, 48–52
- Brake(s), 117, 327–328

- Cable, coaxial, 256
- CAN bus, 224
- Capacitance, 86–88, 132, 256–257
- Capacitor, 26–29, 31, 132
- Chambers, absorption, 255
- Chambers, test, 255–259
- Chattock coils, 219–222
- Chopper circuit, 336–337, 345–347. *See also* Pulsewidth modulated
- Circuit breakers, 3
- Circuit comparisons, 35–36
- Circulation, 13
- Clapper armature actuator, 95–102, 237, 290.
See also Eaton AC solenoid
- Closure time, 156, 278–282, 292–295, 310–311, 314–319, 323–324
- Clutches, 117
- CMOS, 179
- Coenergy, 61–65, 72
- Coil(s)
 - ampere-turns, 15
 - design, 231–245
 - resistance, 131–135, 209, 231–239
 - sensor, 191, 201–223
 - time constant, 234–235
 - voltage induced, 22
- Common-mode noise, 250
- Commutation, 108
- Compass(es), 215
- Complex AC circuit methods, 133, 142
- Complex-plane impedance, 206–209
- Composite materials, 24
- Computational fluid dynamics (CFD), 330
- Conductivity
 - electrical, 21
 - temperature effect on electrical, 231–233

- Conductivity (*Continued*)
 - tensor electrical, 179–182, 265
 - thermal, 239–241
- Contactors, 3. *See also* Eaton AC solenoid
- Continuity, 28
- Contours, 55–57, 258–260
- Controller, 297, 313
- Control system, 5–7, 301–302. *See also* Feedback control
- Control System Toolbox for MATLAB, 301–307
- Coordinates, rectangular (Cartesian), 9
- Core loss
 - curves, 130–131
 - equation, 242
- Corrosion cracks, 210
- Cosimulation, 308
- Coupled electromagnetic
 - analysis, 257–260
 - fields, 28
 - radiation, 249–260
- Coupling, antiferromagnetic, 194
- Coupling electric circuits to finite elements, 266–268
- Cramer's rule, 182
- Curl, 11–14
- Current, 14–17
 - density, 177–191
 - dip, 278, 292, 315–318
 - perpendicular to plane (CPP), 174
 - in plane (CIP), 174
 - sensors, 192, 292, 315–318
 - waveform, 226–231, 236–240
- Cyclotron frequency, 180
- Cylinders, hydraulic, 330, 343–354

- dB, 252
- DC actuators, 95–125
- DC coils, 231–233
- Deadbands, 111
- Delay time, 147. *See also* Diffusion time
- Del operator, 9
- Demagnetization curve, 67–70
- Dependent sources, 335
- Design optimization, *see* Optimization
- Determinant, 12
- Diffusion time, 147–171, 307–319, 348–352
- Digital hydraulics, 353–357
- Digital solver, 297
- Diode, flyback, 336
- Discretization, 43
- Disk drives, 3–6, 107–108, 112, 194–197, 203–205. *See also* Recording heads and Voice coil actuators
- Displacement current, 28–29
- Displacement (mechanical), 272, 302–304
- Dither, 112
- Divergence, 11–16

- Earnshaw theorem, 117
- Eaton AC solenoid
 - flux plot of, 56
 - geometry of, 50
 - shading ring in, 137
 - transient analysis of, 279–282
- Eddy axial formulation, 139–140
- Eddy current(s)
 - braking, 209
 - coefficient, 242
 - effects, 24–25, 236–238, 242. *See also* Diffusion time
 - moving, 209–210
 - resistor, 307–312, 348–352
 - sensors, 206–210
 - stationary, 206–209
- Effusion, 152, 164–169
- Electric
 - charge density, 26
 - circuit, 266–268
 - field intensity, 22
 - field, motional, 23, 275, 292–293
 - flux density, 26
 - scalar potential, 26, 264
- Electrode(s), 177–190
- Electrohydraulic analysis, 327–359
- Electromagnetic compatibility (EMC), 249–260
- Electromagnetic interference (EMI), 249–260
- Electromagnetic problem types, 266
- Electromagnetics, 9–29
- Electromagnets, 69
- Electromechanical analysis, 263–359
- Electronics module, 214
- Electron(s), 179–180, 194–197
- Electrostatic fields, 26, 240–241, 259
- Electrostatic scalar potential, 26, 264
- Emissions, conducted, 249–250
- Emissions, radiated, 249–253
- Encoder(s), 192
- Energy
 - conservation, 43–44
 - conversion, 3, 330
 - density, 60–65
 - functional, 43–45
 - harvesters, 224
 - input, 43–44
 - loss, 235. *See also* Power loss
 - stored, 43–44, 60–64, 259

- Entity in VHDL–AMS models, 296–297
- Equivalent circuits, 131–135
- Excitations, 49–51
- Excitation vector, 47–51, 264–273
- Faraday’s Law, 22–25, 201–213, 250, 270, 292
- Feedback control, 5–6, 191, 204, 328, 347
- Fermi gas theory, 179–181
- Ferrite(s), 24, 41, 69, 237–239
- Ferrofluids, 117
- Ferromagnetic layers, 194
- Ferromagnetics, 17–21
- Film coefficient, 241–244
- Filtering, 249–250
- Finite difference method, 43
- Finite-element analysis, *see also* Maxwell software
 - acoustic, 330
 - electric conduction, 182–190
 - electromechanical, 263–285
 - fluid(s), 329–330
 - magnetic, 43–53, 263–284
 - parametric, 99, 103, 292–293, 345–346
 - structural, 272–285
 - thermal, 239–245
- Finite element(s)
 - axisymmetric, 56–58, 264, 267
 - edge, 47
 - first order, 46–48
 - model, 49–53
 - nodes, 45–49
 - open boundary, 51, 267–268
 - quadratic shape function, 47
 - tangential vector, 47
 - triangular, 45–47
- Flow force, 335–357
- Flow, hydraulic, 329–357
- Flowmeters, 348
- Fluid dynamics, 43, 330
- Fluid power systems, 327–357
- Flux
 - fringing, 38–41, 52, 60
 - leakage, 60, 245
 - lines, 55–56, 253–260
 - linkage, 23, 79–83, 290
 - partial, 60
- Flux density plots, 55–64
- Flux gate sensors, 215–219
- Force(s)
 - bi-directional, 109, 284–285
 - distribution, 272–282
 - integration, 273–275
 - magnetic, *see* Magnetic force
 - on capacitor, 86
 - pulsations, 135–139
 - repulsive, 138
- Frequency, resonant, 132, 285
- Frequency response, 306–307
- Friction, 112–114, 295, 302
- Fringing factor, 41
- Fuel injector(s), 350, 354–355
- Functional minimization, 43–45
- Galerkin’s method, 47
- Gasket, 251–252
- Gradient, 9–11
- Halbach magnets, 70–71, 313
- Hall effect sensors, 177–193
- Hard-disk drives, *see* Disk drives
- Hardware Description Language (HDL), 296
- Heat, 239–245
- Hydraulic(s), 327–357
 - capacitance, 329–338
 - cylinders, 341–352
 - digital, 353–357
 - inductance, 329–331
 - line(s), 328–330
 - pressure(s), 327–357
 - resistor (orifice), 329–357
 - systems, 327–357
- Hysteresis, 67, 130–132, 204
 - coefficient, 242
 - loss, 130–131, 242
- Impedance, 88–90, 206–211, 234
 - characteristic, 256
 - Thevenin, 256
- Inductance, 82–85, 234–244, 290–297
 - end turn, 280
 - incremental, 83
 - matrix, 83–85
 - mutual, 83
 - secant, 83
 - self, 83
- Inductive kick, 283
- Inductor(s), 83, 237–245
 - leakage, 310–311
 - rectangular, 157–158, 164–167
- Infusion, 152–164
- Injectors, fuel, 350–355
- Insulation, glastic, 240–244
- Integrated circuits, 179
- Inverse problem, 207
- Iron (Fe), 17, 24
- Iron filings, 55

- Kirchhoff's Current Law, 11, 267
- Laminar orifice(s), 329–333
- Laminated steel, 24, 130–131
- Laminations, 24
- Laplace transform s domain, 301–306
- Latching switches, 109, 282
- Leakage flux, 60, 245
- Lenz's law, 24
- Levitation, 138
- Light, speed of, 251
- Linear actuators, 95–113
- Linear time invariant (LTI), 303
- Linear variable differential transformers (LVDTs), 210–213, 349
- Lines of force, 55
- Locus, impedance, 207
- Lorentz force, 66–67, 106–108, 312
- Losses, *see* Power loss
- Loudspeakers, 106–108
- Machines, rotary, 95, 112–114
- Magnet, lifting, 134–135
- Magnetic
 - AC actuators, 129–145, 279–282. *See also*
 - Eaton AC solenoid
 - bearings, 114–117
 - brakes and clutches, 117, 209
 - constant force actuator, 103, 110–111
 - couplings, 117
 - DC actuators, 95–125, 275–279, 290–312, 334–341, 343–357. *See also* Bessho DC solenoid
 - diffusion time, linear, 150–156
 - diffusion time, nonlinear, 156–169
 - domains, 17–18
 - effusion, 164–171
 - energy, 44–46, 52, 60–61
 - field, 9–21
 - field intensity, 14–21
 - flux, 79
 - flux density, 14–21
 - flux density magnitudes, 178
 - flux line plots, 55–60
 - flux linkage, 80–83
 - force, 3–4, 55–72, 85–86, 117–125, 147–150, 273–275, 292–294
 - infusion, 156–164
 - materials, 17–21
 - performance parameters, 79–90
 - pole, 37
 - pressure, 65–66, 273–274, 327
 - Resonance Imaging (MRI), 223
 - Reynolds number, 209
 - sensors, 177–225, 327–328, 349–350
 - sensors, inductive, 201–205, 250–253
 - separator, 117–125
 - switches, 282–284
 - torque, 72–73
 - 2D planar actuators, 312–313
 - vector potential, 27, 264–265
 - volume force, 73–75
- Magnetization, 17–18
- Magnetization curves, *see* B–H curves
- Magnetizing fixtures, 204
- Magnetoimpedance (MI) sensors, 223–224
- Magnetometers, 222–223
- Magnetomotive force (MMF), 35
- Magnetostriction (MR), 183–197
 - anisotropic classical, 183–194
 - colossal (CMR), 195
 - extraordinary (EMR), 195
 - giant (GMR), 194–197
 - tunneling (TMR), 194
- Magnetostrictive heads, 195–197
- Magnetostrictive sensors, 183–197, 284
- Magnetostatics, 44–46
- Magnetostriction, 213–215, 224
- Magnetostrictive materials, 109
- Magnetostrictive sensors, 213–215, 224
- Magnets, permanent, 67–75
- Material
 - anisotropic, 19
 - hard magnetic, 20
 - isotropic, 19
 - soft magnetic, 17
- MATLAB, 301–307
- Matrix
 - conductance, 179–180, 265
 - damping, 272
 - equation, 46–49, 264–267, 272
 - mass, 272
 - permittance, 265–266
 - reluctance, 46–49, 265
 - solution sparsity, 49
 - stiffness, 47, 272–273
- Maxwell® finite element software numbered
 - examples
 - chapter 4, 51
 - chapter 5, 59, 64, 71
 - chapter 6, 80, 82, 84, 87, 89
 - chapter 7, 98, 100, 103, 104, 117, 121
 - chapter 8, 134, 138, 144
 - chapter 9, 153, 157, 161, 164, 167, 170
 - chapter 10, 186
 - chapter 11, 204, 208, 212
 - chapter 12, 236, 237, 240
 - chapter 13, 253, 259

- Maxwell's equations, 28
- Maxwell stress tensor, 65–66, 273–275
- Mechanical input, 328
- Mechanical stress, 43, 272–275
- Mechatronics, 7–8
- Metal detectors, 206
- Micro-electromechanical systems (MEMs), 224–225
- Micromachining, 223–224
- Microphone, 5, 203
- Midnode variables, 47
- Model validation, 57–58
- Modulus of elasticity, 275, 280
- MOSFETs, 217–220
- Motes, 224
- Motional EMF effects, 275–277, 292, 303
- Motion control, 3
- Motors, 3–4. *See also* Step motors
- Moving surfaces, 272
- Multisim software, 289

- Nanoparticles, 120–122, 223
- Nanotechnology, 18, 195
- Newton's iterative method, 47
- Newton's Law(s), 272, 345
- Nodes, 45–49, 265–276, 337
- Noise, 249–250
 - common-mode, 250
 - radiated, 249–250
- Non-destructive evaluation (NDE), 206–207
- Non-destructive testing (NDT), 207–208
- Nonlinear B – H curve(s), 10–21, 361–365.
 - See also* Saturation
- Nonsinusoidal waveforms, 133, 136
- Normal AC B – H curves, 131
- Nuclear power plants, 207–209

- Ohm's Law, 23, 35
- Optimization, 313–324, 352–353
- Orifice, hydraulic, 329–353
- Orifice, variable, 329–353. *See also* Valve(s)
- Overshoot, percent (P.O.), 302–306

- Package body, 296
- Packing factor, 233
- Parametric finite element analysis, 99, 103, 292–294
- Path, closed, 15, 33–36
- Pauli exclusion principle, 196
- Performance parameters, 79–90
- Permanent magnet, moving, 203
- Permanent magnet(s)
 - latch, 282
 - modeling, 69–70, 265
 - properties, 67–70
 - sensors, 191–192, 197
- Permeability, 15, 17
 - complex, 252
 - effective, 133
 - incremental, 19
 - relative, 17
 - tensor, 19
- Permeance, 35–36
- Permittivity, 26, 240, 255
- Phase angle, 133, 137, 234–238
- Pickup coils, 201–202, 222. *See also* Coil(s), sensor
- Pig (traveling sensor), 210
- Pins, 298
- Pipe, 207–210
- Plastics, 256
- Plug and play, 224
- Plunger armature, 102–106, 148–150, 155–169.
 - See also* Bessho DC solenoid
- Pneumatic systems, 332
- Poisson's differential equation, 239–240
- Poisson's ratio, 275, 280
- Polynomial order p , 47
- Position versus time, *see* Bessho DC solenoid and Eaton AC solenoid
- Postprocessing, 55
- Potentials, 25–27
- Power loss(es), 130–133, 230–239. *See also* Eddy current effects
- Preprocessing, 51
- Pressure
 - hydraulic, 327–357
 - magnetic, 65–66, 273–274, 327
 - versus flow curves, 332, 344
- Primary winding, 210–212, 268–283
- Proportional actuators, 10–111
- Prosthetic, 4
- Proximity effects in coil wires, 235–245
- Proximity sensors, 206–210
- Pull curve, 96–100
- Pulse, interrogation, 214–215
- Pulse-width modulated (PWM), 111–112, 336–337
- Pump(s), 328–353

- Quickfield, 51

- Reactance, 89–90
- Reciprocating magnetic actuators, 284–285, 329
- Recording heads, *see also* Disk drives
 - inductive, 203–205
 - magnetoresistive, 195–197
- Reduced order model, 303–306

- Reed switches, 282
- Reflections, 255–256
- Relaxation techniques, 43
- Relay(s), 95, 279–282
- Reluctance, 33–42
 - AC complex, 41, 142–145
 - force, 61–65
 - method, 33–42
 - method, limitations of, 41–42
- Reluctivity tensor, 265
- Remanent (residual) flux density, 68
- Resistance, 35–36, 181, 231–233
- Resistivity, 181
- Resistor, eddy current (magnetic) diffusion, 307–312, 348–352
- Resonant frequency, natural, 132, 285
- Right hand rule, 18–21, 25
- Rigid armature motion analogies, 293
- Rigid body motion, 272, 293
- Ripple, *see* Pulse-width modulated
- Robot(s), 4, 206
- Rogowski coil(s), 221
- Roots function of MATLAB, 303–304
- Rotary actuators, 112–114

- Saturation, 19–20, 60–66, 270–272
- Scalar(s), 9
- Scilab software, 301
- Secondary winding, 210–213, 268–284
- Security systems, 206
- Seek time, 108, 204
- Semiconductors, 177–194
- Sensor(s), *see also* Magnetic sensors
 - current, 192, 292, 315–318
 - Hall effect, 5, 177–193
 - LVDT, 210–213
 - magnetoresistive, 185–197
 - magnetostrictive, 213–215
 - proximity, 5, 206–209
 - toothed armature, 39
 - velocity (speed), 5, 201–205, 250
- Separator(s), *see* Magnetic separators
- Shading coil, 137
- Shading ring, 137–139
- Shape functions, 46–47, 265
- Shields, 197, 250–255
- Signals, 249–250
- Signal-to-noise ratio, 249–256
- Simplorer software, 216–220, 289, 295–301, 308–312
 - models of electrohydraulics, 338–353
 - models of electromechanics, 295–301, 308–312
- Simulink, 301

- Skin depth, 129–130, 235–239, 250–255
- Skin effect, 129–130, 235–239, 250–255. *See also* Diffusion time
- Smart dust, 224
- Soft adjacent layers (SALs), 194–195
- Software
 - circuit analysis, 216, 289
 - finite element, 51, 263–284. *See also* Maxwell finite element software systems, 289–307
- Solenoid actuators, 95–106
 - clapper armature, 95–102. *See also* Eaton AC solenoid
 - plunger armature, 102–106. *See also* Bessho DC solenoid
- Solenoidal coil, 95
- Sources, *see* Excitations
- Speed sensors, 190–192, 201–205
- Speed voltage, 291–293. *See also* Motional EMF effects
- SPICE, 216, 289
 - models of electrohydraulics, 334–352
 - models of electromechanics, 289–295, 310–312
 - models of hydraulics, 330–334
- Spin valve sensors, 194–197
- Spring, nonlinear, 279–280
- SQUID magnetometers, 222–223
- Stage, hydraulic, 330
- Stator, 39, 95
- Steel, *see also* Laminated steel
 - B–H* relation, 19–21, 361–366
 - cuts, 142–145
 - cylinder, 140–145, 150–170
 - slab, 150–170
 - solid, 140–143
- Step motor(s), 112–113
- Stiction, 112
- Stiffness matrix, 47, 272
- Stokes' law, 15
- Strain, mechanical, 213–215, 282
- Stress, mechanical, 213–215, 272, 279–282. *See also* Maxwell stress tensor
- Stripe, magnetoresistive, 194–195
- Stroke time, 147–150, 293–312. *See also* Closure time
- Superconducting quantum interference device, *see* SQUID magnetometers
- Superconductors, 69
- Surface, closed, 15
- Susceptance, conducted, 249–250
- Susceptance, radiated, 249–250
- Switch, electronic, 282–284, 336. *See also* Pulswidth modulated

- Switched reluctance motors, 113
- Switches, *see* Magnetic switches *and* Reed switches
- Switchgear, 3
- System(s)
 - models, 289–357
 - second order, 303–307
 - software, *see* MATLAB, Simulink, *and* Simplerer
 - third order, 305–307
- Table, flux linkage, 292–293
- Table, force, 292–293
- Tank, hydraulic, 331
- Target, 206–209
- TEM cells, 255, 257
- Temperature, 231–233, 239–245
- TEM transmission lines, 255–256
- Terfenol-D, 213–214
- Tesla, 15
- Tetrahedrons, 47, 267
- Thermal
 - analysis, 239–245
 - conduction, 239–241
 - convection, forced, 241–242
 - convection, free, 241–245
 - radiation, 241–245
- Time constant, 234–235, 289–303. *See also* Diffusion time
- Time, *see also* Closure time
 - peak, 302–306
 - rise, 302–306
 - settling, 302–306
- Timeline of actuator operation, 147
- Timestepping, 273–275. *See also* Simplerer *and* SPICE
- TINA-TI, 289
- Toothed wheel sensors, 190–192, 201–203
- Tooth pitch, 192
- Torquers, 112
- Torque sensing, 215
- Transducer(s), 95, 304
- Transfer function, 302–307
- Transformers, 23–24, 268–272, 282–284
- Transformers, linear variable differential, 5, 210–213
- Transient operation of actuators, 147–171, 293–312
- Translation, mechanical, 273
- Transmission lines, 255–256
- Tri-plate cells, 257–260
- Turbulent orifices, 329–332
- Turnoff, 147–171. *See also* Effusion
- Turnon, 147–171. *See also* Infusion
- Turns, 15, 22
- Units
 - centimeter-gram-second (CGS), 19
 - SI (meter-kilogram-second), 10, 19, 359–360
- Valve(s)
 - control, 329, 334–342
 - digital, 353–357
 - electrohydraulic, 328, 334–353
 - four-way, 342–348
 - hydraulic, 328–357
 - lands in, 342
 - spool, 342–344
- Variable reluctance sensor, 39–40, 190–192, 201–203
- Variables, across, 298
- Variables, through, 298
- Vectors, 9
- Vector, unknown, 47, 265, 273
- VHDL-AMS, 296–301
- View factors, 242
- Virtual work, 61–67, 72–73
- Voice coil actuators, 106–112
 - MATLAB model of, 302–307
- Voltage, *see also* Hall effect sensors
 - induced, 22–24
 - potential, 25–26
- Wavefront, 156, 161–163
- Waveguide, acoustic, 213–215
- Wavelength, 251–253
- Waves, 251–256
- Wheel, toothed, 190–192, 201–203
- Wire diameter, 231–233
- Wire gauge, 231
- ZigBee, 224