

End cap surface
electrophoresis (black)
(Except for customer
installation surface)

激光打码
Laser printing

BJ42D22-44V26
LOT NO. xxxxxx

“XXXXXX”:生产日期
date of manufacture /
例如For example:131207

"X": 生产线别
Production line no.
例如 For example: A、B...


励磁顺序vs. 旋转方向
Exciting Sequence vs.Direction of rotation





STEP	A	B	C	D
1	+	+	-	-
2	-	+	+	-
3	-	-	+	+
4	+	-	-	+

CCW 从电机的安装端看，按照表格规定的励磁顺序。电机将产生顺时针方向旋转。
Exciting sequence as the table specifies will produce clockwise rotation when viewed from mounting end.

PULLEY 带轮	
TOOTH SPECIFICATION 齿型	2GT
PITCH 节距	2±0.01
NUMBER OF TEETH 齿数	20
OUT DIAMETER 外径	Ø12.22 ^{+0.00} ₋₀
DIA OF PICH CIRCLE 节径	Ø12.73

接线图Wiring Diagram:



Dimensions refer to drawing		未注公差Tolerance sheet			
単位Unit: mm	比例Scale: nts	0°		0	±0.2
Product Code:		0.0°		0.0	±0.1
Model: B-J42D22-44V26		0.00°		0.00	




SHENZHEN KELI MOTOR LTD.

Model:	BJ42D22-44V26
--------	---------------

设计 Designed by

审核 Checked by

批准 Approved by



Drawing No.:

Page 1 of 1 Page

版本Version: A